Code Editor

EXPLORER

- ⌄ 📁 app
  - ❯ 📁 public
  - ⌄ 📁 segments
    - {} default.json
  - ⌄ 📁 services
    - {} standalone.json
  - ⌄ 📁 src
    - ⌄ 📁 domain
      - TS sayHello.ts
    - ⌄ 📁 webui
      - ❯ 📁 assets

CODE → src/domain/sayHello.ts

```
export async function sayHello(name: string): Promise<st
{
    return `Hello, ${name}!`;
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

EXPLORER

- ∨ 📁 app
  - ❯ 📁 public
  - ∨ 📁 segments
    - {} default.json
  - ∨ 📁 services
    - {} standalone.json
  - ∨ 📁 src
    - ∨ 📁 domain
      - TS sayHello.ts
    - ∨ 📁 webui
    - ❯ 📁 assets

CODE → src/domain/sayHello.ts

```typescript
export async function sayHello(name: string): Promise<st
{
    return `Hello, ${name}!`;
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

EXPLORER

- ∨ 📁 app
  - ⟩ 📁 public
  - ∨ 📁 segments
    - 📄 default.json
  - ∨ 📁 services
    - 📄 standalone.json
  - ∨ 📁 src
    - ∨ 📁 domain
      - 📄 sayHello.ts
    - ∨ 📁 webui
    - ⟩ 📁 assets

CODE → src/domain/sayHello.ts

```typescript
export async function sayHello(name: string): Promise<st
{
    return `Hello, ${name}!`;
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

EXPLORER

- ⌄ 📁 app
  - ❯ 📁 public
  - ⌄ 📁 segments
    - {} default.json
  - ⌄ 📁 services
    - {} standalone.json
  - ⌄ 📁 src
    - ⌄ 📁 domain
      - TS sayHello.ts
    - ⌄ 📁 webui
    - ❯ 📁 assets

CODE → src/domain/sayHello.ts

```
export async function sayHello(name: string): Promise<st
{
    return `Hello, ${name}!`;
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

EXPLORER

- 📁 app
  - 📁 public
  - 📁 segments
    - {} default.json
  - 📁 services
    - {} standalone.json
  - 📁 src
    - 📁 domain
      - TS sayHello.ts
    - 📁 webui
    - 📁 assets

CODE → src/domain/sayHello.ts

```typescript
export async function sayHello(name: string): Promise<st
{
    return `Hello, ${name}!`;
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

EXPLORER

- ⌄ 📁 app
  - ⌄ 📁 public
  - ⌄ 📁 segments
    - {} default.json
  - ⌄ 📁 services
    - {} standalone.json
  - ⌄ 📁 src
    - ⌄ 📁 domain
      - TS sayHello.ts
    - ⌄ 📁 webui
    - ⌄ 📁 assets

CODE → segments/default.json

```json
{
    "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

- ⌄ 📁 app
- ⟩ 📁 public
- ⌄ 📁 segments
  - {} default.json
- ⌄ 📁 services
  - {} standalone.json
- ⌄ 📁 src
  - ⌄ 📁 domain
    - TS sayHello.ts
  - ⌄ 📁 webui
    - ⟩ 📁 assets

CODE → segments/default.json

```json
{
    "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
    "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

R

pp

public

segments

default.json

services

standalone.json

src

domain

sayHello.ts

webui

assets

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

nts

t.json

s

lone.json

n

ello.ts

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "/domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
    "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
    "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
    "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
    "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
    "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
    "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

```
CODE → segments/default.json

{
    "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
    "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

Code Editor

CODE → segments/default.json

```json
{
  "./domain/sayHello": { "sayHello": { "access": "public" } }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~