

```
"dev": "vite",
"build": "npm run build-domain && npm run build-webui",
"build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
"build-webui": "vite build",
"standalone": "jitar start --service=services/standalone.json",
"data": "jitar start --service=services/data-worker.json",
"default": "jitar start --service=services/default-worker.json",
"gateway": "jitar start --service=services/gateway.json",
"repository": "jitar start --service=services/repository.json",
"proxy": "jitar start --service=services/proxy.json"
```

# TERMINAL

# ~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3002
```

[INFO] Provided web client

--	--

 gateway

```
>_ repository
```



```
> data
```

**>\_ default**

```
"dev": "vite",
"build": "npm run build-domain && npm run build-webui",
"build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
"build-webui": "vite build",
"standalone": "jitar start --service=services/standalone.json",
"data": "jitar start --service=services/data-worker.json",
"default": "jitar start --service=services/default-worker.json",
"gateway": "jitar start --service=services/gateway.json",
"repository": "jitar start --service=services/repository.json",
"proxy": "jitar start --service=services/proxy.json"
```

# TERMINAL

# ~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3002
```

[INFO] Provided web client

**> gateway**

```
>_ repository
```

```
> data
```

**>\_ default**

```
"dev": "vite",
"build": "npm run build-domain && npm run build-webui",
"build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
"build-webui": "vite build",
"standalone": "jitar start --service=services/standalone.json",
"data": "jitar start --service=services/data-worker.json",
"default": "jitar start --service=services/default-worker.json",
"gateway": "jitar start --service=services/gateway.json",
"repository": "jitar start --service=services/repository.json",
"proxy": "jitar start --service=services/proxy.json"
```

# TERMINAL

# ~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3002
```

[INFO] Provided web client

**> gateway**

```
>_ repository
```



 data

**>\_ default**

```
"dev": "vite",
"build": "npm run build-domain && npm run build-webui",
"build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
"build-webui": "vite build",
"standalone": "jitar start --service=services/standalone.json",
"data": "jitar start --service=services/data-worker.json",
"default": "jitar start --service=services/default-worker.json",
"gateway": "jitar start --service=services/gateway.json",
"repository": "jitar start --service=services/repository.json",
"proxy": "jitar start --service=services/proxy.json"
```

# TERMINAL

# ~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3002
```

[INFO] Provided web client

**> gateway**

```
>_ repository
```



**> data**

**>\_ default**

```
"dev": "vite",
"build": "npm run build-domain && npm run build-webui",
"build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
"build-webui": "vite build",
"standalone": "jitar start --service=services/standalone.json",
"data": "jitar start --service=services/data-worker.json",
"default": "jitar start --service=services/default-worker.json",
"gateway": "jitar start --service=services/gateway.json",
"repository": "jitar start --service=services/repository.json",
"proxy": "jitar start --service=services/proxy.json"
```

# TERMINAL

# ~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3002
```

[INFO] Provided web client

**> gateway**

```
>_ repository
```



 data

**>\_ default**

```
"dev": "vite",
"build": "npm run build-domain && npm run build-webui",
"build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
"build-webui": "vite build",
"standalone": "jitar start --service=services/standalone.json",
"data": "jitar start --service=services/data-worker.json",
"default": "jitar start --service=services/default-worker.json",
"gateway": "jitar start --service=services/gateway.json",
"repository": "jitar start --service=services/repository.json",
"proxy": "jitar start --service=services/proxy.json"
```

# TERMINAL

# ~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3000
```

[INFO] Provided web client

```
[INFO] Ran request: domain/sayHello
```

**> gateway**

```
>_ repository
```



proxy

 data

```
>_ default
```