


Code Editor

CODE → services/proxy.json

```
{  
  "url": "http://127.0.0.1:3000",  
  "proxy":  
    {  
      "gateway": "http://127.0.0.1:3001",  
      "repository": "http://127.0.0.1:3002"  
    }  
}
```



TERMINAL

domain/sayHello

1

Code Editor

CODE → services/proxy.json

```
{  
  "url": "http://127.0.0.1:3000",  
  "proxy":  
    {  
      "gateway": "http://127.0.0.1:3001",  
      "repository": "http://127.0.0.1:3002",  
    }  
}
```



TERMINAL

domain/sayHello

1

Code Editor

CODE → services/proxy.json

```
{  
  "url": "http://127.0.0.1:3000",  
  "proxy":  
  {  
    "gateway": "http://127.0.0.1:3001",  
    "repository": "http://127.0.0.1:3002",  
  }  
}
```



TERMINAL

domain/sayHello

1

Code Editor

CODE → services/proxy.json

```
{  
  "url": "http://127.0.0.1:3000",  
  "proxy":  
    {  
      "gateway": "http://127.0.0.1:3001",  
      "repository": "http://127.0.0.1:3002",  
    }  
}
```

TERMINAL

domain/sayHello

1

Code Editor

CODE → services/proxy.json

```
{  
  "url": "http://127.0.0.1:3000",  
  "proxy":  
    {  
      "gateway": "http://127.0.0.1:3001",  
      "repository": "http://127.0.0.1:3002",  
    }  
}
```

TERMINAL

domain/sayHello

1

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```

TERMINAL

```
domain/sayHello
```

```
1
```

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```

TERMINAL


domain/sayHello

1

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```



TERMINAL


domain/sayHello

1

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```



TERMINAL

```
1 domain/sayHello
```

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```

TERMINAL

domain/sayHello

1

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```

TERMINAL

```
domain/sayHello
```

```
1
```

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```

TERMINAL

domain/sayHello

1

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```

TERMINAL

domain/sayHello

1

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```

TERMINAL

domain/sayHello

1

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```

TERMINAL

```
1 domain/sayHello
```

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```


TERMINAL

```
1 domain/sayHello
```

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```



TERMINAL

```
domain/sayHello
```

```
1
```

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```

TERMINAL

domain/sayHello

1



Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```

TERMINAL

```
1 domain/sayHello
```

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json"
  },
  "dependencies":
```

TERMINAL

```
domain/sayHello
```

```
1
```

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json",
    "data": "jitar start --service=services/data-worker.json",
  },
}
```

TERMINAL

domain/sayHello

1

Code Editor

CODE → package.json

```
{
  "name": "jitar-react-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "npm run build-domain && npm run build-webui",
    "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
    "build-webui": "vite build",
    "standalone": "jitar start --service=services/standalone.json",
    "data": "jitar start --service=services/data-worker.json",
    "default": "jitar start --service=services/default-worker.json",
```

TERMINAL

```
1 domain/sayHello
```

Code Editor

CODE → package.json

```
"name": "jitar-react-starter",
"private": true,
"version": "0.0.0",
"type": "module",
"scripts":
{
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
```

TERMINAL

```
1 domain/sayHello
```

Code Editor

CODE → package.json

```
"private": true,  
"version": "0.0.0",  
"type": "module",  
"scripts":  
{  
  "dev": "vite",  
  "build": "npm run build-domain && npm run build-webui",  
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",  
  "build-webui": "vite build",  
  "standalone": "jitar start --service=services/standalone.json",  
  "data": "jitar start --service=services/data-worker.json",  
  "default": "jitar start --service=services/default-worker.json",  
  "gateway": "jitar start --service=services/gateway.json",  
  "repository": "jitar start --service=services/repository.json",
```

TERMINAL

```
1 domain/sayHello
```

Code Editor

CODE → package.json

```
"version": "0.0.0",  
"type": "module",  
"scripts":  
{  
  "dev": "vite",  
  "build": "npm run build-domain && npm run build-webui",  
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",  
  "build-webui": "vite build",  
  "standalone": "jitar start --service=services/standalone.json",  
  "data": "jitar start --service=services/data-worker.json",  
  "default": "jitar start --service=services/default-worker.json",  
  "gateway": "jitar start --service=services/gateway.json",  
  "repository": "jitar start --service=services/repository.json",  
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL

```
1 domain/sayHello
```

Code Editor

CODE → package.json

```
"version": "0.0.0",  
"type": "module",  
"scripts":  
{  
  "dev": "vite",  
  "build": "npm run build-domain && npm run build-webui",  
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",  
  "build-webui": "vite build",  
  "standalone": "jitar start --service=services/standalone.json",  
  "data": "jitar start --service=services/data-worker.json",  
  "default": "jitar start --service=services/default-worker.json",  
  "gateway": "jitar start --service=services/gateway.json",  
  "repository": "jitar start --service=services/repository.json",  
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL

domain/sayHello

1