

## Code Editor

CODE → package.json

```
"version": "0.0.0",  
"type": "module",  
"scripts":  
{  
  "dev": "vite",  
  "build": "npm run build-domain && npm run build-webui",  
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",  
  "build-webui": "vite build",  
  "standalone": "jitar start --service=services/standalone.json",  
  "data": "jitar start --service=services/data-worker.json",  
  "default": "jitar start --service=services/default-worker.json",  
  "gateway": "jitar start --service=services/gateway.json",  
  "repository": "jitar start --service=services/repository.json",  
  "proxy": "jitar start --service=services/proxy.json"
```

## TERMINAL

```
1 domain/sayHello
```

## Code Editor

CODE → package.json

```
"version": "0.0.0",
"type": "module",
"scripts":
{
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
  "repository": "jitar start --service=services/repository.json",
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL

```
domain/sayHello
```

```
]
[INFO]
```

CODE → package.json

```
"version": "0.0.0",  
"type": "module",  
"scripts":  
{  
  "dev": "vite",  
  "build": "npm run build-domain && npm run build-webui",  
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",  
  "build-webui": "vite build",  
  "standalone": "jitar start --service=services/standalone.json",  
  "data": "jitar start --service=services/data-worker.json",  
  "default": "jitar start --service=services/default-worker.json",  
  "gateway": "jitar start --service=services/gateway.json",  
  "repository": "jitar start --service=services/repository.json",  
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL

```
domain/sayHello  
]  
[INFO] Provided web client  
[INFO] Ran request: domain/sayHello  
[INFO] Request body: {}
```

```
"version": "0.0.0",
"type": "module",
"scripts":
{
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
  "repository": "jitar start --service=services/repository.json",
  "proxy": "jitar start --service=services/proxy.json"
```

## TERMINAL

```
domain/sayHello
]
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
[INFO] Provided web client
```

```
"scripts":  
{  
  "dev": "vite",  
  "build": "npm run build-domain && npm run build-webui",  
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",  
  "build-webui": "vite build",  
  "standalone": "jitar start --service=services/standalone.json",  
  "data": "jitar start --service=services/data-worker.json",  
  "default": "jitar start --service=services/default-worker.json",  
  "gateway": "jitar start --service=services/gateway.json",  
  "repository": "jitar start --service=services/repository.json",  
  "proxy": "jitar start --service=services/proxy.json"
```

## TERMINAL

```
domain/sayHello  
]  
[INFO] Provided web client  
[INFO] Ran request: domain/sayHello  
[INFO] Provided web client  
[INFO] Ran request: domain/sayHello  
[INFO] Provided web client  
[INFO] Ran request: domain/sayHello
```

```
"dev": "vite",
"build": "npm run build-domain && npm run build-webui",
"build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
"build-webui": "vite build",
"standalone": "jitar start --service=services/standalone.json",
"data": "jitar start --service=services/data-worker.json",
"default": "jitar start --service=services/default-worker.json",
"gateway": "jitar start --service=services/gateway.json",
"repository": "jitar start --service=services/repository.json",
"proxy": "jitar start --service=services/proxy.json"
```

## TERMINAL

```
domain/sayHello
]
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
```

```
"dev": "vite",
"build": "npm run build-domain && npm run build-webui",
"build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
"build-webui": "vite build",
"standalone": "jitar start --service=services/standalone.json",
"data": "jitar start --service=services/data-worker.json",
"default": "jitar start --service=services/default-worker.json",
"gateway": "jitar start --service=services/gateway.json",
"repository": "jitar start --service=services/repository.json",
"proxy": "jitar start --service=services/proxy.json"
```

## TERMINAL

```
domain/sayHello
]
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
^C
```



```
"dev": "vite",
"build": "npm run build-domain && npm run build-webui",
"build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
"build-webui": "vite build",
"standalone": "jitar start --service=services/standalone.json",
"data": "jitar start --service=services/data-worker.json",
"default": "jitar start --service=services/default-worker.json",
"gateway": "jitar start --service=services/gateway.json",
"repository": "jitar start --service=services/repository.json",
"proxy": "jitar start --service=services/proxy.json"
```

## TERMINAL

```
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
^C
[INFO] Server stopped
```





```
"dev": "vite",
"build": "npm run build-domain && npm run build-webui",
"build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
"build-webui": "vite build",
"standalone": "jitar start --service=services/standalone.json",
"data": "jitar start --service=services/data-worker.json",
"default": "jitar start --service=services/default-worker.json",
"gateway": "jitar start --service=services/gateway.json",
"repository": "jitar start --service=services/repository.json",
"proxy": "jitar start --service=services/proxy.json"
```

## TERMINAL

```
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
^C
[INFO] Server stopped
app> █
```