Code Editor

CODE → src/domain/keepHelloCount.ts

```typescript
const helloCounts: Record<string, number> = {};

export async function keepHelloCount(name: string): Promise<number>
{
    helloCounts[name] = (helloCounts[name] ?? 0) + 1;

    return helloCounts[name];
}
```

TERMINAL

>

Code Editor

CODE → src/domain/keepHelloCount.ts

```typescript
const helloCounts: Record<string, number> = {};

export async function keepHelloCount(name: string): Promise<number>
{
    helloCounts[name] = (helloCounts[name] ?? 0) + 1;

    return helloCounts[name];
}
```

TERMINAL

>

Code Editor

CODE → src/domain/keepHelloCount.ts

```typescript
const helloCounts: Record<string, number> = {};

export async function keepHelloCount(name: string): Promise<number>
{
    helloCounts[name] = (helloCounts[name] ?? 0) + 1;

    return helloCounts[name];
}
```

TERMINAL

>

Code Editor

CODE → src/domain/keepHelloCount.ts

```typescript
const helloCounts: Record<string, number> = {};

export async function keepHelloCount(name: string): Promise<number>
{
    helloCounts[name] = (helloCounts[name] ?? 0) + 1;

    return helloCounts[name];
}
```

TERMINAL

>

Code Editor

CODE → src/domain/keepHelloCount.ts

```typescript
const helloCounts: Record<string, number> = {};

export async function keepHelloCount(name: string): Promise<number>
{
    helloCounts[name] = (helloCounts[name] ?? 0) + 1;

    return helloCounts[name];
}
```

TERMINAL

> ▌

Code Editor

CODE → src/domain/sayHello.ts

```typescript
export async function sayHello(name: string): Promise<string>
{
    return `Hello, ${name}!`;
}
```

TERMINAL

>

Code Editor

CODE → src/domain/sayHello.ts

```typescript
export async function sayHello(name: string): Promise<string>
{
    return `Hello, ${name}!`;
}
```

TERMINAL

> █

Code Editor

CODE → src/domain/sayHello.ts

```typescript
export async function sayHello(name: string): Promise<string>
{
    return `Hello, ${name}!`;
}
```

TERMINAL

> █

Code Editor

CODE → src/domain/sayHello.ts

```typescript
import { keepHelloCount } from './keepHelloCount';

export async function sayHello(name: string): Promise<string>
{
    return `Hello, ${name}!`;
}
```

TERMINAL

>

Code Editor

CODE → src/domain/sayHello.ts

```typescript
import { keepHelloCount } from './keepHelloCount';

export async function sayHello(name: string): Promise<string>
{

    return `Hello, ${name}!`;
}
```

TERMINAL

> ▮

Code Editor

CODE → src/domain/sayHello.ts

```typescript
import { keepHelloCount } from './keepHelloCount';

export async function sayHello(name: string): Promise<string>
{


    return `Hello, ${name}!`;
}
```

TERMINAL

> █

Code Editor

CODE → src/domain/sayHello.ts

```typescript
import { keepHelloCount } from './keepHelloCount';

export async function sayHello(name: string): Promise<string>
{
    const count = await keepHelloCount(name);

    return `Hello, ${name}!`;
}
```

TERMINAL

>

Code Editor

CODE → src/domain/sayHello.ts

```typescript
import { keepHelloCount } from './keepHelloCount';

export async function sayHello(name: string): Promise<string>
{
    const count = await keepHelloCount(name);

    return `Hello, ${name} ${count}!`;
}
```

TERMINAL

> ▮

Code Editor

CODE → src/domain/sayHello.ts

```typescript
import { keepHelloCount } from './keepHelloCount';

export async function sayHello(name: string): Promise<string>
{
    const count = await keepHelloCount(name);

    return `Hello, ${name} ${count}!`;
}
```

TERMINAL

> █