


```
"dev": "vite",
"build": "npm run build-domain && npm run build-webui",
"build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
"build-webui": "vite build",
"standalone": "jitar start --service=services/standalone.json",
"data": "jitar start --service=services/data-worker.json",
"default": "jitar start --service=services/default-worker.json",
"gateway": "jitar start --service=services/gateway.json",
"repository": "jitar start --service=services/repository.json",
"proxy": "jitar start --service=services/proxy.json"
```

TERMINAL




~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3000
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
```

```
> gateway
> repository
> proxy
> data
> default
```

```
type: module,  
"scripts":  
{  
  "dev": "vite",  
  "build": "npm run build-domain && npm run build-webui",  
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",  
  "build-webui": "vite build",  
  "standalone": "jitar start --service=services/standalone.json",  
  "data": "jitar start --service=services/data-worker.json",  
  "default": "jitar start --service=services/default-worker.json",  
  "gateway": "jitar start --service=services/gateway.json",  
  "repository": "jitar start --service=services/repository.json",  
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL




~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3000  
[INFO] Provided web client  
[INFO] Ran request: domain/sayHello  
█
```

- > gateway
- > repository
- > proxy
- > data
- > default

```
"version": "0.0.0",
"type": "module",
"scripts":
{
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
  "repository": "jitar start --service=services/repository.json",
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL



~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3000
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
```

```
> gateway
> repository
> proxy
> data
> default
```


EXPLORER

- app
 - public
 - segments
 - services
 - data-worker.json
 - default-worker.json
 - gateway.json
 - proxy.json
 - repository.json
 - standalone.json
 - src
- domain
 - keepHelloCount.ts
 - sayHello.ts

CODE → package.json

```
"version": "0.0.0",
"type": "module",
"scripts":
{
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
  "repository": "jitar start --service=services/repository.json",
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL



~ Distributed JavaScript Runtime ~













```
[INFO] Server started at http://127.0.0.1:3000
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
```

- > gateway
- > repository
- > proxy
- > data
- > default



Code Editor


EXPLORER

- ✓  app
 - >  public
 - >  segments
 - ✓  services
 -  data-worker.json
 -  default-worker.json
 -  gateway.json
 -  proxy.json
 -  repository.json
 -  standalone.json
 - ✓  src
 - ✓  domain
 -  keepHelloCount.ts
 -  sayHello.ts

CODE → package.json

```
"version": "0.0.0",
"type": "module",
"scripts":
{
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
  "repository": "jitar start --service=services/repository.json",
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL



~ Distributed JavaScript Runtime ~














```
[INFO] Server started at http://127.0.0.1:3000
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
```

-  gateway
- >_ repository
- >_ proxy
- >_ data
- >_ default



Code Editor


EXPLORER

- ✓  app
 - >  public
 - >  segments
 - ✓  services
 -  data-worker.json
 -  default-worker.json
 -  gateway.json
 -  proxy.json
 -  repository.json
 -  standalone.json
 - ✓  src
 - ✓  domain
 -  keepHelloCount.ts
 -  sayHello.ts

CODE → package.json

```
"version": "0.0.0",
"type": "module",
"scripts":
{
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
  "repository": "jitar start --service=services/repository.json",
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL



~ Distributed JavaScript Runtime ~












```
[INFO] Server started at http://127.0.0.1:3000
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
```

- > gateway
- > repository
- > proxy
- > data
- > default



Code Editor


EXPLORER

- ✓  app
 - >  public
 - >  segments
 - ✓  services
 -  data-worker.json
 -  default-worker.json
 -  gateway.json
 -  proxy.json
 -  repository.json
 -  standalone.json
 - ✓  src
 - ✓  domain
 -  keepHelloCount.ts
 -  sayHello.ts

CODE → package.json

```
"version": "0.0.0",
"type": "module",
"scripts":
{
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
  "repository": "jitar start --service=services/repository.json",
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL



~ Distributed JavaScript Runtime ~















```
[INFO] Server started at http://127.0.0.1:3000
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
```

- > gateway
- > repository
- > proxy
- > data
- > default



Code Editor


EXPLORER

- ✓  app
 - >  public
 - >  segments
 - ✓  services
 -  data-worker.json
 -  default-worker.json
 -  gateway.json
 -  proxy.json
 -  repository.json
 -  standalone.json
 - ✓  src
 - ✓  domain
 -  keepHelloCount.ts
 -  sayHello.ts

CODE → package.json

```
"version": "0.0.0",
"type": "module",
"scripts":
{
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
  "repository": "jitar start --service=services/repository.json",
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL



~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3000
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
```

- > gateway
- > repository
- > proxy
- > data
- > default



Code Editor


EXPLORER

- ✓ app
- > public
- > segments
- ✓ services
 - data-worker.json
 - default-worker.json
 - gateway.json
 - proxy.json
 - repository.json
 - standalone.json
- ✓ src
- ✓ domain
 - TS keepHelloCount.ts
 - TS sayHello.ts

CODE → package.json

```
"version": "0.0.0",
"type": "module",
"scripts":
{
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
  "repository": "jitar start --service=services/repository.json",
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL



~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3000
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
```

- > gateway
- > repository
- > proxy
- > data
- > default

Code Editor


EXPLORER

- ✓ app
 - > public
 - > segments
 - ✓ services
 - data-worker.json
 - default-worker.json
 - gateway.json
 - proxy.json
 - repository.json
 - standalone.json
 - ✓ src
 - domain
 - keepHelloCount.ts
 - sayHello.ts

CODE → package.json

```
"version": "0.0.0",
"type": "module",
"scripts":
{
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
  "repository": "jitar start --service=services/repository.json",
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL



~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3000
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
```

- > gateway
- > repository
- > proxy
- > data
- > default

Code Editor


EXPLORER

- app
 - public
 - segments
 - services
 - data-worker.json
 - default-worker.json
 - gateway.json
 - proxy.json
 - repository.json
 - standalone.json
 - src
 - domain
 - keepHelloCount.ts
 - sayHello.ts

CODE → package.json

```
"version": "0.0.0",
"type": "module",
"scripts":
{
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
  "repository": "jitar start --service=services/repository.json",
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL



~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3000
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
```

- > gateway
- > repository
- > proxy
- > data
- > default

Code Editor


EXPLORER

- ✓ app
 - > public
 - > segments
- ✓ services
 - {} data-worker.json
 - {} default-worker.json
 - {} gateway.json
 - {} proxy.json
 - {} repository.json
 - {} standalone.json
- ✓ src
- ✓ domain
 - TS keepHelloCount.ts
 - TS sayHello.ts

CODE → package.json

```
"version": "0.0.0",
"type": "module",
"scripts":
{
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
  "repository": "jitar start --service=services/repository.json",
  "proxy": "jitar start --service=services/proxy.json"
```

TERMINAL



~ Distributed JavaScript Runtime ~

```
[INFO] Server started at http://127.0.0.1:3000
[INFO] Provided web client
[INFO] Ran request: domain/sayHello
```

- > gateway
- > repository
- > proxy
- > data
- > default

EXPLORER

✓

app

>

public

>

segments

✓

services

data-worker.json

default-worker.json

gateway.json

proxy.json

repository.json

standalone.json

✓

src

✓

domain

TS

keepHelloCount.ts


TS

sayHello.ts

CODE → package.json

```
"version": "0.0.0",
"type": "module",
"scripts": {
  "dev": "vite",
  "build": "npm run build-domain && npm run build-webui",
  "build-domain": "rimraf dist && tsc -p tsconfig.build.json && jitar build",
  "build-webui": "vite build",
  "standalone": "jitar start --service=services/standalone.json",
  "data": "jitar start --service=services/data-worker.json",
  "default": "jitar start --service=services/default-worker.json",
  "gateway": "jitar start --service=services/gateway.json",
  "repository": "jitar start --service=services/repository.json",
  "proxy": "jitar start --service=services/proxy.json"
}
```

TERMINAL



~ Distributed JavaScript Runtime ~

[INFO] Server started at http://127.0.0.1:3000

[INFO] Provided web client

[INFO] Ran request: domain/sayHello


> gateway

> repository

> proxy

> data

> default





Code Editor

