

Code Editor

CODE → services/proxy.json

```
{  
  "url": "http://127.0.0.1:3000",  
  "middleware": [ "./middleware/serverAuth" ],  
  "proxy":  
  {  
    "gateway": "http://127.0.0.1:3001",  
    "repository": "http://127.0.0.1:3002",  
  }  
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

>_ gateway

>_ default

>_ data

Code Editor

CODE → services/proxy.json

```
{
  "url": "http://127.0.0.1:3000",
  "middleware": [ "./middleware/serverAuth" ],
  "proxy": {
    "gateway": "http://127.0.0.1:3001",
    "repository": "http://127.0.0.1:3002",
  }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

[INFO] ... http://127.0.0.1:3001

> gateway

> default

> data

CODE → services/proxy.json

```
{
  "url": "http://127.0.0.1:3000",
  "middleware": [ "./middleware/serverAuth" ],
  "proxy": {
    "gateway": "http://127.0.0.1:3001",
    "repository": "http://127.0.0.1:3002",
  }
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

[INFO] Server started at http://127.0.0.1:4001

[INFO] RPC procedures: [

>_ gateway

>_ default

>_ data

```
{  
  "url": "http://127.0.0.1:3000",  
  "middleware": [ "./middleware/serverAuth" ],  
  "proxy":  
  {  
    "gateway": "http://127.0.0.1:3001",  
    "repository": "http://127.0.0.1:3002",  
  }  
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

[INFO] Server started at http://127.0.0.1:4001

[INFO] RPC procedures: [
 domain/keepHelloCount

]

[INFO] Pan request: domain/keepHelloCount

> gateway

> default

> data

```
"middleware": [ "./middleware/serverAuth" ],
"proxy":
{
  "gateway": "http://127.0.0.1:3001",
  "repository": "http://127.0.0.1:3002",
}
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

[INFO] Server started at http://127.0.0.1:4001

[INFO] RPC procedures: [
 domain/keepHelloCount

]

[INFO] Ran request: domain/keepHelloCount

[WARN] Denied untrusted request: domain/keepHelloCount

>_ gateway

>_ default

>_ data

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

~ Distributed JavaScript Runtime ~

[INFO] Server started at http://127.0.0.1:4001

[INFO] RPC procedures: [
 domain/keepHelloCount

]

[INFO] Ran request: domain/keepHelloCount

[WARN] Denied untrusted request: domain/keepHelloCount



> gateway

> default

> data

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> █

>_ gateway

>_ default

>_ data

>_ terminal

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run repository

> gateway

> default

> data

> terminal


```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run repository



- > gateway
- > default
- > data
- > repository

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run repository




- > gateway
- > default
- > data
- > repository

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run repository



> gateway

> default


> data

> repository

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run repository



> gateway

> default


> data

> repository

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run repository



> gateway

> default


> data

> repository

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run repository




- > gateway
- > default
- > data
- > repository

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run repository




- > gateway
- > default
- > data
- > repository

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run repository




```
> gateway  
> default  
> data  
> repository
```



```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL




~ Distributed JavaScript Runtime ~



```
> gateway  
> default  
> data  
> repository
```

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL




~ Distributed JavaScript Runtime ~



```
> gateway  
> default  
> data  
> repository
```

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL



~ Distributed JavaScript Runtime ~

[INFO] Server started at http://127.0.0.1:3002

```
> gateway  
> default  
> data  
> repository
```

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> 

- > gateway
- > default
- > data
- > repository
- > terminal

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run proxy

- > gateway
- > default
- > data
- > repository
- > terminal

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run proxy



- > gateway
- > default
- > data
- > repository
- > proxy

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run proxy




- > gateway
- > default
- > data
- > repository
- > proxy

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

```
app> npm run proxy
```




- > gateway
- > default
- > data
- > repository
- > proxy


```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run proxy




- > gateway
- > default
- > data
- > repository
- > proxy

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

```
app> npm run proxy
```




- > gateway
- > default
- > data
- > repository
- > proxy

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run proxy




- > gateway
- > default
- > data
- > repository
- > proxy

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL

app> npm run proxy




- > gateway
- > default
- > data
- > repository
- > proxy

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL


app> npm run proxy



```
> gateway  
> default  
> data  
> repository  
> proxy
```

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL




~ Distributed JavaScript Runtime ~



```
> gateway  
> default  
> data  
> repository  
> proxy
```

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL




~ Distributed JavaScript Runtime ~



```
> gateway  
> default  
> data  
> repository  
> proxy
```

```
{  
  "gateway": "http://127.0.0.1:3001",  
  "repository": "http://127.0.0.1:3002",  
}
```

TERMINAL



~ Distributed JavaScript Runtime ~

[INFO] Server started at http://127.0.0.1:3000
█

```
> gateway  
> default  
> data  
> repository  
> proxy
```