

MCUXSDKMIMXRT118XKRN

MCUXpresso SDK Release Notes for MIMXRT1180-EVK

Rev. 6 — 7 February 2024

Release notes

Document information

Information	Content
Keywords	MCUXSDKMIMXRT118XKRN, Release Notes, MIMXRT1180-EVK
Abstract	This document describes the MCUXpresso SDK release notes for MIMXRT1180-EVK.



1 Overview

The MCUXpresso SDK is a comprehensive software enablement package designed to simplify and accelerate application development with Arm Cortex-M-based devices from NXP, including its general purpose, crossover and Bluetooth-enabled MCUs.

MCUXpresso SW and Tools further extend the SDK support to the i.MX counterparts. The MCUXpresso SDK includes production-grade software with integrated RTOS (optional), integrated enabling software technologies (stacks and middleware), reference software, and more.

In addition to working seamlessly with the MCUXpresso IDE, the MCUXpresso SDK also supports and provides example projects for IAR, KEIL, and GCC with Cmake. Support for the MCUXpresso Config Tools allows easy cloning of existing SDK examples and demos, allowing users to leverage the existing software examples provided by the SDK for their own projects.

Underscoring our commitment to high quality, the MCUXpresso SDK is MISRA compliant and checked with Coverity static analysis tools. For details on MCUXpresso SDK, see [MCUXpresso-SDK: Software Development Kit for MCUXpresso](#).

2 MCUXpresso SDK

As part of the MCUXpresso software and tools, MCUXpresso SDK is the evolution of Kinetis SDK, includes support for LPC, DSC, and i.MX System-on-Chip (SoC). The same drivers, APIs, and middleware are still available with support for Kinetis, LPC, DSC, and i.MX silicon. The MCUXpresso SDK adds support for the MCUXpresso IDE, an Eclipse-based toolchain that works with all MCUXpresso SDKs. Easily import your SDK into the new toolchain to access to all of the available components, examples, and demos for your target silicon. In addition to the MCUXpresso IDE, support for the MCUXpresso Config Tools allows easy cloning of existing SDK examples and demos, allowing users to leverage the existing software examples provided by the SDK for their own projects.

In order to maintain compatibility with legacy Freescale code, the filenames and source code in MCUXpresso SDK containing the legacy Freescale prefix FSL has been left as is. The FSL prefix has been redefined as the NXP Foundation Software Library.

3 Development tools

The MCUXpresso SDK is compiled and tested with these development tools:

- GCC Arm Embedded, and the version is 12.3.1.
- IAR Embedded Workbench for Arm, and the version is 9.50.1.
- MCUXpresso IDE, and the version is 11.9.0.
- Keil MDK, and the version is 5.38.

Note:

- *Segger JLink software is also needed for debugging via the JLink debug interface. The lowest required version is 7.94g.*
- *IAR will release the service pack in Q1, 2024, which will provide an out of box support for RT1180. Contact NXP for a supporting patch, if you are using 9.50.1.*

4 Supported development system

[Table 1](#) lists boards and devices supported in this release. The boards and devices in bold were tested in this release.

Table 1. Supported boards and devices

Development boards	MCU devices
MIMXRT1180-EVK	MIMXRT1189CVM8B , MIMXRT1189XVM8B, MIMXRT1187CVM8B, MIMXRT1187XVM8B, MIMXRT1182CVP2B, MIMXRT1182XVP2B, MIMXRT1181CVP2B, MIMXRT1181XVP2B

5 MCUXpresso SDK release package

The MCUXpresso SDK release package content is aligned with the silicon subfamily it supports. This includes the boards, devices, documentation, and middleware.

5.1 Device support

The device folder contains the whole software enablement available for the specific System-on-Chip (SoC) subfamily. This folder includes clock-specific implementation, device register header files, device register feature header files, and the system configuration source files. Included with the standard SoC support are folders containing peripheral drivers, toolchain support, and a standard debug console. The device-specific header files provide a direct access to the microcontroller peripheral registers. The device header file provides an overall SoC memory mapped register definition. The folder also includes the feature header file for each peripheral on the microcontroller. The toolchain folder contains the startup code and linker files for each supported toolchain. The startup code efficiently transfers the code execution to the main() function.

5.2 Board support

The boards folder provides the board-specific demo applications, driver examples, and middleware examples.

5.3 Demo application and other examples

The demo applications demonstrate the usage of the peripheral drivers to achieve a system level solution. Each demo application contains a readme file that describes the operation of the demo and required setup steps. The driver examples demonstrate the capabilities of the peripheral drivers. Each example implements a common use case to help demonstrate the driver functionality.

6 Middleware

6.1 aws_iot

Amazon Web Service (AWS) IoT Core SDK

6.2 Dhara

Dhara is a small flash translation layer designed for use in resource-constrained systems for managing NAND flash.

6.3 edgefast_bluetooth

EdgeFast Protocol Abstraction Layer

6.4 elQ

elQ machine learning SDK containing:

- Arm CMSIS-NN library (neural network kernels optimized for Cortex-M cores)
- Inference engines:
 - TensorFlow Lite Micro
- Example code for TensorFlow Lite Micro

6.5 fatfs

The FatFs file system is integrated with the MCUXpresso SDK and can be used to access either the SD card or the USB memory stick when the SD card driver or the USB Mass Storage Device class implementation is used.

6.6 freemaster

FreeMASTER communication driver for 32-bit platforms.

6.7 LittleFS

A little fail-safe filesystem (LittleFS) designed for microcontrollers.

6.8 llhttp

HTTP parser in LLVM IR

6.9 lwip

The lwIP TCP/IP stack is pre-integrated with MCUXpresso SDK and runs on top of the MCUXpresso SDK Ethernet driver with Ethernet-capable devices/boards.

6.10 mbedtls

mbedtls SSL/TLS library

6.11 mcu-boot

Software for Bootloaders,Flashloaders and host tools

6.12 mcuboot_opensource

A generic bootloader for microcontrollers

6.13 Motor Control Software (ACIM, BLDC, PMSM)

Motor control examples

6.14 multicore

Multicore Software Development Kit.

6.15 NXP Wi-Fi

The MCUXpresso SDK provides driver for NXP Wi-Fi external modules. The Wi-Fi driver is integrated with LWIP TCPIP stack and demonstrated with several network applications (iperf and AWS IoT).

For more information, see *Getting Started with NXP based Wireless Modules and i.MX RT Platform Running on RTOS* (document [UM11441](#))

6.16 pkcs11

Public Key Cryptography Standard #11 defines generic cryptographic token interface.

6.17 PSA Test Suite

Arm Platform Security Architecture (PSA) Test Suite.

6.18 rtcesl

Real-time control embedded software library.

6.19 sdmmc stack

The SDMMC software is integrated with MCUXpresso SDK to support SD/MMC/SDIO standard specification. This also includes a host adapter layer for bare-metal/RTOS applications.

6.20 Simple Open EtherCAT Master

Simple Open EtherCAT Master (SOEM) is an open source EtherCAT master stack that is used to write custom EtherCAT Master applications. For more information on how to use SOEM, see the *Getting Started with MCUXpresso SDK for SOEM* document.

6.21 TF-M

Trusted Firmware - M library.

6.22 TinyCBOR

Tiny Concise Binary Object Representation (CBOR) library.

6.23 USB Host, Device, OTG Stack

For more information, see *MCUXpresso SDK USB Stack User's Guide* (document MCUXSDKUSBSUG).

7 Release contents

[Table 2](#) provides an overview of the MCUXpresso SDK release package contents and locations.

Table 2. MCUXpresso SDK release package contents and locations

Deliverable	Location
Boards	INSTALL_DIR/boards
Demo Applications	INSTALL_DIR/boards/<board_name>/demo_apps
Driver Examples	INSTALL_DIR/boards/<board_name>/driver_examples
Board Project Template for MCUXpresso IDE NPW	INSTALL_DIR/boards/<board_name>/project_template
Driver, SoC header files, extension header files and feature header files, utilities	INSTALL_DIR/devices/<device_name>
CMSIS drivers	INSTALL_DIR/devices/<device_name>/cmsis_drivers
Peripheral drivers	INSTALL_DIR/devices/<device_name>/drivers
Toolchain linker files and startup code	INSTALL_DIR/devices/<device_name>/<toolchain_name>
Utilities such as debug console	INSTALL_DIR/devices/<device_name>/utilities
Device Project Template for MCUXpresso IDE NPW	INSTALL_DIR/devices/<device_name>/project_template
CMSIS Arm Cortex-M header files, DSP library source	INSTALL_DIR/CMSIS
Components and board device drivers	INSTALL_DIR/components
EdgeLock Enclave (ELE) firmware	INSTALL_DIR/firmware/edgeloock
RTOS	INSTALL_DIR/rtos
Release Notes, Getting Started Document and other documents	INSTALL_DIR/docs
Tools such as shared cmake files	INSTALL_DIR/tools
Middleware	INSTALL_DIR/middleware

8 MISRA compliance

All MCUXpresso SDK drivers comply to MISRA 2012 rules with exceptions in [Table 3](#).

Table 3. MISRA exception rules

Exception rules	Description
Directive 4.4	Sections of code should not be commented out.
Directive 4.5	Identifiers in the same name space with overlapping visibility should be typographically unambiguous.
Directive 4.6	Typedefs that indicate size and signedness should be used in place of the basic numerical types.
Directive 4.8	If a pointer to a structure or union is never dereferenced within a translation unit, then the implementation of the object should be hidden.
Directive 4.9	A function should be used in preference to a function-like macro where they are interchangeable.
Directive 4.13	Functions which are designed to provide operations on a resource should be called in an appropriate sequence.
Rule 1.2	Language extensions should not be used.
Rule 2.3	A project should not contain unused type declarations.
Rule 2.4	A project should not contain unused tag declarations.
Rule 2.5	A project should not contain unused macro declarations.
Rule 2.6	A function should not contain unused label declarations.
Rule 2.7	There should be no unused parameters in functions.
Rule 4.2	Trigraphs should not be used.
Rule 5.1	External identifiers shall be distinct.
Rule 5.4	Macro identifiers shall be distinct.
Rule 5.9	Identifiers that define objects or functions with internal linkage should be unique.
Rule 8.7	Functions and objects should not be defined with external linkage if they are referenced in only one translation unit.
Rule 8.9	An object should be defined at block scope if its identifier only appears in a single function.
Rule 8.11	When an array with external linkage is declared, its size should be explicitly specified.
Rule 8.13	A pointer should point to a const-qualified type whenever possible.
Rule 10.5	The value of an expression should not be cast to an inappropriate essential type.
Rule 11.4	A conversion should not be performed between a pointer to object and an integer type.
Rule 11.5	A conversion should not be performed from pointer to void into pointer to object.
Rule 12.1	The precedence of operators within expressions should be made explicit.
Rule 12.3	The comma operator should not be used.
Rule 12.4	Evaluation of constant expressions should not lead to unsigned integer wrap-around.
Rule 13.3	A full expression containing an increment (++) or decrement (–) operator should have no other potential side effects other than that caused by the increment or decrement operator.
Rule 15.4	There should be no more than one break or go to statement used to terminate any iteration statement.

Table 3. MISRA exception rules...continued

Exception rules	Description
Rule 17.5	The function argument corresponding to a parameter declared to have an array type shall have an appropriate number of elements.
Rule 17.8	A function parameter should not be modified.
Rule 19.2	The union keyword should not be used.
Rule 19.2	The union keyword should not be used.
Rule 20.10	The # and ## preprocessor operators should not be used.
Rule 21.1	#define and #undef shall not be used on a reserved identifier or reserved macro name.
Rule 21.2	A reserved identifier or macro name shall not be declared.
Rule 21.12	The exception handling features of <fenv.h> should not be used.

9 Known issues

This section lists the known issues, limitations, and/or workarounds.

9.1 Maximum file path length in Windows 7 operating system

The Windows 7 operating system imposes a 260-character maximum length for file paths. When installing the MCUXpresso SDK, place it in a directory close to the root to prevent file paths from exceeding the maximum character length specified by the Windows operating system. The recommended location is the `C:\<folder>`.

9.2 Segger version

The lowest required J-Link version is v7.94g.

9.3 AWS examples are not fully tested

The examples under `boards/evkmimxrt1180/aws_examples` are not fully tested. The associated features and functionalities are only for the evaluation purpose. Full feature verification will be covered in a future release.

9.4 Missing fsl_cache when create new project with board or kit

When creating a new C/C++ project, if `evkmimxrt1180` or `evkmimxrt1180_om13790host` kit is selected, `fsl_cache` component gets missed and causes build failure. To avoid the build failure, manually select it in **SDK Wizard** page.




Figure 1. Manually select cache component in the SDK wizard

9.5 Misra/Coverity issues

There are several Misra/Coverity issues in the following source code, to be fixed in future releases.

Table 4. Misra issues

Source code location	Possible violation rule	Number of issues
devices/MIMXRT1189/drivers/fsl_tstmr.h	Rule 10.4	1
components/flash/nor/flexspi/fsl_flexspi_nor_flash.c	Rule 9.3	1
components/edgefast_wifi/source/wpl_nxp.c	Rule 10.3, 17.7, 21.6	10

Table 5. Coverity Issues

Source code location	Possible violation rule	Number of issues
middleware/mbedtls3x/port/ele_s4xx/src/opaque/mcux_psa_s4xx_opaque_asymmetric_signature.c	Uninitialized Variables	2
middleware/mbedtls/port/ele_s400/ecc_opaque/ecdsa_alt.c	Uninitialized Variables	2
middleware/wifi_nxp/wifidriver/mlan_glue.c	Memory - corruptions	1

Note: Related tickets are: MCUX-66358, MCUX-66527, MCUX-66528, MCUX-66529.

9.6 Debugging problems

When debugging `hyperram_txt_debug` or `hyperram_txt_release` target, user may encounter issue when debug with breakpoint. The reason is because code is cached. The default breakpoint type is auto/software breakpoint, it will lead soc core and debugger misaligned. As a workaround, please set breakpoint type to hardware breakpoint.

9.7 Other issues

The following are additional known issues in this release.

Table 6. Various other known issues

Ticket	Description	History
MCUX-66649	Build erros when create new project wizard with various component	2.15.000 RT1180
MCUX-65840	Semihost terminal is not working well with JLink	2.15.000 RT1180
MCUX-66342	Edgefast <code>handsfree_ag</code> has a probability of not working properly on MCUX and ARMGCC toolchain	2.15.000 RT1180
MCUX-66442	Edgefast <code>a2dp_sink</code> does not work properly on release target of MDK toolchain	2.15.000 RT1180
MCUX-65874	WIFI <code>wifi_cli</code> and <code>wifi_wpa_supPLICant</code> will show no iperf summary in UDP server mode with both ipv4 and ipv6 in CM33 core	2.15.000 RT1180
MCUX-65801	SPDIF demo has background noise	2.15.000 RT1180

10 Revision history

[Table 7](#) summarizes the revisions to this document.

Table 7. Revision history

Revision number	Release date	Description
6	07 February 2024	Updated for MCUXpresso SDK 2.15.000 RT1180 B0 RFP release <ul style="list-style-type: none">Updated Section 3 "Development tools"Added known issues:<ul style="list-style-type: none">– Section 9.2 "Segger version"– Section 9.3 "AWS examples are not fully tested"– Section 9.4 "Missing fsl_cache when create new project with board or kit"– Section 9.5 "Misra/Coverity issues"– Section 9.6 "Debugging problems"– Section 9.7 "Other issues"
5	16 November 2023	Updated for MCUXpresso SDK 2.14.2 RT1180 B0 EAR2 release <ul style="list-style-type: none">Updated Section 4
4	29 August 2023	Updated for MCUXpresso SDK 2.14.0 RT1180 B0 EAR1 release <ul style="list-style-type: none">Updated Section 3Updated Section 4
3	17 February 2023	Updated for MCUXpresso SDK 2.13 RT1180 RFP release <ul style="list-style-type: none">Updated Section 3Updated Section 7Updated Section 9
2	23 September 2022	Updated for MCUXpresso SDK 2.12.0 RT1180 PRC release <ul style="list-style-type: none">Updated Section 3Updated Section 4
1	08 July 2022	Updated for MCUXpresso SDK 2.11.3 RT1180 EAR2.0 release <ul style="list-style-type: none">Updated Section 3
0	18 March 2022	Initial release

Legal information

Definitions

Draft — A draft status on a document indicates that the content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included in a draft version of a document and shall have no liability for the consequences of use of such information.

Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors and its suppliers accept no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Terms and conditions of commercial sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.nxp.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Suitability for use in non-automotive qualified products — Unless this document expressly states that this specific NXP Semiconductors product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. NXP Semiconductors accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without NXP Semiconductors' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond NXP Semiconductors' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies NXP Semiconductors for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond NXP Semiconductors' standard warranty and NXP Semiconductors' product specifications.

Translations — A non-English (translated) version of a document, including the legal information in that document, is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

Security — Customer understands that all NXP products may be subject to unidentified vulnerabilities or may support established security standards or specifications with known limitations. Customer is responsible for the design and operation of its applications and products throughout their lifecycles to reduce the effect of these vulnerabilities on customer's applications and products. Customer's responsibility also extends to other open and/or proprietary technologies supported by NXP products for use in customer's applications. NXP accepts no liability for any vulnerability. Customer should regularly check security updates from NXP and follow up appropriately. Customer shall select products with security features that best meet rules, regulations, and standards of the intended application and make the ultimate design decisions regarding its products and is solely responsible for compliance with all legal, regulatory, and security related requirements concerning its products, regardless of any information or support that may be provided by NXP.

NXP has a Product Security Incident Response Team (PSIRT) (reachable at PSIRT@nxp.com) that manages the investigation, reporting, and solution release to security vulnerabilities of NXP products.

NXP B.V. — NXP B.V. is not an operating company and it does not distribute or sell products.

Trademarks

Notice: All referenced brands, product names, service names, and trademarks are the property of their respective owners.

NXP — wordmark and logo are trademarks of NXP B.V.

Amazon Web Services, AWS, the Powered by AWS logo, and FreeRTOS — are trademarks of Amazon.com, Inc. or its affiliates.

AMBA, Arm, Arm7, Arm7TDMI, Arm9, Arm11, Artisan, big.LITTLE, Cordio, CoreLink, CoreSight, Cortex, DesignStart, DynamIQ, Jazelle, Keil, Mali, Mbed, Mbed Enabled, NEON, POP, RealView, SecurCore, Socrates, Thumb, TrustZone, ULINK, ULINK2, ULINK-ME, ULINK-PLUS, ULINKpro, µVision, Versatile — are trademarks and/or registered trademarks of Arm Limited (or its subsidiaries or affiliates) in the US and/or elsewhere. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved.

Bluetooth — the Bluetooth wordmark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by NXP Semiconductors is under license.

EDGEFAST — is a trademark of NXP B.V.

eIQ — is a trademark of NXP B.V.

Freescale — is a trademark of NXP B.V.

IAR — is a trademark of IAR Systems AB.

i.MX — is a trademark of NXP B.V.

J-Link — is a trademark of SEGGER Microcontroller GmbH.

Kinetis — is a trademark of NXP B.V.

TensorFlow, the TensorFlow logo and any related marks — are trademarks of Google Inc.

Tables

Tab. 1.	Supported boards and devices	3	Tab. 4.	Misra issues	9
Tab. 2.	MCUXpresso SDK release package contents and locations	6	Tab. 5.	Coverity Issues	10
Tab. 3.	MISRA exception rules	7	Tab. 6.	Various other known issues	10
			Tab. 7.	Revision history	11

Figures

Fig. 1.	Manually select cache component in the SDK wizard	9
---------	--	---

Contents

1	Overview	2
2	MCUXpresso SDK	2
3	Development tools	2
4	Supported development system	3
5	MCUXpresso SDK release package	3
5.1	Device support	3
5.2	Board support	3
5.3	Demo application and other examples	3
6	Middleware	3
6.1	aws_iot	3
6.2	Dhara	3
6.3	edgefast_bluetooth	4
6.4	elQ	4
6.5	fatfs	4
6.6	freemaster	4
6.7	LittleFS	4
6.8	llhttp	4
6.9	lwip	4
6.10	mbedtls	4
6.11	mcu-boot	4
6.12	mcuboot_opensource	4
6.13	Motor Control Software (ACIM, BLDC, PMSM)	4
6.14	multicore	5
6.15	NXP Wi-Fi	5
6.16	pkcs11	5
6.17	PSA Test Suite	5
6.18	rtcs1	5
6.19	sdmmc stack	5
6.20	Simple Open EtherCAT Master	5
6.21	TF-M	5
6.22	TinyCBOR	5
6.23	USB Host, Device, OTG Stack	5
7	Release contents	5
8	MISRA compliance	7
9	Known issues	8
9.1	Maximum file path length in Windows 7 operating system	8
9.2	Segger version	8
9.3	AWS examples are not fully tested	8
9.4	Missing fsl_cache when create new project with board or kit	8
9.5	Misra/Coverity issues	9
9.6	Debugging problems	10
9.7	Other issues	10
10	Revision history	11
	Legal information	12

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.