MCUXpresso SDK Release Notes Supporting evkmimxrt685

Change Logs

NXP Semiconductors

Contents

Driver Change Log

Middleware Change Log

Component Change Log

1 Driver Change Log

CLOCK

The current CLOCK driver version is 2.7.2.

- 2.7.2
  - **–** Bug Fixes
    - ∗ Added clock name array for PUF, HashCrypt and Casper.
- 2.7.1
  - **–** Improvements
    - ∗ Added lost comments for some enumerations.
- 2.7.0
  - **–** Bug Fixes
    - ∗ Updated enum sys_pll_mult_t and audio_pll_mult_t to fix the supported MULT values for PLLs.
    - ∗ Supported more APIs for DSP core.
- 2.6.1
  - **–** New feature
    - ∗ Added CLOCK_SetClkinFreq API.
  - **–** Other Changes
    - ∗ Rmove main_clk from UTICK,WWDT0/1 clock attach define.
  - **–** Bug Fixes
    - ∗ Fixed violations of MISRA C-2012 rules.
- 2.6.0
  - **–** API change
    - ∗ Added enableLowPower parameter in CLOCK_EnableSysOscClk().
    - ∗ Added id parameter in CLOCK_GetSdioClkFreq().
  - **–** Other Changes
    - ∗ Fixed C++ build errors.
    - ∗ Added sdio1 and flexcomm6,7 clock support.
    - ∗ Added syspll pfd clock dividers define.
    - ∗ Updated register access per the B0 header file's change.
    - ∗ Added assert in CLOCK_SetFRGClock(), the FRG DIV should be always set to 0xFF according to User Manual.
- 2.5.0
  - **–** New feature
    - ∗ Moved SDK_DelayAtLeastUs function from clock driver to common driver.
- 2.4.1
  - **–** Bug Fixes
    - ∗ Avoided waiting REQFLAG when divider configured to HALT in CLOCK_SetClkDiv().
- 2.4.0
  - **–** Modify Audio PLL mult parameter range.
  - **–** Update get mclk_in api.

- 2.3.0
    - New feature
        * Adding Deinit PLL&PFD API.
    - API change
        * Add delay_us parameter in CLOCK_EnableSysOscClk()
- 2.2.0
    - Update I3C and SDIO clock get API.
    - Modify wwdt clock API name.
- 2.1.1
    - Update PLL initialization function.
- 2.1.0
    - New feature
        * Adding new API CLOCK_DelayAtLeastUs() implemented by DWT to allow users set delay in unit of microsecond.
- 2.0.5
    - Clean up 3 USB clock enable APIs;
- 2.0.4
    - New feature
        * add get mclk_in api.
    - Bug Fixes
        * The Systick clock value should not be divided except choose main clock.
- 2.0.3
    - Update according to UM 0.7.
- 2.0.2
    - some minor fixes.
- 2.0.0
    - initial version.

POWER

The current POWER driver version is 2.5.0.

- 2.5.0
    - New feature
        * Added new API POWER_PmicPowerModeSelectControl() to allow users changing VD-D1V8 and VDDCore state for various PMIC modes.
- 2.4.0
    - New feature
        * Added new API POWER_SetVddCoreSupplySrc(), POWER_SetPmicCoreSupplyFunc() and POWER_SetVoltageForFreq() to allow users set VDDCORE voltage using a unified API with minimum volatage value.
- 2.3.2
    - Bug Fixes
        * Fixed MISRA issue in function POWER_GetLibVersion.

- 2.3.1
  - Bug Fixes
    * Fixed the return value of function countPartitionSwitches.
- 2.3.0
  - API change: POWER_SetLdoVoltageForFreq()
    * Changed power_part_temp_range_t. 70C->85C.
    * Added parameter power_volt_op_range_t.
    * Changed main clock freq parameter to cpu clock freq.
    * Added return value to indicate success or failure.
  - Optimization
    * Turn on all memory partitions simultaneously on deep sleep wakeup to save time.
  - Release in source code instead of in library.
- 2.2.1
  - Exposed POWER_DisableLVD() and POWER_RestoreLVD() APIs in header.
  - Added PMIC_VDDCORE_RECOVERY_TIME_IGNORE macro for POWER_UpdatePmic-RecoveryTime() API.
  - Adjusted main frequency table for SetXXXVoltageForFreq() API to match latest B0 data.
- 2.2.0
  - Added parameter to POWER_SetLdoVoltageForFreq to specify part temperature range.
- 2.1.0
  - Updated power library implementation for B0.
  - Added POWER_SetLvdFallingTripVoltage() API.
  - Added POWER_GetLvdFallingTripVoltage() API.
  - Added POWER_UpdatePmicRecoveryTime() API.
- 2.0.3
  - Updated PD_bits per the B0 header file's change.
- 2.0.2
  - Added POWER_SetPadVolRange() API
- 2.0.1
  - Add POWER_UpdateOscSettlingTime() API to set on-board system osc settling time.
- 2.0.0
  - initial version.

RESET

The current RESET driver version is 2.2.0.

- 2.2.0
  - Improvements
    * Add RESET_ReleasePeripheralReset API.
- 2.1.3
  - Bug Fixes
    * Added peripheral reset array for CASPER, PUF, HashCrypt, RNG.
- 2.1.2

- – Bug Fixes
    - ∗ Fixed typo in _RSTCTL_RSTn enumeration's comment.
- 2.1.1
    - – Bug Fixes
        - ∗ Fixed MISRA C-2012 rule 10.6 and rule 16.4.
- 2.1.0
    - – Updated register access per the B0 header file's change.
- 2.0.4
    - – Add SDIO1 and Flexcomm6,7 support.
- 2.0.3
    - – Rename RSTCTRL to RSTCTL.
- 2.0.2
    - – Update according to UM 0.7.
- 2.0.1
    - – Update component full_name to "Reset Driver".
- 2.0.0
    - – initial version.

DSP

The current DSP driver version is 2.1.1.

- 2.1.1
    - – Fixed Misra issue.
- 2.1.0
    - – Allowed multiple calls to DSP_Init.
    - – Removed DSP clock gate operation.
- 2.0.1
    - – Update DSP Init&Deinit function.
- 2.0.0
    - – initial version.

ACMP

The current ACMP driver version is 2.1.0.

- 2.1.0
    - – New Feature
        - ∗ Supported the plateforms which don't have hysteresis mode.
- 2.0.6
    - – Bug Fixes
        - ∗ Fixed the wrong comments, the DAC value should range from 0 to 255.
- 2.0.5
    - – Bug Fixes

* Fixed the out-of-bounds error of Coverity caused by missing an assert sentence to avoid the return value of ACMP_GetInstance() exceeding the array bounds.
* Fixed the violations of MISRA C-2012 rules:
  · Rule 10.1, 14.4, 16.4, 17.7.
- 2.0.4
  - Bug Fixes
    * Avoided changing w1c bit in ACMP_SetRoundRobinPreState().
- 2.0.3
  - New Features
    * Added feature functions for usage of different power domains(1.8 V and 3 V). These functions are first enabled in ULP1. They are about:
      · ACMP_EnableLinkToDAC()
      · ACMP_SetDiscreteModeConfig()
      · ACMP_GetDefaultDiscreteModeConfig()
- 2.0.2
  - Other Changes
    * Changed coding style of peripheral base address from "s_acmpBases" to "s_acmpBase".
- 2.0.1
  - Bug Fixes
    * Fixed bug regarding the function "ACMP_SetRoundRobinConfig". It will not continue execution but returns directly after disabling round robin mode.

CACHE

The current CACHE driver version is 2.0.6.

- 2.0.6
  - Bug Fixes
    * Fixed overflow for CACHE64_GetInstanceByAddr()/CACHE64_CleanCacheBy-Range()/CACHE64_InvalidateCacheByRange() APIs.
- 2.0.5
  - Improvement
    * Made use of FSL_FEATURE_CACHE64_CTRL_HAS_NO_WRITE_BUF feature
- 2.0.4
  - Improvement
    * Disable cache policy feature on SoC without CACHE64_POLSEL IP.
  - Bug Fixes
    * Fixed doxygen issue.
- 2.0.3
  - Bug Fixes
    * Fixed violations of the MISRA C-2012 Rule 10.3.
- 2.0.2
  - Bug Fixes
    * Fixed violations of the MISRA C-2012 Rule 10.1, 10.3, 10.4 and 14.4.

∗ Fixed doxygen issue.
- 2.0.1
  - Improvements
    ∗ Moved CLCR register configuration out of the while loop, it's unnecessary to repeat this operation.
- 2.0.0
  - Initial version.

COMMON

The current COMMON driver version is 2.4.0.

- 2.4.0
  - New Features
    ∗ Added EnableIRQWithPriority, IRQ_SetPriority, and IRQ_ClearPendingIRQ for ARM.
    ∗ Added MSDK_EnableCpuCycleCounter, MSDK_GetCpuCycleCount for ARM.
- 2.3.3
  - New Features
    ∗ Added NETC into status group.
- 2.3.2
  - Improvements
    ∗ Make driver aarch64 compatible
- 2.3.1
  - Bug Fixes
    ∗ Fixed MAKE_VERSION overflow on 16-bit platforms.
- 2.3.0
  - Improvements
    ∗ Split the driver to common part and CPU architecture related part.
- 2.2.10
  - Bug Fixes
    ∗ Fixed the ATOMIC macros build error in cpp files.
- 2.2.9
  - Bug Fixes
    ∗ Fixed MISRA C-2012 issue, 5.6, 5.8, 8.4, 8.5, 8.6, 10.1, 10.4, 17.7, 21.3.
    ∗ Fixed SDK_Malloc issue that not allocate memory with required size.
- 2.2.8
  - Improvements
    ∗ Included stddef.h header file for MDK tool chain.
  - New Features:
    ∗ Added atomic modification macros.
- 2.2.7
  - Other Change
    ∗ Added MECC status group definition.
- 2.2.6

- **–** Other Change
    - ∗ Added more status group definition.
- **–** Bug Fixes
    - ∗ Undef __VECTOR_TABLE to avoid duplicate definition in cmsis_clang.h
- 2.2.5
    - **–** Bug Fixes
        - ∗ Fixed MISRA C-2012 rule-15.5.
- 2.2.4
    - **–** Bug Fixes
        - ∗ Fixed MISRA C-2012 rule-10.4.
- 2.2.3
    - **–** New Features
        - ∗ Provided better accuracy of SDK_DelayAtLeastUs with DWT, use macro SDK_DELA-Y_USE_DWT to enable this feature.
        - ∗ Modified the Cortex-M7 delay count divisor based on latest tests on RT series boards, this setting lets result be closer to actual delay time.
- 2.2.2
    - **–** New Features
        - ∗ Added include RTE_Components.h for CMSIS pack RTE.
- 2.2.1
    - **–** Bug Fixes
        - ∗ Fixed violation of MISRA C-2012 Rule 3.1, 10.1, 10.3, 10.4, 11.6, 11.9.
- 2.2.0
    - **–** New Features
        - ∗ Moved SDK_DelayAtLeastUs function from clock driver to common driver.
- 2.1.4
    - **–** New Features
        - ∗ Added OTFAD into status group.
- 2.1.3
    - **–** Bug Fixes
        - ∗ MISRA C-2012 issue fixed.
            - · Fixed the rule: rule-10.3.
- 2.1.2
    - **–** Improvements
        - ∗ Add SUPPRESS_FALL_THROUGH_WARNING() macro for the usage of suppressing fallthrough warning.
- 2.1.1
    - **–** Bug Fixes
        - ∗ Deleted and optimized repeated macro.
- 2.1.0
    - **–** New Features
        - ∗ Added IRQ operation for XCC toolchain.
        - ∗ Added group IDs for newly supported drivers.
- 2.0.2
    - **–** Bug Fixes

* MISRA C-2012 issue fixed.
    · Fixed the rule: rule-10.4.
* 2.0.1
    – Improvements
        ∗ Removed the implementation of LPC8XX Enable/DisableDeepSleepIRQ() function.
        ∗ Added new feature macro switch "FSL_FEATURE_HAS_NO_NONCACHEABLE_S-ECTION" for specific SoCs which have no noncacheable sections, that helps avoid an unnecessary complex in link file and the startup file.
        ∗ Updated the align(x) to **attribute**(aligned(x)) to support MDK v6 armclang compiler.
* 2.0.0
    – Initial version.

CTIMER

The current CTimer driver version is 2.3.1.

* 2.3.1
    – Bug Fixes
        ∗ MISRA C-2012 issue fixed: rule 10.7 and 12.2.
* 2.3.0
    – Improvements
        ∗ Added the CTIMER_SetPrescale(), CTIMER_GetCaptureValue(), CTIMER_Enable-ResetMatchChannel(), CTIMER_EnableStopMatchChannel(), CTIMER_EnableRising-EdgeCapture(), CTIMER_EnableFallingEdgeCapture(), CTIMER_SetShadowValue(),A-PIs Interface to reduce code complexity.
* 2.2.2
    – Bug Fixes
        ∗ Fixed SetupPwm() API only can use match 3 as period channel issue.
* 2.2.1
    – Bug Fixes
        ∗ Fixed use specified channel to setting the PWM period in SetupPwmPeriod() API.
        ∗ Fixed Coverity Out-of-bounds issue.
* 2.2.0
    – Improvements
        ∗ Updated three API Interface to support Users to flexibly configure the PWM period and PWM output.
    – Bug Fixes
        ∗ MISRA C-2012 issue fixed: rule 8.4.
* 2.1.0
    – Improvements
        ∗ Added the CTIMER_GetOutputMatchStatus() API Interface.
        ∗ Added feature macro for FSL_FEATURE_CTIMER_HAS_NO_CCR_CAP2 and FSL_-FEATURE_CTIMER_HAS_NO_IR_CR2INT.
* 2.0.3

- – Bug Fixes
  - ∗ MISRA C-2012 issue fixed: rule 10.3, 10.4, 10.6, 10.7 and 11.9.
- 2.0.2
  - – New Features
    - ∗ Added new API "CTIMER_GetTimerCountValue" to get the current timer count value.
    - ∗ Added a control macro to enable/disable the RESET and CLOCK code in current driver.
    - ∗ Added a new feature macro to update the API of CTimer driver for lpc8n04.
- 2.0.1
  - – Improvements
    - ∗ API Interface Change
      - · Changed API interface by adding CTIMER_SetupPwmPeriod API and CTIMER-_UpdatePwmPulsePeriod API, which both can set up the right PWM with high resolution.
- 2.0.0
  - – Initial version.

DMIC

The current DMIC driver version is 2.3.2.

- 2.3.2
  - – New Features
    - ∗ Supported 4 channels in driver.
- 2.3.1
  - – Bug Fixes
    - ∗ Fixed the issue that DMIC_EnableChannelDma and DMIC_EnableChannelFifo did not clean relevant bits.
- 2.3.0
  - – Improvements
    - ∗ Added new apis DMIC_ResetChannelDecimator/DMIC_EnableChannelGlobalSync/D-MIC_DisableChannelGlobalSync.
- 2.2.1
  - – Bug Fixes
    - ∗ Fixed violations of the MISRA C-2012 rules 14.4, 17.7, 10.4, 10.3, 10.8, 14.3.
- 2.2.0
  - – Bug Fixes
    - ∗ Corrected the usage of feature FSL_FEATURE_DMIC_IO_HAS_NO_BYPASS.
- 2.1.1
  - – Improvements
    - ∗ Added feature FSL_FEATURE_DMIC_HAS_NO_IOCFG for IOCFG register.
- 2.1.0
  - – New Features
    - ∗ Added API DMIC_EnbleChannelInterrupt/DMIC_EnbleChannelDma to replace API D-MIC_SetOperationMode.

* Added API DMIC_SetIOCFG and marked DMIC_ConfigIO as deprecated.
* Added API DMIC_EnableChannelSignExtend to support sign extend feature.

- 2.0.5
  - Improvements
    * Changed some parameters' value of DMIC_FifoChannel API, such as enable, resetn, and trig_level. This is not possible for the current code logic, so it improves the DMIC_FifoChannel logic and fixes incorrect math logic.
- 2.0.4
  - Bug Fixes
    * Fixed the issue that DMIC DMA driver(ver2.0.3) did not support calling DMIC_TransferReceiveDMA in DMA callback as it did before version 2.0.3. But calling DMIC_TransferReceiveDMA in callback is not recommended.
- 2.0.3
  - New Features
  - Supported linked transfer in DMIC DMA driver.
  - Added new API DMIC_EnableChannelFifo/DMIC_DoFifoReset/DMIC_InstallDMA-Descriptor.
- 2.0.2
  - New Features
    * Supported more channels in driver.
- 2.0.1
  - New Features
    * Added a control macro to enable/disable the RESET and CLOCK code in current driver.
- 2.0.0
  - Initial version.

DMIC_DMA

The current DMIC_DMA driver version is 2.4.0.

- 2.4.0
  - Bug Fixes
    * Fixed the issue that DMIC_TransferAbortReceiveDMA can not disable dmic and dma request issue.
- 2.3.1
  - Bug Fixes
    * Fixed violations of the MISRA C-2012 rules 10.3.
- 2.3.0
  - Refer DMIC driver change log 2.0.1 to 2.3.0

FMEAS

The current FMEAS driver version is 2.1.1.

- 2.1.1
  - Bug Fixes
    * MISRA C-2012 issues fixed: rule 10.4, rule 10.8.
- 2.1.0
  - Updated "FMEAS_GetFrequency","FMEAS_StartMeasure","FMEAS_IsMeasureComplete" API and add definition to match ASYNC_SYSCON.
- 2.0.0
  - Initial version ported from LPCOpen.

FLEXCOMM

The current FLEXCOMM driver version is 2.0.2.

- 2.0.2
  - Bug Fixes
    * Fixed typos in FLEXCOMM15_DriverIRQHandler().
    * Fixed MISRA issues.
      · Fixed rules 10.1, 10.3, 10.4, 10.7, 10.8, 11.3, 11.6, 11.8, 11.9, 13.5.
  - Improvements
    * Added instance calculation in FLEXCOMM16_DriverIRQHandler() to align with Flexcomm 14 and 15.
- 2.0.1
  - Improvements
    * Added more IRQHandler code in drivers to adapt new devices.
- 2.0.0
  - Initial version.

I2C

The current I2C driver version is 2.3.3.

- 2.3.3
  - Bug Fixes
    * Fixed violations of the MISRA C-2012 rules 10.1.
    * Fixed issue that if master only sends address without data during I2C interrupt transfer, address nack cannot be detected.
- 2.3.2
  - Improvement
    * Enable or disable timeout option according to enableTimeout.
  - Bug Fixes
    * Fixed timeout value calculation error.
    * Fixed bug that the interrupt transfer cannot recover from the timeout error.
- 2.3.1
  - Improvement

  * Before master transfer with transactional APIs, enable master function while disable slave function and vise versa for slave transfer to avoid the one affecting the other.
  – Bug Fixes
    * Fixed bug in I2C_SlaveEnable that the slave enable/disable should not affect the other register bits.
* 2.3.0
  – Improvement
    * Added new return codes kStatus_I2C_EventTimeout and kStatus_I2C_SclLowTimeout, and added the check for event timeout and SCL timeout in I2C master transfer.
    * Fixed bug in slave transfer that the address match event should be invoked before not after slave transmit/receive event.
* 2.2.0
  – New Features
    * Added enumeration _i2c_status_flags to include all previous master and slave status flags, and added missing status flags.
    * Modified I2C_GetStatusFlags to get all I2C flags.
    * Added API I2C_ClearStatusFlags to clear all clearable flags not just master flags.
    * Modified master transactional APIs to enable bus event timeout interrupt during transfer, to avoid glitch on bus causing transfer hangs indefinitely.
  – Bug Fixes
    * Fixed bug that status flags and interrupt enable masks share the same enumerations by adding enumeration _i2c_interrupt_enable for all master and slave interrupt sources.
* 2.1.0
  – Bug Fixes
    * Fixed bug that during master transfer, when master is nacked during slave probing or sending subaddress, the return status should be kStatus_I2C_Addr_Nak rather than k-Status_I2C_Nak.
  – Bug Fixes
    * Fixed MISRA issues.
      · Fixed rules 10.1, 10.4, 13.5.
  – New Features
    * Added macro I2C_MASTER_TRANSMIT_IGNORE_LAST_NACK, so that user can configure whether to ignore the last byte being nacked by slave during master transfer.
* 2.0.8
  – Bug Fixes
    * Fixed I2C_MasterSetBaudRate issue that MSTSCLLOW and MSTSCLHIGH are incorrect when MSTTIME is odd.
* 2.0.7
  – Bug Fixes
    * Two dividers, CLKDIV and MSTTIME are used to configure baudrate. According to reference manual, in order to generate 400kHz baudrate, the clock frequency after CLK-DIV must be less than 2mHz. Fixed the bug that, the clock frequency after CLKDIV may be larger than 2mHz using the previous calculation method.
    * Fixed MISRA 10.1 issues.
    * Fixed wrong baudrate calculation when feature FSL_FEATURE_I2C_PREPCLKFRG_-

8MHZ is enabled.
- 2.0.6
  - New Features
    * Added master timeout self-recovery support for feature FSL_FEATURE_I2C_TIMEOU-T_RECOVERY.
  - Bug Fixes
    * Eliminated IAR Pa082 warning.
    * Fixed MISRA issues.
      · Fixed rules 10.1, 10.3, 10.4, 10.7, 10.8, 11.3, 11.6, 11.8, 11.9, 13.5.
- 2.0.5
  - Bug Fixes
    * Fixed wrong assignment for datasize in I2C_InitTransferStateMachineDMA.
    * Fixed wrong working flow in I2C_RunTransferStateMachineDMA to ensure master can work in no start flag and no stop flag mode.
    * Fixed wrong working flow in I2C_RunTransferStateMachine and added kReceiveData-BeginState in _i2c_transfer_states to ensure master can work in no start flag and no stop flag mode.
    * Fixed wrong handle state in I2C_MasterTransferDMAHandleIRQ. After all the data has been transfered or nak is returned, handle state should be changed to idle.
  - Improvements
    * Rounded up the calculated divider value in I2C_MasterSetBaudRate.
- 2.0.4
  - Improvements
    * Updated the I2C_WATI_TIMEOUT macro to unified name I2C_RETRY_TIMES
    * Updated the "I2C_MasterSetBaudRate" API to support baudrate configuration for feature QN9090.
  - Bug Fixes
    * Fixed build warnning caused by uninitialized variable.
    * Fixed COVERITY issue of unchecked return value in I2C_RTOS_Transfer.
- 2.0.3
  - Improvements
    * Unified the component full name to FLEXCOMM I2C(DMA/FREERTOS) driver.
- 2.0.2
  - Improvements
    * In slave IRQ:
      1. Changed slave receive process to first set the I2C_SLVCTL_SLVCONTINUE_MA-SK to acknowledge the received data, then do data receive.
      2. Improved slave transmit process to set the I2C_SLVCTL_SLVCONTINUE_MASK immediately after writing the data.
- 2.0.1
  - Improvements
    * Added I2C_WATI_TIMEOUT macro to allow users to specify the timeout times for waiting flags in functional API and blocking transfer API.
- 2.0.0
  - Initial version.

I2S

The current I2S driver version is 2.3.2

- 2.3.2
  - Bug Fixes
    * Fixed warning for comparison between pointer and integer.
- 2.3.1
  - Bug Fixes
    * Updated the value of TX/RX software transfer state machine after transfer contents are submitted to avoid race condition.
- 2.3.0
  - Improvements
    * Added api I2S_InstallDMADescriptorMemory/I2S_TransferSendLoopDMA/I2S_-TransferReceiveLoopDMA to support loop transfer.
    * Added api I2S_EmptyTxFifo to support blocking flush tx fifo.
    * Updated api I2S_TransferAbortDMA by removed the blocking flush tx fifo from this function.
  - Bug Fixes
    * Removed the while loop in abort transfer function to fix the dead loop issue under specific user case.
- 2.2.2
  - Bug Fixes
    * Fixed violations of the MISRA C-2012 rules 8.4.
- 2.2.1
  - Improvements
    * Added feature FSL_FEATURE_FLEXCOMM_INSTANCE_I2S_SUPPORT_SECON-DARY_CHANNELn for the SOC has parts of instance support secondary channel.
  - Bug Fixes
    * Added volatile statement for the state variable of i2s_handle and enable the mainline channel pair before enable interrupt to avoid the issue of code excution reordering which may cause the interrupt generated unexpectedly.
- 2.2.0
  - Improvements
    * Added 8/16/24 bits mono data format transfer support in I2S driver.
    * Added new apis I2S_SetBitClockRate.
  - Bug Fixes
    * Fixed the PA082 build warning.
    * Fixed the sign-compare warning.
    * Fixed violations of the MISRA C-2012 rules 10.4, 10.8, 11.9, 10.1, 11.3, 13.5, 11.8, 10.3, 10.7.
    * Fixed the Operand don't affect result Coverity issue.
- 2.1.0
  - Improvements
    * Added a feature for the FLEXCOMM which supports I2S and has interconnection with DMIC.

* Used a feature to control PDMDATA instead of I2S_CFG1_PDMDATA.
* Added member bytesPerFrame in i2s_dma_handle_t, used for DMA transfer width configure, instead of using sizeof(uint32_t) hardcode.
* Used the macro provided by DMA driver to define the I2S DMA descriptor.
    – Bug Fixes
        * Fixed the issue that I2S DMA driver always generated duplicate callback.
* 2.0.3
    – New Features
        * Added a feature to remove configuration for the second channel on LPC51U68.
* 2.0.2
    – New Features
        * Added ENABLE_IRQ handle after register I2S interrupt handle.
* 2.0.1
    – Improvements
        * Unified the component full name to FLEXCOMM I2S (DMA) driver.
* 2.0.0
    – Initial version.

SPI

The current SPI driver version is 2.3.1

* 2.3.1
    – Improvements
        * Changed SPI_DUMMYDATA to 0x00.
* 2.3.0
    – Update version.
* 2.2.2
    – Bug Fixes
        * Fixed violations of the MISRA C-2012 rules.
* 2.2.1
    – Bug Fixes
        * Fixed MISRA 2012 10.4 issue.
        * Added code to clear FIFOs before transfer using DMA.
* 2.2.0
    – Bug Fixes
        * Fixed bug that slave gets stuck during interrupt transfer.
* 2.1.1
    – Improvements
        * Added timeout mechanism when waiting certain states in transfer driver.
    – Bug Fixes
        * Fixed MISRA 10.1, 5.7 issues.
* 2.1.0
    – Bug Fixes

∗ Fixed Coverity issue of incrementing null pointer in SPI_TransferHandleIRQInternal.

∗ Eliminated IAR Pa082 warnings.

∗ Fixed MISRA issues.

· Fixed rules 10.1, 10.3, 10.4, 10.7, 10.8, 11.3, 11.6, 11.8, 11.9, 13.5.

– New Features

∗ Modified the definition of SPI_SSELPOL_MASK to support the socs that have only 3 SSEL pins.

- 2.0.4

– Bug Fixes

∗ Fixed the bug of using read only mode in DMA transfer. In DMA transfer mode, if transfer->txData is NULL, code attempts to read data from the address of 0x0 for configuring the last frame.

∗ Fixed wrong assignment of handle->state. During transfer handle->state should be kSPI_Busy rather than kStatus_SPI_Busy.

– Improvements

∗ Rounded up the calculated divider value in SPI_MasterSetBaud.

- 2.0.3

– Improvements

∗ Added "SPI_FIFO_DEPTH(base)" with more definition.

- 2.0.2

– Improvements

∗ Unified the component full name to FLEXCOMM SPI(DMA/FREERTOS) driver.

- 2.0.1

– Changed the data buffer from uint32_t to uint8_t which matches the real applications for SPI DMA driver.

– Added dummy data setup API to allow users to configure the dummy data to be transferred.

– Added new APIs for half-duplex transfer function. Users can not only send and receive data by one API in polling/interrupt/DMA way, but choose either to transmit first or to receive first. Besides, the PCS pin can be configured as assert status in transmission (between transmit and receive) by setting the isPcsAssertInTransfer to true.

- 2.0.0

– Initial version.

SPI_DMA

The current SPI_DMA driver version is 2.2.1.

- 2.2.1

– Bug Fixes

∗ Fixed MISRA 2012 11.6 issue..

- 2.2.0

– Improvements

∗ Supported dataSize larger than 1024 data transmit.

USART

The current USART driver version is 2.8.3.

- 2.8.3
  - **–** Bug Fixes
    - ∗ Fixed violations of the MISRA C-2012 rules 10.3, 11.8.
- 2.8.2
  - **–** Bug Fixes
    - ∗ Fixed violations of the MISRA C-2012 rules 14.2.
- 2.8.1
  - **–** Bug Fixes
    - ∗ Fixed the Baud Rate Generator(BRG) configuration in 32kHz mode.
- 2.8.0
  - **–** New Features
    - ∗ Added the rx timeout interrupts and status flags of bus status.
    - ∗ Added new rx timeout configuration item in usart_config_t.
    - ∗ Added API USART_SetRxTimeoutConfig for rx timeout configuration.
  - **–** Improvements
    - ∗ When the calculated baudrate cannot meet user's configuration, lower OSR value is allewed to use.
- 2.7.0
  - **–** New Features
    - ∗ Added the missing interrupts and status flags of bus status.
    - ∗ Added the check of tx error, noise error framing error and parity error in interrupt handler.
- 2.6.0
  - **–** Improvements
    - ∗ Used separate data for TX and RX in usart_transfer_t.
  - **–** Bug Fixes
    - ∗ Fixed bug that when ring buffer is used, if some data is received in ring buffer first before calling USART_TransferReceiveNonBlocking, the received data count returned by USART_TransferGetReceiveCount is wrong.
  - **–** New Features
    - ∗ Added missing API USART_TransferGetSendCountDMA get send count using DMA.
- 2.5.0
  - **–** New Features
    - ∗ Added APIs USART_GetRxFifoCount/USART_GetTxFifoCount to get rx/tx FIFO data count.
    - ∗ Added APIs USART_SetRxFifoWatermark/USART_SetTxFifoWatermark to set rx/tx F-IFO water mark.
  - **–** Bug Fixes
    - ∗ Fixed DMA transfer blocking issue by enabling tx idle interrupt after DMA transmission finishes.
- 2.4.0
  - **–** New Features
    - ∗ Modified usart_config_t, USART_Init and USART_GetDefaultConfig APIs so that the

hardware flow control can be enabled during module initialization.
- **–** Bug Fixes
    - ∗ Fixed MISRA 10.4 violation.
- **•** 2.3.1
    - **–** Bug Fixes
        - ∗ Fixed bug that operation on INTENSET, INTENCLR, FIFOINTENSET and FIFOINTE-NCLR should use bitwise operation not 'or' operation.
        - ∗ Fixed bug that if rx interrupt occurrs before TX interrupt is enabled and after txDataSize is configured, the data will be sent early by mistake, thus TX interrupt will be enabled after data is sent out.
    - **–** Improvements
        - ∗ Added check for baud rate's accuracy that returns kStatus_USART_BaudrateNotSupport when the best achieved baud rate is not within 3% error of configured baud rate.
- **•** 2.3.0
    - **–** New Features
        - ∗ Added APIs to configure 9-bit data mode, set slave address and send address.
        - ∗ Modified USART_TransferReceiveNonBlocking and USART_TransferHandleIRQ to use 9-bit mode in multi-slave system.
- **•** 2.2.0
    - **–** New Features
        - ∗ Added the feature of supporting USART working at 32 kHz clocking mode.
    - **–** Improvements
        - ∗ Modified USART_TransferHandleIRQ so that txState will be set to idle only when all data has been sent out to bus.
        - ∗ Modified USART_TransferGetSendCount so that this API returns the real byte count that USART has sent out rather than the software buffer status.
        - ∗ Added timeout mechanism when waiting for certain states in transfer driver.
    - **–** Bug Fixes
        - ∗ Fixed MISRA 10.1 issues.
        - ∗ Fixed bug that operation on INTENSET, INTENCLR, FIFOINTENSET and FIFOINTE-NCLR should use bitwise operation not 'or' operation.
        - ∗ Fixed bug that if rx interrupt occurrs before TX interrupt is enabled and after txDataSize is configured, the data will be sent early by mistake, thus TX interrupt will be enabled after data is sent out.
- **•** 2.1.1
    - **–** Improvements
        - ∗ Added check for transmitter idle in USART_TransferHandleIRQ and USART_Transfer-SendDMACallback to ensure all the data would be sent out to bus.
        - ∗ Modified USART_ReadBlocking so that if more than one receiver errors occur, all status flags will be cleared and the most severe error status will be returned.
    - **–** Bug Fixes
        - ∗ Eliminated IAR Pa082 warnings.
        - ∗ Fixed MISRA issues.
            - · Fixed rules 10.1, 10.3, 10.4, 10.7, 10.8, 11.3, 11.6, 11.8, 11.9, 13.5.
- **•** 2.1.0

- – New Features
  - ∗ Added features to allow users to configure the USART to synchronous transfer(master and slave) mode.
  - – Bug Fixes
  - ∗ Modified USART_SetBaudRate to get more acurate configuration.
- 2.0.3
  - – New Features
    - ∗ Added new APIs to allow users to enable the CTS which determines whether CTS is used for flow control.
- 2.0.2
  - – Bug Fixes
    - ∗ Fixed the bug where transfer abort APIs could not disable the interrupts. The FIFOINT-ENSET register should not be used to disable the interrupts, so use the FIFOINTENCLR register instead.
- 2.0.1
  - – Improvements
    - ∗ Unified the component full name to FLEXCOMM USART (DMA/FREERTOS) driver.
- 2.0.0
  - – Initial version.

USART_DMA

The current USART_DMA driver version is 2.6.0.

- 2.6.0
  - – Refer USART driver change log 2.0.1 to 2.6.0

USART_FREERTOS

The current USART_FREERTOS driver version is 2.6.0.

- 2.6.0
  - – Refer USART driver change log 2.0.1 to 2.6.0

FLEXSPI

The current FLEXSPI driver version is 2.6.0.

- 2.6.0
  - – New Features
    - ∗ Added new API to set AHB memory-mapped flash base address.
    - ∗ Added support of DLLxCR[REFPHASEGAP] bit field, it is recommended to set it as 0x2 if DLL calibration is enabled.
- 2.5.1

- – Bugfixes
    - ∗ Fixed handling of W1C bits in the INTR register
    - ∗ Removed FIFO resets from FLEXSPI_CheckAndClearError
    - ∗ FLEXSPI_TransferBlocking is observing IPCMDDONE and then fetches the final status of the transfer
    - ∗ Fixed issue that FLEXSPI2_DriverIRQHandler not defined.
- 2.5.0
    - – Improvements
        - ∗ Supported word un-aligned access for write/read blocking/non-blocking API functions.
        - ∗ Fixed dead loop issue in DLL update function when using FRO clock source.
        - ∗ Fixed violations of the MISRA C-2012 Rule 10.3.
- 2.4.0
    - – Improvements
        - ∗ Isolated IP command parallel mode and AHB command parallel mode using feature MACRO.
        - ∗ Supported new column address shift feature for external memory.
- 2.3.5
    - – Bug Fixes
        - ∗ Fixed violations of the MISRA C-2012 Rule 14.2.
- 2.3.4
    - – Bug Fixes
        - ∗ Updated flexspi_config_t structure and FlexSPI_Init to support new feature FSL_FEATURE_FLEXSPI_HAS_NO_MCR0_CONBINATION.
- 2.3.3
    - – Bug Fixes
        - ∗ Removed feature FSL_FEATURE_FLEXSPI_DQS_DELAY_PS for DLL delay setting. Changed to use feature FSL_FEATURE_FLEXSPI_DQS_DELAY_MIN to set slave delay target as 0 for DLL enable and clock frequency higher than 100MHz.
- 2.3.2
    - – Bug Fixes
        - ∗ Fixed violations of the MISRA C-2012 Rule 8.4, 8.5, 10.1, 10.3, 10.4, 11.6 and 14.4.
- 2.3.1
    - – Bug Fixes
        - ∗ Wait for bus to be idle before using it as access to external flash with new setting in FLEXSPI_SetFlashConfig() API.
        - ∗ Fixed the potential buffer overread and Tx FIFO overwrite issue in FLEXSPI_WriteBlocking.
- 2.3.0
    - – New Features
        - ∗ Added new API FLEXSPI_UpdateDllValue for users to update DLL value after updating flexspi root clock.
        - ∗ Corrected grammatical issues for comments.
        - ∗ Added support for new feature FSL_FEATURE_FLEXSPI_DQS_DELAY_PS in DLL configuration.
- 2.2.2

- – Bug Fixes
  - ∗ Fixed violations of the MISRA C-2012 Rule 10.1, 10.3 and 10.4.
  - ∗ Updated _flexspi_command from named enumerator into anonymous enumerator.
- 2.2.1
  - – Bug Fixes
    - ∗ Fixed violations of the MISRA C-2012 Rule 10.1, 10.3, 10.4, 10.8, 11.9, 14.4, 15.7, 16.4, 17.7, 7.3.
    - ∗ Fixed IAR build warning Pe167.
    - ∗ Fixed the potential buffer overwrite and Rx FIFO overread issue in FLEXSPI_Read-Blocking.
- 2.2.0
  - – Bug Fixes
    - ∗ Fixed flag name typos: kFLEXSPI_IpTxFifoWatermarkEmpltyFlag to kFLEXSPI_IpTxFifoWatermarkEmptyFlag; kFLEXSPI_IpCommandExcutionDoneFlag to kFLEXSPI_IpCommandExecutionDoneFlag.
    - ∗ Fixed comments typos such as sequencen->sequence, levle->level.
    - ∗ Fixed FLSHCR2[ARDSEQID] field clean issue.
    - ∗ Updated flexspi_config_t structure and FlexSPI_Init to support new feature FSL_FEATURE_FLEXSPI_HAS_NO_MCR0_ATDFEN and FSL_FEATURE_FLEXSPI_HAS_NO_MCR0_ARDFEN.
    - ∗ Updated flexspi_flags_t structure to support new feature FSL_FEATURE_FLEXSPI_HAS_INTEN_AHBBUSERROREN.
- 2.1.1
  - – Improvements
    - ∗ Defaulted enable prefetch for AHB RX buffer configuration in FLEXSPI_GetDefaultConfig, which is align with the reset value in AHBRXBUFxCR0.
    - ∗ Added software workaround for ERR011377 in FLEXSPI_SetFlashConfig; added some delay after DLL lock status set to ensure correct data read/write.
- 2.1.0
  - – New Features
    - ∗ Added new API FLEXSPI_UpdateRxSampleClock for users to update read sample clock source after initialization.
    - ∗ Added reset peripheral operation in FLEXSPI_Init if required.
- 2.0.5
  - – Bug Fixes
    - ∗ Fixed FLEXSPI_UpdateLUT cannot do partial update issue.
- 2.0.4
  - – Bug Fixes
    - ∗ Reset flash size to zero for all ports in FLEXSPI_Init; fixed the possible out-of-range flash access with no error reported.
- 2.0.3
  - – Bug Fixes
    - ∗ Fixed AHB receive buffer size configuration issue. The FLEXSPI_AHBRXBUFCR0_-BUFSZ field should configure 64 bits size, and currently the AHB receive buffer size is in bytes which means 8-bit, so the correct configuration should be config->ahbConfig.-

buffer[i].bufferSize / 8.

- 2.0.2
    - New Features
        * Supported DQS write mask enable/disable feature during set FLEXSPI configuration.
        * Provided new API FLEXSPI_TransferUpdateSizeEDMA for users to update eDMA transfer size(SSIZE/DSIZE) per DMA transfer.
    - Bug Fixes
        * Fixed invalid operation of FLEXSPI_Init to enable AHB bus Read Access to IP RX FIFO.
        * Fixed incorrect operation of FLEXSPI_Init to configure IP TX FIFO watermark.
- 2.0.1
    - Bug Fixes
        * Fixed the flag clear issue and AHB read Command index configuration issue in FLEXSPI_SetFlashConfig.
        * Updated FLEXSPI_UpdateLUT function to update LUT table from any index instead of previous command index.
        * Added bus idle wait in FLEXSPI_SetFlashConfig and FLEXSPI_UpdateLUT to ensure bus is idle before any change to FlexSPI controller.
        * Updated interrupt API FLEXSPI_TransferNonBlocking and interrupt handle flow FLEXSPI_TransferHandleIRQ.
        * Updated eDMA API FLEXSPI_TransferEDMA.
- 2.0.0
    - Initial version.

FLEXSPI DMA Driver

The current FLEXSPI DMA driver version is 2.2.1.

- 2.2.1
    - Bug Fixes
        * Fixed violations of the MISRA C-2012 Rule 10.1, 10.3, 10.4, 10.8.
- 2.2.0
    - Bug Fixes
        * Fixed violations of the MISRA C-2012 Rule 10.1, 10.3.
    - New Features
        * Updated name of FLEXSPI_TransferGetTransferCountDMA API.
- 2.1.1
    - New Features
        * Updated driver to support feature FSL_FEATURE_FLEXSPI_DMA_MULTIPLE_DES.
- 2.1.0
    - Bug Fixes
        * Updated enumaration flexspi_dma_transfer_nsize_t and remove the unsupported items.
    - New Features
        * Updated driver for deprecating the multiple linked descriptors inside FLEXSPI_TransferDMA, only up to one linked descriptor is needed according to hardware update.

- 2.0.0
  - Initial version.

I3C

The current I3C driver version is 2.10.5.

- 2.10.5
  - New features
    * Added I3C HDR-DDR transfer support.
- 2.10.4
  - Improvements
    * Added one more option for master to not set RDTERM when doing I3C Common Command Code transfer.
- 2.10.3
  - Improvements
    * Masked the slave IBI/MR/HJ request functions with feature macro.
- 2.10.2
  - Bug Fixes
    * Added workaround for errata ERR051617: I3C working with I2C mode creates the unintended Repeated START before actual STOP on some platforms.
- 2.10.1
  - Bug Fixes
    * Fixed the issue that DAA function doesn't wait until all Rx data is read out from FIFO after master control done flag is set.
    * Fixed the issue that DAA function could return directly although the disabled interrupts are not enabled back.
- 2.10.0
  - New features
    * Added I3C extended IBI data support.
- 2.9.0
  - Improvements
    * Added adaptive termination for master blocking transfer. Set termination with start signal when receiving bytes less than 256.
- 2.8.2
  - Improvements
    * Fixed the build warning due to armgcc strict check.
- 2.8.1
  - Bug Fixes
    * Fixed violations of the MISRA C-2012 rules 17.7.
- 2.8.0
  - Improvements
    * Added API I3C_MasterProcessDAASpecifiedBaudrate for temporary baud rate adjustment when I3C master assigns dynamic address.

- 2.7.1
  - Bug Fixes
    * Fixed the issue that I3C slave handle STOP event before finishing data transmission.
- 2.7.0
  - Fixed the CCM problem in file fsl_i3c.c.
  - Fixed the FSL_FEATURE_I3C_HAS_NO_SCONFIG_IDRAND usage issue in I3C_Get-DefaultConfig and I3C_Init.
- 2.6.0
  - Fixed the FSL_FEATURE_I3C_HAS_NO_SCONFIG_IDRAND usage issue in fsl_i3c.h.
  - Changed some static functions in fsl_i3c.c as non-static and define the functions in fsl_i3c.h to make I3C DMA driver reuse:
    * I3C_GetIBIType
    * I3C_GetIBIAddress
    * I3C_SlaveCheckAndClearError
  - Changed the handle pointer parameter in IRQ related funtions to void ∗ type to make it reuse in I3C DMA driver.
  - Added new API I3C_SlaveRequestIBIWithSingleData for slave to request single data byte, this API could be used regardless slave is working in non-blocking interrupt or non-blocking dma.
  - Added new API I3C_MasterGetDeviceListAfterDAA for master application to get the device information list built up in DAA process.
- 2.5.4
  - Improved I3C driver to avoid setting state twice in the SendCommandState of I3C_Run-TransferStateMachine.
  - Fixed MISRA violation of rule 20.9.
  - Fixed the issue that I3C_MasterEmitRequest did not use Type I3C SDR.
- 2.5.3
  - Updated driver for new feature FSL_FEATURE_I3C_HAS_NO_SCONFIG_BAMATCH and FSL_FEATURE_I3C_HAS_NO_SCONFIG_IDRAND.
- 2.5.2
  - Updated driver for new feature FSL_FEATURE_I3C_HAS_NO_MERRWARN_TERM.
  - Fixed the issue that call to I3C_MasterTransferBlocking API did not generate STOP signal when NAK status was returned.
- 2.5.1
  - Improved the receive terminate size setting for interrupt transfer read, now it's set at beginning of transfer if the receive size is less than 256 bytes.
- 2.5.0
  - Added new API I3C_MasterRepeatedStartWithRxSize to send repeated start signal with receive terminate size specified.
  - Fixed the status used in I3C_RunTransferStateMachine, changed to use pending interrupts as status to be handled in the state machine.
  - Fixed MISRA 2012 violation of rule 10.3, 10.7.
- 2.4.0
  - Bug Fixes
    * Fixed kI3C_SlaveMatchedFlag interrupt is not properly handled in I3C_SlaveTransfer-

HandleIRQ when it comes together with interrupt kI3C_SlaveBusStartFlag.
  * Fixed the inaccurate I2C baudrate calculation in I3C_MasterSetBaudRate.
  * Added new API I3C_MasterGetIBIRules to get registered IBI rules.
  * Added new variable isReadTerm in struct _i3c_master_handle for transfer state routine to check if MCTRL.RDTERM is configured for read transfer.
  * Changed to emit Auto IBI in transfer state routine for slave start flag assertion.
  * Fixed the slave maxWriteLength and maxReadLength does not be configured into SMA-XLIMITS register issue.
  * Fixed incorrect state for IBI in I3C master interrupt transfer IRQ handle routine.
  * Added isHotJoin in i3c_slave_config_t to request hot-join event during slave init.
- 2.3.2
  – Bug Fixes
    * Fixed violations of the MISRA C-2012 rules 8.4, 17.7.
    * Fixed incorrect HotJoin event index in I3C_GetIBIType.
- 2.3.1
  – Bug Fixes
    * Fixed the issue that call of I3C_MasterTransferBlocking/I3C_MasterTransferNon-Blocking fails for the case which receive length 1 byte of data.
    * Fixed the issue that STOP signal is not sent when NAK status is detected during execution of I3C_MasterTransferBlocking function.
- 2.3.0
  – Improvements
    * Added I3C common driver APIs to initialize I3C with both master and slave configuration.
    * Updated I3C master transfer callback to function set structure to include callback invoke for IBI event and slave2master event.
    * Updated I3C master non-blocking transfer model and always enable the interrupts to be able to re-act to the slave start event and handle slave IBI.
- 2.2.0
  – Bug Fixes
    * Fixed the issue that I3C transfer size limit to 255 bytes.
- 2.1.2
  – Bug Fixes
    * Reset default hkeep value to kI3C_MasterHighKeeperNone in I3C_MasterGetDefault-Config
- 2.1.1
  – Bug Fixes
    * Fixed incorrect FIFO reset operation in I3C Master Transfer APIs.
    * Fixed i3c slave IRQ handler issue, slave transmit could be underrun because tx FIFO is not filled in time right after start flag detected.
- 2.1.0
  – Added definitions and APIs for I3C slave functionality, updated previous I3C APIs to support I3C functionality.
- 2.0.0
  – Initial version.

I3C_DMA

The current I3C DMA driver version is 2.1.4.

- 2.1.4
  - **Improvements**
    - ∗ Used linked DMA transfer to reduce the latency between DMA transfers previous data and the END byte.
- 2.1.3
  - **Bug Fixes**
    - ∗ Fixed the MISRA issue rule 10.4, 11.3.
- 2.1.2
  - **Bug Fixes**
    - ∗ Fixed the issue that I3C slave send the last byte data without using the END type register.
- 2.1.1
  - **Bug Fixes**
    - ∗ Fixed MISRA issue rule 9.1.
- 2.1.0
  - **Improvements**
    - ∗ Deleted legacy IBI data request code.
- 2.0.1
  - **Bug Fixes**
    - ∗ Fixed issue that bus STOP occurs when Tx FIFO still takes data.
  - **Improvements**
    - ∗ Fixed the build warning due to armgcc strict check.
- 2.0.0
  - **Initial version.**

I3C_EDMA

The current I3C EDMA driver version is 2.2.1.

- 2.2.1
  - **Bug Fixes**
    - ∗ Fixed the issue that I3C slave send the last byte data without using the END type register.
  - **Improvements**
    - ∗ There's no need to reserve two bytes FIFO for DMA transfer which is for IP issue workaround.
- 2.2.0
  - **Improvements**
    - ∗ Deleted legacy IBI data request code.
- 2.1.0
  - **Bug Fixes**
    - ∗ Fixed MISRA issue rule 8.4, 8.6, 11.8.
- 2.0.1

– Bug Fixes

∗ Fixed MISRA issue rule 9.1.

- 2.0.0

– Initial version.

IAP

The current IAP driver version is 2.1.3.

- 2.1.3

– Bug Fixes

∗ Fixed misra issue.

- 2.1.2

– Bug Fixes

∗ Fixed some macro undefined issue.

∗ Put IAP_FlexspiNorInit API into RAM.

- 2.1.1

– Bug Fixes

∗ Fixed misra issue.

- 2.1.0

– New Features

∗ Added IAP_RunBootLoader() API

- 2.0.2

– Bug Fixes

∗ Fixed doxygen issue.

- 2.0.1

– Bug Fixes

∗ Minor update for MISRA issue fix.

- 2.0.0

– Initial version.

INPUTMUX

The current INPUTMUX driver version is 2.0.7.

- 2.0.7

– Improvements

∗ Release peripheral from reset if necessary in init function.

- 2.0.6

– Bug Fixes

∗ Fixed the documentation wrong in API INPUTMUX_AttachSignal.

- 2.0.5

– Bug Fixes

∗ Fixed build error because some devices has no sct.

- 2.0.4
  - Bug Fixes
    * Fixed violations of the MISRA C-2012 rule 10.4, 12.2 in INPUTMUX_EnableSignal() function.
- 2.0.3
  - Bug Fixes
    * Fixed violations of the MISRA C-2012 rules 10.4, 10.7, 12.2.
- 2.0.2
  - Bug Fixes
    * Fixed violations of the MISRA C-2012 rules 10.4, 12.2.
- 2.0.1
  - Support channel mux setting in INPUTMUX_EnableSignal().
- 2.0.0
  - Initial version.

LPADC

The current LPADC driver version is 2.8.4.

- 2.8.4
  - Bug Fixes
    * Remove function 'LPADC_SetOffsetValue' assert statement, this statement may cause runtime errors in existing code.
- 2.8.3
  - Bug Fixes
    * Fixed SDK lpadc driver examples compile issue, move condition 'commandId < ADC_-CV_COUNT' to a more appropriate location.
- 2.8.2
  - Bug Fixes
    * Fixed the violations of MISRA C-2012 rule 18.1, 10.3, 10.1 and 10.4.
- 2.8.1
  - Bug Fixes
    * Fixed LPADC sample mode enum name mistake.
- 2.8.0
  - Improvements
    * Release peripheral from reset if necessary in init function.
  - Bug Fixes
    * Fixed function LPADC_GetConvResult() issue.
    * Fixed function LPADC_SetConvCommandConfig() bugs.
- 2.7.2
  - Improvements
    * Use feature macros instead of header file macros.
  - Bug Fixes
    * Fixed the violations of MISRA C-2012 rule 10.1, 10.3, 10.4 and 14.3.

- 2.7.1
  - **Improvements**
    * Corrected descriptions of several functions.
    * Improved function LPADC_GetOffsetValue and LPADC_SetOffsetValue.
    * Revert changes of feature macros for lpadc.
    * Use feature macros instead of header file macros.
  - **Bug Fixes**
    * Fixed the violations of MISRA C-2012 rule 10.8.
    * Fixed the violations of MISRA C-2012 rule 10.1, 10.3, 10.4 and 14.3.
- 2.7.0
  - **Improvements**
    * Added supports of CFG2 register.
    * Removed some useless macros.
- 2.6.2
  - **Bug Fixes**
    * Fixed the violations of MISRA C-2012 rules.
    * Fixed LPADC driver code compile error issue.
- 2.6.1
  - **Improvements**
    * Updated the use of macros in the driver code.
- 2.6.0
  - **Improvements**
    * Added the API LPADC_SetOffset12BitValue() to configure 12bit ADC conversion offset trim value manually.
    * Added the API LPADC_SetOffset16BitValue() to configure 16bit ADC conversion offset trim value manually.
    * Added API to set offset calibration mode.
    * Added configuration of alternate channel.
    * Updated auto calibration API and added calibration value conversion API.
  - **New feature**
    * Added API LPADC_EnableHardwareTriggerCommandSelection() to enable trigger commands controlled by ADC_ETC.
    * Updated LPADC_DoAutoCalibration() to allow doing something else before the ADC inititialization to be totally complete. Enhance initialization duration time of the ADC.
    * Added two new APIs to get/set calibration value.
- 2.5.2
  - **Improvements**
    * Added while loop, LPADC_GetConvResult() will return only when the FIFO will not be empty.
- 2.5.1
  - **Bug Fixes**
    * Fixed some typos in Lpadc driver comments.
- 2.5.0
  - **Improvements**
    * Added missing items to enable trigger interrupts.

- 2.4.0
  - New features
    * Added APIs to get/clear trigger status flags.
- 2.3.0
  - Improvements
    * Removed LPADC_MeasureTemperature() function for the LPADC supports different temperature sensor calculation equations.
- 2.2.1
  - Improvements
    * Optimized LPADC_MeasureTemperature() function to support the specific series with flash solidified calibration value.
    * Clean doxygen warnings.
  - Bug Fixes
    * Fixed violations of MISRA C-2012 rule 10.3, rule 10.8 and rule 17.7.
- 2.2.0
  - New Feature
    * Added API LPADC_MeasureTemperature() to get correct temperature from the internal sensor.
  - Improvements
    * Separated lpadc_conversion_resolution_mode_t with related feature macro.
  - Bug Fixes
    * Fixed the violations of MISRA C-2012 rules:
      · Rule 10.3, 10.4, 10.6, 10.7 and 17.7.
- 2.1.1
  - Improvements
    * Updated the gain calibration formula.
    * Used feature to segregate the new item kLPADC_TriggerPriorityPreemptSubsequently.
- 2.1.0
  - New Features
    * Added the API LPADC_SetOffsetValue() to support configure offset trim value manually.
    * Added the API LPADC_DoOffsetCalibration() to do offset calibration independently.
  - Improvements
    * Improved the usage of macros and removed invalid macros.
- 2.0.2
  - Improvements
    * Added support for platforms with 2 FIFOs and different calibration measures.
- 2.0.1
  - Bug Fixes
    * Ensured the API LPADC_SetConvCommandConfig configure related registers correctly.
- 2.0.0
  - Initial version.

CRC

The current CRC driver version is 2.1.1.

- 2.1.1
  - Fix MISRA issue.
- 2.1.0
  - Add CRC_WriteSeed function.
- 2.0.2
  - Fix MISRA issue.
- 2.0.1
  - Fixed KPSDK-13362. MDK compiler issue when writing to WR_DATA with -O3 optimize for time.
- 2.0.0
  - Initial version.

DMA

The current DMA driver version is 2.5.1.

- 2.5.1
  - Bug Fixes
    * Fixed violation of the MISRA C-2012 rule 11.6.
- 2.5.0
  - Improvements
    * Added a new api DMA_SetChannelXferConfig to set DMA xfer config.
- 2.4.4
  - Bug Fixes
    * Fixed the issue that DMA_IRQHandle might generate redundant callbacks.
    * Fixed the issue that DMA driver cannot support channel bigger then 32.
    * Fixed violation of the MISRA C-2012 rule 13.5.
- 2.4.3
  - Improvements
    * Added features FSL_FEATURE_DMA_DESCRIPTOR_ALIGN_SIZEn/FSL_FEATU-RE_DMA0_DESCRIPTOR_ALIGN_SIZE/FSL_FEATURE_DMA1_DESCRIPTOR_-ALIGN_SIZE to support the descriptor align size not constant in the two instances.
- 2.4.2
  - Bug Fixes
    * Fixed violation of the MISRA C-2012 rule 8.4.
- 2.4.1
  - Bug Fixes
    * Fixed violations of the MISRA C-2012 rules 5.7, 8.3.
- 2.4.0
  - Improvements
    * Added new APIs DMA_LoadChannelDescriptor/DMA_ChannelIsBusy to support polling

transfer case.

- Bug Fixes
    * Added address alignment check for descriptor source and destination address.
    * Added DMA_ALLOCATE_DATA_TRANSFER_BUFFER for application buffer allocation.
    * Fixed the sign-compare warning.
    * Fixed violations of the MISRA C-2012 rules 18.1, 10.4, 11.6, 10.7, 14.4, 16.3, 20.7, 10.8, 16.1, 17.7, 10.3, 3.1, 18.1.
- 2.3.0
    - Bug Fixes
        * Removed DMA_HandleIRQ prototype definition from header file.
        * Added DMA_IRQHandle prototype definition in header file.
- 2.2.5
    - Improvements
        * Added new API DMA_SetupChannelDescriptor to support configuring wrap descriptor.
        * Added wrap support in function DMA_SubmitChannelTransfer.
- 2.2.4
    - Bug Fixes
        * Fixed the issue that macro DMA_CHANNEL_CFER used wrong parameter to calculate DSTINC.
- 2.2.3
    - Bug Fixes
        * Improved DMA driver Deinit function for correct logic order.
    - Improvements
        * Added API DMA_SubmitChannelTransferParameter to support creating head descriptor directly.
        * Added API DMA_SubmitChannelDescriptor to support ping pong transfer.
        * Added macro DMA_ALLOCATE_HEAD_DESCRIPTOR/DMA_ALLOCATE_LINK_-DESCRIPTOR to simplify DMA descriptor allocation.
- 2.2.2
    - Bug Fixes
        * Do not use software trigger when hardware trigger is enabled.
- 2.2.1
    - Bug Fixes
        * Fixed Coverity issue.
- 2.2.0
    - Improvements
        * Changed API DMA_SetupDMADescriptor to non-static.
        * Marked APIs below as deprecated.
            · DMA_PrepareTransfer.
            · DMA_Submit transfer.
        * Added new APIs as below:
            · DMA_SetChannelConfig.
            · DMA_PrepareChannelTransfer.
            · DMA_InstallDescriptorMemory.

      · DMA_SubmitChannelTransfer.
      · DMA_SetChannelConfigValid.
      · DMA_DoChannelSoftwareTrigger.
      · DMA_LoadChannelTransferConfig.

- 2.0.1
  - Improvements
    * Added volatile for DMA descriptor member xfercfg to avoid optimization.
- 2.0.0
  - Initial version.

GPIO

The current GPIO driver version is 2.1.7.

- 2.1.7
  - Improvements
    * Enhanced GPIO_PinInit to enable clock internally.
- 2.1.6
  - Bug Fixes
    * Clear bit before set it within GPIO_SetPinInterruptConfig() API.
- 2.1.5
  - Bug Fixes
    * Fixed violations of the MISRA C-2012 rules 3.1, 10.6, 10.7, 17.7.
- 2.1.4
  - Improvements
    * Added API GPIO_PortGetInterruptStatus to retrieve interrupt status for whole port.
    * Corrected typos in header file.
- 2.1.3
  - Improvements
    * Updated "GPIO_PinInit" API. If it has DIRCLR and DIRSET registers, use them at set 1 or clean 0.
- 2.1.2
  - Improvements
    * Removed deprecated APIs.
- 2.1.1
  - Improvements
    * API interface changes:
      · Refined naming of APIs while keeping all original APIs, marking them as deprecated. Original APIs will be removed in next release. The mainin change is updating APIs with prefix of _PinXXX() and _PorortXXX
- 2.1.0
  - New Features
    * Added GPIO initialize API.
- 2.0.0

– Initial version.

IOPCTL

The current IOPCTL driver version is 2.0.0.

- 2.0.0
    - Initial version.

RTC

The current RTC driver version is 2.2.0.

- 2.2.0
    - New Features
        * Created new APIs for the RTC driver.
            · RTC_EnableSubsecCounter
            · RTC_GetSubsecValue
- 2.1.3
    - Bug Fixes
        * Fixed issue that RTC_GetWakeupCount may return wrong value.
- 2.1.2
    - Bug Fixes
        * MISRA C-2012 issue fixed: rule 10.1, 10.4 and 10.7.
- 2.1.1
    - Bug Fixes
        * MISRA C-2012 issue fixed: rule 10.3 and 11.9.
- 2.1.0
    - Bug Fixes
        * Created new APIs for the RTC driver.
            · RTC_EnableTimer
            · RTC_EnableWakeUpTimerInterruptFromDPD
            · RTC_EnableAlarmTimerInterruptFromDPD
            · RTC_EnableWakeupTimer
            · RTC_GetEnabledWakeupTimer
            · RTC_SetSecondsTimerMatch
            · RTC_GetSecondsTimerMatch
            · RTC_SetSecondsTimerCount
            · RTC_GetSecondsTimerCount
        * deprecated legacy APIs for the RTC driver.
            · RTC_StartTimer
            · RTC_StopTimer
            · RTC_EnableInterrupts
            · RTC_DisableInterrupts

· RTC_GetEnabledInterrupts
- 2.0.0
  - Initial version.

MRT

The current MRT driver version is 2.0.4.

- 2.0.4
  - Improvements
    * Don't reset MRT when there is not system level MRT reset functions.
- 2.0.3
  - Bug Fixes
    * Fixed violations of MISRA C-2012 rule 10.1 and 10.4.
    * Fixed the wrong count value assertion in MRT_StartTimer API.
- 2.0.2
  - Bug Fixes
    * Fixed violations of MISRA C-2012 rule 10.4.
- 2.0.1
  - Added control macro to enable/disable the RESET and CLOCK code in current driver.
- 2.0.0
  - Initial version.

MU

The Current MU driver version is 2.1.3.

- 2.1.3
  - Improvements
    * Release peripheral from reset if necessary in init function.
- 2.1.2
  - Bug Fixes
    * Fixed issue that MU_GetInstance() is defined but never used.
- 2.1.1
  - Bug Fixes
    * Fixed general interrupt comment typo.
- 2.1.0
  - Improvements
    * Added new enum mu_msg_reg_index_t.
- 2.0.7
  - Bug Fixes
    * Fixed MU_GetInterruptsPending bug that can not get general interrupt status.
- 2.0.6
  - Bug Fixes

   * Fixed violations of the MISRA C-2012 rules 17.7.
- 2.0.5
  - Bug Fixes
    * Fixed violations of the MISRA C-2012 rules 14.4, 15.5.
- 2.0.4
  - Improvements
    * Improved for the platforms which don't support reset assert interrupt and get the other core power mode.
- 2.0.3
  - Bug fixes
    * MISRA C-2012 issue fixed.
      · Fixed rules, containing: rule-10.3, rule-14.4, rule-15.5.
- 2.0.2
  - Improvements
    * Added support for MIMX8MQx.
- 2.0.1
  - Improvements
    * Added support for MCIMX7Ux_M4.
- 2.0.0
  - Initial version.

OSTIMER

The current OSTIMER driver version is 2.2.1.

- 2.2.1
  - Improvements
    * Release peripheral from reset if necessary in init function.
- 2.2.0
  - Improvements
    * Move the PMC operation out of the OSTIMER driver to board specific files.
    * Added low level APIs to control OSTIMER MATCH and interrupt.
- 2.1.2
  - Bug Fixes
    * Fixed MISRA-2012 rule 10.8.
- 2.1.1
  - Bug Fixes
    * removes the suffix 'n' for some register names and bit fields' names
  - Improvements
    * Added HW CODE GRAY feature supported by CODE GRAY in SYSCTRL register group.
- 2.1.0
  - Bug Fixes
    * Added a workaround to fix the issue that no interrupt was reported when user set smaller

period.

* Fixed violation of MISRA C-2012 rule 10.3 and 11.9.

– Improvements

* Added return value for the two APIs to set match value.

· OSTIMER_SetMatchRawValue

· OSTIMER_SetMatchValue

- 2.0.3

– Bug Fixes

* Fixed violation of MISRA C-2012 rule 10.3, 14.4, 17.7.

- 2.0.2

– Improvements

* Added support for OSTIMER0

- 2.0.1

– Improvements

* Removed the software reset function out of the initialization API.

* Enabled interrupt directly instead of enabling deep sleep interrupt. Users need to enable the deep sleep interrupt in application code if needed.

- 2.0.0

– Initial version.

OTFAD

The current driver version is 2.1.4.

- 2.1.4

– Bug fixes

* Fixed MISRA 2012 issue: 10.1.

- 2.1.3

– Bug fixes

* Fixed the error that waiting for both FLEXSPI AHB idle and SEQ idle.

- 2.1.2

– Bug fixes

* Fixed MISRA 2012 issue: 10.4.

- 2.1.1

– Improvements:

* Hided some bits in CR and SR registers for selected platforms.

* Fixed doxygen issues.

- 2.1.0

– Improvements:

* Used boolean type to define 1-bit field concepts.

- 2.0.0

– Initial version.

PINT

The current PINT driver version is 2.1.12.

- 2.1.12
  - **–** Bug Fixes
    - ∗ Fixed coverity issue.
- 2.1.11
  - **–** Bug Fixes
    - ∗ Fixed MISRA C-2012 rule 10.7 violation.
- 2.1.10
  - **–** New Features
    - ∗ Added the driver support for MCXN10 platform with combined interrupt handler.
- 2.1.9
  - **–** Bug Fixes
    - ∗ Fixed MISRA-2012 rule 8.4.
- 2.1.8
  - **–** Bug Fixes
    - ∗ Fixed MISRA-2012 rule 10.1 rule 10.4 rule 10.8 rule 18.1 rule 20.9.
- 2.1.7
  - **–** Improvements
    - ∗ Added fully support for the SECPINT, making it can be used just like PINT.
- 2.1.6
  - **–** Bug Fixes
    - ∗ Fixed the bug of not enabling common pint clock when enabling security pint clock.
- 2.1.5
  - **–** Bug Fixes
    - ∗ Fixed issue for MISRA-2012 check.
      - · Fixed rule 10.1 rule 10.3 rule 10.4 rule 10.8 rule 14.4.
    - ∗ Changed interrupt init order to make pin interrupt configuration more reasonable.
- 2.1.4
  - **–** Improvements
    - ∗ Added feature to control distinguish PINT/SECPINT relevant interrupt/clock configurations for PINT_Init and PINT_Deinit API.
    - ∗ Swapped the order of clearing PIN interrupt status flag and clearing pending NVIC interrupt in PINT_EnableCallback and PINT_EnableCallbackByIndex function.
    - ∗ Bug Fixes
      - · Fixed build issue caused by incorrect macro definitions.
- 2.1.3
  - **–** Bug fix:
    - ∗ Updated PINT_PinInterruptClrStatus to clear PINT interrupt status when the bit is asserted and check whether was triggered by edge-sensitive mode.
    - ∗ Write 1 to IST corresponding bit will clear interrupt status only in edge-sensitive mode and will switch the active level for this pin in level-sensitive mode.
    - ∗ Fixed MISRA c-2012 rule 10.1, rule 10.6, rule 10.7.
    - ∗ Added   FSL_FEATURE_SECPINT_NUMBER_OF_CONNECTED_OUTPUTS   to

distinguish IRQ relevant array definitions for SECPINT/PINT on lpc55s69 board.
* Fixed PINT driver c++ build error and remove index offset operation.
- 2.1.2
  – Improvement:
    * Improved way of initialization for SECPINT/PINT in PINT_Init API.
- 2.1.1
  – Improvement:
    * Enabled secure pint interrupt and add secure interrupt handle.
- 2.1.0
  – Added PINT_EnableCallbackByIndex/PINT_DisableCallbackByIndex APIs to enable/disable callback by index.
- 2.0.2
  – Added control macro to enable/disable the RESET and CLOCK code in current driver.
- 2.0.1
  – Bug fix:
    * Updated PINT driver to clear interrupt only in Edge sensitive.
- 2.0.0
  – Initial version.

POWERQUAD

The current POWERQUAD driver version is 2.2.0.

- 2.2.0
  – New Features
    * Added new API PQ_Arctan2Fixed.
- 2.1.1
  – Bug Fixes
    * Remove PQ_WaitDone from PQ_ArctanFixed and PQ_ArctanhFixed because it is unnecessary.
- 2.1.0
  – Improvements
    * Fixed typo issue for biquad related function name.
    * Changed operator from "%" into "&" to reduce heavy cycle for biquad functions.
- 2.0.5
  – Improvements
    * Added a note in driver for FIR that powerquad has a hardware limitation, when using it for FIR increment calculation, the address of pSrc needs to be a continuous address.
- 2.0.4
  – Improvements
    * Supported the platforms which don't have PowerQuad clock and reset control.
- 2.0.3
  – Bug Fixes
    * Fixed violations of the MISRA C-2012 rules 8.4, 10.1, 10.3, 10.4, 10.6, and so on.

- 2.0.2
    - Bug Fixes
        * Fixed array size issue in fsl_powerquad_data.h file.
        * Fixed vector function pipeline issue.
- 2.0.1
    - Bug Fixes
        * Fixed build error in C++ mode.
- 2.0.0
    - Initial version.

PUF

The current PUF driver version is 2.1.6.

- 2.1.6
    - Changed wait time in PUF_Init(), when initialization fails it will try PUF_Powercycle() with shorter time. If this shorter time will also fail, initialization will be tried with worst case time as before.
- 2.1.5
    - Use common SDK delay in puf_wait_usec().
- 2.1.4
    - Replace register uint32_t ticksCount with volatile uint32_t ticksCount in puf_wait_usec() to prevent optimization out delay loop.
- 2.1.3
    - Fix MISRA C-2012 issue.
- 2.1.2
    - Update: Add automatic big to little endian swap for user (pre-shared) keys destinated to secret hardware bus (PUF key index 0).
- 2.1.1
    - Fix ARMGCC build warning .
- 2.1.0
    - Align driver with PUF SRAM controller registers on LPCXpresso55s16.
    - Update initizalition logic .
- 2.0.3
    - Fix MISRA C-2012 issue.
- 2.0.2
    - New feature:
        * Add PUF configuration structure and support for PUF SRAM controller.
    - Improvements:
        * Remove magic constants.
- 2.0.1
    - Bug Fixes:
        * Fixed puf_wait_usec function optimization issue.
- 2.0.0

– Initial version.

SCTIMER

The current SCTimer driver version is 2.4.9.

- 2.4.9
  - Improvements
    * Supported platforms which don't have system level SCTIMER reset.
- 2.4.8
  - Bug Fixes
    * Fixed the issue that the SCTIMER_UpdatePwmDutycycle() can't writes MATCH_H bit and RELOADn_H.
- 2.4.7
  - Bug Fixes
    * Fixed the issue that the SCTIMER_UpdatePwmDutycycle() can't configure 100% duty cycle PWM.
- 2.4.6
  - Bug Fixes
    * Fixed the issue where the H register was not written as a word along with the L register.
    * Fixed the issue that the SCTIMER_SetCOUNTValue() is not configured with high 16 bits in unify mode.
- 2.4.5
  - Bug Fixes
    * Fix SCT_EV_STATE_STATEMSKn macro build error.
- 2.4.4
  - Bug Fixes
    * Fix MISRA C-2012 issue 10.8.
- 2.4.3
  - Bug Fixes
    * Fixed the wrong way of writing CAPCTRL and REGMODE registers in SCTIMER_-SetupCaptureAction.
- 2.4.2
  - Bug Fixes
    * Fixed SCTIMER_SetupPwm 100% duty cycle issue.
- 2.4.1
  - Bug Fixes
    * Fixed the issue that MATCHn_H bit and RELOADn_H bit could not be written.
- 2.4.0
- 2.3.0
  - Bug Fixes
    * Fixed the potential overflow issue of pulseperiod variable in SCTIMER_SetupPwm/SCT-IMER_UpdatePwmDutycycle API.
    * Fixed the issue of SCTIMER_CreateAndScheduleEvent API does not correctly work with

32 bit unified counter.
  * Fixed the issue of position of clear counter operation in SCTIMER_Init API.
  – Improvements
    * Update SCTIMER_SetupPwm/SCTIMER_UpdatePwmDutycycle to support generate 0% and 100% PWM signal.
    * Add SCTIMER_SetupEventActiveDirection API to configure event activity direction.
    * Update SCTIMER_StartTimer/SCTIMER_StopTimer API to support start/stop low counter and high counter at the same time.
    * Add SCTIMER_SetCounterState/SCTIMER_GetCounterState API to write/read counter current state value.
    * Update APIs to make it meaningful.
      · SCTIMER_SetEventInState
      · SCTIMER_ClearEventInState
      · SCTIMER_GetEventInState
- 2.2.0
  – Improvements
    * Updated for 16-bit register access.
- 2.1.3
  – Bug Fixes
    * Fixed the issue of uninitialized variables in SCTIMER_SetupPwm.
    * Fixed the issue that the Low 16-bit and high 16-bit work independently in SCTIMER driver.
  – Improvements
    * Added an enumerable macro of unify counter for user.
      · kSCTIMER_Counter_U
    * Created new APIs for the RTC driver.
      · SCTIMER_SetupStateLdMethodAction
      · SCTIMER_SetupNextStateActionwithLdMethod
      · SCTIMER_SetCOUNTValue
      · SCTIMER_GetCOUNTValue
      · SCTIMER_SetEventInState
      · SCTIMER_ClearEventInState
      · SCTIMER_GetEventInState
    * Deprecated legacy APIs for the RTC driver.
      · SCTIMER_SetupNextStateAction
- 2.1.2
  – Bug Fixes
    * MISRA C-2012 issue fixed: rule 10.3, 10.4, 10.6, 10.7, 11.9, 14.2 and 15.5.
- 2.1.1
  – Improvements
    * Updated the register and macro names to align with the header of devices.
- 2.1.0
  – Bug Fixes
    * Fixed issue where SCT application level Interrupt handler function is occupied by SCT driver.

       ∗ Fixed issue where wrong value for INSYNC field inside SCTIMER_Init function.

       ∗ Fixed issue to change Default value for INSYNC field inside SCTIMER_GetDefault-Config.

- 2.0.1
  - New Features
    - ∗ Added control macro to enable/disable the RESET and CLOCK code in current driver.
- 2.0.0
  - Initial version.

SEMA42

The current SEMA42 driver version is 2.0.4.

- 2.0.4
  - Improvements
    - ∗ Release peripheral from reset if necessary in init function.
- 2.0.3
  - Improvements
    - ∗ Changed to implement SEMA42_Lock base on SEMA42_TryLock.
- 2.0.2
  - Bug Fixes
    - ∗ Fixed violations of the MISRA C-2012 rules 17.7.
- 2.0.1
  - Bug Fixes
    - ∗ Fixed violations of the MISRA C-2012 rules 10.3, 10.4, 14.4, 18.1.
- 2.0.0
  - Initial version.

USDHC

The current USDHC driver version is 2.8.4.

- 2.8.4
  - Improvements
    - ∗ Add feature macro FSL_FEATURE_USDHC_HAS_NO_VS18.
- 2.8.3
  - Improvements
    - ∗ Improved api USDHC_EnableAutoTuningForCmdAndData to adapt to new bit field name for USDHC_VEND_SPEC2 register.
- 2.8.2
  - Improvements
    - ∗ Added feature macro FSL_FEATURE_USDHC_HAS_NO_VOLTAGE_SELECT.
- 2.8.1
  - Bug Fixes

* Fixed violations of MISRA C-2012 rule 11.9.
* 2.8.0
  – Improvements
    * Fixed the mmc boot transfer failed issue which is caused by the Dma complete interrupt not enabled.
    * Marked api USDHC_AdjustDelayForManualTuning as deprecated and added new api U-SDHC_SetTuingDelay/USDHC_GetTuningDelayStatus.
    * Improved the manual tuning flow accroding to specification.
    * Added memory address conversion to support buffers which could only be accessed using alias address by non-core masters.
    * Fixed violations of MISRA C-2012 rule 10.4.
* 2.7.0
  – Improvements
    * Added api USDHC_TransferScatterGatherADMANonBlocking to support scatter gather transfer.
    * Added feature FSL_FEATURE_USDHC_REGISTER_HOST_CTRL_CAP_HAS_NO_-RETUNING_TIME_COUNTER for re-tuning time counter field in HOST_CTRL_CAP register.
  – Bug Fixes
    * Fixed violations of MISRA C-2012 rule 11.9, 10.1, 10.3, 10.4, 8.4.
* 2.6.0
  – Improvements
    * Added api USDHC_SetStandardTuningCounter to support adjust tuning counter of Standard tuning.
* 2.5.1
  – Improvements
    * Used different status code for command and data interrupt callback.
    * Added cache line invalidate for receive buffer in driver IRQ handler to fix CM7 speculative access issue.
* 2.5.0
  – Improvements
    * Added new api USDHC_SetStrobeDllOverride for HS400 strobe dll override mode delay taps configurations.
    * Corrected the STROBE DLL configurations sequence.
* 2.4.0
  – Improvements
    * Added feature macro for read/write burst length.
      · Disabled redundant interrupt per different transfer request.
      · Disabled interrupt and reset command/data pointer in handle when transfer completes.
  – Bug Fixes
    * Fixed violations of MISRA C-2012 rule 11.9, 15.7, 4.7, 16.4, 10.1, 10.3, 10.4, 11.3, 14.4, 10.6, 17.7, 16.1, 16.3.
    * Fixed PA082 build warning.
    * Fixed logically dead code Coverity issue.
* 2.3.0

- Improvements
    * Added USDHC_SetDataConfig API to support manual tuning.
    * Removed the limitaion that source clock must be bigger than the target in function USD-HC_SetSdClock by using source clock frequency as target directly.
    * Added peripheral reset in USDHC_Init function.
    * Added tuning reset support in function USDHC_Reset function.
- 2.2.8
    - Bug Fixes
        * Fixed out-of bounds write in function USDHC_ReceiveCommandResponse.
- 2.2.7
    - Improvements
        * Added API USDHC_GetEnabledInterruptStatusFlags and used in USDHC_Transfer-HandleIRQ.
        * Removed useless member interruptFlags in usdhc_handle_t.
- 2.2.6
    - Improvements
        * Added address align check for ADMA descriptor table address.
        * Changed USDHC_ADMA1_DESCRIPTOR_MAX_LENGTH_PER_ENTRY to (65536-4096) to make sure the data address is 4KB align for a transfer which need more than one ADMA1 descriptor.
- 2.2.5
    - Bug Fixes
        * Fixed MDK 66-D warning.
- 2.2.4
    - Bug Fixes
        * Fixed issue that real clock frequency wss mismatched with target clock frequency, which was caused by an incorrect prescaler calculation.
    - New Features
        * Added control macro to enable/disable the CLOCK code in current driver.
- 2.2.3
    - Bug Fixes
        * Fixed issue where AMDA did not disable with DMAEN clear.
    - Improvements
        * Improved set clock function to check the output frequency range.
        * Dynamic set SDCLKFS during DDR enable or disable.
- 2.2.2
    - Improvements
        * Improved read transfer cache maintain operation, combined clean, and invalidated them into one function.
- 2.2.1
    - Bug Fixes
        * Disabled the invalidate cache operation for tuning.
- 2.2.0
    - Improvements
        * Improved USDHC to support MMC boot feature.

- 2.1.3
    - Bug Fixes
        * Fixed MISRA issue.
- 2.1.2
    - Bug Fixes
        * Fixed Coverity issue.
        * Added base address and userData parameter for all callback functions.
- 2.1.1
    - Improvements
        * Added cache maintain operation.
        * Added timeout status check for the DATA transfer which ignore error.
        * Added feature macro for SDR50/SDR104 mode.
        * Removed useless IRQ handler from different platforms.
- 2.1.0
    - Improvements
        * Integrated tuning into transfer function.
        * Added strobe DLL feature.
        * Added enableAutoCommand23 in data structure.
        * Removed enable card clock function because the controller would handle the clock on/off.
- 2.0.0
    - Initial version.

UTICK

The current UTICK driver version is 2.0.5.

- 2.0.5
    - Improvements
        * Improved for SOC RW610.
- 2.0.4
    - Bug Fixes
        * Fixed compile fail issue of no-supporting PD configuration in utick driver.
- 2.0.3
    - Bug Fixes
        * Fixed violations of MISRA C-2012 rules: 8.4, 14.4, 17.7
- 2.0.2
    - Added new feature definition macro to enable/disable power control in drivers for some devices have no power control function.
- 2.0.1
    - Added control macro to enable/disable the CLOCK code in current driver.
- 2.0.0
    - Initial version.

WWDT

The current WWDT driver version is 2.1.9.

- 2.1.9
  - **Bug Fixes**
    - ∗ Fixed violation of the MISRA C-2012 rule 10.4.
- 2.1.8
  - **Improvements**
    - ∗ Updated the "WWDT_Init" API to add wait operation. Which can avoid the TV value read by CPU still be 0xFF (reset value) after WWDT_Init function returns.
- 2.1.7
  - **Bug Fixes**
    - ∗ Fixed the issue that the watchdog reset event affected the system from PMC.
    - ∗ Fixed the issue of setting watchdog WDPROTECT field without considering the backwards compatibility.
    - ∗ Fixed the issue of clearing bit fields by mistake in the function of WWDT_ClearStatus-Flags.
- 2.1.5
  - **Bug Fixes**
    - ∗ deprecated a unusable API in WWWDT driver.
      - · WWDT_Disable
- 2.1.4
  - **Bug Fixes**
    - ∗ Fixed violation of the MISRA C-2012 rules Rule 10.1, 10.3, 10.4 and 11.9.
    - ∗ Fixed the issue of the inseparable process interrupted by other interrupt source.
      - · WWDT_Init
- 2.1.3
  - **Bug Fixes**
    - ∗ Fixed legacy issue when initializing the MOD register.
- 2.1.2
  - **Improvements**
    - ∗ Updated the "WWDT_ClearStatusFlags" API and "WWDT_GetStatusFlags" API to match QN9090. WDTOF is not set in case of WD reset. Get info from PMC instead.
- 2.1.1
  - **New Features**
    - ∗ Added new feature definition macro for devices which have no LCOK control bit in MOD register.
    - ∗ Implemented delay/retry in WWDT driver.
- 2.1.0
  - **Improvements**
    - ∗ Added new parameter in configuration when initializing WWDT module. This parameter, which must be set, allows the user to deliver the WWDT clock frequency.
- 2.0.0
  - **Initial version.**

2 Middleware Change Log

DSP Audio Streamer

The current version of DSP Audio Streamer is 2.6p2.

- 2.6p2
  - Update to version 2.6p2 (2.6 patch)
- 2.6p1
  - Update to version 2.6p1 (2.6 patch release 1)
- 2.6
  - Update to version 2.6 GA
- 2.0
  - Initial version of DSP Audio Streamer

NatureDSP

The current version of NatureDSP is 4.1.1.

- 4.1.1
  - Updated to 4.1.1 version of NatureDSP from Cadence for HiFi4 DSP. Library built with nxp-_rt600_RI23_11_newlib build configuration.
- 4.1.0
  - Updated to 4.1.0 version of NatureDSP from Cadence for HiFi4 DSP. Library built with nxp-_rt600_RI2021_8_newlib build configuration.
- 4.0.0
  - Initial version of NatureDSP from Cadence for HiFi4 DSP.

eIQ TensorFlow Lite for Microcontrollers library

Current version is 23-09-18

- 22-09-18
  - New Features
    * Updated eIQ TensorFlow Lite for Microcontrollers library to version from the 18th of September 2023
    * Updated third party library source codes:
      · CMSIS-NN
- 22-03-23
  - New Features
    * Updated eIQ TensorFlow Lite for Microcontrollers library to version from the 23rd of March 2023
    * Updated third party library source codes:

    · CMSIS-NN

    · Xtensa NN library

- 22-09-19
  - New Features
    * Updated eIQ TensorFlow Lite for Microcontrollers library to version from the 19th of September 2022
    * Updated third party library source codes:
      · CMSIS-NN
      · FFT2D
      · FlatBuffers
      · Gemmlowp
      · Ruy
      · Xtensa NN library
  - Improvements
    * Shortened example names
- 22-02-16
  - New Features
    * Updated eIQ TensorFlow Lite for Microcontrollers library to version from the 16th of February 2022
    * Updated third party library source codes:
      · CMSIS-NN
      · FFT2D
      · FlatBuffers
      · Gemmlowp
      · Ruy
      · Xtensa NN library
- 2.6.0
  - New Features
    * Updated eIQ TensorFlow Lite for Microcontrollers library to version 2.6.0
    * Updated third party library source codes:
      · CMSIS-NN
      · FFT2D
      · FlatBuffers
      · Gemmlowp
      · Ruy
      · Xtensa NN library
- 2.4.1
  - New Features
    * Updated eIQ TensorFlow Lite for Microcontrollers library to version 2.4.1
    * Removed source codes related to TensorFlow Lite library only
    * Updated third party library source codes:
      · CMSIS-NN
      · FFT2D
      · FlatBuffers
      · Gemmlowp

        · Ruy
- ∗ Converted TensorFlow Lite examples to TensorFlow Lite for Microcontrollers (changed API use)
- 2.3.1
  - **New Features**
    - ∗ Updated eIQ TensorFlow Lite library to version based on the TensorFlow Lite library version 2.3.1
    - ∗ Added TensorFlow Lite for Microcontrollers library source codes
    - ∗ Updated third party library source codes:
      - · Abseil
      - · Eigen
      - · Farmhash
      - · FFT2D
      - · FlatBuffers
      - · Gemmlowp
    - ∗ Added third party library source codes:
      - · CMSIS-NN
      - · Ruy
    - ∗ Added examples:
      - · tensorflow_lite_micro_label_image
- 2.1.0
  - **New Features**
    - ∗ Updated eIQ TensorFlow Lite library to version based on the TensorFlow Lite library version 2.1.0
    - ∗ Updated third party library source codes:
      - · Eigen
      - · Farmhash
      - · FFT2D
      - · FlatBuffers
      - · Gemmlowp
    - ∗ Added third party library source codes:
      - · Abseil
    - ∗ Added examples:
      - · tensorflow_lite_benchmark
- 1.14.0
  - **New Features**
    - ∗ Updated eIQ TensorFlow Lite library to version based on the TensorFlow Lite library version 1.14.0
    - ∗ Updated third party library source codes:
      - · Eigen
      - · Farmhash
      - · FFT2D
      - · FlatBuffers
      - · Gemmlowp
    - ∗ Added examples:

· tensorflow_lite_adt
  - **Improvements**
    * Extended examples:
      · tensorflow_lite_cifar10
      · Added camera and LCD support
      · Realtime camera image inference
      · tensorflow_lite_kws
      · Added microphone and headphone support
      · Realtime audio inference
      · tensorflow_lite_label_image
      · Added camera and LCD support
      · Realtime camera image inference
- 1.11.0
  - **New Features**
    * Added eIQ TensorFlow Lite library based on TensorFlow Lite version 1.11.0
    * Added third party library source codes:
      · Eigen
      · Farmhash
      · FFT2D
      · FlatBuffers
      · Gemmlowp
    * Added examples:
      · tensorflow_lite_cifar10
      · tensorflow_lite_kws
      · tensorflow_lite_label_image
      · tensorflow_lite_lib

emWin library

The currently supported version is 6.34c

- v6.34c
  - upgraded to v6.34c
- v6.28_rev1
  - add cm33_nodsp_fpu libraries for Cortec M33 without DSP extension with SP FPU
- v6.28
  - upgraded to v6.28
- v6.24_rev2
  - add cm33_nodsp libraries for Cortex M33 without DSP extension
- v6.24_rev1
  - recompiled cm33 library with fpu single precision
  - added cm7_sp library for Cortex M7 with sp fpu for IAR
- v6.24
  - upgraded to v6.24

- v6.16c
    - upgraded to v6.16c
    - updated temperature_control demo generated by AppWizard
- v6.14d
    - upgraded to v6.14d
- v6.10f
    - upgraded to v6.10f

FatFs for MCUXpresso SDK

Current version is FatFs R0.15_rev0.

- R0.15_rev0
    - Upgraded to version 0.15
    - Applied patches from http://elm-chan.org/fsw/ff/patches.html
- R0.14b_rev1
    - Applied patches from http://elm-chan.org/fsw/ff/patches.html
- R0.14b_rev0
    - Upgraded to version 0.14b
- R0.14a_rev0
    - Upgraded to version 0.14a
    - Applied patch ff14a_p1.diff and ff14a_p2.diff
- R0.14_rev0
    - Upgraded to version 0.14
    - Applied patch ff14_p1.diff and ff14_p2.diff
- R0.13c_rev0
    - Upgraded to version 0.13c
    - Applied patches ff_13c_p1.diff,ff_13c_p2.diff, ff_13c_p3.diff and ff_13c_p4.diff.
- R0.13b_rev0
    - Upgraded to version 0.13b
- R0.13a_rev0
    - Upgraded to version 0.13a. Added patch ff_13a_p1.diff.
- R0.12c_rev1
    - Add NAND disk support.
- R0.12c_rev0
    - Upgraded to version 0.12c and applied patches ff_12c_p1.diff and ff_12c_p2.diff.
- R0.12b_rev0
    - Upgraded to version 0.12b.
- R0.11a
    - Added glue functions for low-level drivers (SDHC, SDSPI, RAM, MMC). Modified diskio.c.
    - Added RTOS wrappers to make FatFs thread safe. Modified syscall.c.
    - Renamed ffconf.h to ffconf_template.h. Each application should contain its own ffconf.h.
    - Included ffconf.h into diskio.c to enable the selection of physical disk from ffconf.h by macro definition.

– Conditional compilation of physical disk interfaces in diskio.c.

FreeMASTER Communication Driver

Current version is 3.0.6. Visit https://www.nxp.com/freemaster for more information. Reach out for a support at https://community.nxp.com/community/freemaster.

- 3.0.0
  - Initial version of FreeMASTER driver reworked from a standalone package to MCUXpresso SDK middleware.
  - This driver version supports new version V4 of FreeMASTER serial communication protocol.
  - Supports UART, LPUART, USART, MINIUSART, FlexCAN, USB-CDC and JTAG/BDM communication.
  - Initial version was tested with the following boards: evkmimxrt1060, frdmk64f, frdmke15z, frdmkl28z, lpcxpresso54628 lpcxpresso55s69, lpcxpresso845max and twrk64f120m.
  - Use with FreeMASTER PC Host tool version 2.5 or later.
- 3.0.1
  - FreeMASTER driver extended to support wide range of Kinetis, LPC and i.MX-RT platforms.
  - Low-level communication drivers also available for few non-SDK NXP platforms like S12Z, S32x and more.
  - Use with FreeMASTER PC Host tool version 3.0 or later.
- 3.0.2
  - FreeMASTER driver support of DSC56F800EX and S12 platforms extended.
  - Removed dependency on C99 compiler features.
  - Use with FreeMASTER PC Host tool version 3.0.2 or later.
- 3.0.3
  - General update for SDK 2.9.0
  - fmstr_any demo added to selected platforms - use with MCUXpresso SDK and FreeMASTER peripheral configuration tool.
  - New example.pmp project file embedded into application flash storage.
  - USB-CDC implementation fixed, new JTAG EOnCE communication interface added to DSC 56F800E family.
  - Use with FreeMASTER PC Host tool version 3.0.3 or later. Version 3.1.x is recommended.
- 3.0.4
  - Fixed component dependency logic of FreeMASTER driver.
  - Use with FreeMASTER PC Host tool version 3.1.x
- 3.0.5
  - General update for SDK 2.11 and 2.12
  - New TCP and UDP support with lwIP stack
  - New communication over Segger RTT interface
  - Add fmstr_net and fmstr_wifi examples for selected i.MX-RT platforms
  - Add fmstr_rtt example for selected platforms
  - Fixed negative recorder threshold trigger processing
- 3.0.6

– General update for SDK 2.13
– Use of new Ethernet MDIO driver concept.
– Support of ENET and NETC Ethernet modules in the fmstr_net example application.
• 3.0.7
– General update for SDK 2.14

fail-safe filesystem for MCUXpresso SDK

The current version littlefs filesystem is 2.5.0_rev0.

• 2.5.0_rev0
– littlefs updated to version 2.5.0
• 2.4.1_rev0
– littlefs updated to version 2.4.1
• 2.4.0_rev0
– littlefs updated to version 2.4.0
• 2.2.1_rev0
– littlefs updated to version 2.2.1
• 2.1.4_rev0
– littlefs updated to version 2.1.4
• 1.3_rev0
– Initial version of littlefs filesystem for MCUXpresso SDK

LVGL for KSDK

• 8.3.10_rev1
– Integrate LVGL 8.3.10 to SDK.
• 8.3.9_rev1
– Integrate LVGL 8.3.9 to SDK.
• 8.3.5_rev1
– Integrate LVGL 8.3.5 to SDK.
• 8.3.2_rev1
– Integrate LVGL 8.3.2 to SDK.
• 8.3.0_rev1
– Integrate LVGL 8.3.0 to SDK.
• 8.2.0_rev1
– Integrate LVGL 8.2.0 to SDK.
• 8.0.2_rev1
– Integrate LVGL 8.0.2 to SDK.
• 7.10.1_rev1
– Integrate LVGL 7.10.1 to SDK.
– Added PXP, VGLite hardware acceleration.
• 7.4.0_rev1

– Integrate LVGL 7.4.0 to SDK.
- 7.0.0_rev1
    – Integrate LVGL 7.0.0 to SDK.
    – Added PXP hardware acceleration initial version.
- 6.1.1_rev1
    – Integrate LVGL 6.1.1 to SDK.
- 5.3_rev1
    – Integrate LVGL 5.3 to SDK.

lwIP for MCUXpresso SDK

Lightweight IP (lwIP) is a small independent implementation of the TCP/IP protocol suite. Source code included in this SDK is based on version 2.2.0 taken from 3rd party lwIP GIT repository. The webpage <https://git.savannah.nongnu.org/cgit/lwip.git> allows to browse the repository and also contains URLs for its cloning. The development versions (X.Y.Z.dev) do not refer to a single source code snapshots. To avoid ambiguity, change log below contains SHA-1 hashes of GIT commits used when importing the code into the SDK.

- 2.2.0_rev10
    – New features:
        * Ported lwIP 2.2.0 (2023-09-25, branch: master, SHA-1: 0a0452b2c39bdd91e252aef045c115f88f6c tag: STABLE-2_2_0_RELEASE) to MCUXpresso SDK.
        * Enabled hardware-accelerated CRC computation and verification (MAC, IPv4, TCP, UDP, ICMPv4, ICMPv6) for ENET Kinetis, ENET QoS and ENET LPC.
        * Enabled link state detection based on PHY interrupts. The ETH_LINK_POLLING_INTERVAL_MS macro controls this - setting it to 0 and specifying ethernetif_config_t->phyIntGpio enables it, setting it to a value greater than zero enables polling instead. Supported only under an RTOS (NO_SYS == 0). By default, the link state is polled.
        * ND6: Implemented RFC 4191 type C host, which means default router list (learned from Router Advertisement messages) has been replaced with routing table, which contains default route records for each router and also routes learned from received Route Information Options. Changes partially based on <https://savannah.-nongnu.org/patch/?10114>. The option LWIP_ND6_NUM_ROUTERS has been removed, and the new option LWIP_ND6_NUM_ROUTES has been added to configure the size of the routing table.
        * IPv6: Implemented a new hook - LWIP_HOOK_IP6_CANFORWARD. This hook can be used, for example, for multicast forwarding between netifs. Defining this hook enables multicast traffic forwarding, thus the hook is also invoked for multicast traffic.
        * MLD6: Multicast Listener Discovery v1 replaced by v2 (RFC 3810) but without support of source specific multicast.
        * port/enet_ethernetif_kinetis.c: Added check to generate/validate ICMPv6 checksum in SW as the Kinetis ENET peripheral does not do it.
        * Added disabling of Rx interrupt when the port is out of Rx buffers. See port/README.md for more details.

- Bug fixes:
  * src/apps/lwiperf: Fixed access to invalid data when UDP report is to be sent from a timer but abort has been called before.
  * src/apps/lwiperf: Fixed deallocation of TCP server started by client (in reverse or dual modes) which failed to connect.
  * port/netc_ethernetif.c: Fixed cache control enablement macro (FSL_SDK_ENABLE_-DRIVER_CACHE_CONTROL > FSL_ETH_ENABLE_CACHE_CONTROL).
  * port/sys_arch.c: The function sys_assert does not call portENTER_CRITICAL when called from an interrupt.
  * src/core/ipv4/ip4.c: Fixed checksum reset condition.
  * ND6:
    · Lladdr length is now taken from netif->hwaddr_len so ND6 works properly regardless of NETIF_MAX_HWADDR_LEN.
    · Added check of sufficient length of lladdr options from incoming messages.
  * src/apps/httpsrv/httpsrv.c: Fixed hangup in HTTPSRV_release if caller's task has higher priority than server task.
- port/arch/cc.h: LWIP_PLATFORM_DIAG is defined (and can be overridden) independently of the LWIP_DEBUG setting. Removed printing extra newline symbols from LWIP_PLAT-FORM_DIAG.
- src/apps/lwiperf: The "end of test" UDP datagram is resent more often. This increases the probability of the server to receive it and end the test when datagrams are getting lost.
- Added port/README.md describing possible settings and helper functions in the port layer.
- 2.2.0_rev9
  - New features:
    * Ported lwIP 2.2.0.dev (2023-01-03, branch: master, SHA-1: 3fe8d2fc43a9b69f7ed28c63d44a7744f to MCUXpresso SDK.
    * Applied patch to allow sending IPv6 router advertisement. Improved to allow selection of interface and router life time and to allow sending route information options.
    * src/apps/lwiperf: Support for reverse test (client receives, server sends). Requires iperf version 2.1.0 or newer.
  - Bug fixes:
    * src/apps/httpsrv: Fixed operation with LWIP_IPV6 enabled. Server can be also accessed using both IPv4 and IPv6 at the same time if compiled with both LWIP_IP-V4=1 and LWIP_IPV6=1. Note the type of the field struct httpsrv_param_struct.address has changed from struct sockaddr to struct sockaddr_storage.
- 2.2.0_rev8
  - New features:
    * src/apps/lwiperf: Added new parameter "buffer_len" to functions lwiperf_start_tcp_-client() and lwiperf_start_udp_client() to configure TCP/UDP packet size.
    * src/apps/lwiperf: Added new parameter "tos" to functions lwiperf_start_tcp_client() to configure TCP packet priority.
    * NETC adaptation layer: Not forcing the RX/TX buffers placement in non-cacheable memory. Requires the symbol FSL_ETH_ENABLE_CACHE_CONTROL to be defined on project level if the memory region, where the buffers are placed by a linker, has cache enabled.

- **–** Bug fixes:
    - ∗ src/apps/httpsrv: Added missing includes.
    - ∗ src/apps/lwiperf: Fixed TCP client to send settings at the beginning of each 128 KB block like the PC iperf 2.0.x application does.
    - ∗ src/apps/lwiperf: Fixed validation of TCP received data (with LWIPERF_CHECK_R-X_DATA enabled, works with iperf 2.0.x).
    - ∗ src/apps/lwiperf: Fixed lwiperf_list_remove() to clear references to the removed item.
- **–** src/apps/lwiperf: Program does not assert when buffer cannot be cloned in UDP test, only "can't clone buffer" message is printed.
- **•** 2.2.0_rev7
    - **–** New features:
        - ∗ Ported lwIP 2.2.0.dev (2022-05-09, branch: master, SHA-1: 239918ccc173cb2c2a62f41a40fd893f5 to MCUXpresso SDK.
        - ∗ Added function ethernetif_probe_link() which reads actual link, speed and duplex settings from phy and passes them to driver. Stack could be set to call this function periodically by setting ETH_LINK_POLLING_INTERVAL_MS to value higher than zero.
        - ∗ Added helper functions ethernetif_wait_linkup() and ethernetif_wait_ipv4_valid() to allow blocking of RTOS task or bare metal application until link is up or IPv4 address becomes valid.
        - ∗ Added NETC adaptation layer.
        - ∗ Processing of rx packets under RTOS moved from ISR to a separate task to improve system reaction times. Switch back to old behavior can be done by setting ETH_DO_-RX_IN_SEPARATE_TASK macro to 0.
    - **–** Bug fixes:
        - ∗ port: Fixed copying of pbuf contents. Previous code was using an incorrect end condition and could result in the overrun of the destination buffer if more packets were on the queue.
        - ∗ port: Delegating pbuf_free calls to tcpip_thread via pbuf_free_callback where possible (RTOS), ensured pbuf_free is not called from interrupt context when LWIP_ALLOW-_MEM_FREE_FROM_OTHER_CONTEXT is not set (bare metal).
        - ∗ port/enet_ethernetif_qos.c - Fixed ENET_RXBD_NUM which was used instead of E-NET_TXBD_NUM.
        - ∗ port/enet_ethernetif_qos.c - Fixed buffer alignment to be at least 64.
        - ∗ src/apps/lwiperf: Fixed IPv6 TCP TX throughput lower than IPv4 by modifying maximum segment size to avoid sending two segments instead of one.
        - ∗ src/apps/lwiperf: Out-of-order datagrams in UDP RX server mode are counted to the throughput.
        - ∗ src/apps/httpsrv: Implemented receive timeouts on sockets.
        - ∗ src/apps/httpsrv: Don't assert on HTTP session task creation failure.
        - ∗ src/apps/httpsrv: Fixed build with IPv6 enabled.
        - ∗ src/apps/httpsrv: Updated endianess macros required for websocket SHA generation.
        - ∗ src/apps/httpsrv: Added missing includes.
- **•** 2.2.0_rev6
    - **–** New features:

  * Ported lwIP 2.2.0.dev (2022-03-25, branch: master, SHA-1: 124dc0a64ef5d7c14a27e3115e5888df(
    to MCUXpresso SDK.
  * Implemented leaving of multicast groups on ENET and ENET QOS.
- 2.2.0_rev5
    - New features:
        * Ported lwIP 2.2.0.dev (2021-05-11, branch: master, SHA-1: 7ec4e9be304e7f8953740f10b2c810a29
          to MCUXpresso SDK.
        * LPC ENET adaptation layer allocates more buffers for frame reception now. Previously
          the number of receive buffers was determined by ENET_RXBD_NUM, which defaults
          to 5. It is determined by ENET_RXBUFF_NUM now, which is 2 ∗ ENET_RXBD_N-
          UM by default. Increase was needed because the actual version of LPC ENET driver
          always hold ENET_RXBD_NUM number of buffers and few additional buffers are
          needed for passing zero-copy frame data to lwIP. If this takes too much memory in
          your application, you can counteract by decreasing PBUF_POOL_SIZE, since PBUF_-
          POOL is used only for transmission when LPC ENET, Kinetis ENET or ENET QOS is
          used.
- 2.2.0_rev4
    - New features:
        * Ported lwIP 2.2.0.dev (2021-03-05, branch: master, SHA-1: 0056522cc974d2be2005c324f37187b5
          to KSDK 2.0.0.
        * LWIP_DHCP_DOES_ACD_CHECK option default changed to 0 (disabled):
            · Although the ACD check makes getting IP address from DHCP more robust, it
              added several seconds delay at startup of all applications which use DHCP.
            · This feature was not present in earlier versions of lwIP.
        * ENET QOS adaptation layer - implemented zero-copy on receive.
        * Kinetis ENET and ENET QOS adaptation layers allocate more buffers for frame
          reception now. Previously the number of receive buffers was determined by ENET-
          _RXBD_NUM, which defaults to 5. It is determined by ENET_RXBUFF_NUM now,
          which is 2 ∗ ENET_RXBD_NUM by default. Increase was needed because the actual
          version of Kinetis ENET and ENET QOS drivers always hold ENET_RXBD_NUM
          number of buffers and few additional buffers are needed for passing zero-copy frame
          data to lwIP. If this takes too much memory in your application, you can counteract
          by decreasing PBUF_POOL_SIZE, since PBUF_POOL is used only for transmission
          when Kinetis ENET or ENET QOS is used.
        * Removed ethernetif_config_t.non_dma_memory field which was required to configure
          memory ranges unusable by ENET DMA on LPC devices. The setting has been
          replaced by BOARD_ENET_NON_DMA_MEMORY_ARRAY macro.
- 2.2.0_rev3
    - New features:
        * Ported lwIP 2.2.0.dev (2020-07-07, branch: master, SHA-1: c385f31076b27efb8ee37f00cb5568783
          to KSDK 2.0.0.
- 2.2.0_rev2
    - New features:
        * Kinetis ENET adaptation layer - implemented zero-copy on receive.
        * lwiperf - counter of transferred bytes extended from 32 to 64 bit

- Bug fixes:
  - * Fixed restarting Auto IP from DHCP.
- 2.2.0_rev1
  - New features:
    - * Ported lwIP 2.2.0.dev (2019-12-12, branch: master, SHA-1: 555812dcec38c9a2ef1ef9b31816291154 to KSDK 2.0.0.
    - * Implemented LWIP_ASSERT_CORE_LOCKED related functions in sys_arch.c. It can be enabled in lwipopts.h:
      - · `#define LWIP_ASSERT_CORE_LOCKED() sys_check_core_-`
        `locking()`
      - · `#define LWIP_MARK_TCPIP_THREAD() sys_mark_tcpip_thread()`
        `// if NO_SYS == 0`
      - · `#define LOCK_TCPIP_CORE() sys_lock_tcpip_core() // if`
        `NO_SYS == 0 and LWIP_TCPIP_CORE_LOCKING == 1`
      - · `#define UNLOCK_TCPIP_CORE() sys_unlock_tcpip_core()`
        `// if NO_SYS == 0 and LWIP_TCPIP_CORE_LOCKING == 1`
- 2.1.2_rev5
  - New features:
    - * Implemented TCP_USER_TIMEOUT socket option.
    - * Implemented SIOCOUTQ ioctl.
- 2.1.2_rev4
  - New features:
    - * Ported lwIP 2.1.3.dev (2019-02-27, branch: STABLE-2_1_x, SHA-1: 1bb6e7f52de1cd86be0eed31 to KSDK 2.0.0.
    - * Updated sys_thread_new implementation and comment.
    - * Kinetis ENET adaptation layer - reading frames into a pbuf chain is conditionally compiled only when a single pbuf from pool cannot hold maximum frame size (PBU-F_POOL_BUFSIZE >= maximum frame size). Avoiding this code also reduces stack size requirements by about 1.5 kilobytes.
  - Bug fixes:
    - * Fixes in ethernetif_linkoutput() in enet_ethernetif_lpc.c:
      - · Removed access to possibly freed pbuf.
      - · Call pbuf_free() when transmit buffers not available.
      - · When copying pbuf chain, updating the number of necessary transmit buffers to wait for, which can be often smaller in the copy.
    - * When CGI script is reading POST data by chunks, the loop in httpsrv_read() may cause blocking in receive function waiting for more data at the end of the stream
      - · HTTPSRV_cgi_read() - added limiting of the last chunk length according to content length to avoid undesired blocking
    - * Applied AUTOIP patch https://savannah.nongnu.org/patch/?9847 - with modification to support multiple network interfaces.
    - * Fixed buffer overflow in httpsrv when application provided CGI script does not handle the whole content of POST request
  - Removed LwipMibCompiler contrib application as it contained LGPL licensed files in Sharp-SnmpLib.

- 2.1.2_rev3
    - New features:
        * lwiperf updated with UDP client/server support from the patch 9751 (`https-://savannah.nongnu.org/patch/?9751`)
- 2.1.2_rev2
    - Bug fixes:
        * Fixed lwiperf_abort() in lwiperf.c to correctly close connections and free resources
- 2.1.2_rev1
    - New features:
        * Ported lwIP 2.1.2 (2018-11-22, SHA-1: 159e31b689577dbf69cf0683bbaffbd71fa5ee10) to KSDK 2.0.0.
        * Ported lwIP-contrib 2.1.0 (2018-09-24, SHA-1: 35b011d4cf4c4b480f8859c456587a884ec9d287) to KSDK 2.0.0.
- 2.0.3_rev1
    - New features:
        * Ported lwIP 2.0.3 (2017-09-15, SHA-1: 92f23d6ca0971a32f2085b9480e738d34174417b) to KSDK 2.0.0.
- 2.0.2_rev1
    - New features:
        * Ported lwIP 2.0.2 (2017-03-13, SHA-1: c0862d60746e2d1ceae69af4c6f24e469570ecef) to KSDK 2.0.0.
- 2.0.0_rev3
    - New features:
        * Ported lwIP 2.0.0 (2016-11-10, SHA-1: 216bf89491815029aa15463a18744afa04df58fe) to KSDK 2.0.0.
- 2.0.0_rev2
    - New features:
        * Ported lwIP 2.0.0 RC2 (2016-08-08, SHA-1: b1dfd00f9233d124514a36a8c8606990016f2ad4) to KSDK 2.0.0.
- 2.0.0_rev1
    - New features:
        * Ported lwIP 2.0.0 RC0 (2016-05-26) to KSDK 2.0.0.
        * Changed lwIP bare-metal examples to use poll-driven approach instead of interrupt-driven one.
- 1.4.1_rev2
    - New features:
        * Enabled critical sections in lwIP.
    - Bug fixes:
        * Fixed default lwIP packet-buffer size to be able to accept a maximum size frame from the ENET driver.
        * Fixed possible drop of multi-frame packets during transmission.
- 1.4.1_rev1
    - New features:
        * Ported lwIP 1.4.1 to KSDK 2.0.0.

mbedTLS for MCUXpresso SDK

The current version of mbedTLS is based on mbed TLS 2.28.5 branch released 2023-10-05

- 2.28.5
    - New features:
        * Ported mbedTLS 2.28.5 to SDK.
- 2.28.4
    - New features:
        * Ported mbedTLS 2.28.4 to SDK.
- 2.28.3
    - New features:
        * Ported mbedTLS 2.28.3 to SDK.
- 2.28.1
    - New features:
        * Ported mbedTLS 2.28.1 to SDK.
- 2.28.0
    - New features:
        * Ported mbedTLS 2.28.0 to SDK.
- 2.27.0
    - New features:
        * Ported mbedTLS 2.27.0 to SDK.
- 2.26.0
    - New features:
        * Ported mbedTLS 2.26.0 to SDK.
- 2.16.6_rev7
    - Bug fixes:
        * Corrected definition of global variable g_isCryptoHWInitialized to be only internal static variable in sssapi_mbedtls.c file.
- 2.16.6_rev6
    - Bug fixes:
        * Adding #ifdef in ecdsa.c to remove warning: "function "derive_mpi" was declared but never referenced", when alternative implementation of ECDSA sign and verify is used and not used Deterministic ECDSA, then was derive_mpi function never used.
- 2.16.6_rev5
    - New features:
        * Changed return type of CRYPTO_InitHardware() from void to status_t. Added check of this return value in selftest.c and benchmark.c files.
- 2.16.6_rev4
    - New features:
        * Added mutex for HW modules HASHCRYPT and CASPER. Enabled by MBEDTLS_THREADING_C
- 2.16.6_rev3
    - New features:
        * Added support for KW45 device with latest Sentinel200. Port of SSS API mbedtls implementation to KW45.

- 2.16.6_rev2
    - New features:
        * Added support for SW computing AES-192/256 while using DCP driver.
- 2.16.6_rev1
    - New features:
        * Added support for NIST P-521 elliptic curve with CASPER driver.
        * Added support for using multiple elliptic curves at once with CASPER driver.
- 2.16.6
    - New features:
        * Ported mbedTLS 2.16.6 to SDK.
- 2.16.2_rev2
    - Bug fixes:
        * Add support for HASHCRYPT context switch check, Hashcrypt without context switch is not able to calculate SHA in parallel with AES. HW acceleration of SHA is disabled by default in MbedTLS integration, enabled on chip with context switch.
- 2.16.2_rev1
    - Bug fixes:
        * Add support for CTR_DRBG using AES-128 for crypto engines without AES-256 capability.
- 2.16.2
    - New features:
        * Ported mbedTLS 2.16.2 to SDK.
- 2.13.1_rev5
    - Bug fixes:
        * ecp_alt_ksdk.c fix CASPER port for ECJPAKE shortcut when points equal 1. This case is point addition and this shortcut follows original mbedtls_ecp_muladd() implementation which is required for ecjpake_ecp_add3().
- 2.13.1_rev4
    - New features:
        * Added support for NIST P-384 elliptic curve with CASPER driver.
- 2.13.1_rev3
    - Bug fixes:
        * Force align AES_CCM and AES_GCM self-test keys to fix unaligned key issue when using HW acceleration.
- 2.13.1_rev2
    - Bug fixes:
        * Disable default HW acceleration of SHA in parallel with AES.
- 2.13.1_rev1
    - Bug fixes:
        * Fixed incorrect macro check when skipping AES-192 or AES-256
- 2.13.1
    - New features:
        * Ported mbedTLS 2.13.1 to KSDK.
- 2.12.0_rev1
    - New features:

* Added support for NIST P-256 elliptic curve with CASPER driver.
* 2.12.0
  - New features:
    * Ported mbedTLS 2.12.0 to KSDK.
* 2.9.0_rev2
  - New features:
    * Added support for Hashcrypt driver.
* 2.9.0_rev1
  - New features:
    * Added support for CASPER driver.
* 2.9.0
  - New features:
    * Ported mbedTLS 2.9.0 to KSDK.
* 2.6.0_rev2
  - Bug fixes:
    * ssl_cookie.c now uses SHA256 for COOKIE_MD (instead of original SHA224). Some hw crypto acceleration (such as CAU3) don't support SHA224 but all support SHA256.
* 2.6.0_rev1
  - Bug fixes:
    * ksdk_mbedtls.c bignum functions now read sign of input mbedtls_mpi at beginning of functions to properly support in place computations (when output bignum is the same as one of input bignums). Affected functions: mbedtls_mpi_mul_mpi(), mbedtls_mpi-_mod_mpi(), ecp_mul_comb().
* 2.6.0
  - New features:
    * Ported mbedTLS 2.6.0 to KSDK.
    * Added MBEDTLS_FREESCALE_FREERTOS_CALLOC_ALT to allow alternate implementation of pvPortCalloc() when using /middleware/mbedtls/port/ksdk/ksdk_-mbedtls.c.
* 2.5.1_rev1
  - New features:
    * Added support for DCP driver.
* 2.5.1
  - New features:
    * Ported mbedTLS 2.5.1 to KSDK.
* 2.4.2_rev2
  - New features:
    * Added Curve25519 support for CAU3.
    * Added MBEDTLS_ECP_MUL_MXZ_ALT configuration parameter enabling overloading of ecp_mul_mxz().
* 2.4.2_rev1
  - New features:
    * Added support for CAU3 driver.
    * Added new files:
    * /middleware/mbedtls/port/ksdk/des_alt.c - contains regular software implementation of

DES algorithm with added MBEDTLS_DES3_SETKEY_DEC_ALT and MBEDTLS-_DES3_SETKEY_ENC_ALT config parameters.

* /middleware/mbedtls/port/ksdk/des_alt.h - contains modified mbedtls_des_context and mbedtls_des3_context structures.
* Added MBEDTLS_DES3_SETKEY_DEC_ALT configuration parameter enabling reloading of mbedtls_des3_set2key_dec() and mbedtls_des3_set3key_dec().
* Added MBEDTLS_DES3_SETKEY_ENC_ALT configuration parameter enabling reloading of mbedtls_des3_set2key_enc() and mbedtls_des3_set3key_enc().

- 2.4.2
  - New features:
    * Ported mbedTLS 2.4.2 to KSDK 2.0.0.
    * Added CRYPTO_InitHardware() function.
    * Added new file:
      · /middleware/mbedtls/port/ksdk/ksdk_mbedtls.h - contains declaration of CRYPTO_InitHardware() function and should be included in applications.
- 2.3.0_rev1
  - New features:
    * Added support for CAAM driver.
    * In LTC-specific wrapper, allocate temporary integers from heap in one large block.
- 2.3.0
  - New features:
    * Ported mbedTLS 2.3.0 to KSDK 2.0.0.
- 2.2.1
  - New features:
    * Ported mbedTLS 2.2.1 to KSDK 2.0.0.
    * Added support of MMCAU cryptographic acceleration module. Accelerated MD5, S-HA, AES, and DES.
    * Added support of LTC cryptographic acceleration module. Accelerated AES, DES, and PKHA.
    * Added new files:
    * /middleware/mbedtls/port/ksdk/ksdk_mbedtls.c - alternative implementation of cryptographic algorithm functions using LTC and MMCAU module drivers.
    * /middleware/mbedtls/port/ksdk/ksdk_mbedtls_config.h - configuration settings used by mbedTLS KSDK bare metal examples.
    * Added mbedTLS KSDK bare-metal examples:
      · /boards/<board name>/demo_apps/mbedtls/mbedtls_benchmark - KSDK mbed-TLS benchmark application.
      · /boards/<board name>/demo_apps/mbedtls/mbedtls_selftest - KSDK mbedTLS self-test application.
    * Added MBEDTLS_GCM_CRYPT_ALT configuration parameter enabling reloading of mbedtls_gcm_crypt_and_tag().
    * Added MBEDTLS_ECP_MUL_COMB_ALT to enable alternate implementation of ecp_mul_comb().
    * Added MBEDTLS_ECP_ADD_ALT configuration parameter enabling reloading of ecp_add().

* Added MBEDTLS_DES_SETKEY_DEC_ALT configuration parameter enabling reloading of mbedtls_des_setkey_dec(), mbedtls_des3_set2key_dec() and mbedtls_-des3_set3key_dec().
* Added MBEDTLS_DES_SETKEY_ENC_ALT configuration parameter enabling reloading of mbedtls_des_setkey_enc(), mbedtls_des3_set2key_enc() and mbedtls_-des3_set3key_enc().
* Added MBEDTLS_DES_CRYPT_CBC_ALT configuration parameter enabling reloading of mbedtls_des_crypt_cbc().
* Added MBEDTLS_DES3_CRYPT_CBC_ALT configuration parameter enabling reloading of mbedtls_des3_crypt_cbc().
* Added MBEDTLS_AES_CRYPT_CBC_ALT configuration parameter enabling reloading of mbedtls_aes_crypt_cbc().
* Added MBEDTLS_AES_CRYPT_CTR_ALT configuration parameter enabling reloading of mbedtls_aes_crypt_ctr().
* Added MBEDTLS_CCM_CRYPT_ALT configuration parameter enabling reloading of mbedtls_ccm_encrypt_and_tag() and mbedtls_ccm_auth_decrypt().
* Added MBEDTLS_MPI_ADD_ABS_ALT configuration parameter enabling reloading of mbedtls_mpi_add_abs().
* Added MBEDTLS_MPI_SUB_ABS_ALT configuration parameter enabling reloading of mbedtls_mpi_sub_abs().
* Added MBEDTLS_MPI_EXP_MOD_ALT configuration parameter enabling reloading of mbedtls_mpi_exp_mod().
* Added MBEDTLS_MPI_MUL_MPI_ALT configuration parameter enabling reloading of mbedtls_mpi_mul_mpi().
* Added MBEDTLS_MPI_MOD_MPI_ALT configuration parameter enabling reloading of mbedtls_mpi_mod_mpi().
* Added MBEDTLS_MPI_GCD_ALT configuration parameter enabling reloading of mbedtls_mpi_gcd().
* Added MBEDTLS_MPI_INV_MOD_ALT configuration parameter enabling reloading of mbedtls_mpi_inv_mod().
* Added MBEDTLS_MPI_IS_PRIME_ALT configuration parameter enabling reloading of mbedtls_mpi_is_prime().
* Added encrypt/decrypt mode to mbedtls_des_context and mbedtls_des3_context structure.
* Added carriage return '\r' for mbedtls_printf() in self test functions.

Multicore SDK

The current version of Multicore SDK is 2.15.0

* 2.15.0
  – Multicore SDK component versions:
    * embedded Remote Procedure Call (eRPC) v1.12.0
    * eRPC generator (erpcgen) v.1.12.0

* Multicore Manager (MCMgr) v4.1.5
* RPMsg-Lite v5.1.1
 – New features:
   * eRPC: Add dynamic/static option for transport init, GitHub PR #361.
   * eRPC: Fix receive error value for spidev, GitHub PR #363.
   * eRPC: UartTransport::init adaptation to changed driver.
   * eRPC: Fix typo in assert, GitHub PR #371.
   * eRPC,erpcgen: Move enums to enum classes, GitHub PR #379.
   * eRPC: Fixed rpmsg tty transport to work with serial transport, GitHub PR #373.
   * eRPC,erpcgen: Winsock2 support, GitHub PR #365.
   * eRPC,erpcgen: Feature/support multiple clients, GitHub PR #271.
   * eRPC,erpcgen: Feature/buffer head - Framed transport header data stored in Message-Buffer, GitHub PR #378.
   * eRPC,erpcgen: Add experimental Java support.
   * MCMgr: Added notification into MCMGR_EarlyInit and mcmgr_early_init_internal functions to avoid using uninitialized data in their implementations.
   * RPMsg-Lite: Minor changes in platform and env. layers, minor test code updates.
 • 2.14.0
 – Multicore SDK component versions:
   * embedded Remote Procedure Call (eRPC) v1.11.0
   * eRPC generator (erpcgen) v.1.11.0
   * Multicore Manager (MCMgr) v4.1.4
   * RPMsg-Lite v5.1.0
 – New features:
   * eRPC: Makefiles update, GitHub PR #301.
   * eRPC: Resolving warnings in Python, GitHub PR #325.
   * eRPC: Python3.8 is not ready for usage of typing.Any type, GitHub PR #325.
   * eRPC: Improved codec function to use reference instead of address, GitHub PR #324.
   * eRPC: Fix NULL check for pending client creation, GitHub PR #341.
   * eRPC: Replace sprintf with snprintf, GitHub PR #343.
   * eRPC: Use MU_SendMsg blocking call in MU transport.
   * eRPC: New LPSPI and LPI2C transport layers.
   * eRPC: Freeing static objects, GitHub PR #353.
   * eRPC: Fixed casting in deinit functions, GitHub PR #354.
   * eRPC: Align LIBUSBSIO.GetNumPorts API use with libusbsio python module v. 2.1.-11.
   * erpcgen: Renamed temp variable to more generic one, GitHub PR #321.
   * erpcgen: Add check that string read is not more than max length, GitHub PR #328.
   * erpcgen: Move to g++ in pytest, GitHub PR #335.
   * erpcgen: Use build=release for make, GitHub PR #334.
   * erpcgen: Removed boost dependency, GitHub PR #346.
   * erpcgen: Mingw support, GitHub PR #344.
   * erpcgen: VS build update, GitHub PR #347.
   * erpcgen: Modified name for common types macro scope, GitHub PR #337.
   * erpcgen: Fixed memcpy for template, GitHub PR #352.

- ∗ eRPC,erpcgen: Change default build target to release + adding artefacts, GitHub PR #334.
- ∗ eRPC,erpcgen: Remove redundant includes, GitHub PR #338.
- ∗ eRPC,erpcgen: Many minor code improvements, GitHub PR #323.
- ∗ MCMgr: Avoid calling tx isr callbacks when respective Messaging Unit Transmit Interrupt Enable flag is not set in the CR/TCR register.
- ∗ MCMgr: Messaging Unit RX and status registers are cleared after the initialization.
- ∗ RPMsg-Lite: Resolved issues in ThreadX env. layer implementation.
- ∗ RPMsg-Lite: Added aarch64 support.
- ∗ RPMsg-Lite: Increased the queue size to (2 ∗ RL_BUFFER_COUNT) to cover zero copy cases.
- 2.13.0_imxrt1180a0
  - Multicore SDK component versions:
    - ∗ embedded Remote Procedure Call (eRPC) v1.10.0
    - ∗ eRPC generator (erpcgen) v.1.10.0
    - ∗ Multicore Manager (MCMgr) v4.1.3
    - ∗ RPMsg-Lite v5.0.0
  - New features:
    - ∗ MCMgr, RPMsg-Lite: Added porting layers for imxrt1180.
    - ∗ MCMgr: mu_isr() updated to avoid calling tx isr callbacks when respective Transmit Interrupt Enable flag is not set in the CR/TCR register.
    - ∗ RPMsg-Lite, eRPC: RPMsg_Lite queue size adjusted.
    - ∗ eRPC: MU transport layer switched to blocking MU_SendMsg() API use.
- 2.13.0
  - Multicore SDK component versions:
    - ∗ embedded Remote Procedure Call (eRPC) v1.10.0
    - ∗ eRPC generator (erpcgen) v.1.10.0
    - ∗ Multicore Manager (MCMgr) v4.1.3
    - ∗ RPMsg-Lite v5.0.0
  - New features:
    - ∗ eRPC: MUTransport adaptation to new supported SoCs.
    - ∗ eRPC: Simplifying CI with installing dependencies using shell script, GitHub PR #267.
    - ∗ eRPC: Using event for waiting for sock connection in TCP python server, formatting python code, C specific includes, GitHub PR #269.
    - ∗ eRPC: Endianness agnostic update, GitHub PR #276.
    - ∗ eRPC: Assertion added for functions which are returning status on freeing memory, GitHub PR #277.
    - ∗ eRPC: Fixed closing arbitrator server in unit tests, GitHub PR #293.
    - ∗ eRPC: Makefile updated to reflect the correct header names, GitHub PR #295.
    - ∗ eRPC: Compare value length to used length() in reading data from message buffer, GitHub PR #297.
    - ∗ eRPC: Add TCP_NODELAY option to python, GitHub PR #298.
    - ∗ eRPC: Replace EXPECT_TRUE with EXPECT_EQ in unit tests, GitHub PR #318.
    - ∗ eRPC: Adapt rpmsg_lite based transports to changed rpmsg_lite_wait_for_link_up() API parameters.

- ∗ eRPC, erpcgen: Better distuingish which file can and cannot by linked by C linker, GitHub PR #266.
- ∗ eRPC, erpcgen: Stop checking if pointer is NULL before sending it to the erpc_free function, GitHub PR #275.
- ∗ eRPC, erpcgen: Changed api to count with more interfaces, GitHub PR #304.
- ∗ erpcgen: Check before reading from heap the buffer boundaries, GitHub PR #287.
- ∗ erpcgen: Several fixes for tests and CI, GitHub PR #289.
- ∗ erpcgen: Refactoring erpcgen code, GitHub PR #302.
- ∗ erpcgen: Fixed assigning const value to enum, GitHub PR #309.
- ∗ erpcgen: Enable runTesttest_enumErrorCode_allDirection, serialize enums as int32 instead of uint32.
- ∗ MCMgr: mcmgr_mu_internal.c code adaptation to new supported SoCs.
- ∗ RPMsg-Lite: Improveed debug check buffers implementation - instead of checking the pointer fits into shared memory check the presence in the VirtIO ring descriptors list.
- ∗ RPMsg-Lite: Timeout parameter added to rpmsg_lite_wait_for_link_up API function.
- ∗ RPMsg-Lite: VRING_SIZE is set based on number of used buffers now (as calculated in vring_init) - updated for all platforms that are not communicating to Linux rpmsg counterpart.
- ∗ RPMsg-Lite: Fixed wrong RL_VRING_OVERHEAD macro comment in platform.h files.
- ∗ RPMsg-Lite: Misra corrections.
- 2.12.0_imx93
  - Multicore SDK component versions:
    - ∗ embedded Remote Procedure Call (eRPC) v1.9.1
    - ∗ eRPC generator (erpcgen) v.1.9.1
    - ∗ Multicore Manager (MCMgr) v4.1.2
    - ∗ RPMsg-Lite v4.0.1
  - New features:
    - ∗ RPMsg-Lite: Added porting layers for i.mx93 device.
- 2.12.0
  - Multicore SDK component versions:
    - ∗ embedded Remote Procedure Call (eRPC) v1.9.1
    - ∗ eRPC generator (erpcgen) v.1.9.1
    - ∗ Multicore Manager (MCMgr) v4.1.2
    - ∗ RPMsg-Lite v4.0.0
  - New features:
    - ∗ eRPC: Construct the USB CDC transport, rather than a client, GitHub PR #220.
    - ∗ eRPC: Fix premature import of package, causing failure when attempting installation of Python library in a clean environment, GitHub PR #38, #226.
    - ∗ eRPC: Improve python detection in make, GitHub PR #225.
    - ∗ eRPC: Fix several warnings with deprecated call in pytest, GitHub PR #227.
    - ∗ eRPC: Fix freeing union members when only default need be freed, GitHub PR #228.
    - ∗ eRPC: Fix making test under Linux, GitHub PR #229.
    - ∗ eRPC: Assert costumizing, GitHub PR #148.
    - ∗ eRPC: Fix corrupt clientList bug in TransportArbitrator, GitHub PR #199.

* eRPC: Fix build issue when invoking g++ with -Wno-error=free-nonheap-object, Git-Hub PR #233.
* eRPC: Fix inout cases, GitHub PR #237.
* eRPC: Remove ERPC_PRE_POST_ACTION dependency on return type, GitHub PR #238.
* eRPC: Adding NULL to ptr when codec function failed, fixing memcpy when fail is present during deserialization, GitHub PR #253.
* eRPC: MessageBuffer usage improvement, GitHub PR #258.
* eRPC: Get rid for serial and enum34 dependency (enum34 is in python3 since 3.4 (from 2014)), GitHub PR #247.
* eRPC: Several MISRA violations addressed.
* eRPC: Fix timeout for Freertos semaphore, GitHub PR #251.
* eRPC: Use of rpmsg_lite_wait_for_link_up() in rpmsg_lite based transports, GitHub PR #223.
* eRPC: Fix codec nullptr dereferencing, GitHub PR #264.
* erpcgen: Fix two syntax errors in erpcgen Python output related to non-encapsulated unions, improved test for union, GitHub PR #206, #224.
* erpcgen: Fix serialization of list/binary types, GitHub PR #240.
* erpcgen: Fix empty list parsing, GitHub PR #72.
* erpcgen: Fix templates for malloc errors, GitHub PR #110.
* erpcgen: Get rid of encapsulated union declarations in global scale, improve enum usage in unions, GitHub PR #249, #250.
* erpcgen: Fix compile error:UniqueIdChecker.cpp:156:104:'sort' was not declared, Git-Hub PR #265.
* MCMgr: Update mcmgr_stop_core_internal() implementations to set core state to kM-CMGR_ResetCoreState.
* RPMsg-Lite: Introduce new rpmsg_lite_wait_for_link_up() API function - this allows to avoid using busy loops in rtos environments, GitHub PR #21.
* RPMsg-Lite: Adjust rpmsg_lite_is_link_up() to return RL_TRUE/RL_FALSE.

- 2.11.1
  - Multicore SDK component versions:
    * embedded Remote Procedure Call (eRPC) v1.9.0
    * eRPC generator (erpcgen) v.1.9.0
    * Multicore Manager (MCMgr) v4.1.1
    * RPMsg-Lite v3.2.1
  - New features:
    * RPMsg-Lite: Add support for custom shared memory arangement per the RPMsg_Lite instance.
- 2.11.0
  - Multicore SDK component versions:
    * embedded Remote Procedure Call (eRPC) v1.9.0
    * eRPC generator (erpcgen) v.1.9.0
    * Multicore Manager (MCMgr) v4.1.1
    * RPMsg-Lite v3.2.0
  - New features:

- ∗ eRPC: Improving template usage, GitHub PR #153.
- ∗ eRPC: run_clang_format.py cleanup, GitHub PR #177.
- ∗ eRPC: Build TCP transport setup code into liberpc, GitHub PR #179.
- ∗ eRPC: Fix multiple definitions of g_client error, GitHub PR #180.
- ∗ eRPC: Fix memset past end of buffer in erpc_setup_mbf_static.cpp, GitHub PR #184.
- ∗ eRPC: Fix deprecated error with newer pytest version, GitHub PR #203.
- ∗ eRPC: Allow used LIBUSBSIO device index being specified from the Python command line argument.
- ∗ eRPC, erpcgen: Static allocation support and usage of rpmsg static FreeRTOSs related APi, GitHub PR #168, #169.
- ∗ erpcgen: Remove redundant module imports in erpcgen, GitHub PR #196.
- ∗ RPMsg-Lite: Improve static allocations - allow OS-specific objects being allocated statically, GitHub PR #14.
- ∗ RPMsg-Lite: Minor Misra and typo corrections, GitHub PR #19, #20.

- 2.10.0
  - Multicore SDK component versions:
    - ∗ embedded Remote Procedure Call (eRPC) v1.8.1
    - ∗ eRPC generator (erpcgen) v.1.8.1
    - ∗ Multicore Manager (MCMgr) v4.1.1
    - ∗ RPMsg-Lite v3.1.2
  - New features:
    - ∗ eRPC: Fix misra erpc c, GitHub PR #158.
    - ∗ eRPC: Allow conditional compilation of message_loggers and pre_post_action.
    - ∗ eRPC: New i2c_slave_transport trasnport introduced.
    - ∗ eRPC: (D)SPI slave transports updated to avoid busy loops in rtos environments.
    - ∗ erpcgen: Re-implement EnumMember::hasValue(), GitHub PR #159.
    - ∗ erpcgen: Fixing several misra issues in shim code, erpcgen and unit tests updated, GitHub PR #156.
    - ∗ erpcgen: Fix bison file, GitHub PR #156.
    - ∗ RPMsg-Lite: Fixed incorrect description of the rpmsg_lite_get_endpoint_from_addr function.
    - ∗ RPMsg-Lite: Updated RL_BUFFER_COUNT documentation.
    - ∗ RPMsg-Lite: env_print macro adjusted to address MISRA 21.6 rule in MCUXpressoSDK projects.

- 2.9.0
  - Multicore SDK component versions:
    - ∗ embedded Remote Procedure Call (eRPC) v1.8.0
    - ∗ eRPC generator (erpcgen) v.1.8.0
    - ∗ Multicore Manager (MCMgr) v4.1.1
    - ∗ RPMsg-Lite v3.1.1
  - New features:
    - ∗ eRPC: Support win32 thread, GitHub PR #108.
    - ∗ eRPC: Add mbed support for malloc() and free(), GitHub PR #92.
    - ∗ eRPC: Update makefile.
    - ∗ eRPC: Fixed warnings and error with using MessageLoggers, GitHub PR #127.

* ∗ eRPC: Extend error msg for python server service handle function, GitHub PR #132.
* ∗ eRPC: Update CMSIS UART transport layer to avoid busy loops in rtos environments, introduce semaphores.
* ∗ eRPC: Introduced pre and post callbacks for eRPC call, GitHub PR #131.
* ∗ eRPC: Introduced new USB CDC transport.
* ∗ eRPC: Introduced new Linux spidev-based transport.
* ∗ eRPC: SPI transport update to allow usage without handshaking GPIO.
* ∗ eRPC: Native *WIN32 erpc serial transport and threading.*
* ∗ *eRPC: Arbitrator deadlock fix, TCP transport updated, TCP setup functions introduced, GitHub PR #121.*
* ∗ *eRPC: Update of matrix_multiply.py example: Add –serial and –baud argument, Git-Hub PR #137.*
* ∗ *eRPC: Added formatting extension for VSC, GitHub PR #134.*
* ∗ *eRPC: Update of .clang-format, GitHub PR #140.*
* ∗ *eRPC: Update of erpc_framed_transport.cpp: return error if received message has zero length, GitHub PR #141.*
* ∗ *eRPC, erpcgen: Fixed error messages produced by -Wall -Wextra -Wshadow -pedantic-errors compiler flags, GitHub PR #136, #139.*
* ∗ *eRPC, erpcgen: Core re-formatted using Clang version 10.*
* ∗ *erpcgen: Enable deallocation in server shim code when callback/function pointer used as out parameter in IDL.*
* ∗ *erpcgen: Removed '$' character from generated symbol name in '$union' suffix, Git-Hub PR #103.*
* ∗ erpcgen: Resolved mismatch between C++ and Python for callback index type, GitHub PR #111.
* ∗ erpcgen: Python generator improvements, GitHub PR #100, #118.
* ∗ erpcgen: Fixed error messages produced by -Wall -Wextra -Wshadow -pedantic-errors compiler flags, GitHub PR #136.
* ∗ erpcgen: Introduce ustring type for unsigned char and force cast to char∗, GitHub PR #125.
* ∗ RPMsg-Lite: Introduced RL_ALLOW_CONSUMED_BUFFERS_NOTIFICATION config option to allow opposite side notification sending each time received buffers are consumed and put into the queue of available buffers.
* ∗ RPMsg-Lite: Added environment layers for Threadx.

* 2.8.0
  * – Multicore SDK component versions:
    * ∗ embedded Remote Procedure Call (eRPC) v1.7.4
    * ∗ eRPC generator (erpcgen) v.1.7.4
    * ∗ Multicore Manager (MCMgr) v4.1.0
    * ∗ RPMsg-Lite v3.1.0
  * – New features:
    * ∗ eRPC: Unit test code updated to handle service add and remove operations.
    * ∗ eRPC: Several MISRA issues in rpmsg-based transports addressed.
    * ∗ eRPC: Support MU transport unit testing.
    * ∗ eRPC: Adding mbed os support.

* eRPC: Fixed Linux/TCP acceptance tests in release target.
* eRPC: Minor documentation updates, code formatting.
* erpcgen: Whitespace removed from C common header template.
* RPMsg-Lite: MISRA C-2012 violations fixed (7.4).
* RPMsg-Lite: Fix missing lock in rpmsg_lite_rx_callback() for QNX env.
* RPMsg-Lite: Correction of rpmsg_lite_instance structure members description.
* RPMsg-Lite: Address -Waddress-of-packed-member warnings in GCC9.
* RPMsg-Lite: Clang update to v10.0.0, code re-formatted.

- 2.7.0
    - Multicore SDK component versions:
        * embedded Remote Procedure Call (eRPC) v1.7.3
        * eRPC generator (erpcgen) v.1.7.3
        * Multicore Manager (MCMgr) v4.1.0
        * RPMsg-Lite v3.0.0
    - New features:
        * eRPC: Improved the test_callbacks logic to be more understandable and to allow requested callback execution on the server side.
        * eRPC: TransportArbitrator::prepareClientReceive modified to avoid incorrect return value type.
        * eRPC: The ClientManager and the ArbitratedClientManager updated to avoid performing client requests when the previous serialization phase fails.
        * erpcgen: Generate the shim code for destroy of statically allocated services.
        * MCMgr: Code adjustments to address MISRA C-2012 Rules
        * RPMsg-Lite: MISRA C-2012 violations fixed, incl. data types consolidation.
        * RPMsg-Lite: Code formatted

- 2.6.0
    - Multicore SDK component versions:
        * embedded Remote Procedure Call (eRPC) v1.7.2
        * eRPC generator (erpcgen) v.1.7.2
        * Multicore Manager (MCMgr) v4.0.3
        * RPMsg-Lite v2.2.0
    - New features:
        * eRPC: Improved support of const types.
        * eRPC: Fixed Mac build.
        * eRPC: Fixed serializing python list.
        * eRPC: Documentation update.
        * eRPC: Add missing doxygen comments for transports.
        * RPMsg-Lite: Added configuration macro RL_DEBUG_CHECK_BUFFERS.
        * RPMsg-Lite: Several MISRA violations fixed.
        * RPMsg-Lite: Added environment layers for QNX and Zephyr.
        * RPMsg-Lite: Allow environment context required for some environments (controlled by the RL_USE_ENVIRONMENT_CONTEXT configuration macro).
        * RPMsg-Lite: Data types consolidation.
        * MCMgr: Documentation updated to describe handshaking in a graphic form.
        * MCMgr: Minor code adjustments based on static analysis tool findings

- 2.5.0
  - Multicore SDK component versions:
    * embedded Remote Procedure Call (eRPC) v1.7.1
    * eRPC generator (erpcgen) v.1.7.1
    * Multicore Manager (MCMgr) v4.0.2
    * RPMsg-Lite v2.0.2
  - New features:
    * RPMsg-Lite, MCMgr: Align porting layers to the updated MCUXpressoSDK feature files.
    * eRPC: Fixed semaphore in static message buffer factory.
    * erpcgen: Fixed MU received error flag.
    * erpcgen: Fixed tcp transport.
- 2.4.0
  - Multicore SDK component versions:
    * embedded Remote Procedure Call (eRPC) v1.7.0
    * eRPC generator (erpcgen) v.1.7.0
    * Multicore Manager (MCMgr) v4.0.1
    * RPMsg-Lite v2.0.1
  - New features:
    * eRPC: Improved code size of generated code.
    * eRPC: Generating crc value is optional.
    * eRPC: Fixed CMSIS Uart driver. Removed dependency on KSDK.
    * eRPC: List names are based on their types. Names are more deterministic.
    * eRPC: Service objects are as a default created as global static objects.
    * eRPC: Added missing doxygen comments.
    * eRPC: Forbid users use reserved words.
    * eRPC: Removed outByref for function parameters.
    * eRPC: Added support for 64bit numbers.
    * eRPC: Added support of program language specific annotations.
    * eRPC: Optimized code style of callback functions.
    * RPMsg-Lite: New API rpmsg_queue_get_current_size()
    * RPMsg-Lite: Fixed bug in interrupt handling for lpc5411x, lpc5410x
    * RPMsg-Lite: Code adjustments based on static analysis tool findings
- 2.3.1
  - Multicore SDK component versions:
    * embedded Remote Procedure Call (eRPC) v1.6.0
    * eRPC generator (erpcgen) v.1.6.0
    * Multicore Manager (MCMgr) v4.0.0
    * RPMsg-Lite v1.2.0
  - New features:
    * eRPC: Improved code size of generated code.
    * eRPC: Improved eRPC nested calls.
    * eRPC: Improved eRPC list length variable serialization.
    * eRPC: Added @nullable support for scalar types.
    * MCMgr: Added new MCMGR_TriggerEventForce() API.

- 2.3.0
  - Multicore SDK component versions:
    * embedded Remote Procedure Call (eRPC) v1.5.0
    * eRPC generator (erpcgen) v.1.5.0
    * Multicore Manager (MCMgr) v3.0.0
    * RPMsg-Lite v1.2.0
  - New features:
    * eRPC: Added support for unions type non-wrapped by structure.
    * eRPC: Added callbacks support.
    * eRPC: Added support @external annotation for functions.
    * eRPC: Added support @name annotation.
    * eRPC: Added Messaging Unit transport layer.
    * eRPC: Added RPMSG Lite RTOS TTY transport layer.
    * eRPC: Added version verification and IDL version verification between eRPC code and eRPC generated shim code.
    * eRPC: Added support of shared memory pointer.
    * eRPC: Added annotation to forbid generating const keyword for function parameters.
    * eRPC: Added python matrix multiply example.
    * eRPC: Added nested call support.
    * eRPC: Added struct member "byref" option support.
    * eRPC: Added support of forward declarations of structures
    * eRPC: Added Python RPMsg Multiendpoint kernel module support
    * eRPC: Added eRPC sniffer tool
    * MCMgr: Unused API removed
    * MCMgr: Added the ability for remote core monitoring and event handling
    * RPMsg-Lite: Several source files renamed to avoid conflicts with other middleware sw components
    * RPMsg-Lite: Added the ability to use Multicore Manager (MCMGR) as the IPC interrupts router
- 2.2.0
  - Multicore SDK component versions:
    * embedded Remote Procedure Call (eRPC) v1.4.0
    * eRPC generator (erpcgen) v.1.4.0
    * Multicore Manager (MCMgr) v2.0.1
    * RPMsg-Lite v1.1.0
  - New features:
    * eRPC: win_flex_bison.zip for windows updated.
    * eRPC: Use one codec (instead of inCodec outCodec).
    * eRPC: New RPMsg-Lite Zero Copy (RPMsgZC) transport layer.
    * MCMgr: code updated to be Misra compliant.
    * RPMsg-Lite: Added macros for packed structures (compiler.h).
    * RPMsg-Lite: Improved interrupt handling in platform layer.
    * RPMsg-Lite: Changed RL_BUFFER_SIZE definition.
    * RPMsg-Lite: Fix of double initialization of vring shared data structure.
    * RPMsg-Lite: Support for the multi-instance.

- 2.1.0
  - Multicore SDK component versions:
    * embedded Remote Procedure Call (eRPC) v1.3.0
    * eRPC generator (erpcgen) v.1.3.0
  - New features:
    * eRPC: New annotation types introduced (@length, @max_length, ...).
    * eRPC: Support for running both erpc client and erpc server on one side.
    * eRPC: New transport layers for (LP)UART, (D)SPI.
    * eRPC: Error handling support.
- 2.0.0
  - Multicore SDK component versions:
    * embedded Remote Procedure Call (eRPC) v1.2.0
    * eRPC generator (erpcgen) v.1.2.0
    * Multicore Manager (MCMgr) v2.0.0
    * RPMsg-Lite v1.0.0
  - New features:
    * Multicore SDK support for lpcxpresso54114 board added.
    * RPMsg component of the Open-AMP framework re-implemented and the RPMsg-Lite version introduced.
    * eRPC source directory organization changed.
    * Many eRPC improvements.
- 1.1.0
  - Multicore SDK component versions:
    * embedded Remote Procedure Call (eRPC) v1.1.0
    * Multicore Manager (MCMgr) v1.1.0
    * Open-AMP / RPMsg based on SHA1 ID 44b5f3c0a6458f3cf80 rev01
  - New features:
    * Multicore SDK 1.1.0 ported to KSDK 2.0.0.
    * Python support added into eRPC.
- 1.0.0
  - Multicore SDK component versions:
    * embedded Remote Procedure Call (eRPC) v1.0.0
    * Multicore Manager (MCMgr) v1.0.0
    * Open-AMP / RPMsg based on SHA1 ID 44b5f3c0a6458f3cf80 rev00

Host USDHC driver for MCUXpresso SDK

The current driver version is 2.6.3.

- 2.6.3
  - Improvements
    * Added macro SDMMCHOST_SUPPORT_VOLTAGE_CONTROL.
- 2.6.2
  - Bug Fixes

        ∗ Added clock force on during standard tuning to fix the card access not stable after initialization.

- 2.6.1
  - Improvements
    - ∗ Increased the delay after enable DAT3 detect card feature to fix the misdetect issue.
- 2.6.0
  - Improvements
    - ∗ Removed deprecated api in SDHC host driver.
    - ∗ Added SDMMCHOST_ConvertDataToLittleEndian api.
    - ∗ Added capability/maxBlockCount/maxBlockSize in host decriptior.
    - ∗ Improved the manual tuning flow according to specification.
    - ∗ Added mutual exclusive access for function init/deinit/reset/transfer function.
    - ∗ Fixed violations of MISRA C-2012 rule 10.1, 10.4, 16.3, 4.7.
- 2.5.3
  - Bug Fixes
    - ∗ Corrected the DAT3 detect card flow by PULL down the DAT3 pin firstly and then enable the host DAT3 function.
- 2.5.2
  - Improvements
    - ∗ Improved DAT3 card detect mechanism to avoid card false detection.
- 2.5.1
  - Improvements
    - ∗ Enabled DAT3 card detect interrupt in function SDMMCHOST_PollingCardDetect-Status to support DAT3 re-detect card.
- 2.5.0
  - Improvements
    - ∗ Added cache line size alignment maintain for the read transfer.
    - ∗ Added FSL_FEATURE_HAS_L1CACHE to enable cache maintain operation for the soc has LMEM cache.
  - Bug Fixes
    - ∗ Fixed violations of MISRA C-2012 rule 11.9, 15.7, 4.7, 16.4, 10.1, 10.3, 10.4, 11.3, 14.4, 10.6, 17.7, 16.1, 16.3.
- 2.4.0
  - Improvements
    - ∗ Added cache maintain functionality in the host driver.
    - ∗ Enabled DAT3 card detect feature.
    - ∗ Increase the default STD tuning counter to 60 to cover range of the tuning window.
    - ∗ Added host instance capability macro.
    - ∗ Added clear card inserted/removed event when card removed/inserted interrupt generated.
- 2.3.0
  - Improvements
    - ∗ Merged the host controller driver from polling/freertos/interrupt to non_blocking/blocking.
    - ∗ Added SDMMC OSA layer to support muxtex access/event/delay.
- 2.2.14

 – Bug Fixes
   * Fixed uninitialized value Coverity issue.
 • 2.0.0
   – Initial version

MMC Card driver for MCUXpresso SDK

The current driver version is 2.5.0.

 • 2.5.0
   – Improvements
     * Added api MMC_SetSleepAwake to support enter/exit sleep state.
     * Added new api MMC_PollingCardStatusBusy for application polling card status.
     * Removed deprecated api in mmc driver and mark MMC_HostReset as deprecated.
     * Improved the read/write/erase function flow.
     * Added mutual exclusive access for init/deinit/read/write/erase function.
     * Fixed violations of MISRA C-2012 rule 4.7, 17.7, 10.7, 10.4, 13.5, 14.4, 10.6.
 • 2.4.1
   – Improvements
     * Improved the voltage window argument of CMD1 according to host capabilty instead of use card ocr directly.
     * Added host HS200/HS400/8bit bus width capability validation during card initialization.
     * Used cache line size align buffer for MMC relate api.
     * Increased the CMD13 timeout count to avoid polling CMD13 time out issue.
   – Bug Fixes
     * Fixed violations of MISRA C-2012 rule 11.9, 15.7, 4.7, 16.4, 10.1, 10.3, 10.4, 11.3, 14.4, 10.6, 17.7, 16.1, 16.3.
 • 2.4.0
   – Improvements
     * Added new apis MMC_EnableCacheControl/MMC_FlushCache to support cache feature.
 • 2.3.1
   – Improvements
     * Removed the dead loop while polling DAT0 and CMD13 instead of using timeout mechanism.
     * Added card state check before switching to HS400 to improve the emmc initialization stability.
     * Removed the redundant operation of memset internal buffer in MMC_WrtiteBlocks function.
   – Bug Fixes
     * Fixed the sandisk emmc always busy while sending CMD1 without supported voltage provide in argument.
 • 2.3.0
   – Improvements

* Deprecated api MMC_PowerOnCard/MMC_PowerOffCard by api MMC_SetCard-Power.
* Added internalBuffer in mmc_card_t and removed rawCid/rawCsd/rawExtendedCsd.
* Added retuning support during data transfer under HS200 mode.
* Increased the read/write blocks failed retry times for stability.
* Added delay while retry the CMD1 for stability.
* Added legacy card support, the card not support CMD6, CMD8.

- 2.2.13
  - Improvements
    * Used the boot mode value instead of boot mode mask value as the parameter of MMC-_SetBootConfig to improve user experience.
    * Removed dynamic voltage switch feature for mmc, according to JEDEC standard, the voltage should be fixed after power up.

- 2.2.12
  - Improvement
    * Increased the CMD1 retry times in the MMC card driver to improve driver compatibility.
  - Bug Fixes
    * Fixed the build warning by changing the old style function declaration static status_t inline to static inline status_t(found by adding -Wold-style-declaration in armgcc build flag).
    * Fixed the fall through build warning by adding SUPPRESS_FALL_THROUGH_WA-RNING() in mmc driver.

- 2.2.7
  - Bug Fixes
    * Fixed MDK 66-D warning.

- 2.2.6
  - Improvements
    * Saved MMC OCR registers while sending CMD1 with argument 0.
  - Bug Fixes
    * Added MMC_PowerOn function in which there is delay function after powerup sdcard. Otherwise, the card initialization by fail.

- 2.2.5
  - Improvements
    * Added SDMMC_ENABLE_SOFTWARE_TUNING to enable/disable software tuning and it is disabled by default.

- 2.2.4
  - Bug Fixes
    * Fixed DDR mode data sequence miss issue, which is caused by NIBBLE_POS.
  - Improvements
    * Increased g_sdmmc 512byte to improve the performance when application use a non-word align data buffer address.
    * Used OCR access mode bits to determine the mmccard high capacity flag.

- 2.2.3
  - Bug Fixes

* Added response check for send operation condition command. If not checked, the card may occasionally init fail.
- 2.2.1
  - Improvements
    * Improved MMC Boot feature.
- 2.2.0
  - Improvements
    * Optimized tuning/mmc switch voltage/mmc select power class/mmc select timing function.
    * Added strobe dll for mmc HS400 mode.
    * Added write complete wait operation for MMC_Write to fix command timeout issue.
- 2.1.2
  - Improvements
    * Improved SDMMC to support eMMC v5.0.
  - Bug Fixes
    * Fixed incorrect comparison between count and length in MMC_ReadBlocks/MMC_WriteBlocks.
- 2.1.1
  - Bug Fixes
    * Fixed the block range boundary error when transferring data to MMC card.
- 2.1.0
  - Improvements
    * Optimized the function of setting maximum data bus width for MMC card.
- 2.0.0
  - Initial version

SD Card driver for MCUXpresso SDK

The current driver version is 2.4.2.

- 2.4.2
  - Improvements
    * Improved the erase timeout calculation logical in function SD_EraseBlocks according to SD specifications.
    * Added polling erase done status after each erase operations.
- 2.4.1
  - Improvements
    * Added macro SDMMCHOST_SUPPORT_VOLTAGE_CONTROL for the host which not support voltage control.
- 2.4.0
  - Improvements
    * Removed deprecated api in sd driver.
    * Added new api SD_PollingCardStatusBusy for application polling card status.
    * Improved the read/write/erase function flow.

* Improved the signal line voltage switch flow.
* Added powerOnDelayMS/powerOffDelayMS in sd_usr_param_t to allow redefine the default power on/off delay.
* Added mutual exclusive access for init/deinit/read/write/erase function.
* Fixed the driver strength configurations missed when timing mode switch to non SD-R50/SDR104 mode.
* Fixed violations of MISRA C-2012 rule 4.7, 17.7, 10.7, 10.4, 13.5, 14.4.

- 2.3.3
  - Improvements
    * Added host SDR timing mode capability validation during card initialization.
    * Added plling card ready for data status when transfer data failed.
    * Used cache line size align buffer for SD initialization api.
  - Bug Fixes
    * Fixed violations of MISRA C-2012 rule 11.9, 15.7, 4.7, 16.4, 10.1, 10.3, 10.4, 11.3, 14.4, 10.6, 17.7, 16.1, 16.3.
- 2.3.2
  - Improvements
    * Moved power off function after card detect in SD_Init for DAT3 detect card feature.
- 2.3.1
  - Improvements
    * Removed the dead loop while polling DAT0 and CMD13 instead of using timeout mechanism.
- 2.3.0
  - Improvements
    * Marked api SD_HostReset/SD_PowerOnCard/SD_PowerOffCard/SD_WaitCard-DetectStatus as deprecated.
    * Added new api SD_SetCardPower/SD_PollingCardDetectStatus/SD_HostDoReset.
    * Added internalBuffer in sd_card_t and removed rawCid/rawCsd/rawScr.
    * Added retuning support during data transfer under SDR50/SDR104 mode.
    * Increased the read/write blocks failed retry times for stability.
    * Added delay while retry the ACMD41 for stability.
- 2.2.12
  - Improvements
    * Increased the sd io driver strength for SD2.0 card.
  - Bug Fixes
    * Fixed the build warning by changing the old style function declaration static status_t inline to static inline status_t(found by adding -Wold-style-declaration in armgcc build flag).
- 2.2.10
  - Bug Fixes
    * Added event value check for all the FreeRTOS events to fix program hangs when a card event occurs before create.
- 2.2.7
  - Bug Fixes
    * Fixed MDK 66-D warning.

- 2.2.5
  - Improvements
    * Added SD_ReadStatus api to get 512bit SD status.
    * Added error log support in sdcard functions.
    * Added SDMMC_ENABLE_SOFTWARE_TUNING to enable/disable software tuning and it is disabled by default.
- 2.2.4
  - Bug Fixes
    * Fixed DDR mode data sequence miss issue, which is caused by NIBBLE_POS.
  - Improvements
    * Increased g_sdmmc 512byte to improve the performance when application use a non-word align data buffer address.
    * Enabled auto cmd12 for SD read/write.
- 2.2.3
  - Bug Fixes
    * Added response check for send operation condition command. If not checked, the card may occasionally init fail.
- 2.2.1
  - Improvements
    * Kept SD_Init function for forward compatibility.
- 2.2.0
  - Improvements
    * Separated the SD/MMC/SDIO init API to xxx_CardInit/xxx_HostInit.
    * SD_Init/SDIO_Init will be deprecated in the next version.
- 2.1.6
  - Improvements
    * Enhanced SD IO default driver strength.
- 2.1.5
  - Bug Fixes
    * Fixed Coverity issue.
    * Fixed SD v1.x card write fail issue. It was caused by the block length set error.
    * Fixed card cannot detect dynamically.
- 2.1.3
  - Bug Fixes
    * Fixed Non high-speed sdcard init fail at switch to high speed.
  - Improvements
    * Added Delay for SDCard power up.
- 2.1.2
  - Improvements
    * Improved SDMMC to support SD v3.0.
- 2.1.1
  - Bug Fixes
    * Fixed the bit mask error in the SD card switch to high speed function.
  - Improvements
    * Optimized the SD card initialization function.

- 2.1.0
  - Bug Fixes
    * Changed the callback mechanism when sending a command.
    * Fixed the performance low issue when transferring data.
  - Improvements
    * Changed the name of some error codes returned by internal function.
    * Merged all host related attributes to one structure.
- 2.0.0
  - Initial version.

SDIO Card driver for MCUXpresso SDK

The current driver version is 2.4.1.

- 2.4.1
  - Improvements
    * Added macro SDMMCHOST_SUPPORT_VOLTAGE_CONTROL for the host which not support voltage control.
- 2.4.0
  - Improvements
    * Removed deprecated api in sdio driver.
    * Improved the signal line voltage switch flow.
    * Added powerOnDelayMS/powerOffDelayMS in sdio_usr_param_t to allow redefine the default power on/off delay.
    * Added mutual exclusive access for init/deinit/direct/extend function.
    * Fixed violations of MISRA C-2012 rule 4.7, 17.7, 10.1, 12.2.
- 2.3.3
  - Bug Fixes
    * Fixed logical dead code coverity issue.
  - Improvements
    * Removed deprecated api in sdio driver.
- 2.3.2
  - Improvements
    * Added host SDR timing mode capability validation during card initialization.
    * Used cache line size align buffer for SDIO initialization api.
  - Bug Fixes
    * Fixed violations of MISRA C-2012 rule 11.9, 15.7, 4.7, 16.4, 10.1, 10.3, 10.4, 11.3, 14.4, 10.6, 17.7, 16.1, 16.3.
- 2.3.1
  - Improvements
    * Moved power off function after card detect in SD_Init for DAT3 detect card feature.
- 2.3.0
  - Improvements
    * Marked api SDIO_HostReset/SDIO_PowerOnCard/SDIO_PowerOffCard/SDIO_Wait-

CardDetectStatus as deprecated.

* Added new api SDIO_SetCardPower/SDIO_PollingCardDetectStatus/SDIO_HostDo-Reset.
* Added internalBuffer in sdio_card_t for card register content extract and improve the data access efficiency.
* Added retry function after switch to target timing failed in SDIO_SelectBusTiming.
* Changed defalut bus clock from 400KHZ to 25MHZ.

- 2.2.13
  - Improvements
    * Removed the sdio card interrupt from sdio host initialization, since the card interrupt enablement should be determined by application.
  - Bug Fixes
    * Fixed Out-of-bounds write Coverity issue.
- 2.2.12
  - Improvements
    * Added manual tuning function for looking for the tuning window automatically.
    * Fixed the build warning by changing the old style function declaration static status_t inline to static inline status_t(found by adding -Wold-style-declaration in armgcc build flag).
    * Fixed the fall through build warning by adding SUPPRESS_FALL_THROUGH_WARNING() in sdio driver.
- 2.2.11
  - Bug Fixes
    * Added check card async interrupt capability in function SDIO_GetCardCapability.
    * Fixed OUT OF BOUNDS access in function SDIO_IO_Transfer.
- 2.2.10
  - Bug Fixes
    * Fixed SDIO card driver get an incorrect io number when the card io number is bigger than 2.
  - Improvements
    * Added SDIO 3.0 support.
    * Added API SDIO_IO_RW_Direct for direct read/write card register access.
- 2.2.9
  - Improvements
    * Added API SDIO_SetIOIRQHandler/SDIO_HandlePendingIOInterrupt to handle multi io pending IRQ.
- 2.2.8
  - Improvements
    * Updated sdmmc to support SDIO interrupt.
    * Added API SDIO_GetPendingInterrupt to get the pending io interrupt.
- 2.2.7
  - Bug Fixes
    * Fixed MDK 66-D warning.
- 2.2.6
  - Improvements

       ∗ Added an unify transfer interface for SDIO.
- **–** Bug Fixes
  - ∗ Fixed Wrong pointer address used by SDMMCHOST_Init.
- **2.1.5**
  - **–** Improvements
    - ∗ Improved SDIO card init sequence and add retry option for SDIO_SwitchToHighSpeed function.
- **2.1.4**
  - **–** Improvements
    - ∗ Added Go_Idle function for SDIO card.
- **2.0.0**
  - **–** Initial version.

USB stack for MCUXpresso SDK

The current version of USB stack is 2.9.1.

- **2.9.1**
  - **–** Improvement:
    - ∗ Update EHCI controller driver for basic support of eUSB.
    - ∗ Replace the hard code in audio cases with macro.
    - ∗ Uniform the Chapter9 for device lite cases.
- **2.9.0**
  - **–** Improvement:
    - ∗ Change ROOT2 as enabled by default in device stack.
    - ∗ Implement independent frequency adjustment for speaker and recorder of composite audio unified demos.
    - ∗ Fix vulnerability for host stack. CVE number: CVE-2023-38749
    - ∗ Delete deprecated enet driver function for enet adapter.
- **2.8.4**
  - **–** Improvement:
    - ∗ Add the new netc adatper for the new netc driver.
    - ∗ Fix issues for USB device dfu and usb device msc when enable the macro USB_DEVICE_CONFIG_RETURN_VALUE_CHECK.
    - ∗ Change the header file including order for usb.h header.
    - ∗ Update the USB host audio class driver to fix the wrong output log.
    - ∗ Add the workaround on dev_hid_mouse_bm case for the errata TN00071.
    - ∗ Enable ROOT2 macro in USB device stack.
    - ∗ Use an unified definiton for the base address of RTxxxx platforms.
- **2.8.3**
  - **–** Improvement:
    - ∗ Update the EHCI controller driver to support the address convert for TCM.
    - ∗ Update the USB host EHCI controller driver to make sure the mutual exclusion access under multiple tasks' environment.

- 2.8.2
  - Improvement:
    * Fix noise issue of UAC 3.1, UAC 5.1, UAC 7.1 on usb audio speaker demo.
    * Fix the issue that incorrect PC behavior when ejecting USB MSC devices.
    * Update the EHCI controller driver to support RW610 that does not reply on PHY driver, especially for low power feature.
    * Update the USB_HostHelperParseAlternateSetting to fix the wrong interface parse.
    * Update dev_composite_hid_audio_unified_bm demo to suppport independent mute/unmute and volume control.
- 2.8.1
  - Improvement:
    * update USB audio demos to use audio component (components/audio).
    * Add the checking of function call return value.
    * Add audio multiple channels demo (usb_device_composite_audio_multi_ch_unified) on RT600 audio board.
    * Fix audio noise on sync mode and improve overflow/underflow checking method.
    * Support UAC 3.1, 5.1 and 7.1 on audio speaker demo.
    * Set USB device CDC demo not to depend on DTR setting from host.
    * Support MCUX toolchain on some RTxxxx platforms.
- 2.8.0
  - Improvement:
    * Fix the USB device stack vulnerability issues.
    * Update the audio PLL and FRO adjustment codes for audio examples in RTxxx, LP-C54xxx and LPC55xxx.
    * Improve the USB PD AMS collision avoidance.
    * Improve IP3511 controller driver's dedicated ram allocation.
    * Change the USB_DATA_ALIGN_SIZE to 4 because the controller driver uses the dedicated RAM to do memcpy.
  - New features:
    * Enable USB host audio recorder demo for mutilple boards.
- 2.7.0
  - Improvement:
    * Use new feeback solution and low latency playback for usb device speaker demo and unified demos. Add underflow and overflow protection.
    * Optimize hard code for usb audio demos.
    * Update Unconstrained Power field in the Sink Capabilities Message according to the external power state.
    * Fix CVE-2021-38258 and CVE-2021-38260
  - New features:
    * Enable USB host video demo for mutilple boards.
    * Enable USB device MTP demo for mutilple boards.
    * Add PPS message to usb pd stack.
- 2.6.1
  - Improvement:
    * rename sdcard as disk for all of sdcard demos. For ramdisk demos, they are not changed.

* add wrapper for all of disk demos to support emmc.
- 2.6.0
  - Improvement:
    * Added more ufi event to support dynamic sdcard capacity.
    * Passed MISRA-2012 mandatory and required rules.
      · Except rule 17.2 in host hub and otg stack.
      · Except rule 5.1, rule 5.4, rule 21.1 and rule 21.2.
    * Re-implemented USB components and supported NPW.
    * Improved IP3511 controller driver's cancelling transfer function.
    * Enabled the audio2.0 defaultly for device audio demos.
    * Enabled the host audio2.0 function in host audio class driver and host audio speaker demo.
  - New features:
    * enable two USB controllers in one USB host mouse demo which named as host_hid_-mouse_dual.
    * enable UAC 5.1 for usb device audio speaker demo.
- 2.5.0
  - Improvement:
    * Integrated sdk components (OSA, Timer, GPIO and serial_manager) to USB stack and demos.
    * Improved the ip3511 driver throughput.
    * Improved audio initialization codes after SDK audio drivers update.
    * Improved auido to support the audio2.0 in win10.
    * Add one "enumeration fail" callback event to host stack.
- 2.4.2
  - Improvement:
    * Put the USB controller data and transfer buffer to noncache section, removed the setting that sets the whole ocram and sdram as noncached.
    * Separated composite audio examples' channel,sample rate,format parameters from commom macro to in dedicated macro and out dedicated macro.
    * replaced USB_PrepareData with USB_AudioRecorderGetBuffer.
- 2.4.1
  - New features:
    * Added enumeration fail callback to host stack when the attached device's enumeration failed.
- 2.4.0
  - Improvement:
    * Device Charger Detection (DCD) software architecture was refactored.
  - New features:
    * Enabled Device Charger Detection (DCD) on RT1060.
    * Enabled Device Charger Detection on RT600.
    * Enabled host battery charger function on RT600.
- 2.3.0
  - New features:
    * Added host video camera support. example: usb_host_video_camera

∗ Added a new device example. example: usb_device_composite_cdc_hid_audio_unified

- 2.2.0
  - New features:
    - ∗ Added device DFU support.
    - ∗ Supported OM13790DOCK on LPCXpresso54018.
    - ∗ Added multiple logical unit support in msc class driver, updated usb_device_lba_-information_struct_t to support this.
    - ∗ Supported multiple transfers for host ISO on IP3516HS.
  - Bug fixes:
    - ∗ Fixed device ip3511 prime data length than maxpacket size issue.
    - ∗ Initialized interval attribute in usb_device_endpoint_struct_t/usb_device_endpoint_-init_struct_t.
    - ∗ Removed unnecessary header file in device CDC class driver, removed unnecessary usb-_echo, and added DEBUG macro for necessary usb_echo in device CDC class driver.
    - ∗ Fixed device IP3511HS unfinished interrupt transfer missing issue.
- 2.1.0
  - New features:
    - ∗ Added host RNDIS support. example: lwip_dhcp_usb
    - ∗ Enabled USB 3.0 support on device stack.
    - ∗ Power Delivery feature: Added OM13790HOST support; Added auto policy feature; Printed e-marked cable information;
- 2.0.1
  - Bug fixes:
    - ∗ Fixed some USB issues: Fixed MSC CV test failed in MSC examples.
    - ∗ Changed audio codec interfaces.
- 2.0.0
  - New features:
    - ∗ PTN5110N support.
  - Bug fix:
    - ∗ Added some comments, fixed some minor USB issues.
- 1.9.0
  - New features:
    - ∗ Examples:
      - · usb_pd_alt_mode_dp_host
- 1.8.2
  - Updated license.
- 1.8.1
  - Bug fix:
    - ∗ Verified some hardware issues, support aruba_flashless.
- 1.8.0
  - New features:
    - ∗ Examples:
      - · usb_device_composite_cdc_vcom_cdc_vcom
      - · usb_device_composite_hid_audio_unified
      - · usb_pd_sink_battery

· Changed usb_pd_battery to usb_pd_charger_battery.
  – Bug fix:
    ∗ Code clean up, removed some irrelevant code.
- 1.7.0
  – New features:
    ∗ USB PD stack support.
  – Examples:
    ∗ usb_pd
    ∗ usb_pd_battery
    ∗ usb_pd_source_charger
- 1.6.3
  – Bug fix: -IP3511_HS driver control transfer sequence issue, enabled 3511 ip cv test.
- 1.6.2
  – New features:
    ∗ Multi instance support.
- 1.6.1
  – New features:
  – Changed the struct variable address method for device_video_virtual_camera and host_phdc-_manager.
- 1.6.0
  – New features:
    ∗ Supported Device Charger Detect feature on usb_device_hid_mouse.
- 1.5.0
  – New features:
    ∗ Supported controllers
      · OHCI (Full Speed, Host mode)
      · IP3516 (High Speed, Host mode)
      · IP3511 (High Speed, Device mode)
    ∗ Examples:
      · usb_lpm_device_hid_mouse
      · usb_lpm_device_hid_mouse_lite
      · usb_lpm_host_hid_mouse
- 1.4.0
  – New features:
    ∗ Examples:
      · usb_device_hid_mouse/freertos_static
      · usb_suspend_resume_device_hid_mouse_lite
- 1.3.0
  – New features:
    ∗ Supported roles
      · OTG
    ∗ Supported classes
      · CDC RNDIS
    ∗ Examples
      · usb_otg_hid_mouse

· usb_device_cdc_vnic
· usb_suspend_resume_device_hid_mouse
· usb_suspend_resume_host_hid_mouse

- 1.2.0
  - New features:
    * Supported controllers
      · LPC IP3511 (Full Speed, Device mode)
- 1.1.0
  - Bug fix:
    * Fixed some issues in USB certification.
    * Changed VID and Manufacturer string to NXP.
  - New features:
    * Supported classes
      · Pinter
    * Examples:
      · usb_device_composite_cdc_msc_sdcard
      · usb_device_printer_virtual_plain_text
      · usb_host_printer_plain_text
- 1.0.1
  - Bug fix:
    * Improved the efficiency of device audio speaker by changing the transfer mode from interrupt to DMA, thus providing the ability to eliminate the periodic noise.
- 1.0.0
  - New features:
    * Supported roles
      · Device
      · Host
    * Supported controllers:
      · KHCI (Full Speed)
      · EHCI (High Speed)
    * Supported classes:
      · AUDIO
      · CCID
      · CDC
      · HID
      · MSC
      · PHDC
      · VIDEO
    * Examples:
      · usb_device_audio_generator
      · usb_device_audio_speaker
      · usb_device_ccid_smart_card
      · usb_device_cdc_vcom
      · usb_device_cdc_vnic
      · usb_device_composite_cdc_msc

· usb_device_composite_hid_audio
· usb_device_composite_hid_mouse_hid_keyboard
· usb_device_hid_generic
· usb_device_hid_mouse
· usb_device_msc_ramdisk
· usb_device_msc_sdcard
· usb_device_phdc_weighscale
· usb_device_video_flexio_ov7670
· usb_device_video_virtual_camera
· usb_host_audio_speaker
· usb_host_cdc
· usb_host_hid_generic
· usb_host_hid_mouse
· usb_host_hid_mouse_keyboard
· usb_host_msd_command
· usb_host_msd_fatfs
· usb_host_phdc_manager
· usb_keyboard2mouse
· usb_pin_detect_hid_mouse

NXP WiFi

Version 1.3.r47.p16

- Updates:
  - Updated FC's f/w version to 2.p66.155.
  - Updated CA2 and RB3+ f/w version to 21.p124.
  - Fine tuning of GTK rekey offload feature.

Version 1.3.r47.p15

- Bug Fix:
  - DUT fails to connect to Ex-AP configured with wpa2 Enterprise security (Auth method Fast-mschapv2).
  - Incorrect AKM types PSK(2), PSK(SHA-256) are seen in beacon after configuring APUT in wpa2-psk security mode.
  - Link lost seen after wlan-scan when DUT is connected in wpa2 ft-psk security in 2.4Ghz band.

Version 1.3.r47.p12

- Bug Fix:
  - Throughput numbers for TCP-Rx traffic on APUT are dropping to 0mbps in HE20/VHT20 mode.

Version 1.3.r47.p11

- Bug Fix:

- Failed to connect STAUT configured in WPA2+PMF required security to Ex-AP configured in WPA2/WPA3 mixed mode+PMF capable security.
- STAUT is waking up with Broadcast traffic while running MEF AUTO PING ALLOW and WAKE HOST & MEF AUTO PING DISCARD and WAKE HOST.
- Cannot connec to AP with security wpa3_sb_192_eap_tls.
- Cannot out band independent reset successfully.

Version 1.3.r47.p10

- Bug Fix:
  - Auto reconnect - link lost reported when ap shut down.
  - STAUT failed to roam from Ex-AP1 to Ex-AP2 with WPA3 security mode while running UDP-Tx traffic.
  - STAUT is not waking up from suspend state while running Host-sleep test even after running Unicast/Broadcast traffic from Ex-AP to STAUT.
  - STAUT is waking up with Unicast data and without unicast data as well before running Broadcast data traffic from AP backend to STAUT.
  - While running WPS connection with Ex-AP, DUT gets deauthenticated after M4 packet, W-PS_NACK is recvd. M1 packet does not have WPS PBC or keypad specific bit set
  - "Network not found" is seen on the STAUT after disconnection and reconnection of the same profile in UNII4 channels (169,173,177).
  - When Dut reported Link lost, After configured time interval, DUT reconnects to AP but fails to ping to AP_BACKEND after reconnection.
  - Coverity Fixes.

Version 1.3.r47.p9

- Bug Fix:
  - APUT is advertising channel width information for 40Mhz in HE-phy capabilities instead of 20Mhz bandwidth in Assoc response frame.
  - STAUT failed to roam from Ex-AP1 to Ex-AP2 with WPA3 security mode with same channel same band and different channel same band scenario.
  - 15-20% Throughput degradation observed in TCP-TX and UDP-TX of HE[40Mhz/80MHz], VHT[40Mhz/80Mhz] compared to previous release[R45.p12].
  - "WLAN: Network not found" is observed while connecting STAUT configured in wpa2 security PMF capable to Ex-AP in wpa2 security with PMF required.
  - Coverity Fixes.

Version 1.3.r47.p8

- Bug Fix:
  - "WLAN: network not found & Warn: Scan temporary failure" is observed after disconnecting from one network and Re-connecting to same network after renaming SSID of Ex-AP.
  - "Network not found" is seen on the STAUT after disconnection and reconnection of the same profile in UNII4 channels (169,173,177).
  - Beacons not stopping in the older channel, after uAP switching the channel according to the Ex-AP in simultaneous mode.
  - Incorrect return value on error.

Version 1.3.r47.p7

- Bug Fix:
  - STA STRESS | Independent Reset, DUT went to hang state after 134 iterations of independent reset with status "ASSERT: wlan_process_hang: 982 Assert failed: Panic"!
  - Error message "'is_mef' undeclared(first use in this function)" is observed while the time of compilation of binary after enabling macro for the host-sleep.
  - DUT not able to roam from AP1 to AP2 in different channel (DFS) and same Band on reducing the RSSI of AP1.
  - STAUT failed to roam from Ex-AP1 to Ex-AP2 with WPA3 security mode while running UDP-Tx traffic.
  - MEF, DUT fails to wakeup with mef conditions ping 1,3 and arp 1 & 3.

Version 1.3.r47.p6

- Features
  - Add GTK rekey offload support.
  - Independent Reset via In-band
  - Independent Reset via Out-of-Band
- Updates:
  - Updated FC's f/w version to 2.p66.14.
- Bug Fix:
  - Power save/host sleep support improvements.
  - Messy log output after in band independent reset(17 in 31)
  - Association_Req content corrupted when Dut config as WPA/WPA2 mix mode and connecting to AP WPA+TKIP
  - Cannot connect to AP with security wpa3_sb_192_eap_tls.
  - Command "wlan-add-packet-filter 1" is not available for setting MEF filter configuration in Host-sleep.
  - WPA3 Enterprise support (Host based - Remaining set of authentication methods)
  - STAUT failed to roam from Ex-AP1 to Ex-AP2 with WPA3 security mode while running UDP-Tx traffic.
  - No Link lost is observed while switching from 11n[2.4G | 20Mhz] to legacy[2.4G] mode.
  - The introduction of new features does not follow the scope limitations of modules and apps
  - STAUT 11r, DUT unable to roam to particular BSSID after 10 to 15 iterations of roam, showing "Roaming already in progress Started FT roaming"
  - STAUT | After DUT wake up from Hostsleep condition 0x10 (WAKE_ON_ARP_BROAD-CAST) Ping failed from AP_Backend to DUT and Delayed ping from DUT to AP_Backend
  - Error: ignoring scan request in invalid state
  - Fix COVERITY Issue for midware_wifi

Version 1.3.r47.p5

- Updates:
  - Updated FC's f/w version to 2.p66.11.
- Bug Fix:
  - AKM checks are wrong for UAP PMF MANDATORY WPA2 PSK STA PMF MANDATO-RY WPA2 PSK for 11AN[20Mhz] as well as BGN[20Mhz] mode.

– STAUT is not waking up in any scenarios after giving Host-sleep commands with default power save enabled mode.

Version 1.3.r47.p4

- Features
  – Added support for Doxygen.
- Bug Fix:
  – AKM checks are wrong for UAP PMF MANDATORY WPA2 PSK STA PMF MANDATORY WPA2 PSK for 11AN[20Mhz] as well as BGN[20Mhz] mode.
  – On DUT manually configured parameters of 11axcfg, not getting reset to default after "wlan-reset" command execution.
  – 2G to 5G and 5G to 2G FTOA roaming fails , link lost observed with permanent disconnect
  – Change of bandwidth from 80Mhz to 40 MHz is observed after uAP (APUT) is stopped and started again, in HE/VHT band.
  – STAUT unable to scan Ex-AP in UNII4 channels (169,173,177) with any Band/security.
  – "Command response timed out. command 0x107" observed after 945 iterations in Scan--Connect-Disconnect Test without any traffic [Idle Test].
  – RT Console hangs after enabling WLAN/BT Independent Download.
  – Cannot get full iperf summary.
  – While running UDP Bi-directional traffic, QOS data packets are not going from APUT/STAUT.

Version 1.3.r47.p3

- Updates:
  – Updated FC's f/w version to 2.p66.6.
  – Updated CA2 and RB3+ f/w version to 21.221.
- Features
  – Added FW (Parallel) Download support.
- Bug Fix:
  – WiFi hang up with memory alloc buffer error during perform WiFi-scan along with WiFi independent reset loop test(OT already form the NTW)
  – TCP-Keep-Alive packets are not seen in sniffer after successfully setting configuration commands for cloud keep alive and STAUT is not waking up after putting in suspend state.
  – STAUT is not waking up from suspend state while running Host-sleep test even after running Unicast/Broadcast traffic from Ex-AP to STAUT.
  – AKM checks are wrong for UAP PMF MANDATORY WPA2 PSK STA PMF MANDATORY WPA2 PSK for 11AN[20Mhz] as well as BGN[20Mhz] mode.
  – Ex-STA (Kestrel, Firecrest RT1060-EVKC) Failed to associate in WPA2 PMF disabled mode to APUT configured in WPA2/WPA3 mixed security mode.
  – STAUT, failed to Associate in WPA2 security with PMF disabled to Ex-AP configured in WPA2/WPA3 mixed security mode.

Version 1.3.r47.p2

- Bug Fix:
  – Fail to disable IEEE Power save mode, while giving command to disable it.

- NXP devices Kestrel/KF2-RD(STA) unable to connect to DUT as MMH-AP but connecting with Mobile, Four way Handshake Timeout is observed with NXP Devices
- Ex-STA(Kestrel, KF2) Assoc-reject is observed with uAP configured in OWE security mode.
- Cannot connect to 5g external AP.

Version 1.3.r47.p1

- Updates:
  - Updated CA2 and RB3+ f/w version to 21.p109
  - Updated 8801 f/w version to 36_186
  - Updated Firecrest firmware version to p66.5.
- Features
  - Added EVKC board support for all SoCs.
  - Added WPA2/3 Enterprise support for EAP-SIM/EAP-AKA/EAP-AKA-PRIME for STA and uAP.
  - Added CSI support.
  - Added Auto Reconnect support.
  - Added CA2 and RB3+ Parallel FW Download support.
  - Added CA2 and RB3+ Independent Reset via In-band support.
  - Added CA2 and RB3+ Independent Reset via Out-of-Band support.
  - Added CA2 and RB3+ Boot sleep patch support.

Version 1.3.r46.p7

- Updates:
  - Updated Falcon to p185, CA2 and RB3+ f/w version to 21.p91.5
- Bug Fix:
  - uAP reassociation not working
  - Traffic stops wen moving from auto rate to mcs0
  - DUT not sending TCP-KEEP-ALIVE in suspend state
  - DUT not able to roam from WPA-R1 enabled AP to WPA3-R3 enabled AP
  - Ex-AP1 to Ex-AP2 roaming not working in wpa3
  - STAUT is nto following BSS transition correctly
  - RF test mode commands crash issue
  - Ping is not working when uAP configured with wpa3-sb-192 bit EAP-TLS/EAP-TTLS/EAP-PEAP enterprise security.
  - DUT shows network not found, even when connected to Ex-AP
  - Stress test fixes

Version 1.3.r46.p5

- Updates:
  - Updated CA2 and RB3+ f/w version to 21.p91.5
- Bug Fix:
  - Wifi random crash issue when DUT set to sleep
  - Enable 11D for uAP by default
  - STA doesnt get IP address when ieee-ps and deep sleep are enabled
  - Coverity fixes

– BT/BLE fix for PTS test case

Version 1.3.r46.p4

- Updates:
    – Updated CA2 and RB3+ f/w version to 21.p91.4
- Bug Fix:
    – Fixed: pre-cert: 20/40 BSS coexistence management is not supported in association request.
    – Fixed: pre-cert: STAUT is not correctly following the MU EDCA parameters advertised by the AP.
    – Fixed: Fail to connect to external AP with security wpa3.
    – Fixed: uAP with wpa3 security is not connectable.
    – Fixed: DUT not able to connect to Ex-AP in WPA2 security when PMF required is set.
    – Fixed: Remove BAND_B rates from Supported rates for 5G channels during scan.
    – Fixed: pre-cert STAUT is not including operating class 81 and 115 under Alternate Operating Classes in assoc request.
    – Fixed: Cannot connect to external AP successfully.
    – Fixed: 5Ghz channel are configured acceptable in 2.4Ghz band
    – Fixed: wlan_set_rf_tx_power is not consistent with tx-frame power output
    – Fixed: Getting compilation errors while compiling the binary after defining "CONFIG_UNI-I4_BAND_SUPPORT" macro in wifi_config.h file.
    – Fixed: uAP Beacons advertise 3 AKM suites (PSK & PSK SHA256 & SAE SHA256) in RSNIE when WPA2+WPA3 mixed mode is set on AP with mfpc 1 and mfpr 0.
    – Fixed: STAUT configured with WPA3-SAE associates to WPA2 configured AP.
    – Fixed: DUT unable to roam from Ex-AP1 to Ex-AP2 on lowering the RSSI of Ex-AP1.
    – Fixed: pre-cert STAUT is not correctly following the MU EDCA parameters advertised by the AP.
    – Fixed: DUT-STA is unable to associate with WPA/WPA2 Mixed mode AP when DUT-STA is configure WPA security.
    – Fixed: pre-cert STAUT fails to roam from WPA3 configured AP1 to WPA2-PSK configured AP2.
    – Removed IEEE_MGMT_ACTION_CATEGORY_PUBLIC enum.
    – Fixed logic for consecutive connect for both embedded and wpa supplicant.
    – Fixed all compilation errors and warnings seen on dapeng.
    – Resolved MISRA and coverity defects.

Version 1.3.r46.p3

- Updates:
    – Updated CA2 and RB3+ f/w version to 21.p91.2
- Bug Fix:
    – Fixed: TCP and UDP TX traffic stream not working with ex-sta
    – Fixed: pre-cert: STAUT is not following BSS transition correctly
    – Fixed: Extend wlan-get-antcfg to print current antenna
    – Fixed: DUT able to configure MFPR 0 in WPA3 security.
    – Fixed: DUT MCS rates are not updating to default after stopping/removing previous profile with MCS set to fixed number via fixed rate command.

– Fixed: DUT-uAP unable to start with ACS configuration.
– Fixed: While running WPS connection with Ex-AP, DUT gets deauthenticated after M4 packet, WPS_NACK is recvd. M1 packet does not have WPS PBC or keypad specific bit set.
– Fixed: Fail to create ipv6 iperf client.
– Fixed: uAP beacons contain incorrect bit, UAPSD bit is set in WME QoS Info even though it is not supported.
– Fixed: uAP beacons contain incorrect bits, SU/MU Beamformer bits are set in HE Phy capabilities and UAPSD bit is set in WME QoS Info even though it is not supported.
– Fixed: Data path blocks once we initiate wlan-scan on DUT and change Ex-AP channel at the same time.
– Fixed: MISRA defects.

Version 1.3.r46.p2

- Updates:
  – Updated CA2 and RB3+ f/w version to 21.p91
- Bug Fix:
  – Fixed BT connection issue on RB3+

Version 1.3.r46.p1

- Updates:
  – Updated CA2 and RB3+ f/w version to 21.p90
  – Updated 8801 f/w version to 36_181
  – CA2 Fixed FIPS GCMP support
  – Added all changes as part of r45.p3 as applicable for CA2 and RB3+
  – Added information for BSD3 license.
  – Updated WLCMGR and Wi-Fi driver to support WPA supplicant and hostapd.
  – Deepsleep feature in BLE peripheral role
  – Deep Sleep and wakeup feature is enabled for CA2 and RB3+
- Features
  – Added WPA supplicant and hostapd support.
  – Added WPS 2.0 support for STA and uAP.
  – Added WPA2 enterprise support for STA and uAP.
  – Added WPA3 enterprise support with suite b and suite b 192 bit mode for STA and uAP.
- Bug Fixes:
  – Fixed: APUT goes into hang state after every disassociation of STA.
  – Fixed: (pre-cert)AMSDU Rx test fails as STAUT returns the throughput received as 0.
  – Fixed: Country Information IE with default country code (WW) is seen in beacon even after changing the regions from WW to US/EU/CA/CN.
  – Fixed: DUT should show "Network not found" message in cli, when Configure SSID is not present in network area.
  – Fixed: DUT not able to connect to Ex-AP in WPA3R3 security.
  – Fixed: DUT not able to roam from Ex-AP1 to Ex-AP2.
  – Fixed: Hostsleep/MEF test condition failures are seen.
  – Fixed: uAP not coming up in WPA2/WPA3 mixed mode security., getting "WPA initialization

failed" on DUT console.

– Fixed: DUT shows wrong channel number in wlan-scan-opt and wlan-info command results.

– Fixed: DUT sending QoS data packets with LDPC coding when LDPC coding is disabled on Ex-STA.

– Fixed: Country Information IE is not seen in uAP Beacon.

– Fixed: DUT is going into hang state while running Connect/Disconnect Stress Test

– Fixed: Supported MCS and NSS rates are not properly set under HE capabilities IE in beacon frame when CAPA enabled binary is flashed on DUT.

– Fixed: Channel Bandwidth is setting to 80Mhz when uAP is configured in 11AX-40Mhz/20-Mhz.

– Fixed: Beacon frame includes HE IE when uAP is configured in 11AC using Capa command.

– Fixed: DUT is not connecting in WPA2/WPA3 Enterprise security.

– Fixed: DUT is not getting ipv4 address after Roaming to Ex-AP2.

– Fixed: DUT is not roaming from AP1 to Ex-AP2 after running wlan-ft-roam command in 5Ghz.

– Fixed: DUT is not following BSS transition Correctly.

– Fixed: DUT is not responding Beacon Report Action frame after sending the Beacon request from Ex-AP to DUT.

– Fixed: Automatic Channel Selection is not working when DUT configured in MMH mode.

– Fixed: DUT is going for Reassociation with the same Ex-AP after running "wlan-host-11k-neighbour-req" command.

– Fixed: uAP Beacons does not include SHA256 in RSNIE when PMF mandatory is set on AP in WPA2-PSK security.

– Fixed: Low Throughput seen in 11AX, 11AC, 11N (80MHz, 40MHz & 20MHz) TCP-RX/T-X, UDP-TX/RX in 2.4Ghz & 5Ghz.

– Fixed: DUT is not using "FT using PSK" AKM suite when 802.11R is enabled.

– Fixed: DUT not able to connect to Ex-AP in WPA2 security when PMF required is set.

– Fixed: Need to reset DUT every time for every new connection to happen.

– Fixed: Incorrect VHT IE "RX/TX MCS Map" is seen in uAP beacons.

– Fixed: uAP Beacons is advertising 4 Pairwise Cipher Suites [CCMP (256), GCMP (256), AES (CCM), GCMP (128)] in RSNIE with WPA2/WPA3 security.

– Fixed: uAP not coming up in 2.4GHz channel 11, getting "uAP start failed, giving up" on DUT console.

– Fixed: DUT is going in hang state after Stop/Remove/Start network in wpa2 and wpa3 security, when configured in MMH mode.

– Fixed: HE IE is not reflecting in beacons, when DUT is configured in default mode without capa in MMH.

– Fixed: DUT is not connecting in WPA3 security, shows "Error: Init of random number generator failed."

Version 1.3.r45.p12

- Updates:
    – Uodated tx pwr limit files for murata 2el module.
    – Added config macro for RU Tx power.
    – Updated WPA2/3 Enterprise support to handle pre-cert tests.

- Bug Fixes:
  - Fixed: uAP not starting up in channel 14 showing start failed when uAP country code is set to JP.

Version 1.3.r45.p11

- Updates:
  - Added integrate tx pwr limit files for murata 2el module.
  - Added support for legacy mode of RU Tx power.
  - Updated WPA2/3 Enterprise support to handle pre-cert tests.
- Bug Fixes:
  - Fixed: Bi-directional traffic converts to uni-directional traffic.
  - Fixed: The support for "wlan-multi-mef" command to configure MEF parameters on cli is not available.
  - Fixed: Country Information IE with default country code (WW) is seen in uAP beacon even after changing the regions from WW to US/EU/CA/CN.
  - Fixed: Failed to wakeup card after turned on IEEE Power Save mode.
  - Fixed: Bi-directional iperf traffic is not running getting dropped to 0.000 bits/sec.
  - Fixed: Macbook not connecting with DUT-AP in channel 48 and BW 80MHz.
  - Fixed: [pre-cert] DUT fails to connect to Ex-AP configured with wpa/wpa2 enterprise security (AES Encryption) and the radius server configured with hostapd, unsupported certificate error.
  - Fixed: Not connecting to AP in WPA-TKIP and WPA-AES, M2 is not being initiated by STA.

Version 1.3.r45.p10

- Updates:
  - Updated firmware version to 2.p7.19 and added TP signed FW(with VDLL) too.
  - Changed the init and command flow for uart_wifi_bridge app.
- Bug Fixes:
  - Fixed: [pre-cert] DUT not correctly receiving AMPDU+AMSDU , AMSDU bit is not set to 1 in QOS data frame.
  - Fixed: uAP not starting up in channel 14 showing start failed when uAP country code is set to JP.
  - Fixed: Data path blocks once we initiate wlan-scan on DUT and change Ex-AP channel at the same time.
  - Fixed: App will block/output error log when trying to set rf tx frame.

Version 1.3.r45.p9

- Updates:
  - Updated firmware version to 2.p7.17 and added TP signed FW(with VDLL) too.
  - Added support for channel based RU Tx power.
  - Added support of reassociate command on STAUT to test reassociate feature.
- Bug Fixes:
  - Fixed: Ex-STA(Kestrel) not able to connect to uAP with "reassociate" command in first attempt, getting deauthentication and again connection is initiated with Association Request and connection happens, in wpa3 security.

- Fixed: [pre-cert] STAUT is sending incomplete beacon report response to AP's beacon report request.
- Fixed: Messy log output when trying to turn off deep sleep mode.
- Fixed: Unable to set TX-OMI on uAP using command "wlan-set-tx-omi".
- Fixed: DUT is not re-connecting when bandwidth/mode changed on Ex-AP.

Version 1.3.r45.p7

- Updates:
  - Updated firmware version to 2.p7.15 and added TP signed FW(with VDLL) too.
- Bug Fixes:
  - Fixed: STAUT is not following BSS transition correctly.
  - Fixed: DUT is not sending TCP-KEEP-ALIVE packets in suspend state, when TCP connection is established via Cloud keep alive command.
  - Fixed: DUT not able to roam from Ex-AP1 to Ex-AP2 on lowering the RSSI of Ex-AP1 in wpa3 security.
  - Fixed: STAUT's probe request does not contain MBO-OCE IE
  - Fixed: Ping is not working when uAP configured with wpa3-sb-192 bit EAP-TLS/EAP-TTL-S/EAP-PEAP enterprise security.
  - Fixed: STAUT's probe request does not contain MBO-OCE IE.
  - Fixed: Throughput enhancement for STA and uAP mode for various TCP/UDP and Tx-Rx modes for embedded and wpa supplicant.
  - Fixed: "TCP_ABORTED_LOCAL" message seen on DUT console instead of "TCP_DONE" when running iperf traffic
  - Fixed: [pre-cert] STAUT is not dropping TP when AP is increasing MPDU spacing factor from 0 to 3.

Version 1.3.r45.p6

- Updates:
  - Updated firmware version to 2.p7.11 and added TP signed FW(with VDLL) too.
  - uart_wifi_bridge added and errors fixed for RT1170-EVKB.
- Bug Fixes:
  - Fixed: Traffic stops after moving from auto rate to fixed mcs0. Command is triggered on the fly.
  - Fixed: DUT not able to roam from WPA3R1 enabled AP to WPA3R3 enabled AP showing network not found.

Version 1.3.r45.p5

- Updates:
  - Updated firmware version to 2.p7.10 and added TP signed FW(with VDLL) too.
- Bug Fixes:
  - Fixed: Data path blocks once we initiate wlan-scan on DUT and change Ex-AP channel at the same time.
  - Fixed: uAP beacons contain incorrect bits, SU/MU Beamformer bits are set in HE Phy capabilities and UAPSD bit is set in WME QoS Info even though it is not supported.
  - Fixed: uAP beacons contain incorrect bit, UAPSD bit is set in WME QoS Info even though it

is not supported.
- – Fixed: [pre-cert] STAUT is not correctly following the MU EDCA parameters advertised by the AP
- – Fixed: [pre-cert] 20/40 BSS coexistence management is not supported in association request.
- – Fixed: Fail to connect to external AP with security wpa3.
- – Fixed: uAP with wpa3 security is not connectable.
- – Fixed: DUT not able to connect to Ex-AP in WPA2 security when PMF required is set.
- – Fixed: Remove BAND_B rates from Supported rates for 5G channels during scan.
- – Fixed: Fix wifi_cli_prov example hang when connect if enable ieee power save and deep sleep.
- – Fixed: RFTM: 5Ghz channel are configured acceptable in 2.4Ghz band.
- – Fixed: RFTM: wlan_set_rf_tx_power is not consistent with tx-frame power output.
- – Fixed: DUT not able to roam from AP1 to AP2 in different channel (DFS) and same Band on reducing the RSSI of AP1.
- – Fixed: uAP Beacons advertise 3 AKM suites (PSK & PSK SHA256 & SAE SHA256) in RSNIE when WPA2+WPA3 mixed mode is set on AP with mfpc 1 and mfpr 0.
- – Fixed: DUT unable to roam from Ex-AP1 to Ex-AP2 on lowering the RSSI of Ex-AP1.
- – Fixed: Fixed build errors and warnings for matter, MISRA, coverity and other compilers.

Version 1.3.r45.p4

- • Updates:
  - – Updated firmware version to 2.p7.4 and added TP signed FW(with VDLL) too.
- • Bug Fixes:
  - – Fixed: Fail to create ipv6 iperf client.
  - – Fixed: DUT MCS rates are not updating to default after stopping/removing previous profile with MCS set to fixed number via fixed rate command.
  - – Fixed: MISRA Defect fixed.
  - – Fixed: IEEE PS event not getting triggered.
  - – Fixed: While running WPS connection with Ex-AP, DUT gets deauthenticated after M4 packet, WPS_NACK is recvd. M1 packet does not have WPS PBC or keypad specific bit set.
  - – Fixed: Fail to create ipv6 iperf client.
  - – Fixed: Hang issue seen when assoc reject event received.

Version 1.3.r45.p3

- • Updates:
  - – Enabled h/w acceleration APIs via mbedtls.
  - – VDLL support added.
- • Bug Fixes:
  - – Fixed: (pre-cert)Need support to set UL MU Disable/Data Disable element through TX-OMI command.
  - – Fixed: iTCP and UDP TX traffic stream not working with ex-sta.
  - – Fixed: STA not able to connect to APUT when APUT is configured in OWE security.
  - – Fixed: DUT is going on hang state after running "wlan-reset" command.
  - – Fixed: "TCP_ABORTED_REMOTE" message seen on DUT console when running UDP

traffic.

- – Fixed: (pre-cert)STAUT is not scanning Non Transmitted SSID in MBSSID test.
- – Fixed: 6+ ms of traffic burst is seen which is failing cert criteria of max cot as 6ms.
- – Fixed: DUT not getting IP address(DHCP) when "WMM_ENH" Macro is defined in "wifi_-config.h" file for TWT feature.
- – Fixed: For Tx Frame & tx-continuous, the Measured tx-power value is 2dBm irrespective of configured Tx-power(10/12/15/20dBm)
- – Fixed: Data path blocks once we initiate wlan-scan on DUT and change Ex-AP channel at the same time.
- – Fixed: DUT not able to scan and connect to DFS channels when Broadcast SSID is disabled.
- – Fixed: Aggregation is broken when TCP/UDP TX Data is going with TID 6-7 (Voice), and TID 3 (Best Effort).
- – Fixed: uAP not beaconing in 40MHz when uAP configured in channel 12/13-40MHz in MMH mode
- – Fixed: STA Ping is not working once it roams to Ex-AP2.
- – Fixed: Wi-Fi lwip port does not protect correctly concurrent accesses to lwip stack.
- – Fixed: Beacon frame does not include RSN XE IE when uAP configured in WPA3R3 security.
- – Fixed: Beacon frame includes HT IE when uAP configured in 11A mode using capa legacy command.
- – Fixed: DUT not connecting to Ex-AP when PMF is configured using "wlan-set-pmfcfg" command.
- – Resolved IAR, MCUX and MDK build errors.

Version 1.3.r45.p2

- • Updates:
    - – Updated firmware version to 2.p7.1 and added TP signed FW too.
    - – Added RFTM commands missing CLI commands related to OFDMA feature.
    - – Added support for EVKB board.
- • Bug Fixes:
    - – Fixed: uAP not coming up in channel 14 when country code is set to JP.
    - – Fixed: DUT not able to connect with 32-character SSID when Ex-AP configured in open/wpa2/wpa3 security.
    - – Fixed: QoS Data packets not seen on air when we run "wlan-set-tx-omi 0x48 0xff 16" command on DUT.
    - – Fixed: [pre-cert] Not able to set non-preferred channel in MBO through wpa_cli on RTOS.
    - – Fixed: Automatic Channel Selection is not working when DUT configured in MMH mode.
    - – Fixed: STA not able to connect to APUT when APUT is configured in OWE security.
    - – Fixed: Wi-Fi lwip port does not protect correctly concurrent accesses to lwip stack.
    - – Fixed: DUT is going on hang state after running "wlan-reset" command.
    - – Resolved IAR, MCUX and MDK build errors.

Version 1.3.r43.p9

- • Updates:
    - – Added support for RF test mode.
- • Bug Fixes:

– Fixed: (pre-cert)Updated help message for TX-OMI command.
– Fixed: (pre-cert)STAUT is not scanning Non Transmitted SSID in MBSSID test.
– Fixed: (pre-cert)STAUT is not governing OBSS Narrow Bandwidth RU in UL OFDMA Tolerance Support.
– Fixed compilation errors and warnings after branch merge.

Version 1.3.r44.p3

- Bug fixes:
  – Added RSNX IE for WPA3-R3 for uAP

Version 1.3.r44.p2

- Updates:
  – Updated CA2, RB3+ firmware to p82
  – Bug fixes:
    * Fixes for 11KR
    * Fixes for WPA3-R3 STA
    * Added extra event for Connected notification in case of uAP

Version 1.3.r44.p1

- Updates:
  – Updated CA2, RB3+ firmware to p79
  – Updated 8801 firmware to p180
- Features:
  – Added 11KVR support for CA2 and RB3+
- Bug fixes:
  – Fixed: Association Request does not include Group Management Cipher Suite IE in RSNIE when PMF mandatory is set on STA in WPA2-PSK/WPA3/OWE security.
  – Fixed: Sending of deauth codes in all scenarios
  – Fixed: Command timeout issues for wlan-eu-crypto
  – Added Coverity fixes
  – Fixed command timeout seen during simultaneous AP + STA mode, with high traffic on 8801
  – Set proper value for Edmac value updated to support Murata 2DS Module
  – Fixed Channel switch announcement is not seen in beacon in AP+STA mode, when AP changes channel on 8801
  – Added few BT Sig qualification fixes

Version 1.3.r43.p8

- Updates:
  – Updated firmware version to p182.1 and added TP signed secure FW too.
- Bug Fixes:
  – Fixed: (pre-cert)APUT beacons does not have RSNXE when configured in H2E mode.

Version 1.3.r43.p7

- Updates:
  – Updated firmware version to p182.
  – Added TP signed secure FW.

- Added support for 2EL M2 module for Firecrest.
- Added wifi capability configuration support.
- Added FIPS validation feature.
- Added wifi rf test mode example.
- Unified all wifi examples in wifi_cli.
- 11R is not surrpoted for FC.
- Bug Fixes:
  - Modified the method to load RU tx power limit with RT.
  - Modified txrate config design for 11AC and 11AX features.
  - Added support for roaming and neighbor request processing.
  - Fixed: "Error in sending Background traffic" messages seen on DUT while running Background TX-Traffic.
  - Fixed: STAUT is not associating in WPA3 Hash-to-Element only mode.
  - Fixed: Not able to change HE MAC Capabilities or HE PHY Capabilities in Association Request using 11axcfg command.
  - Fixed: DUT not waking up from suspend state when we start multicast traffic after 30sec-1 minute.
  - Fixed: STAUT hangs after scanning AP in scenario K of SI-5.2.2 test case.
  - Fixed: STAUT is not including operating class 81 and 115 under Alternate Operating Classes in assoc request.
  - Fixed: STAUT fails to roam from WPA3 cionfigured AP1 to WPA2-PSK configured AP2.
  - Fixed: DUT goes for DHCP DORA Process after roaming to AP2 from AP1.
  - Fixed build errors and warnings.
  - Corrected description related to num_dat_pkts parameter of tx-omi command.

Version 1.3.r43.p6

- Updates:
  - Updated firmware version to p174 and added latest signed FW bins as well.
- Bug Fixes:
  - Fixed: Command timeout issues observed for various offload commands.
  - Fixed: TWT requester bit not set in Extended Capabilities IE (127) in Association Request and Probe Request of STAUT.
  - Fixed: Not able to scan and connect Firecrest-STA to Firecrest-uAP configured in UNII-4 band channels 173 and 177.
  - Fixed: Multiple error messages are seen on DUT while running the stress "RX ping on STA, Start-stop uAP" in loop.
  - Added 11AX macro so that nss settings can be available for 11AC as well as 11AX based configurations.
  - Fixed various warning for IAR, MDK, armgcc and mcuXpresso compilers.

Version 1.3.r43.p5

- Updates:
  - Updated firmware version to p168(however signed firmware is not updated in this release and has version p164).
- Bug Fixes:

- Fixed: DUT not able to connect to AP configured in WPA2/WPA3 mixed mode security.
- Fixed: Association Request does not include Group Management Cipher Suite IE in RSNIE when PMF mandatory is set on STA in WPA2-PSK/WPA3/OWE security.
- Fixed: uAP Beacons does not include SHA256 in RSNIE when PMF mandatory is set on AP in WPA2-PSK security.
- Fixed: Device getting hanged while setting txpwrlimit by CMD 'wlan-set-txpwrlimit'.
- Fixed: Not able to load RU tx power limit with RT.
- Fixed: Not able to change HE parameters in HE MAC Capabilities or HE PHY Capabilities using 11axcfg command.

Version 1.3.r43.p4

- Updates:
  - None.
- Bug Fixes:
  - Updated helper message for owe_only cli.
  - Fixed: Observed bi-directional data traffic on air while running uni-directional TCP-RX traffic.
  - Fixed: UDP-TX traffic going without using aggregation.
  - Throughput values will now be displayed on DUT while running iperf Tx and Rx traffic.

Version 1.3.r43.p3

- Updates:
  - Updated firmware version to p164.
- Bug Fixes:
  - Added ed mac config support for uAP.
  - Modified process_rsn_ie function on driver side to provide support for Group Management Cipher suite.
  - Added conditional logic related to handling of region code.

Version 1.3.r43.p2

- Bug Fixes:
  - Added delay in uart_wifi_bridge application to correctly read calibration data for RB3P board.

Version 1.3.r43.p1

- Updates:
  - Updated firmware version to p162.
  - Added MBO feature support.
  - Added OWE feature support.
- Bug Fixes:
  - uAP Beacons contains MFPC & MFPR bits set to 1 in WPA2-PSK security after removing the previous WPA3 security profile.
  - Added new cli parameters for wlan-set-tx-omi command to send OMI using QoS Null Packet or QoS Data Packet according to input provided.
  - Corrected 11R configuration macro in allMacros_iw61x.txt file and removed the same from ignoreMacros_iw61x.txt file.

– Coverity fix: Changed all WM_FAIL to -WM_FAIL.

Version 1.3.r42.p4 -New Additions:

- CA2 and RB3+ f/w updated to v16_xx.21.p64.1

Version 1.3.r42.p3 -New Additions:

- 8801 f/w update -Bug Fixes:
- Fixed Misra issues.

Version 1.3.r42.p2 -Bug Fixes:

- Fixed Misra issues.

Version 1.3.r42.p1 -New Additions:

- RTOS abstraction improvement
- Added support for FIPS for CA2 and RB3+
- Added uAP 11AC support
- Deprecated support for 88W8977 Wi-Fi SoC
- Added 8978 SoC firmware p64.
- Added 8987 SoC firmware p64.
- Added mlanutl equivalent utility on RT to create wifi fw compatible command arrays.

-Bug Fixes:

- Fixed Misra issues.

Version 1.3.r41.p2 -New Additions:

- Updated license header as a github friendly license.
- Added 8801 SoC firmware p177 with get Coex Statistics support.
- Added 8987 SoC firmware p32.2 with Bluetooth related fixes. Added fix for automatic ble disconnect issue.

-Bug Fixes:

- Fixed Unable to start/stop 11n rx reorder timer(50%).
- Fixed Getting Improper Channel Number in "wlan-get-uap-channel" command.
- Fixed DUT fails to start DHCP intermittently.
- Fixed wrong wlan-list output.
- Fixed station connect issue after host sleep is enabled and disabled.
- Fixed Misra and coverity issues.
- Fixed automatic ble disconnect issue after 30 seconds of connection establishment.

Version 1.3.r41.p1 -Bug Fixes:

- Updated 8801 SoC firmware to toggle GRANT Pin with WLAN/BT time on HIGH Request with Low Priority.
- Added coverity fixes.

Version 1.3.r40.p5 -Bug Fixes:

- Fixed issue of DUT not entering Powersave mode on all SoCs.

Version 1.3.r40.p4 -Bug Fixes:

- Default bandwidth set to 20 MHz for uAP on 8977.
- Fixed an issue in static IPv4 address assignment.
- Fixed warning and errors for IAR, MDK and gn + ninja + armgcc toolchains.

Version 1.3.r40.p3 -Bug Fixes:

- Added wlan_uap_set_httxcfg API to set 40 MHz support in 2.4 GHz.
- Fix for build issue seen for wifi_setup 1020

Version 1.3.r40.p2 -Bug Fixes:

- Fixed IPv6 address and state updates as per the networking stack configuration.
- Removed errors shown in channel validation and in setting custom CFP tables
- Added API to support selection of 20 and 40 MHz bandwidth
- Added -b(bandwidth) option in wifi_cli iperf command
- DHCP client doesn't report the failure of obtaining IP address
- Remove dependency for wifi_config_internal.h
- Remove warnings reported for channel list variables
- Fix STA not sending data in 40M bandwidth for BGN 40 in 2.4G

Version 1.3.r38.p2

- New Additions:
    - Added Support for IPv6.
    - Added support for Hostsleep and packet filters.
    - Updated Firecrest Firmware version to p50.5.
    - Updated CA2 Firmware version to p21.22.

-Bug Fixes:

- Fixed an issue where DUT not able to start UAP Network in 2G MMH Mode.
- Fixed an issue where Command 0xb2 timeout is seen when stopped uAP while running DL traffic.

Version 1.3.r37.p4

- New Additions:
    - Added support for new API for HostCmd in RT Platform.
    - Added provision to set tx rates for HE mode in wlan_set_txratecfg API.
    - Added support for new command to set tx OMI.
    - Added WPA3 R3 support for 8801, RB3, RB3+ and CA2.
    - Updated Firecrest firmware version to p50.2.
    - Updated CA2 firmware version to p235.2
    - Updated RB3+ firmware version to p11.3.
    - Updated 8801 firmware version to p191.2
    - Updated RB3 firmware version to p186.2.
- Bug Fixes:
    - Fixed an issue where default netif was not set to STA after closing uAP.
    - Fixed an issue where 30% low RX throughput was seen with 11AN 40Mhz.
    - Fixed wlan_start and wlan_stop API working.

- Fixed High ping latency when DUT is put in IEEEPS mode.
- Fixed an issue where wlan_get_dtim_period API was not returning any value.
- Fixed SVD vulnerability issue on RB3+.
- Fixed MISRA/Coverity issues.
- Fixed SVD vulnerability issue on 8977, 8801 and CA2.
- Fixed an issue in Firecrest where STAUT is disconnecting immediately after ieeeps command is fired.
- Fixed an issue where UDP traffic was not working on uAP mode.
- Country code not being displayed in 11d is being fixed

Version 1.3.r35.p2

- New Additions:
  - Added support for 11ax for Firecrest.
  - Updated Firecrest firmware version to p27.
- Bug Fixes:
  - Fixed an issue for CA2 where tcp/udp Rx traffic was not seen with Linksys AP.
  - Fixed tx power limit issue for Firecrest.
  - Fixed an issue for Firecrest where Ping stops working after TCP traffic is started from DUT.
  - Changed WLAN_PSK_MAX_LENGTH to 64 from 65.
  - Fixed an issue where mfpc was not set properly.

Version 1.3.r34.p2

- New Additions:
  - Updated CA2(8987) SoC firmware to p235.1.
- Bug Fixes:
  - Fixed WPA3 Authentication failure for CA2.
  - Fixed SPP connection issue.

version 1.3.r34.p1

- New Additions:
  - Updated CA2(8987) SoC firmware to p235.
  - Added Separation of fw download from Wi-Fi initialization.
  - Added support for Multicast group creation
  - Updated license content in the wlan src for Murata or Generic customer.
  - Added support for new firmware version display.
  - Added config Macro for disabling Rx SDIO aggregation. This is enabled by default.
- Bug Fixes:
  - Fixed CH 144 connection issue.

version 1.3.r33.p2

- New Additions:
  - Updated RB3+(8978) SoC firmware to p214.
  - Updated CA2(8987) SoC firmware to p200.
- Bug Fixes:
- Fixed an issue where, wifi connection was failing during BLE activity.

- Fixed an issue where a2dp profile app could not find a2dp sink device.

version 1.3.r32.p5

- New Additions:
    - Updated RB3+(8978) SoC firmware to p198.
    - Updated CA2(8987) SoC firmware to p199.
- Bug Fixes:
    - Fixed an issue where BT pairing auth failure was observed between two 8987 or two IW416 devices due to same DH Public Key being generated.

version 1.3.r32.p4

- New Additions:
    - Updated RB3+(8978) SoC firmware to p197.
- Bug Fixes:
    - Fixed an issue where, in presence of WLAN, BT A2DP SNK scenario can observe continuous glitches because of BT utilizing the WLAN overlapping channels.
    - Fixed an issue where, in presence of BT A2DP SRC scenario and WLAN traffic, both will share air-time. WLAN Rx TP can drop to 15-20% of its baseline because of A2DP occupying more air-time duty cycle.

version 1.3.r32.p3

- New Additions:
    - Updated RB3+(8978) SoC firmware to p196.
    - Updated CA2(8987) SoC firmware to p162.
    - Updated RB3(8977) SoC firmware to p186.
    - Updated Falcon(8801) SoC firmware to p191.
- Bug Fixes:
    - Fixed an issue where STAUT was not advertising extended capabilities in assoc request
    - Fixed an issue where cal data download API is not setting the cal data correctly.
    - Fixed an issue where Ping of 10000 bytes is not workingfor WMM case with 11n/11ac pre-cert WFA testbed AP's.
    - VU FFD(vulnerability) fixes have been made for CA2(8987)/RB3+(8978)/RB3(8977)/-Falcon(8801).

version 1.3.r31.p1

- New Additions:
    - Updated RB3+(8978) SoC firmware to p152.
    - Updated CA2(8987) SoC firmware to p152.
    - Added WMM feature for 8987 SoC -Updates
    - Enabled wifi deep sleep and IEEEPS modes as part of CLI initialisation.
    - Updated module macro for CA2 from WIFI_BOARD_AW_CM358MA to WIFI_BOARD_-AW_CM358.
- Bug Fixes:
    - Fixed deepsleep error when called immediately after disconnection
    - Fixed an issue where uAP was not turned on when country is specified using wlan_set_country

API.

version 1.3.r30.p2

- New Additions:
    - Updated 8978 SoC firmware to p185.
    - Updated 8987 SoC firmware to p185.
- Bug Fixes:
    - Fixed a regression issue in WiFi FW where Ex-client is not able to associate with uAP on 8978 and 8987 SoC.

version 1.3.r30.p1

- New Additions:
    - Updated RB3+(8978) SoC firmware to p145.
    - Updated CA2(8987) SoC firmware to p145.
- Bug Fixes:
    - Fixed MISRA C-2012 Rule 14.4 issues.
    - Updated TX Power configuration table for uAP.
    - Fixed an issue where in MFG mode measured TX power value for 2.4GHz is 10.97dBm and for 5GHz is 12.03dBm always irrespective of TX-power values configured in CA2.
    - Fixed an issue where in control frames measured TX power is less than configured Tx power by 3dBm for 5Ghz 40Mhz BW and ∼7dBm for 5Ghz 80Mhz BW in CA2.

version 1.3.r29.p2

- New Additions:
    - Updated 8987 SoC firmware to p142.
    - Updated 8978 SoC firmware to p142.
- Bug Fixes:
    - Fixed MISRA C-2012 Directive 4.7, Directive 4.10, Rule 15.7 and Rule 14.4 issues
    - Fixed wlan_get_sta_tx_power() API implementation for retrieving station tx power level.
    - Fixed wlan-set/get-txpwrlimit CLI command for setting/getting TX power limit for 11AC modulation groups in 8987.
    - Fixed an issue where in MFG mode(rf_test_mode=1) after disabling wlan_set_rf_cont_-mode(CMD18_CW=1) command response timeout is seen in 8987.

version 1.3.r29.p1

- New Additions:
    - Added support for 8987 SoC with p141 firmware version.
    - Updated 8978 SoC firmware to p141.
- Bug Fixes:
    - Fixed Misra C-2012 required category issues for Rule 17.7.
    - Fixes for BCA-TDM in Co-Ex for 8978 SoC.
    - Fixed A2DP glitches in BT when WLAN connected for 8978 SoC.

version 1.3.r27.p2

- New Additions:
    - Updated FW versions to p130 for 8978.

version 1.3.r27.p1

- Bug Fixes:
  - Fixed PMF pre-cert issue where STAUT is not associating to PSK-SHA-256 enabled AP.
  - Fixed 11N pre-cert issue where 11N-5.2.47 STAUT AMPDU TX test case is failing.

version 1.3.r26.p2

- New Additions:
  - Updated FW versions to p184 for 8977 and p122 FW for 8978.
  - Added wifi_cert application under wifi_examples.
- Bug Fixes:
  - Fixed an issue where connection problem is seen with uAP in wifi_webconfig after removing stored credentials.
  - Fixed RF Test Mode issue for setting data rate in uAP mode.
  - Fixed Coverity and MISRA issues in WiFi Driver.
  - Fixed WPA3 SAE pre-cert requirement where there was requirement of Auth confirm to be initiated by either STA or Ex-AP.
  - Removed following API's from WiFi driver as they were not supported:
    * wifi_auto_reconnect_enable()
    * wifi_auto_reconnect_disable()
    * wifi_get_auto_reconnect_config()
    * wifi_get_tbtt_offset()
    * wifi_set_packet_filters()
    * wifi_set_auto_arp()
    * wifi_tcp_keep_alive()
    * wifi_nat_keep_alive()

version 1.3.r23.p2

- New Additions:
  - Minor update to wifi_test_mode CLIs for better usability.
  - Added bug fixes in WiFi FW and updated FW versions to p155 for 8801, p182 for 8977 and p106 for 8978.
  - Added new wlan_uap_set_htcapinfo() API for setting HT Capability field for uAP.
- Bug Fixes:
  - Fixed RF Test Mode issues for SD8801 and SD8977 reported by QA.
  - Fixed WiFi 802.11n WPA3 SAE pre-cert test failures for SD8978.
  - Fixed stack overflow issue with WLCMGR thread during wlan-connect.
  - Fixed memory corruption issue cause by scan list overflow when using 11D.

version 1.3.r21.p1

- New Additions:
  - Added support for SD8978.
  - Added Test Mode support for 8801, 8977 and 8978.
  - Added new FW binaries for 8801, 8977 and 8978.
  - Added OTP Force Region support in WiFi Driver.
  - Added support for DHCP Server CLI to print IP addresses of connected clients to uAP.

- – Added support to set HT Capability field for uAP.
- – Added wlan_get_chanlist API and CLI.
- – Added WiFi Driver task priority configurability option.
- – Reduced WiFi Driver SRAM footprint.
- – Added support in Wi-Fi driver to print debug events from WLAN FW.
- – Added support for FW Dump generation using a micro-USB mass storage device.
- Bug Fixes:
    - – Fixed an issue where a redundant Link Loss disconnect timer was defined in the wifi_iperf app.
    - – Fixed an issue where sometimes the wlan_disconnect call did not abort an ongoing re-association.
    - – Fixed an issue where station connection to an Open security Ext-AP fails after connection to a WPA3-SAE Ext-AP.
    - – Fixed an issue where uAP did not start with WPA3-SAE security type.
- Known Issues
    - – Wi-Fi sample apps do not work with Rev-C (2018) version of RT685 board

version 1.3.r20.p1

- New Additions:
    - – Added new FW for 8801.
- Bug Fixes:
    - – Fixed an issue where STAUT went to hang state when doing a disconnect in the wifi_iperf app.
    - – Fixed an issue where STAUT failed to reassociate with an Ext-AP after band switch.
    - – Fixed an issue where Scan command timeout was observed after changing the ssid of Ext-AP to which STAUT is connected.
- Known Issues
    - – Wi-Fi sample apps do not work with Rev-C (2018) version of RT685 board

version 1.3.r19.p1

- New Additions:
    - – Added new FW for 8801.
    - – Updated WiFi API reference manual.
- Bug Fixes:
    - – Fixed an issue where STAUT attempted to connect with Ext-AP continuously even when an Auth Failure occured due to incorect passphrase.
    - – Fixed an issue where SDIO write error occured sometimes for some packet sizes during Tx.
    - – Fixed an issue where packet leakage was noticed on SD8801 when noise was applied.
    - – Fixed an issue to supress Association Failed warning generated during a connection attempt.
- Known Issues
    - – Wi-Fi sample apps do not work with Rev-C (2018) version of RT685 board

version 1.3.r18.p1

- New Additions:
    - – Added new FW for 8977.

- Bug Fixes:
  - Fixed an issue where STAUT fails to scan after Channel Switch and STAUT moves to new channel after eCSA IE.
  - Fixed IAR, MDK build compilation warnings.
- Known Issues
  - Wi-Fi sample apps do not work with Rev-C (2018) version of RT685 board

version 1.3.r17.p1

- New Additions:
  - Added new FW for 8977.
  - Added CLI command to get a list of stations connected to uAP.
- Bug Fixes:
  - Fixed an issue where Scan was temporarily aborted due to noise but correct status was not being returned to the host.
  - Fixed an issue where STAUT failed to connect with an AP with hidden SSID.
  - Fixed IAR, MDK build compilation warnings.
  - Fixed an issue where TCP bi-directional throughput stops abruptly for SD8801 and STAUT is disconnected.
  - Fixed an issue where UDP Dual Mode throughput stops abruptly and disconnection is seen.
  - Fixed an issue where Tx got stuck after removal of interference noise.
- Known Issues
  - Wi-Fi sample apps do not work with Rev-C (2018) version of RT685 board

version 1.3.r16.p1

- New Additions:
  - Added PMF Configuration for uAP.
  - Updated WLAN Versioning.
  - Updated WLAN CLIs.
- Bug Fixes:
  - Fixed an issue where the STAUT sometimes did not send aggregated packets during Tx.
  - Fixed an issue External Client could not associate with the UAP in WPA3-SAE mode.
  - Fixed IAR build compilation warnings.
  - Fixed an issue where the STAUT failed to associate with an AP with hidden SSID.
  - Fixed an issue where active scan probe requests were sent for DFS channels.
  - Fixed an issue where 2.4GHz-HT40 power values were exposed via CLI configuration.
  - Fixed an issue where the STAUT will be continuously in re-association mode after link-loss.
- Known Issues
  - Wi-Fi sample apps do not work with Rev-C (2018) version of RT685 board

version 1.3.r15.p1

- New Additions
  - Added support for Tx Power Limit configuration.
  - Added support for Channel List configuration.
  - Added support for CW MODE.
  - Added support for sysinfo CLI to get threads information, network stats, wlan stats and heap

stats.

- – Added -d and -r options to iperf CLI for dual and trade-off mode.
- – Added support for antenna configuration for 8801.
- – Added support for band configuration.
- – Added new FW for 8977
- Bug Fixes:
    - – Fixed an issue where UDP Rx data rate was low in iperf dual mode operation.
    - – Fixed an issue where STAUT traffic was getting halted when there is traffic in overlapping BSS on the extension channel.
    - – Fixed an issue where STAUT was not able to transmit above MCS 4.
    - – Fixed an issue where association with uAP failed with WPA2 security mode.
    - – Fixed an issue where STAUT failed to connect to WPA3 AP due to PMF config mismatch.
    - – Fixed an issue where ping loss was observed for packets of size greater than 10000 bytes.
    - – Fixed an issue in CLI where CR and LF characters where not handled properly.
    - – Fixed an issue where TCP-Tx traffic abruptly stops when parallel traffic is ongoing on another device using the same AP.
    - – Fixed an issue where DUT goes into hang state when iperf run is aborted.
    - – Fixed an issue where the STATU was not sending aggregated packets to the AP.
    - – Fixed an issue where UAP did not start with WPA2 security mode when ACS is configured.
    - – Fixed an issue where ED MAC was not enabled by default.
- Known Issues
    - – WiFi sample apps do not work with Rev-C (2018) version of RT685 board

version 1.3.r14.p1

- New Additions
    - – Added support for Panasonic PAN9026 module.
    - – Added -t option in iperf CLI for setting traffic running time.
    - – Added -B option for supporting Tx/Rx Multicast packets during iperf runs.
    - – Added World Wide Safe Mode configurability to the WiFi Driver.
    - – Added ED MAC support for 8977.
    - – Added support for PMF APIs and CLIs.
    - – Added new FW for 8977 and 8801.
- Bug Fixes:
    - – Fixed Coverity and mandatory MISRA issues reported on v1.3.r13.p1 release.
    - – Fixed an isuue where DUT console was getting stuck after intiating connection with an AP which has different RSN values than expected.
    - – Fixed an issue where DUT was not able to roam from SAE-PSK to PSK configured AP.
    - – Fixed an issue where the app became unresponsive after Soft AP is stopped.
    - – Removed unnecessary files after Blackduck scan.
- Known Issues
    - – WiFi sample apps do not work with Rev-C (2018) version of RT685 board

version 1.3.r1r3.p1

- New Additions
    - – Updated WiFi Driver to be independednt of the LwIP stack. Only the WLAN Connection

Manager now uses LwIP.
- – Added WiFi Roaming feature.
- – Added CLI support for iperf in wifi_cli app.
- – Added support for CSA handling from wlan station side.
- – Added WLAN APIs for wlan-set-txratecfg, wlan-get-txratecfg, wlan-get-data-rate, wlan-set-reg and wlan-get-reg.
- – Updated External AP SSID required for wifi_iperf app.
- Bug Fixes:
  - – Fixed Coverity issues reported on v1.3.r12.p1 release.
  - – Added a fix for ping loss observed during ping test.
  - – Added a fix where the console became unresponsive after wlan-start-network+wlan-stop-network commands are executed in loop.
  - – Added a fix for HT IE missing from beacon for both 2.4GHz and 5GHZ bands.
  - – Fixed warnings reported for IAR.
  - – Added a fix for increasing DHCP leave time to 24 hrs for long duration stress tests.
- Known Issues
  - – WiFi sample apps do not work with Rev-C (2018) version of RT685 board

version 1.3.r12.p1

- New Additions
  - – Added support for ping utility.
- Bug Fixes
  - – Restart of SoftAP fails once SoftAP is stopped.
  - – HT IE is missing from beacon for both 2.4GHz and 5GHZ bands.
  - – Low TCP-Rx and UDP-Rx throughput observed for 5GHz-HT40 band.
  - – uAP couldn't be started after STA is associated to Ex-AP.
  - – Stopping SoftAP results in disconnection of In-STA from Ex-AP.
  - – DHCP server is not started for BSS created using "wlan-add" command.
- Known Issues
  - – N.A

version 1.3.r11.p2

- New Additions
  - – Updated SDK version for RT1060 to 2.7.1 RFP RC2.
  - – Added FP91 based WiFi FW for SD8801, SD8977, SD8978, and SD8987.
  - – SD8801, SD8977, SD8978 and SD8987 WiFi Fw have embedded WPA3 SAE support from version v1.3.r11.p1 onwards.
  - – Added WLAN CLI support. Added new wifi_cli for CLI demo.
- Enhancements
  - – License and Copyright Updates.
  - – Formated code base with clang-format 10.0.0 standards.
  - – Integrated PICK utility for WiFi Driver code scrubbing.
- Bug Fixes
  - – Removed unnecessary prints LwIP stats display.
  - – Fixed an issue where uAP did not start on 5GHz band.

– Fixed an issue where loww TCP/UDP-Rx throughput was observed for 5GHz-HT40Mhz.
- Known Issues
    - N.A

version 1.3.r10.p1

- New Additions
    - Moved to using LwIP provided IPerf App.
    - Added SDIO Rx Aggregation support to improve throughput.
    - Added support for 11ac configuration API.
    - Updated License and Copyright information on all WiFi driver files and sample apps.
    - Moved MCUXpresso SDK base for RT1060 platform from 2.6.2 to 2.7.0 rc3.
- Known Issues
    - N.A

version 1.3.r9.p1

- New Additions
    - Achieved additional TP improvements by updating LwIP parameters.
- Bug Fixes
    - Fixed the issue of low throughput for both TCP and UDP (Tx/Rx) by updating LwIP parameters.
    - TCP Throughput was observed to be lower than UDP throughput by 70%-80%. Fixed this issue by updating TCP related LwIP configurations.
- Known Issues
    - N.A

EdgeFast Bluetooth Protocol Abstraction Layer Implementation for MCU-Xpresso SDK

The current version is 1.5.0.

- 1.5.0
    - Improvement:
        * Update source files to align Zephyr V3.5 base.
- 1.4.0
    - New features:
        * Add example wifi_cli_over_ble_wu
        * Add following LE audio examples, including,
            · wifi_cli_over_ble_wu
            · broadcast_media_sender and broadcast_media_receiver
            · unicast_media_sender and unicast_media_receiver
            · tmap_central and tmap_peripheral
            · call_gateway and call_terminal
        * Update the shell example to support LE audio features.
- 1.3.1
    - Improvement:

     ∗ Fix MISRA and Coverity issue.

     ∗ Fix building warnings.

     ∗ Fix autopts issues.

     ∗ Improve audio_profile aws part based on new middleware/aws_iot.

    – New features:

     ∗ Support MCUXpresso IDE NPW

     ∗ Support OpenCMSIS Pack

- 1.3.0

    – Improvement:

     ∗ Updated to Zephyr Bluetooth 3.2.0.

     ∗ Fix autopts issues.

     ∗ Improve audio_profile aws part based on new middleware/aws_iot/iot-reference/examples/evkbmim example.

    – New features:

     ∗ Enable EVKMIMXRT1160

     ∗ Default Bluetooth module is changed to Murata

    – Others:

     ∗ Remove WIFI_provisioning example.

- 1.2.1

    – Improvement:

     ∗ Fix autopts issues.

     ∗ Support creating audio streaming without calling in handsfree_ag.

    – New features:

     ∗ Enable EVKMIMXRT1040.

     ∗ Support muRata modules on EVKMIMXRT1040, EVKBIMXRT1050 and EVKBIM-XRT1060.

- 1.2.0

    – Improvement:

     ∗ Updated to Zephyr Bluetooth 3.0.0

     ∗ Fix autopts issues.

    – New features:

     ∗ Enable EVKBIMXRT1050

     ∗ Enable peripheral_beacon on all boards.

- 1.1.1

    – New features:

     ∗ Enable peripheral_beacon example in EVKMIMXRT1170 board.

- 1.1.0

    – Improvement:

     ∗ Updated to Zephyr Bluetooth 2.6.0

     ∗ change fixed wireless_uart central and peripheral role number to flexiable number.

- 1.0.0

    – New features:

     ∗ Enable SMP Pairing and Bonding feature for BLE

     ∗ Enable AVRCP

     ∗ Enable L2CAP for BR

* Add examples wireless_uart and edgefast_bluetooth_shell
* Enable data signing, GATT caching, GATT service changed features
* Enable data len update, whitelist, phy update
* Enable privacy mode
* Enable setting for bonding
* Enable A2DP content protection/recovery/reporting/delay reporting/header compression/multiplexi
  services.

– Improvement:
* Enhance SPP to support multiple connection
* Use LittleFS to manage the NVM.
* Improve A2DP APIs and implementation.
    · Add endpoint callbacks to struct bt_a2dp_endpoint.
    · Add content protection/recovery/reporting/delay reporting/header compression/multiplexing related fields to struct bt_a2dp_endpoint and struct bt_a2dp_control_cb.
    · Upgrade struct a2dp_configure_result to struct bt_a2dp_endpoint_configure_result.
    · Add deconfigured callback.
    · Change sink_start_play callback to start_play callback.
    · Change sink_suspend_play callback to stop_play callback.
    · Add bt_a2dp_disconnect API.
    · Remove bt_a2dp_register_control_callback API.
    · Change bt_a2dp_configure API's callback.
    · Add peer_endpoint to bt_a2dp_configure_endpoint API.
    · Change bt_a2dp_src_start to bt_a2dp_start.
    · Change bt_a2dp_src_suspend to bt_a2dp_stop.
    · Remove bt_a2dp_get_configured_peer_endpoint.
    · Change the parameter as endpoint for the APIs: bt_a2dp_deconfigure, bt_a2dp_start, bt_a2dp_stop, bt_a2dp_reconfigure, bt_a2dp_src_media_write and bt_a2dp_snk_media_sync.
    · Add new APIs for content protection/delay reporting services: bt_a2dp_set_cp_header, bt_a2dp_set_initial_delay_report and bt_a2dp_send_delay_report.

• 0.1.0
– New features:
* Initialization version

3 Component Change Log

CODEC

The current codec common driver version is 2.3.1.

- 2.3.1
    - **Bug Fixes**
        - ∗ Fixed violations of MISRA C-2012 rule 16.1,16.3.
- 2.3.0
    - **Improvements**
        - ∗ Added enum _codec_volume_capability for CODEC_SetVolume/CODEC_SetMute to cover more volume configurations.
- 2.2.2
    - **Bug Fixes**
        - ∗ Fixed the typo in codec common driver.
- 2.2.1
    - **Bug Fixes**
        - ∗ Fixed violations of MISRA C-2012 rule 10.3, 8.3, 10.7, 17.7.
- 2.2.0
    - **Improvements**
        - ∗ Used HAL_CODEC_HANDLER_SIZE which is determined by low level driver instead of use CODEC_HANDLE_SIZE for the codec device handle definition.
- 2.1.1
    - **Improvements**
        - ∗ Supported all of the codec in the codec adapter.
        - ∗ Modified the codec handle definition to improve user experience.
        - ∗ Modified the capability member type from entity to pointer in codec handle.
    - **Bug Fixes**
        - ∗ Fixed the Coverity issue regrading array compared agaist 0.
- 2.1.0
    - **Deprecated APIs**
        - ∗ CODEC_GetMappedFormatBits
        - ∗ CODEC_I2C_WriteReg
        - ∗ CODEC_I2C_ReadReg
        - ∗ CODEC_I2C_ModifyReg
        - ∗ CODEC_SetEncoding
    - **new APIs**
        - ∗ CODEC_SetPower
        - ∗ CODEC_SetVolume
        - ∗ CODEC_SetMute
        - ∗ CODEC_SetPlay
        - ∗ CODEC_SetRecord
        - ∗ CODEC_SetRecordChannel

  * CODEC_ModuleControl
 – new features
  * Removed duplicate members in codec_handle_t and codec_config_t.
  * Added codec_config_t pointer in codec_handle_t.
  * Added codec capability flag in codec_handle_t.
  * Used codec adapter instead of function opinter in codec common driver.
 • 2.0.1
 – Added delayMs function pointer in codec handle.
 • 2.0.0
 – Initial version.

WM8904

The current wm8904 driver version is 2.5.1.

 • 2.5.1
 – Bug Fixes
  * Fixed invalid clock divider issue generated form WM8904_SetMasterClock api
  * Replace '__REV16' with general implementation to swap bytes in a short variable.
 • 2.5.0
 – Improvements
  * Added master clock configuration support in function WM8904_SetAudioFormat.
  * Align the sysclk paramter definition for the WM8904_SetAudioFormat/WM8904_Set-MasterClock.
  * Added api WM8904_SetDACVolume to support adjust DAC volume.
  * Fixed the MISRA-2012 violation of 12.2, 10.3.
 • 2.4.4
 – Bug Fixes
  * Added the 11.025kHz/22.05kHz/44.1kHz samplerate support on codec WM8904.
  * Fixed the MISRA-2012 violation of 4.7.
 • 2.4.3
 – Bug Fixes
  * Fixed the MISRA-2012 violations.
   · Fixed rule 8.6, 9.3, 10.1, 10.3, 10.4, 10.7, 10.8, 11.8, 11.9, 14.4, 16.1, 16.3, 16.4, 17.7, 20.9.
 • 2.4.2
 – Bug Fixes
  * Corrected the volume setting function behavior in wm8904 driver, support range align with its specification range.
  * Corrected the volume setting function behavior in wm8904 adapter, support range 0 - 100, 0 for mute, 100 for maximum volume.
 • 2.4.1
 – Bug Fixes
  * Fixed the bit width reigster field overwritten issue.

- 2.4.0
  - New features
    - ∗ Added fll support in wm8904 driver.
- 2.3.0
  - Improvements
    - ∗ Added new API WM8904_SetMasterClock to support BCLK/LRCLK output mode.
- 2.1.0
  - new APIs
    - ∗ WM8904_ReadRegister
    - ∗ WM8904_WriteRegister
    - ∗ WM8904_ModifyRegister
    - ∗ WM8904_SetRecord
    - ∗ WM8904_SetPlay
    - ∗ WM8904_SetRecordChannel
    - ∗ WM8904_SetModulePower
    - ∗ WM8904_SetChannelVolume
    - ∗ WM8904_SetChannelMute
  - New features
    - ∗ Removed dependency on codec common driver.
    - ∗ Added dependency on codec i2c.
  - Bug Fixes
    - ∗ Fixed unchecked return value in WM8904_Deinit.
    - ∗ Fixed the alignment fault issue by adding __NOP between continuous memory access.
- 2.0.3
  - Bug Fixes
    - ∗ Fixed issue that wm8904 register access function truncated return value.
- 2.0.2
  - Bug Fixes
    - ∗ Fixed using uninitialized value format.fsRatio when calling WM8904_UpdateFormate.
- 2.0.1
  - Added WM8904_CheckAudioFormat API.
  - Changed the second parameter's name of WM8904_SetAudioFormat to sysclk.
- 2.0.0
  - Initial version.

CS42888

The current cs42888 driver version is 2.1.3

- 2.1.3
  - Improvements
    - ∗ Removed the assertion for codec reset function pointer.
- 2.1.2
  - Improvements

∗ Corrected the volume setting function behavior in CS42888 adapter, support range 0 - 100, 0 for mute, 100 for maximum volume.
 – Bug Fixes
 ∗ Fixed violations of MISRA C-2012 rule 4.7, 10.3, 8.3, 10.7, 17.7.
 ∗ Corrected the channel index during setting AIN volume in CS42888_Init.
- 2.1.1
 – Improvements
 ∗ Used software delay with delayMs pointer not provided by application.
 ∗ Fixed error status overwrite issue in CS42888_Init function.
 ∗ Removed dependency on codec common driver.
 ∗ Added API CS42888_SelectFunctionalMode/CS42888_SetChannelMute.
 ∗ Added dependency on codec i2c.
- 2.1.0
 – Improvements
 ∗ Unified CS42888 codec driver interface.
 – Bug Fixes
 ∗ Corrected the ADC/DAC functional mode macro definitaion.
 ∗ Added TDM and OLM mode support in the function CS42888_SetProtocol.
- 2.0.0
 – Initial version.

SERIAL_MANAGER

The current Serial_Manager component version is 1.0.2.

- 1.0.2
 – Add SerialManager_WriteTimeDelay()/SerialManager_ReadTimeDelay() for serial manager's read/write non-blocking mode.
- 1.0.1
 – Add prefixing fsl_component_xxx/fsl_adapter_xxx.
- 1.0.0
 – Initial version