




MP3 Decoder **Programmer's Guide**

For HiFi DSPs and Fusion F1 DSP



Cadence Design Systems, Inc.
2655 Seely Ave.
San Jose, CA 95134
www.cadence.com

© 2023 Cadence Design Systems, Inc. All rights reserved.
Printed in the United States of America.

Cadence Design Systems, Inc. (Cadence), 2655 Seely Ave., San Jose, CA 95134, USA.

Trademarks: Trademarks and service marks of Cadence Design Systems, Inc. (Cadence) contained in this document are attributed to Cadence with the appropriate symbol. For queries regarding Cadence's trademarks, contact the corporate legal department at the address shown above or call 1-800-862-4522.

All other trademarks are the property of their respective holders.

Restricted Print Permission: This publication is protected by copyright and any unauthorized use of this publication may violate copyright, trademark, and other laws. Except as specified in this permission statement, this publication may not be copied, reproduced, modified, published, uploaded, posted, transmitted, or distributed in any way, without prior written permission from Cadence. This statement grants you permission to print one (1) hard copy of this publication subject to the following conditions:

1. The publication may be used solely for personal, informational, and noncommercial purposes;
2. The publication may not be modified in any way;
3. Any copy of the publication or portion thereof must include all original copyright, trademark, and other proprietary notices and this permission statement; and
4. Cadence reserves the right to revoke this authorization at any time, and any such use shall be discontinued immediately upon written notice from Cadence.

Disclaimer: Information in this publication is subject to change without notice and does not represent a commitment on the part of Cadence. The information contained herein is the proprietary and confidential information of Cadence or its licensors, and is supplied subject to, and may be used only by Cadence's customer in accordance with, a written agreement between Cadence and its customer. Except as may be explicitly set forth in such agreement, Cadence does not make, and expressly disclaims, any representations or warranties as to the completeness, accuracy or usefulness of the information contained in this document. Cadence does not warrant that use of such information will not infringe any third party rights, nor does Cadence assume any liability for damages or costs of any kind that may result from use of such information.

Restricted Rights: Use, duplication, or disclosure by the Government is subject to restrictions as set forth in FAR52.227-14 and DFAR252.227-7013 et seq. or its successor..

Version: 3.14

Last Updated: March 2023

Cadence Design Systems, Inc.
2655 Seely Ave.
San Jose, CA 95134 www.cadence.com
..

Contents

Contents	1
Figures	3
Tables	3
Document Change History	5
1. Introduction to the HiFi MP3 Decoder	6
1.1 MP3 Description	6
1.2 Document Overview	6
1.3 HiFi MP3 Decoder Specifications	7
1.4 HiFi MP3 Decoder Performance	8
1.4.1 MP2 Decoder Memory	8
1.4.2 MP2 Decoder Timings	8
1.4.3 MP3 Decoder Memory	9
1.4.4 MP3 Decoder Timings	9
1.4.5 MP3 5.1-Channel Decoder Memory	9
1.4.6 MP3 5.1-Channel Decoder Timings	9
2. Generic HiFi Audio Codec API	11
2.1 Memory Management	11
2.2 C Language API	12
2.3 Generic API Errors	14
2.4 Commands	15
2.4.1 Start-up API Stage	16
2.4.2 Set Codec-Specific Parameters Stage	16
2.4.3 Memory Allocation Stage	17
2.4.4 Initialize Codec Stage	18
2.4.5 Get Codec-Specific Parameters Stage	19
2.4.6 Execute Codec Stage	19
2.5 Files Describing the API	20
2.6 HiFi API Command Reference	20
2.6.1 Common API Errors	21
2.6.2 XA_API_CMD_GET_LIB_ID_STRINGS	22
2.6.3 XA_API_CMD_GET_API_SIZE	25
2.6.4 XA_API_CMD_INIT	26
2.6.5 XA_API_CMD_GET_MEMTABS_SIZE	30
2.6.6 XA_API_CMD_SET_MEMTABS_PTR	31
2.6.7 XA_API_CMD_GET_N_MEMTABS	32
2.6.8 XA_API_CMD_GET_MEM_INFO_SIZE	33

2.6.9	XA_API_CMD_GET_MEM_INFO_ALIGNMENT	34
2.6.10	XA_API_CMD_GET_MEM_INFO_TYPE	35
2.6.11	XA_API_CMD_GET_MEM_INFO_PRIORITY	37
2.6.12	XA_API_CMD_SET_MEM_PTR	39
2.6.13	XA_API_CMD_INPUT_OVER	40
2.6.14	XA_API_CMD_SET_INPUT_BYTES	41
2.6.15	XA_API_CMD_GET_CURIDX_INPUT_BUF	42
2.6.16	XA_API_CMD_EXECUTE	43
2.6.17	XA_API_CMD_GET_OUTPUT_BYTES	46
2.6.18	XA_API_CMD_GET_CONFIG_PARAM	47
2.6.19	XA_API_CMD_SET_CONFIG_PARAM	49
3.	HiFi DSP MP3 Decoder	50
3.1	Files Specific to the MP3 Decoder	51
3.2	Configuration Parameters	51
3.3	Usage Notes	53
3.4	MP3 Decoder-Specific Commands	54
3.4.1	Initialization and Execution Errors	54
3.4.2	XA_API_CMD_SET_CONFIG_PARAM	56
3.4.3	XA_API_CMD_GET_CONFIG_PARAM	62
4.	Introduction to the Example Test Bench	78
4.1	Making the Executable	78
4.2	Usage	79
4.3	ID3 Decoding Example	81
5.	Reference	83

Figures

Figure 1: HiFi Audio Codec Interfaces	11
Figure 2 API Command Sequence Overview	15
Figure 3 Flow Chart for MP3 Decoder Integration	50

Tables

Table 2-1: Codec API	13
Table 2-2 Commands for Initialization	16
Table 2-3 Commands for Setting Parameters	16
Table 2-4 Commands for Initial Table Allocation	17
Table 2-5 Commands for Memory Allocation Command / Subcommand	17
Table 2-6 Commands for Initialization	18
Table 2-7 Commands for Getting Parameters	19
Table 2-8 Commands for Codec Execution	19
Table 2-9 XA_CMD_TYPE_LIB_NAME subcommand	22
Table 2-10 XA_CMD_TYPE_LIB_VERSION subcommand	23
Table 2-11 XA_CMD_TYPE_API_VERSION subcommand	24
Table 2-14 XA_CMD_TYPE_INIT_API_POST_CONFIG_PARAMS subcommand	27
Table 2-15 XA_CMD_TYPE_INIT_PROCESS subcommand	28
Table 2-16 XA_CMD_TYPE_INIT_DONE_QUERY subcommand	29
Table 2-17 XA_API_CMD_GET_MEMTABS_SIZE command	30
Table 2-19 XA_API_CMD_GET_N_MEMTABS command	32
Table 2-20 XA_API_CMD_GET_MEM_INFO_SIZE command	33
Table 2-21 XA_API_CMD_GET_MEM_INFO_ALIGNMENT command	34
Table 2-22 XA_API_CMD_GET_MEM_INFO_TYPE command	35
Table 2-23 Memory Type Indices	36
Table 2-24 XA_API_CMD_GET_MEM_INFO_PRIORITY command	37
Table 2-25 Memory Priorities	38
Table 2-26 XA_API_CMD_SET_MEM_PTR command	39
Table 2-27 XA_API_CMD_INPUT_OVER command	40
Table 2-28 XA_API_CMD_SET_INPUT_BYTES command	41
Table 2-29 XA_API_CMD_GET_CURIDX_INPUT_BUF command	42
Table 2-30 XA_CMD_TYPE_DO_EXECUTE subcommand	43
Table 2-31 XA_CMD_TYPE_DONE_QUERY subcommand	43

Table 2-32 XA_CMD_TYPE_DO_RUNTIME_INIT subcommand	45
Table 2-33 XA_API_CMD_GET_OUTPUT_BYTES command	46
Table 2-34 XA_CONFIG_PARAM_CUR_INPUT_STREAM_POS subcommand	47
Table 2-35 XA_CONFIG_PARAM_GEN_INPUT_STREAM_POS subcommand	48
Table 2-36 XA_CONFIG_PARAM_CUR_INPUT_STREAM_POS subcommand	49
Table 3-1 XA_MP3DEC_CONFIG_PARAM_PCM_WDSZ subcommand	56
Table 3-2 XA_MP3DEC_CONFIG_PARAM_CRC_CHECK subcommand	57
Table 3-3 XA_MP3DEC_CONFIG_PARAM_MCH_ENABLE subcommand	58
Table 3-4 XA_MP3DEC_CONFIG_PARAM_DAB_MP2 subcommand	59
Table 3-5 XA_MP3DEC_CONFIG_PARAM_ACTIVATE_VLC_REWIND subcommand	60
Table 3-6 XA_MP3DEC_CONFIG_PARAM_NONSTD_STRM_SUPPORT subcommand	61
Table 3-7 XA_MP3DEC_CONFIG_PARAM_SAMP_FREQ subcommand	62
Table 3-8 XA_MP3DEC_CONFIG_PARAM_NUM_CHANNELS subcommand	63
Table 3-9 XA_MP3DEC_CONFIG_PARAM_CHMODE_INFO subcommand	64
Table 3-10 XA_MP3DEC_CONFIG_PARAM_BITRATE subcommand	65
Table 3-11 XA_MP3DEC_CONFIG_PARAM_PCM_WDSZ subcommand	66
Table 3-12 XA_MP3DEC_CONFIG_PARAM_MCH_STATUS subcommand	67
Table 3-13 XA_MP3DEC_CONFIG_PARAM_EXTN_PRESENT subcommand	68
Table 3-14 XA_MP3DEC_CONFIG_PARAM_LFE_PRESENT subcommand	69
Table 3-15 XA_MP3DEC_CONFIG_PARAM_NUM_XCHANS subcommand	70
Table 3-16 XA_MP3DEC_CONFIG_PARAM_CHAN_CONFIG subcommand	71
Table 3-17 XA_MP3DEC_CONFIG_PARAM_CHAN_MAP subcommand	72
Table 3-18 XA_MP3DEC_CONFIG_PARAM_DAB_MP2 subcommand	73
Table 3-19 XA_MP3DEC_CONFIG_PARAM_ORIGINAL_OR_COPY subcommand	74
Table 3-20 XA_MP3DEC_CONFIG_PARAM_COPYRIGHT_FLAG subcommand	75
Table 3-21 XA_MP3DEC_CONFIG_PARAM_MCH_EXT_HDR_INFO subcommand	76
Table 3-22 XA_MP3DEC_CONFIG_PARAM_MCH_COPYRIGHT_ID_PTR subcommand	77

Document Change History

Version	Changes
3.7	History section added. Added memory and timing performance data for HiFi Mini and HiFi 3.
3.8	Updated memory and timing data.
3.9	Added memory and timing data for HiFi 4.
3.10	Added performance data for HiFi 3z in Section 1.4.
3.11	Added performance data for Fusion F1 in Section 1.4.
3.12	Added performance data for HiFi 5 in Section 1.4.
3.13	Added performance and memory data for HiFi 1 in Section 1.4 . Updates in Section 3.4.
3.14	Added performance and memory data in Section 1.4

1. Introduction to the HiFi MP3 Decoder

The HiFi MP3 Decoder implements the features for audio codec, which are specified by MPEG-1, MPEG-2 and MPEG-2.5 standards. MPEG-1 and MPEG-2 standards are originated from the Moving Picture Experts Group (MPEG), (a working group of ISO/IEC ^{[1][2]}). MPEG-2.5 is a proprietary extension to MPEG-1/2 Layer III by the Fraunhofer Institute for Integrated Circuits (FhG IIS), Germany.

The HiFi MP3 Decoder is a general term for three different levels of MPEG-1/2/2.5 audio technology supplied by Cadence Tensilica, as separate libraries:

- The MP2 Decoder library (mp2_dec) implements MPEG-1/2 Layers I and II 2-channel decoding.
- The MP3 Decoder library (mp3_dec) implements MPEG-1/2/2.5 Layers I, II and III 2-channel decoding.
The MP3 5.1-Channel Decoder library (mp3mch_dec) implements MPEG-1/2/2.5 Layers I, II and III 2-channel decoding as well as MPEG-2 Layer II 5.1-channel decoding.

For this document, HiFi DSPs include Fusion F1 DSP.

1.1 MP3 Description

Quote from the Moving Picture Experts Group:

"MPEG-1 Audio Layer III, also known as MP3, has been implemented in manifold ways. Many software packages exist to rip a track from a CD Audio and compress it in MP3. This has given rise to innovative ways of consuming music, such as the ability to create compilations to one's liking that can then downloaded to light non-mechanical MP3 players. With the arrival of MP3, the music world has been changed without recognition."

MP3 was further extended to MPEG-2 to support sampling rates and encoded bit rates. The first of the MP3 players arrived in 1998. This success was due to the compression achieved with respect to the CD format.

The target of 1.33 bits per sample results in a bitstream of 128kbts/s for stereo 48 kHz audio. This is a compression of 11.7 times over the uncompressed PCM Audio.

The codec handles audio signals sampled in the range of 8 kHz to 48 kHz. It operates on a frame of 1152 samples (Layers II and III) or 384 samples (Layer I).

1.2 Document Overview

This document covers all the information required to integrate the HiFi Audio Codecs into an application. The HiFi codec libraries implements a simple API to encapsulate the complexities of the coding operations and simplifies the application and system implementation. The parts of the API are common to all the HiFi

codecs; these are described in Section 2. Section 3 covers all the features and information particular to the HiFi MP3 Decoder. The example test benches are described in Section 4.

1.3 HiFi MP3 Decoder Specifications

The HiFi DSP MP3 Decoder from Cadence Tensilica is a full-precision MP3 decoder that supports MPEG-1 and MPEG-2 Layer I, II, and III and MPEG-2.5 Layer III audio streams. It implements the following features in conformance to the MPEG-1, MPEG-2, and MPEG 2.5 specifications. Cadence Audio Codec API is used in all three libraries.

MPEG-1

- Compliant with ISO/IEC 11172-3
 - MPEG-1 Layers I and II decoding
 - MPEG-1 Layer III decoding (`mp3_dec` and `mp3mch_dec` only)
- Sample rates: 32, 44.1 and 48 kHz
- Bit rates 32-320 Kbps for Layer III
- Bit rates 32-384 Kbps for Layer II
- Bit rates 32-448 Kbps for Layer I
- Supports free format bit-rate decoding for Layer III
- Mono and stereo channels
- Joint stereo (MS and Intensity Stereo)
- Support for VBR
- CRC check support for Layers I and II
- Full precision decoder

MPEG-2

Features in addition to MPEG-1:

- Compliant with ISO/IEC 13818-3
 - Main audio channels (Lo/Ro) decoding of MPEG-2 Layers I and II
 - Main audio channels (Lo/Ro) decoding of MPEG-2 Layer III (`mp3_dec` and `mp3mch_dec` only)
 - 5.1-channel decoding of MPEG-2 Layer II (`mp3mch_dec` only)
- Additional sample rates: 16, 22.05 and 24 kHz
- Additional bit rates 8 -160 Kbps for Layer III applicable to lower sample rates

- Additional bit rates 8 -160 Kbps for Layer II applicable to lower sample rates
- Additional bit rates 32-256 Kbps for Layer I applicable to lower sample rates
- Bit rates up to 1067 Kbps for Layer II 5.1-Channel decoding
- Support for VBR

MPEG-2.5

Features in addition to MPEG-2:

- Decoding of MPEG-2.5 Layer III (`mp3_dec` and `mp3mch_dec` only)
- Sample rates: 8, 11.025 and 12 kHz
- Bit rates 8-160 kbps for Layer III
- Support for VBR

Note: Other than these standard features, Cadence Tensilica MP3 decoder may support other common sampling rate and bit-rate combinations as well, under each layer. Those are not the part of conformance test.

1.4 HiFi MP3 Decoder Performance

The HiFi DSP MP3 Decoder from Cadence was characterized on the 5-stage HiFi DSP core. The memory usage and performance figures are provided for design reference.

1.4.1 MP2 Decoder Memory

For memory specifications of MP2 Decoder, refer the tables below:

Text (Kbytes)						Data (Kbytes)
Fusion F1	HiFi 1	HiFi 3	HiFi 3z	HiFi 4	HiFi 5	
12.3	12.2	11.8	11.9	12.3	14.8	4.0

Run Time Memory (Kbytes)				
Persistent	Scratch	Stack	Input	Output
7.3	1.9	0.4	2.0	4.5

1.4.2 MP2 Decoder Timings

For timing specifications of MP2 Decoder, refer the table below:

Rate kHz	Channels	Bit Rate kbps	Average CPU Load (MHz)					
			Fusion F1	HiFi 1	HiFi 3	HiFi 3z	HiFi 4	HiFi 5
48	2	192	4.0	3.5	3.5	3.1	2.8	2.7

1.4.3 MP3 Decoder Memory

For memory specifications of MP3 Decoder, refer the tables below:

Text (Kbytes)						Data (Kbytes)
Fusion F1	HiFi 1	HiFi 3	HiFi 3z	HiFi 4	HiFi 5	
24.5	24.1	23.8	24.3	25.9	32.3	14.9

Run Time Memory (Kbytes)				
Persistent	Scratch	Stack	Input	Output
12.4	7.0	0.8	2.0	4.5

1.4.4 MP3 Decoder Timings

For timing specifications of MP3 Decoder, refer the table below:

Rate kHz	Channels	Bit Rate kbps	Average CPU Load (MHz)					
			Fusion F1	HiFi 1	HiFi 3	HiFi 3z	HiFi 4	HiFi 5
44.1	2	128	4.2	3.7	3.4	3.1	2.8	2.5
44.1	2	320	5.1	4.5	4.2	3.9	3.5	3.1
48	2	128	4.4	3.9	3.5	3.3	2.9	2.6
48	2	320	5.6	4.9	4.5	4.2	3.8	3.4

1.4.5 MP3 5.1-Channel Decoder Memory

For memory specifications of MP3 5.1-Channel Decoder, refer the tables below:

Text (Kbytes)						Data (Kbytes)
Fusion F1	HiFi 1	HiFi 3	HiFi 3z	HiFi 4	HiFi 5	
40.8	40.6	39.1	41.3	43.0	55.1	15.7

Run Time Memory (Kbytes)				
Persistent	Scratch	Stack	Input	Output
21.6	36.5	1.2	4.0	27

1.4.6 MP3 5.1-Channel Decoder Timings

For timing specifications of MP3 5.1-Channel Decoder, refer the table below:

Rate kHz	Channels	Bit Rate kbps	Average CPU Load (MHz)					
			Fusion F1	HiFi 1	HiFi 3	HiFi 3z	HiFi 4	HiFi 5
48	6	1.66	19.5	18.2	20.2	16.4	15.7	15.4

Note	Performance specification measurements are carried on a cycle-accurate simulator assuming an ideal memory system, <i>i.e.</i> , one with zero memory wait states. This is equivalent to running with all code and data in local memories or using an infinite-size, pre-warmed cache model.
Note	The MCPS numbers for HiFi 3z/ HiFi 4/ Fusion F1 are obtained by running the test with binary that is recompiled from the HiFi 3 optimized source code in the HiFi 3z/ HiFi 4/ Fusion F1 configuration. No specific optimization is done for HiFi 3z/ HiFi 4/ Fusion F1.
Note	The MCPS numbers for HiFi 5 are obtained by running the test with binary that is recompiled from the HiFi 1 optimized source code in HiFi 5 configuration. No specific optimization is done for HiFi 5.
Note	The output of the HiFi 3/ HiFi 3z/ HiFi 4/ Fusion F1 code is not bit-exact with that of the HiFi 1/ HiFi 5 optimized code.
Note	Output buffer requirements are specified for 16-bit output, which is typically used. For 24-bit output, the output buffer size is doubled.
Note	All the memory and MCPS numbers are captured with XT-CLANG compiler and RI-2022.10 tools.

2. Generic HiFi Audio Codec API

This section describes the API which is common to all the HiFi audio codec libraries. The API facilitates any codec that works in the overall method shown in the following diagram.




Figure 1: HiFi Audio Codec Interfaces

[Memory Management](#) on page 6 discusses all the types of run time memory required by the codecs. There is no state information held in static memory, therefore a single thread can perform time division processing of multiple codecs. Additionally, multiple threads can perform concurrent codec processing. The API is implemented, so that the application does not need to consider the codec implementation.

Through the API, the codec requests the minimum sizes required for the input and output buffers. Prior to executing the codec execution command, the codec requires that the input buffer be filled with data up to the minimum size for the input buffer. However, the codec may not consume all of the data in the input buffer. Therefore, the application must check the amount of input data consumed, copy downwards any unused portion of the input buffer, and then continue to fill the rest of the buffer with new data, until the input buffer is again filled to the minimum size. The codec produces data in the output buffer. The output data must be removed from the output buffer, after the codec operation.

Applications that use these libraries should not make any assumptions about the size of the PCM “chunks” of data that each call to a codec produces or consumes. Although normally the “chunks” are the exact size of the underlying frame of the specified codec algorithm, they will vary between codecs and also between different operating modes of the same codec. The application should provide enough data to fill the input buffer. However, some codecs do provide information, after the initialization stage, to adjust the number of bytes of PCM data they need.

2.1 Memory Management

The HiFi audio codec API supports a flexible memory scheme and a simple interface that eases the integration into the final application. The API allows the codecs to request the required memory for their operations during run time.

The run time memory requirement consists primarily of the scratch and persistent memory. The codecs also require an input buffer and output buffer for the passing of data into and out of the codec.

API Object

The codec API stores its data in a small structure that is passed via a handle that is a pointer to an opaque object from the application for each API call. All state information and the memory tables that the codec requires are referenced from this structure.

API Memory Table

During the memory allocation the application is prompted to allocate memory for each of the following memory areas. The reference pointer to each memory area is stored in this memory table. The reference to the table is stored in the API object.

Persistent Memory

This is also known as static or context memory. This is the state or history information that is maintained from one codec invocation to the next within the same thread or instance. The codecs expect that the contents of the persistent memory be unchanged by the system apart from the codec library itself for the complete lifetime of the codec operation.

Scratch Memory

This is the temporary buffer used by the codec for processing. The contents of this memory region should be unchanged, if the actual codec execution process is active, that is, if the thread running the codec is inside any API call. This region can be used freely by the system between successive calls to the codec.

Input Buffer

The input buffer is used by the algorithm for accepting input data. Before the call to the codec, the input buffer needs to be completely filled with input data.

From API Version 1.16 or later, the input buffer can be partially filled before the call to the codec. The codec returns a non-fatal error indicating insufficient data if data in the input buffer is not enough to decode PCM samples.

Output Buffer

This is the buffer in which the algorithm writes the output. This buffer must be made available for the codec before its execution call. The output buffer pointer can be changed by the application between calls to the codec. This allows the codec to write directly to the required output area. The codec will never write more data than the requested size of the output buffer.

2.2 C Language API

A single interface function is used to access the codec, with the operation specified by command codes. The actual API C call is defined per codec library, and is specified in the codec-specific section. Each library has a single C API call. The C parameter definitions for every codec library are the same and are specified in [Table 2-1: Codec API](#) on page 7.

Table 2-1: Codec API

xa_<codec>	
Description	This C API is the only access function to the audio codec.
Syntax	<pre>XA_ERRORCODE xa_<codec>(xa_codec_handle_t p_xa_module_obj, WORD32 i_cmd, WORD32 i_idx, pVOID pv_value);</pre>
Parameters	<p>p_xa_module_obj Pointer to opaque API structure.</p> <p>i_cmd Command.</p> <p>i_idx Command subtype or index.</p> <p>pv_value Pointer to the variable used to pass in, or get out properties, from state structure.</p>
Returns	Error Code based on the success or failure of API command.

The types used for the C API call are defined in the supplied header files as:

```
typedef signed int      WORD32;
typedef void            *pVOID;
```

Each time the 'C' API for the codec is called, a pointer to a private allocated data structure is passed as the first argument. This argument is treated as an opaque handle as there is no requirement by the application to look at the data within the structure. The size of the structure is supplied by a specific API command so that the application can allocate the required memory. Do not use `sizeof()` on the type of the opaque handle.

Some command codes are further divided into subcommands. The command and its subcommand are passed to the codec via the second and third arguments respectively.

When a value must be passed to a particular API command or an API command returns a value, the value expected or returned is passed through a pointer which is given as the fourth argument to the C API function. In the case of passing a pointer value to the codec the pointer is just cast to `pVOID`. It is incorrect to pass a pointer to a pointer in these cases. An example would be when the application is passing the codec a pointer to an allocated memory region.

Due to the similarities of the operations required to decode or encode audio streams, the HiFi DSP API allows the application to use a common set of procedures for each stage. By maintaining a pointer to the

single API function, and passing the correct API object, the same code base can be used to implement the operations required for any of the supported codecs.

2.3 Generic API Errors

The error code returned is of type `XA_ERRORCODE`, which is of type `signed int`. The format of the error codes are defined in the following table.

31	30-15	14 - 11	10 - 6	5 - 0
Fatal	Reserved	Class	Codec	Sub code

The errors that can be returned from the API are sub divided into those that are “fatal”, which require the restarting of the entire codec, and those that are “nonfatal” and are provided for information to the application.

The class of an error can be API, Config, or Execution. The API errors are concerned with the incorrect use of the API. The Config errors are produced when the codec parameters are incorrect, or outside the supported usage. The Execution errors are returned after a call to the main encoding or decoding process and indicate situations that have arisen due to the input data.

2.4 Commands

This section covers the commands associated with the command sequence overview flow chart below. For each stage of the flow chart, there is a section that lists the required commands in the order they should occur. For individual commands definitions and examples, refer to [HiFi API Command Reference](#) on page 15. The codecs have a common set of generic API commands that are represented by the white stages. The yellow stages are specific to each codec.




Figure 2 API Command Sequence Overview

2.4.1 Start-up API Stage

The following commands should be executed once each during start-up. The commands to get the various identification strings from the codec library are for information only and are optional. The command to get the API object size is mandatory as the real object type is hidden in the library, and therefore there is no type available to use with `sizeof()`.

Table 2-2 Commands for Initialization

Command / Subcommand	Description
XA_API_CMD_GET_LIB_ID_STRINGS XA_CMD_TYPE_LIB_NAME	Get the name of the library.
XA_API_CMD_GET_LIB_ID_STRINGS XA_CMD_TYPE_LIB_VERSION	Get the version of the library.
XA_API_CMD_GET_LIB_ID_STRINGS XA_CMD_TYPE_API_VERSION	Get the version of the API.
XA_API_CMD_GET_API_SIZE	Get the size of the API structure.
XA_API_CMD_INIT XA_CMD_TYPE_INIT_API_PRE_CONFIG_PARAMS	Set the default values of all the configuration parameters.

2.4.2 Set Codec-Specific Parameters Stage

Refer to the specific codec section for the parameters that can be set. These parameters either control the encoding process or determine the output format of the decoder PCM data.

Table 2-3 Commands for Setting Parameters

Command / Subcommand	Description
XA_API_CMD_SET_CONFIG_PARAM XA_<codec>_CONFIG_PARAM_<param_name>	Set codec-specific parameter. See the codec-specific section for parameter definitions.

2.4.3 Memory Allocation Stage

The following commands should be executed once only after all the codec-specific parameters have been set. The API passes the pointer to the memory table structure (MEMTABS) after it is allocated by the application to the size specified. Once the codec specific parameters are set, the initial codec setup is completed by performing the post-configuration portion of the initialization to determine the initial operating mode of the codec, and assign sizes to the blocks of memory required for its operation. The application then requests a count of the number of memory blocks.

Table 2-4 Commands for Initial Table Allocation

Command / Subcommand	Description
XA_API_CMD_GET_MEMTABS_SIZE	Get the size of the memory structures to be allocated for the codec tables.
XA_API_CMD_SET_MEMTABS_PTR	Pass the memory structure pointer allocated for the tables.
XA_API_CMD_INIT XA_CMD_TYPE_INIT_API_POST_CONFIG_PARAMS	Calculate the required sizes for all the memory blocks based on the codec-specific parameters.
XA_API_CMD_GET_N_MEMTABS	Obtain the number of memory blocks required by codec.

The following commands should then be executed in a loop to allocate the memory. The application first requests all the attributes of the memory block and then allocates it. It is important to abide by the alignment requirements. Finally, the pointer to the allocated block of memory is passed back through the API. For the input and output buffers, it is not necessary to assign the correct memory at this point. The input and output buffer locations must be assigned before their first use in the “EXECUTE” stage. The type field refers to the memory blocks, for example input or persistent, as described in [Memory Management](#) on page 6.

Table 2-5 Commands for Memory Allocation

Table 2-5 Commands for Memory Allocation Command / Subcommand	Description
XA_API_CMD_GET_MEM_INFO_SIZE	Get the size of the memory type being referred to by the index.
XA_API_CMD_GET_MEM_INFO_ALIGNMENT	Get the alignment information of the memory-type being referred to by the index.
XA_API_CMD_GET_MEM_INFO_TYPE	Get the type of memory being referred to by the index.
XA_API_CMD_GET_MEM_INFO_PRIORITY	Get the allocation priority of memory being referred to by the index.
XA_API_CMD_SET_MEM_PTR	Set the pointer to the memory allocated for the referred index to the input value.

2.4.4 Initialize Codec Stage

The following commands should be executed in a loop during initialization. These commands should be called until the initialization is completed as indicated by the `XA_CMD_TYPE_INIT_DONE_QUERY` command. In general, decoders can loop multiple times until the header information is found. However, encoders will perform exactly one call before they signal they are done.

There is a major difference between encoding (Pulse Code Modulated) PCM data and decoding stream data. During the initialization of a decoder, the initialization task reads the input stream to discover the parameters of the encoding. However, for an encoder there is no header information in PCM data. Even so, the encode application is still required to perform the initialization described in this stage. However, encoders will not consume data during initialization. Furthermore, this has an implication in that some encoders provide parameters that can be used to modify the input buffer data requirements after the initialization stage. These modifications will always be a reduction in the size. The application only needs to provide the reduced amount per execution of the main codec process.

In general, the application will signal to the codec the number of bytes available in the input buffer and signal, if it is the last iteration. It is not normal to hit the end of the data during initialization, but in the case of a decoder being presented with a corrupt stream, it will allow a graceful termination. After the codec initialization is called the application will ask for the number of bytes consumed. The application can also ask if the initialization is complete, it is advisable to always ask even in the case of encoders that require only a single pass. A decoder application must keep iterating until it is complete.

Table 2-6 Commands for Initialization

Command / Subcommand	Description
<code>XA_API_CMD_SET_INPUT_BYTES</code>	Set the number of bytes available in the input buffer for initialization.
<code>XA_API_CMD_INPUT_OVER</code>	Signals to the codec the end of the bitstream
<code>XA_API_CMD_INIT</code> <code>XA_CMD_TYPE_INIT_PROCESS</code>	Search for the valid header, does header decoding to get the parameters and initializes state and configuration structures.
<code>XA_API_CMD_INIT</code> <code>XA_CMD_TYPE_INIT_DONE_QUERY</code>	Check if the initialization process has completed.
<code>XA_API_CMD_GET_CURIDX_INPUT_BUF</code>	Get the number of input buffer bytes consumed by the last initialization.

2.4.5 Get Codec-Specific Parameters Stage

Finally, after the initialization, the codec can supply the application with information. In the case of decoders, this would be the parameters it has extracted from the encoded header in the stream.

Table 2-7 Commands for Getting Parameters

Table 2-7 Commands for Getting Parameters Command / Subcommand	Description
XA_API_CMD_GET_CONFIG_PARAM XA_<codec>_CONFIG_PARAM_<param_name>	Get the value of the parameter from the codec. See the codec-specific section for parameter definitions.

2.4.6 Execute Codec Stage

The following commands should be executed continuously until the data is exhausted or the application wants to terminate the process. This is similar to the initialization stage but includes support for the management of the output buffer. After each iteration, the application requests how much data is written to the output buffer. This amount is always limited by the size of the buffer requested during the memory block allocation. (To alter the output buffer position, use XA_API_CMD_SET_MEM_PTR with the output buffer index.).

Table 2-8 Commands for Codec Execution

Table 2-8 Commands for Codec Execution Command / Subcommand	Description
XA_API_CMD_INPUT_OVER	Signal the end of bitstream to the library.
XA_API_CMD_SET_INPUT_BYTES	Set the number of bytes available in the input buffer for the execution.
XA_API_CMD_EXECUTE XA_CMD_TYPE_DO_EXECUTE	Execute the codec thread.
XA_API_CMD_EXECUTE XA_CMD_TYPE_DONE_QUERY	Check if the end of stream has been reached.
XA_API_CMD_GET_OUTPUT_BYTES	Get the number of bytes output by the codec in the last frame.
XA_API_CMD_GET_CURIDX_INPUT_BUF	Get the number of input buffer bytes consumed by the last call to the codec.

2.5 Files Describing the API

Following are the common include files (`include`):

`xa_apicmd_standards.h`

The command definitions for the generic API calls.

`xa_error_standards.h`

The macros and definitions for all the generic errors.

`xa_memory_standards.h`

The definitions for memory block allocation.

`xa_type_def.h`

All the types required for the API calls.

2.6 HiFi API Command Reference

In this section, the different commands are described along with their associated subcommands. The only commands missing are those specific to a single codec. The particular codec commands are generally the SET and GET commands for the operational parameters.

The commands are listed below in sections based on their primary commands type (`i_cmd`). Each section contains a table for every subcommand. In the case of no subcommands the one primary command is presented.

The commands are followed by an example C call. Along with the call there is a definition of the variable types used. This is to avoid any confusion over the type of the 4th argument. The examples are not complete C code extracts as there is no initialization of the variables before they are used.

The errors returned by the API are detailed after each of the command definitions. However, there are a few errors that are common to all the API commands and they are listed in [Common API Errors](#) on page 16. All the errors possible from the codec-specific commands will be defined in the codec-specific sections. Furthermore, the codec-specific sections will also cover the Execution errors that occur during the initialization or execution calls to the API.

2.6.1 Common API Errors

All these errors are fatal and should not be encountered during normal application operation. They signal that a serious error has occurred in the application that is calling the codec.

- **XA_API_FATAL_MEM_ALLOC**
`p_xa_module_obj` is NULL
- **XA_API_FATAL_MEM_ALIGN**
`p_xa_module_obj` is not aligned to 4 bytes
- **XA_API_FATAL_INVALID_CMD**
`i_cmd` is not a valid command
- **XA_API_FATAL_INVALID_CMD_TYPE**
`i_idx` is invalid for the specified command (`i_cmd`)

2.6.2 XA_API_CMD_GET_LIB_ID_STRINGS

Table 2-9 XA_CMD_TYPE_LIB_NAME subcommand

Subcommand	XA_CMD_TYPE_LIB_NAME
Description	This command obtains the name of the library in the form of a string. The maximum length of the string that the library will provide is 30 bytes. Therefore, the application shall pass a pointer to a buffer of a minimum size of 30 bytes. This command is optional.
Actual Parameters	<p>p_xa_module_obj NULL</p> <p>i_cmd XA_API_CMD_GET_LIB_ID_STRINGS</p> <p>i_idx XA_CMD_TYPE_LIB_NAME</p> <p>pv_value process_name – Pointer to a character buffer in which the name of the library is returned.</p>
Restrictions	None

Note No codec object is required due to the name being static data in the codec library.

Example

```
char process_name[30];
res = (*api_func) (NULL,
                  XA_API_CMD_GET_LIB_ID_STRINGS,
                  XA_CMD_TYPE_LIB_NAME,
                  (pVOID) process_name);
```

Errors

- XA_API_FATAL_MEM_ALLOC
This error is suppressed as p_xa_module_obj is NULL
- XA_API_FATAL_MEM_ALLOC
pv_value is NULL

Table 2-10 XA_CMD_TYPE_LIB_VERSION subcommand

Subcommand	XA_CMD_TYPE_LIB_VERSION
Description	This command obtains the version of the library in the form of a string. The maximum length of the string that the library will provide is 30 bytes. Therefore, the application shall pass a pointer to a buffer of a minimum size of 30 bytes. This command is optional.
Actual Parameters	<p>p_xa_module_obj NULL</p> <p>i_cmd XA_API_CMD_GET_LIB_ID_STRINGS</p> <p>i_idx XA_CMD_TYPE_LIB_VERSION</p> <p>pv_value lib_version – Pointer to a character buffer in which the version of the library is returned.</p>
Restrictions	None

Note No codec object is required due to the version being static data in the codec library.

Example

```
char lib_version[30];
res = (*api_func) (NULL,
                  XA_API_CMD_GET_LIB_ID_STRINGS,
                  XA_CMD_TYPE_LIB_VERSION,
                  (pVOID) lib_version);
```

Errors

- XA_API_FATAL_MEM_ALLOC
This error is suppressed as p_xa_module_obj is NULL
- XA_API_FATAL_MEM_ALLOC
pv_value is NULL

Table 2-11 XA_CMD_TYPE_API_VERSION subcommand

Subcommand	XA_CMD_TYPE_API_VERSION
Description	This command obtains the version of the API in the form of a string. The maximum length of the string that the library will provide is 30 bytes. Therefore the application shall pass a pointer to a buffer of a minimum size of 30 bytes. This command is optional.
Actual Parameters	<p>p_xa_module_obj</p> <p>NULL</p> <p>i_cmd</p> <p>XA_API_CMD_GET_LIB_ID_STRINGS</p> <p>i_idx</p> <p>XA_CMD_TYPE_API_VERSION</p> <p>pv_value</p> <p>api_version – Pointer to a character buffer in which the version of the API is returned.</p>
Restrictions	None

Note No codec object is required due to the version being static data in the codec library.

Example

```
char api_version[30];
res = (*api_func) (NULL,
                  XA_API_CMD_GET_LIB_ID_STRINGS,
                  XA_CMD_TYPE_API_VERSION,
                  (pVOID) api_version);
```

Errors

- XA_API_FATAL_MEM_ALLOC
This error is suppressed as p_xa_module_obj is NULL
- XA_API_FATAL_MEM_ALLOC
pv_value is NULL

2.6.3 XA_API_CMD_GET_API_SIZE

Table 2-12 XA_API_CMD_GET_API_SIZE command

Subcommand	None
Description	This command is used to obtain the size of the API structure, in order to allocate memory for the API structure. The pointer to the API size variable is passed, and the API returns the size of the structure in bytes. The API structure is used for the interface and is persistent.
Actual Parameters	<p>p_xa_module_obj NULL</p> <p>i_cmd XA_API_CMD_GET_API_SIZE</p> <p>i_idx NULL</p> <p>pv_value &api_size – Pointer to API size variable</p>
Restrictions	The application shall allocate memory with an alignment of 4 bytes.

Note No codec object is required due to the size being fixed for the codec library.

Note: No codec object is required due to the size being fixed for the codec library.

Example

```
unsigned int api_size;
res = (*api_func) (NULL,
                  XA_API_CMD_GET_API_SIZE,
                  0,
                  (pVOID) &api_size);
```

Errors

- XA_API_FATAL_MEM_ALLOC
This error is suppressed as p_xa_module_obj is NULL.
- XA_API_FATAL_MEM_ALLOC
pv_value is NULL

2.6.4 XA_API_CMD_INIT

Table 2-13 XA_CMD_TYPE_INIT_API_PRE_CONFIG_PARAMS subcommand

Subcommand	XA_CMD_TYPE_INIT_API_PRE_CONFIG_PARAMS
Description	This command is used to set the default value of the configuration parameters. The configuration parameters can then be altered by using one of the codec-specific parameter setting commands. Refer to the codec-specific section.
Actual Parameters	<p>p_xa_module_obj api_obj – Pointer to API structure</p> <p>i_cmd XA_API_CMD_INIT</p> <p>i_idx XA_CMD_TYPE_INIT_API_PRE_CONFIG_PARAMS</p> <p>pv_value NULL</p>
Restrictions	None

Example

```
res = (*api_func)(api_obj,  
                 XA_API_CMD_INIT,  
                 XA_CMD_TYPE_INIT_API_PRE_CONFIG_PARAMS,  
                 NULL);
```

Errors

Common API Errors

Table 2-14 XA_CMD_TYPE_INIT_API_POST_CONFIG_PARAMS subcommand

Subcommand	XA_CMD_TYPE_INIT_API_POST_CONFIG_PARAMS
Description	This command is used to calculate the sizes of all the memory blocks required by the application. It should occur after the codec-specific parameters have been set.
Actual Parameters	<p>p_xa_module_obj api_obj – Pointer to API structure</p> <p>i_cmd XA_API_CMD_INIT</p> <p>i_idx XA_CMD_TYPE_INIT_API_POST_CONFIG_PARAMS</p> <p>pv_value NULL</p>
Restrictions	None

Example

```
res = (*api_func)(api_obj,  
                 XA_API_CMD_INIT,  
                 XA_CMD_TYPE_INIT_API_POST_CONFIG_PARAMS,  
                 NULL);
```

Errors

Common API Errors

Table 2-15 XA_CMD_TYPE_INIT_PROCESS subcommand

Subcommand	XA_CMD_TYPE_INIT_PROCESS
Description	This command initializes the codec. In the case of a decoder, it searches for the valid header and performs the header decoding to get the encoded stream parameters. This command is part of the initialization loop. It must be repeatedly called until the codec signals it has finished. In the case of an encoder, the initialization of codec is performed. No output data is created during initialization.
Actual Parameters	<p>p_xa_module_obj api_obj – Pointer to API structure</p> <p>i_cmd XA_API_CMD_INIT</p> <p>i_idx XA_CMD_TYPE_INIT_PROCESS</p> <p>pv_value NULL</p>
Restrictions	None

Example

```
res = (*api_func)(api_obj,
                  XA_API_CMD_INIT,
                  XA_CMD_TYPE_INIT_PROCESS,
                  NULL);
```

Errors

- Common API Errors
- See the codec-specific section for execution errors

Table 2-16 XA_CMD_TYPE_INIT_DONE_QUERY subcommand

Subcommand	XA_CMD_TYPE_INIT_DONE_QUERY
Description	This command checks to see if the initialization process has completed. If it has, the flag value is set to 1, else it is set to zero. A pointer to the flag variable is passed as an argument.
Actual Parameters	<p>p_xa_module_obj api_obj – Pointer to API structure</p> <p>i_cmd XA_API_CMD_INIT</p> <p>i_idx XA_CMD_TYPE_INIT_DONE_QUERY</p> <p>pv_value &init_done – Pointer to flag that indicates the completion of initialization process.</p>
Restrictions	None

Example

```

unsigned int init_done;
res = (*api_func) (api_obj,
                  XA_API_CMD_INIT,
                  XA_CMD_TYPE_INIT_DONE_QUERY,
                  (pVOID) &init_done);

```

Errors

- Common API Errors
- XA_API_FATAL_MEM_ALLOC
pv_value is NULL

2.6.5 XA_API_CMD_GET_MEMTABS_SIZE

Table 2-17 XA_API_CMD_GET_MEMTABS_SIZE command

Subcommand	None
Description	This command is used to obtain the size of the table used to hold the memory blocks required for the codec operation. The API returns the total size of the required table. A pointer to the size variable is sent with this API command and the codec writes the value to the variable.
Actual Parameters	<p>p_xa_module_obj api_obj – Pointer to API structure</p> <p>i_cmd XA_API_CMD_GET_MEMTABS_SIZE</p> <p>i_idx NULL</p> <p>pv_value &proc_mem_tabs_size – Pointer to memory size variable</p>
Restrictions	The application shall allocate memory with an alignment of 4 bytes.

Example

```
unsigned int proc_mem_tabs_size;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_MEMTABS_SIZE,
                  0,
                  (pVOID) &proc_mem_tabs_size);
```

Errors

- Common API Errors
- XA_API_FATAL_MEM_ALLOC
pv_value is NULL

2.6.6 XA_API_CMD_SET_MEMTABS_PTR

Table 2-18 XA_API_CMD_SET_MEMTABS_PTR command

Subcommand	None
Description	This command is used to set the memory structure pointer in the library to the allocated value.
Actual Parameters	<p>p_xa_module_obj api_obj – Pointer to API structure</p> <p>i_cmd XA_API_CMD_SET_MEMTABS_PTR</p> <p>i_idx NULL</p> <p>pv_value alloc – Allocated pointer</p>
Restrictions	The application shall allocate memory with an alignment of 4 bytes.

Example

```
int * alloc; //alloc is a pointer to the allocated memory
res = (*api_func)(api_obj,
                  XA_API_CMD_SET_MEMTABS_PTR,
                  0,
                  (pVOID) alloc);
```

Errors

- Common API Errors
- XA_API_FATAL_MEM_ALLOC
pv_value is NULL
- XA_API_FATAL_MEM_ALIGN
pv_value is not aligned to 4 bytes

2.6.7 XA_API_CMD_GET_N_MEMTABS

Table 2-19 XA_API_CMD_GET_N_MEMTABS command

Subcommand	None
Description	This command is used to obtain the number of memory blocks needed by the codec. This value is used as the iteration counter for the allocation of the memory blocks. A pointer to each memory block will be placed in the previously allocated memory tables. The pointer to the variable is passed to the API, and the codec writes the value to this variable.
Actual Parameters	<p>p_xa_module_obj api_obj – Pointer to API structure</p> <p>i_cmd XA_API_CMD_GET_N_MEMTABS</p> <p>i_idx NULL</p> <p>pv_value &n_mems – Number of memory blocks required to be allocated.</p>
Restrictions	None

Example

```
int n_mems;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_N_MEMTABS,
                  0,
                  (pVOID) &n_mems);
```

Errors

- Common API Errors
- XA_API_FATAL_MEM_ALLOC

pv_value is NULL

2.6.8 XA_API_CMD_GET_MEM_INFO_SIZE

Table 2-20 XA_API_CMD_GET_MEM_INFO_SIZE command

Subcommand	Memory index
Description	<p>This command obtains the size of the memory type being referred to by the index. The size in bytes is returned in the variable pointed to by the final argument.</p> <p>Note: This is the actual size needed not including any alignment packing space.</p>
Actual Parameters	<p>p_xa_module_obj api_obj – Pointer to API structure</p> <p>i_cmd XA_API_CMD_GET_MEM_INFO_SIZE</p> <p>i_idx Index of the memory</p> <p>pv_value &size – Pointer to memory size</p>
Restrictions	None

Example

```
int index;
unsigned int size;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_MEM_INFO_SIZE,
                  index,
                  (pVOID) &size);
```

Errors

- Common API Errors
- XA_API_FATAL_MEM_ALLOC
pv_value is NULL
- XA_API_FATAL_INVALID_CMD_TYPE
i_idx is an invalid memory block number; valid block numbers obey the relation $0 \leq i_idx < n_mems$ (See XA_API_CMD_GET_N_MEMTABS).

2.6.9 XA_API_CMD_GET_MEM_INFO_ALIGNMENT

Table 2-21 XA_API_CMD_GET_MEM_INFO_ALIGNMENT command

Subcommand	Memory index
Description	This command gets the alignment information of the memory-type being referred to by the index. The alignment required in bytes is returned to the application.
Actual Parameters	<p>p_xa_module_obj api_obj – Pointer to API structure</p> <p>i_cmd XA_API_CMD_GET_MEM_INFO_ALIGNMENT</p> <p>i_idx Index of the memory</p> <p>pv_value &alignment – Pointer to the alignment info variable</p>
Restrictions	None

Example

```
int index;
unsigned int alignment;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_MEM_INFO_ALIGNMENT,
                  index,
                  (pVOID) &alignment);
```

Errors

- Common API Errors
- XA_API_FATAL_MEM_ALLOC
pv_value is NULL
- XA_API_FATAL_INVALID_CMD_TYPE
i_idx is an invalid memory block number; valid block numbers obey the relation $0 \leq i_idx < n_mems$ (See XA_API_CMD_GET_N_MEMTABS).

2.6.10 XA_API_CMD_GET_MEM_INFO_TYPE

Table 2-22 XA_API_CMD_GET_MEM_INFO_TYPE command

Subcommand	Memory index
Description	This command gets the type of memory being referred to by the index.
Actual Parameters	<p>p_xa_module_obj</p> <p>api_obj – Pointer to API structure</p> <p>i_cmd</p> <p>XA_API_CMD_GET_MEM_INFO_TYPE</p> <p>i_idx</p> <p>Index of the memory</p> <p>pv_value</p> <p>&type – Pointer to the memory type variable</p>
Restrictions	None

Example

```
int index;
unsigned int type;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_MEM_INFO_TYPE,
                  index,
                  (pVOID) &type);
```

Table 2-23 Memory Type Indices

Type	Description
XA_MEMTYPE_PERSIST	Persistent memory
XA_MEMTYPE_SCRATCH	Scratch memory
XA_MEMTYPE_INPUT	Input Buffer
XA_MEMTYPE_OUTPUT	Output Buffer

Errors

- Common API Errors

- XA_API_FATAL_MEM_ALLOC

`pv_value` is NULL

- XA_API_FATAL_INVALID_CMD_TYPE

`i_idx` is an invalid memory block number; valid block numbers obey the relation $0 \leq i_idx < n_mems$ (See XA_API_CMD_GET_N_MEMTABS).

2.6.11 XA_API_CMD_GET_MEM_INFO_PRIORITY

Table 2-24 XA_API_CMD_GET_MEM_INFO_PRIORITY command

Subcommand	Memory index
Description	This command gets allocation priority of memory being referred by the index. (The meaning of the levels is defined on a codec-specific basis. This command returns a fixed dummy value unless the codec defines it otherwise.)
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> <i>XA_API_CMD_GET_MEM_INFO_PRIORITY</i></p> <p><i>i_idx</i> Index of the memory</p> <p><i>pv_value</i> <i>&priority</i> – Pointer to the memory priority variable</p>
Restrictions	None

Example

```
int index;
unsigned int priority;
res = (*api_func) (api_obj,
                  XA_API_CMD_GET_MEM_INFO_PRIORITY,
                  index,
                  (pVOID) &priority);
```

Table 2-25 Memory Priorities

Priority	Type
0	XA_MEMPRIORITY_ANYWHERE
1	XA_MEMPRIORITY_LOWEST
2	XA_MEMPRIORITY_LOW
3	XA_MEMPRIORITY_NORM
4	XA_MEMPRIORITY_ABOVE_NORM
5	XA_MEMPRIORITY_HIGH
6	XA_MEMPRIORITY_HIGHER
7	XA_MEMPRIORITY_CRITICAL

Errors

- Common API Errors

- XA_API_FATAL_MEM_ALLOC

`pv_value` is NULL

- XA_API_FATAL_INVALID_CMD_TYPE

`i_idx` is an invalid memory block number; valid block numbers obey the relation $0 \leq i_idx < n_mems$ (See XA_API_CMD_GET_N_MEMTABS).

2.6.12 XA_API_CMD_SET_MEM_PTR

Table 2-26 XA_API_CMD_SET_MEM_PTR command

Subcommand	Memory index
Description	This command passes to the codec the pointer to the allocated memory. This is then stored in the memory tables structure allocated earlier. For the input and output buffers, it is legitimate to execute this command during the main codec loop.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> <i>XA_API_CMD_SET_MEM_PTR</i></p> <p><i>i_idx</i> Index of the memory</p> <p><i>pv_value</i> <i>alloc</i> – Pointer to memory buffer allocated</p>
Restrictions	The pointer must be correctly aligned to the requirements.

Example

```
int index;
void * alloc; //alloc is a pointer to the aligned memory
res = (*api_func)(api_obj,
                  XA_API_CMD_SET_MEM_PTR,
                  index,
                  (pVOID) alloc);
```

Errors

- Common API Errors
- XA_API_FATAL_MEM_ALLOC
pv_value is NULL
- XA_API_FATAL_INVALID_CMD_TYPE
i_idx is an invalid memory block number; valid block numbers obey the relation $0 \leq i_idx < n_mems$ (See XA_API_CMD_GET_N_MEMTABS).
- XA_API_FATAL_MEM_ALIGN
pv_value is not of the required alignment for the requested memory block

2.6.13 XA_API_CMD_INPUT_OVER

Table 2-27 XA_API_CMD_INPUT_OVER command

Subcommand	None
Description	This command is used to tell the codec that the end of the input data has been reached. This situation can arise both in the initialization loop and the execute loop.
Actual Parameters	<i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure <i>i_cmd</i> <i>XA_API_CMD_INPUT_OVER</i> <i>i_idx</i> NULL <i>pv_value</i> NULL
Restrictions	None

Example

```
res = (*api_func)(api_obj,  
                  XA_API_CMD_INPUT_OVER,  
                  0,  
                  NULL);
```

Errors

Common API Errors.

2.6.14 XA_API_CMD_SET_INPUT_BYTES

Table 2-28 XA_API_CMD_SET_INPUT_BYTES command

Subcommand	None
Description	This command sets the number of bytes available in the input buffer for the codec. It is used both in the initialization loop and execute loop. It is the number of valid bytes from the buffer pointer. It should be at least the minimum buffer size requested unless this is the end of the data.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_SET_INPUT_BYTES</p> <p><i>i_idx</i> NULL</p> <p><i>pv_value</i> <i>&buff_size</i> – Pointer to the input byte variable</p>
Restrictions	None

Example

```
int buff_size;
res = (*api_func) (api_obj,
                  XA_API_CMD_SET_INPUT_BYTES,
                  0,
                  (pVOID) &buff_size);
```

Errors

- Common API Errors
 - XA_API_FATAL_MEM_ALLOC
- pv_value* is NULL

2.6.15 XA_API_CMD_GET_CURIDX_INPUT_BUF

Table 2-29 XA_API_CMD_GET_CURIDX_INPUT_BUF command

Subcommand	None
Description	This command gets the number of input buffer bytes consumed by the codec. It is used both in the initialization loop and execute loop.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_GET_CURIDX_INPUT_BUF</p> <p><i>i_idx</i> NULL</p> <p><i>pv_value</i> &bytes_consumed – Pointer to bytes consumed variable</p>
Restrictions	None

Example

```
int bytes_consumed;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_CURIDX_INPUT_BUF,
                  0,
                  (pVOID) &bytes_consumed);
```

Errors

- Common API Errors
- XA_API_FATAL_MEM_ALLOC
pv_value is NULL

2.6.16 XA_API_CMD_EXECUTE

Table 2-30 XA_CMD_TYPE_DO_EXECUTE subcommand

Subcommand	XA_CMD_TYPE_DO_EXECUTE
Description	This command executes the codec.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_EXECUTE</p> <p><i>i_idx</i> XA_CMD_TYPE_DO_EXECUTE</p> <p><i>pv_value</i> NULL</p>
Restrictions	None

Example

```
res = (*api_func)(api_obj,
                  XA_API_CMD_EXECUTE,
                  XA_CMD_TYPE_DO_EXECUTE,
                  NULL);
```

Errors

- Common API Errors
- See the codec-specific section for execution errors

Table 2-31 XA_CMD_TYPE_DONE_QUERY subcommand

Subcommand	XA_CMD_TYPE_DONE_QUERY
Description	This command checks to see if the end of processing has been reached. If it is, the flag value is set to 1, else it is set to zero. The pointer to the flag is passed as an argument. Processing by the codec can continue for several invocations of the DO_EXECUTE command after the last input data has been passed to the codec, so the application should not assume that the codec has finished generating all its output until so indicated by this command.

Actual Parameters	<i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure <i>i_cmd</i> <i>XA_API_CMD_EXECUTE</i> <i>i_idx</i> <i>XA_CMD_TYPE_DONE_QUERY</i> <i>pv_value</i> <i>&flag</i> – Pointer to the flag variable
Restrictions	None

Example

```
int flag;  
res = (*api_func)(api_obj,  
                  XA_API_CMD_EXECUTE,  
                  XA_CMD_TYPE_DONE_QUERY,  
                  (pVOID) &flag);
```

Errors

- Common API Errors
- XA_API_FATAL_MEM_ALLOC

pv_value is NULL

Table 2-32 XA_CMD_TYPE_DO_RUNTIME_INIT subcommand

Subcommand	XA_CMD_TYPE_DO_RUNTIME_INIT
Description	<p>This command resets the decoder's history buffers. It can be used to avoid distortions and clicks by facilitating playback ramping up and down during trick-play.</p> <p>Note: This command is available in API version 1.14 or later.</p>
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_EXECUTE</p> <p><i>i_idx</i> XA_CMD_TYPE_DO_RUNTIME_INIT</p> <p><i>pv_value</i> NULL</p>
Restrictions	None

Example

```
res = (*api_func) (api_obj,  
                  XA_API_CMD_EXECUTE,  
                  XA_CMD_TYPE_DO_RUNTIME_INIT,  
                  NULL);
```

Errors

Common API Errors.

2.6.17 XA_API_CMD_GET_OUTPUT_BYTES

Table 2-33 XA_API_CMD_GET_OUTPUT_BYTES command

Subcommand	None
Description	This command obtains the number of bytes output by the codec during the last execution.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_GET_OUTPUT_BYTES</p> <p><i>i_idx</i> NULL</p> <p><i>pv_value</i> &<i>out_bytes</i> – Pointer to the output bytes variable</p>
Restrictions	None

Example

```
int out_bytes;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_OUTPUT_BYTES,
                  0,
                  (pVOID) &out_bytes);
```

Errors

- Common API Errors
- XA_API_FATAL_MEM_ALLOC
pv_value is NULL

2.6.18 XA_API_CMD_GET_CONFIG_PARAM

Table 2-34 XA_CONFIG_PARAM_CUR_INPUT_STREAM_POS subcommand

Subcommand	XA_CONFIG_PARAM_CUR_INPUT_STREAM_POS
Description	<p>This command reads the current input stream position, which is equal to the total number of consumed input bytes until the start of the input buffer. This running counter is set to zero at library initialization time and incremented every time the codec library consumes any bytes from the input buffer. If the application layer places a unit of input data with a byte size equal to <i>size</i> at byte offset in the input buffer, then the input stream position range for this unit may be calculated as follows:</p> $\text{start_pos} = \text{CUR_INPUT_STREAM_POS} + \text{offset}$ $\text{end_pos} = \text{CUR_INPUT_STREAM_POS} + \text{offset} + \text{size}$
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_CONFIG_PARAM_CUR_INPUT_STREAM_POS</p> <p><i>pv_value</i> &<i>ui_cur_input_stream_pos</i> – Pointer to the current input stream position variable.</p>
Restrictions	<p>The current input stream position counter is of 32 bits and, therefore, will overflow and wrap-around if the input stream length is more than $2^{32}-1$ bytes.</p> <p>This command is available in API version 1.15 or later.</p>

Example

```

unsigned int ui_cur_input_stream_pos;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_CONFIG_PARAM_CUR_INPUT_STREAM_POS,
                  (void *) &ui_cur_input_stream_pos);

```

Errors

Common API Errors.

Table 2-35 XA_CONFIG_PARAM_GEN_INPUT_STREAM_POS subcommand

Subcommand	XA_CONFIG_PARAM_GEN_INPUT_STREAM_POS
Description	This command reads the input stream position of the unit (e.g., frame) corresponding to the generated (decoded or encoded) output data block. That is, if the main processing (DO_EXECUTE) call into the library generates any data in the output buffer, then this command reads the total number of input bytes consumed until the start of the unit that has been processed and placed into the output buffer. For example, if the application layer places a unit in the input buffer at input stream position <code>start_pos</code> (see Table 2-34 XA_CONFIG_PARAM_CUR_INPUT_STREAM_POS subcommand on page 43), when the library generates the decoded or encoded data corresponding to this unit, it sets <code>GEN_INPUT_STREAM_POS</code> to <code>start_pos</code> .
Actual Parameters	<p><code>p_xa_module_obj</code> <code>api_obj</code> – Pointer to API structure</p> <p><code>i_cmd</code> <code>XA_API_CMD_GET_CONFIG_PARAM</code></p> <p><code>i_idx</code> <code>XA_CONFIG_PARAM_GEN_INPUT_STREAM_POS</code></p> <p><code>pv_value</code> <code>&ui_gen_input_stream_pos</code> – Pointer to the input stream position of the generated data variable.</p>
Restrictions	<p>The input stream position of the generated data counter is 32bits and therefore will overflow and wrap-around, if the input stream length is more than $2^{32}-1$ bytes.</p> <p>This command is available in API version 1.15 or later.</p>

Example

```

unsigned int ui_gen_input_stream_pos;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_CONFIG_PARAM_GEN_INPUT_STREAM_POS,
                  (void *) &ui_gen_input_stream_pos);

```

Errors

Common API Errors.

2.6.19 XA_API_CMD_SET_CONFIG_PARAM

Table 2-36 XA_CONFIG_PARAM_CUR_INPUT_STREAM_POS subcommand

Subcommand	XA_CONFIG_PARAM_CUR_INPUT_STREAM_POS
Description	<i>This command resets the current input stream position. See Table 2-34 XA_CONFIG_PARAM_CUR_INPUT_STREAM_POS subcommand on page 43 for details.</i>
Actual Parameters	<p>p_xa_module_obj api_obj – Pointer to API structure.</p> <p>i_cmd XA_API_CMD_SET_CONFIG_PARAM</p> <p>i_idx XA_CONFIG_PARAM_CUR_INPUT_STREAM_POS</p> <p>pv_value &ui_cur_input_stream_pos – Pointer to the current input stream position variable.</p>
Restrictions	This command is available in API version 1.15 or later.

Example

```

unsigned int ui_cur_input_stream_pos = 0;
res = (*api_func)(api_obj,
                  XA_API_CMD_SET_CONFIG_PARAM,
                  XA_CONFIG_PARAM_CUR_INPUT_STREAM_POS,
                  (void *) &ui_cur_input_stream_pos);

```

Errors

Common API Errors.

3. HiFi DSP MP3 Decoder

The HiFi DSP MP3 Decoder conforms to the generic codec API. The following flowchart shows the command sequence used in the example test bench.




Figure 3 Flowchart for MP3 Decoder Integration

3.1 Files Specific to the MP3 Decoder

The MP3 decoder parameter header file (`include/mp3_dec`)

`xa_mp3_dec_api.h`

The MP3 decoder libraries (`lib`):

`xa_mp2_dec.a` (MP2 Decoder)
`xa_mp3_dec.a` (MP3 Decoder)
`xa_mp3mch_dec.a` (MP3 5.1-Channel Decoder)

The MP3 decoder API call is defined as:

```
XA_ERRORCODE xa_mp3_dec(xa_codec_handle_t p_xa_module_obj,
                        WORD32             i_cmd,
                        WORD32             i_idx,
                        pVOID              pv_value);
```

3.2 Configuration Parameters

The HiFi MP3 decode algorithm accepts the following parameters from the user.

- **pcm_wd_sz** – The PCM word size requested.
 - Smaller or equal to 16 – Value used is 16.
 - Greater than 16 – Value used is 24.
- **crc_check** – Enable (non-zero) or disable (0) CRC validation for error-protected Layer I and II streams. If CRC validation is enabled and fails for an error-protected stream, a non-fatal error code is returned along with the decoded output. By default, CRC checking is disabled.
- **mch_enable** – Enable (non-zero) or disable (0) Layer II 5.1-channel decoding. This flag is supported by the MP3 5.1-Channel Decoder only and is enabled by default.
- **dabmp2** – Enable (non-zero) or disable (0) DAB specific Scale factor CRC (see *ETSI EN 300 401 V1.4.1 Radio Broadcasting Systems* ^[3]).

The parameters required for storage and audio output through a DAC are obtained from the bitstream during the initialization stage. After the initialization the following parameters are available:

- **samp_freq** – This is the sample frequency of the output buffer samples. The units are Hz (samples per second). For example, a valid output is 44100.
- **num_chan** – This is the number of channels of data put into the output buffer.
 - In the stereo-only libraries (`mp2_dec` and `mp3_dec`), there are only two valid values 1 (mono) and 2 (stereo) for this parameter. In the case of stereo, the output data are interleaved in the output buffer with the first output sample in each pair being the left channel value and the second sample in each pair being the right channel value.

- In the MP3 5.1-Channel Decoder, the value of this parameter is between 1 and 6. The PCM samples for the separate channels are interleaved in the output buffer – the exact channel mapping can be retrieved through the `chan_map` parameter.

Note: The `um_chan` parameter indicates the actual number of channels present in the output buffer, that is, there will be no unused PCM sample offsets in the output

chmode_info – This is the channel mode information:

- bits 1:0 – 0 (stereo), 1 (joint stereo), 2 (dual mono), 3 (mono).
- bit 4: intensity stereo, if set to 1.
- bit 5: mid-side stereo, if set to 1.

bitrate – This is the data rate (bit rate) of the input bitstream. The units are kbps (kbits per second). For example, a valid output is 320.

pcm_wd_sz – This is the PCM word size of the data in the output buffer. The only values are 16 or 24. This is only useful if neither 16 nor 24 were given to the decoder.

mch_status – This is the multi-channel status of the library and the input stream. Status codes:

- `XA_MP3DEC_MCH_STATUS_UNSUPPORTED` (0) – the library does not support multi-channel decoding (i.e., the library is either `mp2_dec` or `mp3_dec`).
- `XA_MP3DEC_MCH_STATUS_DISABLED` (1) – multi-channel decoding is disabled through the `mch_enable` configuration parameter (`mp3mch_dec` only).
- `XA_MP3DEC_MCH_STATUS_NOT_PRESENT` (2) – multi-channel decoding is supported but the input stream is mono or stereo (`mp3mch_dec` only).
- `XA_MP3DEC_MCH_STATUS_PRESENT` (3) – the library is decoding multi-channel content (`mp3mch_dec` only).

extn_present – This indicates if an extension substream is present in the input stream (`mp3mch_dec` only).

lfe_present – This indicates if the LFE (low-frequency effects) channel is present in the input multi-channel stream (`mp3mch_dec` only).

num_xchan – This is the number of extra full-bandwidth channels in addition to the main audio channels. This number does not include the LFE channel.

- Valid values: 0 through 3
- For example, a 5.1-Channel stream will have `num_xchan` set to 3 and `lfe_present` set to 1.

chan_config – This specifies the channel configuration of the input stream (`mp3mch_dec` only). Valid values and channel configurations:

- 1 – L(Left) / C (Center) / R (Right) / Ls (Left Surround) / Rs (Right Surround)
- 2 – L / C / R / Cs (Center Surround)
- 3 – L / C / R
- 4 – L / C / R / L2 (Second Left) / R2 (Second Right)
- 5 – L / R / Ls / Rs
- 6 – L / R / Cs

- 7 – L / R
- 8 – L / R / L2 / R2
- 9 – C
- 10 – C / L2 / R2

chan_map – This parameter specifies how the channels are arranged in the output buffer.

Note: The values of the `num_chan`, `lfe_present`, `num_xchan` and `chan_config` parameters can be derived from this parameter.

their sample offsets in the interleaved output PCM buffer. If a channel (with channel index C) appears at sample offset N in the interleaved output PCM buffer, then Nth nibble of the `chan_map` parameter is set to C.

- Valid channel indices: 0 – L, 1 – C, 2 – R, 3 – Ls/Cs, 4 – Rs, 5 – L2, 6 – R2, 7 – LFE, 0 x F – invalid PCM sample offset.
- For example, `chan_map = 0xFF743120` indicates that the left channel (channel index 0) is present at sample offset 0, the right channel (channel index 2) is present at sample offset 1, the center channel (channel index 1) is present at sample offset 2, the left surround (channel index 3) is present at sample offset 3, the right surround (channel index 4) is present at sample offset 4, and the LFE channel (channel index 7) is present at sample offset 5.

3.3 Usage Notes

Although the HiFi MP3 Decoder conforms to the generic codec API described in Section 2, the following notes must be considered to ensure correct decoder operation.

- The MP3 5.1-Channel Decoder can process both base and extension input streams. If an extension stream is present, the input to the decoder must be a frame-by-frame concatenation of the base and extension streams:
 - [base frame 0] [extension frame 0] [base frame 1] [extension frame 1] ...
- The PCM samples for the separate channels are interleaved in the output buffer. The number of channels present in the output buffer depends on the number of channels present in the input stream. There are no unused PCM offsets in the output buffer.
- For each `DO_EXECUTE` call, the MP3 Decoder expects enough data in the input buffer to parse and decode one complete frame. If there is insufficient data in the input buffer, the MP3 Decoder does not consume any bytes and returns a non-fatal error that allows the application to fill in additional data before calling the decoder again.

Note that the MP3 5.1-Channel Decoder consumes both the base frame and the extension frame (if present) and produces the decoded audio data in a single `DO_EXECUTE` call.

- During initialization, the MP3 5.1-Channel Decoder detects availability of multi-channel content in the input stream by doing a CRC check on the base and extension frames (if present). If the CRC check fails, the MP3 5.1-Channel Decoder indicates through the `mch_status` parameter that multi-channel content is not present and switches to 2-channel decoding only.

3.4 MP3 Decoder-Specific Commands

These are the commands unique to the HiFi MP3 Decoder. They are listed in sections based on their primary commands type (`i_cmd`). Each section contains a table for every subcommand. In the case of no subcommands, the one primary command is presented.

3.4.1 Initialization and Execution Errors

These errors can result from the initialization or execution API calls:

`XA_MP3DEC_CONFIG_NONFATAL_MCH_NOT_SUPPORTED`

The application tried to enable multi-channel support in the MP2 Decoder or the MP3 Decoder libraries. Layer II 5.1-Channel decoding is supported only by the MP3 5.1-Channel Decoder library.

`XA_MP3DEC_CONFIG_NONFATAL_INVALID_GEN_STRM_POS`

The input stream position of the decoded data is invalid. This may occur, if the decoder has not generated any output data, or a runtime-init ramp-down frame is active, or the current input stream position is reset by the application.

`XA_MP3DEC_CONFIG_NONFATAL_INVALID_PARAM_VALUE`

Invalid set parameter. This error occurs when the config parameter value given to set is invalid but non-fatal.

`XA_MP3DEC_EXECUTE_NONFATAL_NEED_MORE`

The codec requires more bits to continue the processing.

`XA_MP3DEC_EXECUTE_NONFATAL_CANNOT_REWIND`

The MP3 bitstream syntax states that some bits corresponding to the current frame can be contained in the space designated for the previous frame. This error situation occurs when the bitstream needs to be rewound beyond the buffered bits.

`XA_MP3DEC_EXECUTE_NONFATAL_CHANGED_CHANNELS`

The number of channels changed between successive frames.

`XA_MP3DEC_EXECUTE_NONFATAL_CHANGED_SAMP_FREQ`

The sample frequency changed between successive frames.

`XA_MP3DEC_EXECUTE_NONFATAL_CHANGED_LAYER`

The MPEG layer of the bitstream changed between successive frames.

`XA_MP3DEC_EXECUTE_NONFATAL_NEXT_SYNC_NOT_FOUND`

The bytes required for the current frame exceeded the buffer limit.

`XA_MP3DEC_EXECUTE_NONFATAL_CRC_FAILED`

CRC validation failed for an error-protected stream.

`XA_MP3DEC_EXECUTE_NONFATAL_NO_MAIN_AUDIO_INPUT`

Insufficient data present to decode main audio data. This error may occur at broken frame boundaries or during trick play where input frames are not time continuous.

`XA_MP3DEC_EXECUTE_NONFATAL_MCH_CRC_ERROR`

The CRC check of the multi-channel frame failed during normal decoding. Only the stereo channels will be decoded, and the rest will be set to 0. This error can be returned only by the MP3 5.1-Channel Decoder.

XA_MP3DEC_EXECUTE_NONFATAL_MCH_EXT_NOTFOUND

The CRC check of the extension multi-channel frame failed during normal decoding. Only the stereo channels will be decoded, and the rest will be set to 0. This error can be returned only by the MP3 5.1-Channel Decoder.

XA_MP3DEC_EXECUTE_NONFATAL_SCF_CRC_FAILED1

The DAB-specific scale factor CRC check failed. 1 CRC is in error.

XA_MP3DEC_EXECUTE_NONFATAL_SCF_CRC_FAILED2

The DAB-specific scale factor CRC check failed. 2 CRC's are in error.

XA_MP3DEC_EXECUTE_NONFATAL_SCF_CRC_FAILED3

The DAB-specific scale factor CRC check failed. 3 CRC's are in error.

XA_MP3DEC_EXECUTE_NONFATAL_SCF_CRC_FAILED4

The DAB-specific scale factor CRC check failed. 4 CRC are in error.

XA_MP3DEC_EXECUTE_NONFATAL_INVALID_BITRATE_MODE_COMB

The MP3 bitstream syntax states that for layer II, not all combinations of total bit rate and mode are allowed.

Fatal errors require the codec to be completely reinitialized and presented with an alternative bitstream.

XA_MP3DEC_EXECUTE_FATAL_UNSUPPORTED_LAYER

A bitstream is presented with an unsupported MPEG layer.

XA_MP3DEC_EXECUTE_FATAL_OVERLOADED_IN_BUF

The decoder attempted to decoding the bitstream beyond the available data.

XA_MP3DEC_EXECUTE_FATAL_STREAM_ERROR

Errors were encountered in the bitstream.

3.4.2 XA_API_CMD_SET_CONFIG_PARAM

Table 3-1 XA_MP3DEC_CONFIG_PARAM_PCM_WDSZ subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_PCM_WDSZ
Description	This command sets the PCM Word format size of the output samples in bits. The word format is set to 16 bits or 24 bits.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure.</p> <p><i>i_cmd</i> XA_API_CMD_SET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_PCM_WDSZ</p> <p><i>pv_value</i> &pcm_wd_sz – Pointer to word size variable.</p>
Restrictions	<p>Only 16 and 24 are valid internal word format word sizes.</p> <p>16, if pcm_wd_sz <= 16</p> <p>24, if pcm_wd_sz > 16</p> <p>See non-fatal errors below.</p>

Note The 24-bit format is returned in 32-bit aligned words with the data left justified in the word. This is the reason that the buffer size requirement for 24-bit samples is double the requirement for 16-bit samples.

Example

```
int pcm_wd_sz = 24;
res = (*api_func)(api_obj,
                  XA_API_CMD_SET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_PCM_WDSZ,
                  (pVOID) &pcm_wd_sz);
```

Errors

Common API Errors.

XA_API_FATAL_MEM_ALLOC

pv_value is NULL.

XA_MP3DEC_CONFIG_NONFATAL_MP3_PCM_ADJUST_16

The value given has been adjusted to 16.

XA_MP3DEC_CONFIG_NONFATAL_MP3_PCM_ADJUST_24

The value given has been adjusted to 24.

Table 3-2 XA_MP3DEC_CONFIG_PARAM_CRC_CHECK subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_CRC_CHECK
Description	This command enables or disables CRC validation for error-protected Layer I and II streams. During the execution phase, CRC failures are signaled to the application through a non-fatal error code (see Initialization and Execution Errors).
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_SET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_CRC_CHECK</p> <p><i>pv_value</i> &<i>crc_check</i> – Pointer to CRC check variable</p>
Restrictions	0 – disable CRC validation (default); non-zero – enable CRC validation.

Example

```
int crc_check = 1;
res = (*api_func)(api_obj,
                  XA_API_CMD_SET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_CRC_CHECK,
                  (pVOID) &crc_check);
```

Errors

Common API Errors.

Table 3-3 XA_MP3DEC_CONFIG_PARAM_MCH_ENABLE subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_MCH_ENABLE
Description	This command enables or disables multi-channel decoding in the MP3 5.1-Channel Decoder library.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure.</p> <p><i>i_cmd</i> XA_API_CMD_SET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_MCH_ENABLE</p> <p><i>pv_value</i> &<i>mch_enable</i> – Pointer to multi-channel enable flag.</p>
Restrictions	<p>This flag is supported by the MP3 5.1-Channel Decoder library only.</p> <p>0 – disable multi-channel decoding; non-zero – enable multi-channel decoding (default).</p>

Example

```
int mch_enable = 0;
res = (*api_func)(api_obj,
                  XA_API_CMD_SET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_MCH_ENABLE,
                  (pVOID) &mch_enable);
```

Errors

Common API Errors.

Table 3-4 XA_MP3DEC_CONFIG_PARAM_DAB_MP2 subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_DAB_MP2
Description	This command enables or disables DAB-specific Scale Factor CRC checking.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure.</p> <p><i>i_cmd</i> XA_API_CMD_SET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_DAB_MP2</p> <p><i>pv_value</i> & <i>dabmp2</i> – Pointer to dabmp2 enable flag.</p>
Restrictions	0 – disable DAB-specific Scale Factor CRC validation (default); non-zero – enable DAB-specific Scale Factor CRC validation.

Example

```
int dabmp2 = 0;
res = (*api_func)(api_obj,
                  XA_API_CMD_SET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_DAB_MP2,
                  (pVOID) &dabmp2);
```

Errors

Common API Errors.

Table 3-5 XA_MP3DEC_CONFIG_PARAM_ACTIVATE_VLC_REWIND subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_ACTIVATE_VLC_REWIND
Description	This command enables or disables VLC rewind. This is a method to recover from bitstream overrun caused by a bitstream error, during the VLC decoding process. If this feature is disabled, the decoder will drop the frame.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure.</p> <p><i>i_cmd</i> XA_API_CMD_SET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_ACTIVATE_VLC_REWIND</p> <p><i>pv_value</i> & <i>activate_vlc_rewind</i> – Pointer to <i>activate_vlc_rewind</i> flag.</p>
Restrictions	0 – disable (default) 1 – enable.

Example

```
Int activate_vlc_rewind = 0;
res = (*api_func)(api_obj,
                  XA_API_CMD_SET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_ACTIVATE_VLC_REWIND,
                  (pVOID) & activate_vlc_rewind);
```

Errors

Common API Errors.

Table 3-6 XA_MP3DEC_CONFIG_PARAM_NONSTD_STRM_SUPPORT subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_NONSTD_STRM_SUPPORT
Description	This command enables or disables non-standard stream support by relaxing the standard validity checks for streams.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_SET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_NONSTD_STRM_SUPPORT</p> <p><i>pv_value</i> & <i>activate_nonstd</i> – Pointer to <i>activate_nonstd</i> flag.</p>
Restrictions	0 – disable (default) 1 – enable.

Example

```
Int activate_nonstd = 0;
res = (*api_func) (api_obj,
                  XA_API_CMD_SET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_NONSTD_STRM_SUPPORT,
                  (pVOID) & activate_nonstd);
```

Errors

Common API Errors.

XA_MP3DEC_CONFIG_NONFATAL_INVALID_PARAM_VALUE

3.4.3 XA_API_CMD_GET_CONFIG_PARAM

Table 3-7 XA_MP3DEC_CONFIG_PARAM_SAMP_FREQ subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_SAMP_FREQ
Description	This command gets the sampling frequency from the codec. The sampling frequency can be used for example to write a '.wav' file header or to initialize a DAC or sample rate converter for real-time payout. The sampling frequency (in Hz) is returned.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_SAMP_FREQ</p> <p><i>pv_value</i> &samp_freq – Pointer to sampling frequency variable</p>
Restrictions	None

Example

```
int samp_freq;
res = (*api_func) (api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_SAMP_FREQ,
                  (pVOID) &samp_freq);
```

Errors

Common API Errors.
XA_API_FATAL_MEM_ALLOC
pv_value is NULL

Table 3-8 XA_MP3DEC_CONFIG_PARAM_NUM_CHANNELS subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_NUM_CHANNELS
Description	This command gets the number of channels in the decoded bitstream. This information can be used to write a '.wav' file header or to initialize a DAC or sample rate converter for real-time payout.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure.</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_NUM_CHANNELS</p> <p><i>pv_value</i> &num_chan – Pointer to number of channels.</p>
Restrictions	None

Example

```
int num_chan;
res = (*api_func) (api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_NUM_CHANNELS,
                  (pVOID) &num_chan);
```

Errors

Common API Errors.

XA_API_FATAL_MEM_ALLOC

pv_value is NULL

Table 3-9 XA_MP3DEC_CONFIG_PARAM_CHMODE_INFO subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_CHMODE_INFO
Description	<p>This command gets the channel mode information present in the frame header. The information can be used to derive the channel mode (nibble 0) and the mode extension values (nibble 1). The channel mode information is decoded as specified:</p> <p>Bits 1:0 – 0 (stereo), 1 (joint stereo), 2 (dual mono), 3 (mono)</p> <p>Bit 4 – intensity stereo, if set to 1</p> <p>Bit 5 – mid-side stereo, if set to 1</p>
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure.</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_CHMODE_INFO</p> <p><i>pv_value</i> &chmode_info – Pointer to the channel mode variable.</p>
Restrictions	None

Example

```
int chmode_info;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_CHMODE_INFO,
                  (pVOID) &chmode_info);
```

Errors

Common API Errors.

XA_API_FATAL_MEM_ALLOC

pv_value is NULL

Table 3-10 XA_MP3DEC_CONFIG_PARAM_BITRATE subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_BITRATE
Description	This command gets the data rate (bit rate) of the input stream in kbps.
Actual Parameters	<i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure <i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM <i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_BITRATE <i>pv_value</i> <i>&bitrate</i> – Pointer to bit rate variable
Restrictions	None

Example

```
int bitrate;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_BITRATE,
                  (pVOID) &bitrate);
```

Errors

Common API Errors.

XA_API_FATAL_MEM_ALLOC

pv_value is NULL

Table 3-11 XA_MP3DEC_CONFIG_PARAM_PCM_WDSZ subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_PCM_WDSZ
Description	This command gets the output PCM word size in bits, which may be different from the one given by the user, if the user specified a value other than 16 or 24.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure.</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_PCM_WDSZ</p> <p><i>pv_value</i> &<i>pcm_wd_sz</i> – Pointer to PCM word size.</p>
Restrictions	None

Example

```
int pcm_wd_sz;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_PCM_WDSZ,
                  (pVOID) &pcm_wd_sz);
```

Errors

Common API Errors.
XA_API_FATAL_MEM_ALLOC
pv_value is NULL

Table 3-12 XA_MP3DEC_CONFIG_PARAM_MCH_STATUS subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_MCH_STATUS
Description	<p>This command gets the multi-channel status of the library and the input stream. The status may be one of the following:</p> <ul style="list-style-type: none"> 0 – multi-channel decoding not supported, 1 – multi-channel decoding disabled, 2 – multi-channel content not available, 3 – multi-channel content decoding in progress. <p>See Configuration Parameters on page 46.</p>
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure.</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_MCH_STATUS</p> <p><i>pv_value</i> &mch_status – Pointer to the multi-channel status variable.</p>
Restrictions	None

Example

```
int mch_status;
res = (*api_func) (api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_MCH_STATUS,
                  (pVOID) &mch_status);
```

Errors

Common API Errors.
XA_API_FATAL_MEM_ALLOC
pv_value is NULL

Table 3-13 XA_MP3DEC_CONFIG_PARAM_EXTN_PRESENT subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_EXTN_PRESENT
Description	This command indicates if an extension substream is present in the input stream. This command is supported only by the MP3 5.1-Channel Decoder.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure.</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_EXTN_PRESENT</p> <p><i>pv_value</i> &extn_present – Pointer to the extension substream present flag.</p>
Restrictions	None

Example

```
int extn_present;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_EXTN_PRESENT,
                  (pVOID) &extn_present);
```

Errors

Common API Errors.
XA_API_FATAL_MEM_ALLOC
pv_value is NULL

Table 3-14 XA_MP3DEC_CONFIG_PARAM_LFE_PRESENT subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_LFE_PRESENT
Description	This command indicates if the LFE channel is present in the input multi-channel stream. This command is supported only by the MP3 5.1-Channel Decoder.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_LFE_PRESENT</p> <p><i>pv_value</i> &lfe_present – Pointer to the LFE present flag</p>
Restrictions	None

Example

```
int lfe_present;
res = (*api_func) (api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_LFE_PRESENT,
                  (pVOID) &lfe_present);
```

Errors

Common API Errors

XA_API_FATAL_MEM_ALLOC

pv_value is NULL

Table 3-15 XA_MP3DEC_CONFIG_PARAM_NUM_XCHANS subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_NUM_XCHANS
Description	This command gets the number of extra channels in addition to the main audio channels and potentially the LFE channel. This command is supported only by the MP3 5.1-Channel Decoder.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_NUM_XCHANS</p> <p><i>pv_value</i> &num_xchan – Pointer to the number of extra channels variable</p>
Restrictions	None

Example

```
int num_xchan;
res = (*api_func) (api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_NUM_XCHANS,
                  (pVOID) &num_xchan);
```

Errors

Common API Errors
XA_API_FATAL_MEM_ALLOC
pv_value is NULL

Table 3-16 XA_MP3DEC_CONFIG_PARAM_CHAN_CONFIG subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_CHAN_CONFIG
Description	This command gets the channel configuration of the input stream. The valid channel configuration codes are listed in Configuration Parameters on page 46 . This command is supported only by the MP3 5.1-Channel Decoder.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_CHAN_CONFIG</p> <p><i>pv_value</i> &<i>chan_config</i> – Pointer to the channel configuration variable</p>
Restrictions	None

Example

```
int chan_config;
res = (*api_func) (api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_CHAN_CONFIG,
                  (pVOID) &chan_config);
```

Errors

Common API Errors.

XA_API_FATAL_MEM_ALLOC

pv_value is NULL

Table 3-17 XA_MP3DEC_CONFIG_PARAM_CHAN_MAP subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_CHAN_MAP
Description	This command gets the channel map specifying how the channels are arranged in the output buffer. See Configuration Parameters on page 46.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_CHAN_MAP</p> <p><i>pv_value</i> &<i>chan_map</i> – Pointer to the channel map variable</p>
Restrictions	None

Example

```
int chan_map;
res = (*api_func) (api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_CHAN_MAP,
                  (pVOID) &chan_map);
```

Errors

Common API Errors.
XA_API_FATAL_MEM_ALLOC
pv_value is NULL

Table 3-18 XA_MP3DEC_CONFIG_PARAM_DAB_MP2 subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_DAB_MP2
Description	This command gets the dabmp2 flag. See Configuration Parameters on page 46.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_DAB_MP2</p> <p><i>pv_value</i> &dabmp2 – Pointer to the channel map variable</p>
Restrictions	None

Example

```
int dabmp2;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_DAB_MP2,
                  (pVOID) &dabmp2);
```

Errors

Common API Errors.
XA_API_FATAL_MEM_ALLOC
pv_value is NULL

Table 3-19 XA_MP3DEC_CONFIG_PARAM_ORIGINAL_OR_COPY subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_ORIGINAL_OR_COPY
Description	This command gets the original/copy flag encoded in frame header. 1 – The bitstream is original 0 – The bitstream is copy
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_ORIGINAL_OR_COPY</p> <p><i>pv_value</i> <i>&IsOriginal</i> – Pointer to the flag variable</p>
Restrictions	<p>This API returns the value read from the `recently decoded frame header`. Hence this API should be called only after successful decoding of a frame.</p> <p>The return value may not be valid, if there is any frame decoding error.</p>

Example

```
int IsOriginal;
res = (*api_func) (api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_ORIGINAL_OR_COPY,
                  (pVOID) &IsOriginal);
```

Errors

Common API Errors.

XA_API_FATAL_MEM_ALLOC

pv_value is NULL

Table 3-20 XA_MP3DEC_CONFIG_PARAM_COPYRIGHT_FLAG subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_COPYRIGHT_FLAG
Description	This command gets the copyright flag encoded in the bitstream 1 – The bitstream is copy right protected 0 – There is no copy right in the stream
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_COPYRIGHT_FLAG</p> <p><i>pv_value</i> &IsCopyRigthProtected – Pointer to the flag variable</p>
Restrictions	<p>This API returns the value read from the `recently decoded frame header`. Hence this API should be called only after successful decoding of a frame.</p> <p>The return value may not be valid, if there is any frame decoding error.</p>

Example

```
int IsCopyRigthProtected;
res = (*api_func) (api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_COPYRIGHT_FLAG,
                  (pVOID) &IsCopyRigthProtected);
```

Errors

Common API Errors.

XA_API_FATAL_MEM_ALLOC

pv_value is NULL

Table 3-21 XA_MP3DEC_CONFIG_PARAM_MCH_EXT_HDR_INFO subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_MCH_EXT_HDR_INFO
Description	This command returns the header info read from the multi-channel extension header. This Info contains downmixing procedures, multi-channel audio playback info, info related to multi-lingual audio, etc. Interpretation of this information is given in ISO/IEC 13818 part 3.
Actual Parameters	<p><i>p_xa_module_obj</i> <i>api_obj</i> – Pointer to API structure</p> <p><i>i_cmd</i> XA_API_CMD_GET_CONFIG_PARAM</p> <p><i>i_idx</i> XA_MP3DEC_CONFIG_PARAM_MCH_EXT_HDR_INFO</p> <p><i>pv_value</i> &mchExtHdrInfo info – Pointer to the structure of type <i>xa_mch_ext_hdr_info_t</i> into which multi-channel extension header info is stored. The definition of the structure is present in <i>xa_mp3_dec_api.h</i></p>
Restrictions	<p>This API returns the value read from the `recently decoded frame header`. Hence this API should be called only after successful decoding of a frame.</p> <p>The return value may not be valid, if there is any frame decoding error.</p> <p>This API is available only in <i>mp3mch_dec</i>.</p>

Example

```
xa_mch_ext_hdr_info_t mchExtHdrInfo;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_MCH_EXT_HDR_INFO,
                  (pVOID) &mchExtHdrInfo);
```

Errors

Common API Errors.

XA_API_FATAL_MEM_ALLOC

pv_value is NULL

Table 3-22 XA_MP3DEC_CONFIG_PARAM_MCH_COPYRIGHT_ID_PTR subcommand

Subcommand	XA_MP3DEC_CONFIG_PARAM_MCH_COPYRIGHT_ID_PTR
Description	This command returns a pointer to an array of nine unsigned characters (representing 72 bits of copyright identification information received from the bitstream). The first bit is in bit 7 of <code>p_copyright_info[0]</code> and the last bit is in bit 0 of <code>p_copyright_info[8]</code> .
Actual Parameters	<p><code>p_xa_module_obj</code> <code>api_obj</code> – Pointer to API structure.</p> <p><code>i_cmd</code> <code>XA_API_CMD_GET_CONFIG_PARAM</code></p> <p><code>i_idx</code> <code>XA_MP3DEC_CONFIG_PARAM_MCH_COPYRIGHT_ID_PTR</code></p> <p><code>pv_value</code> <code>&p_copyright_info</code> – Pointer to <code>copyright_info</code> array.</p>
Restrictions	<p>The application should treat the array containing the copyright identification as read-only.</p> <p>As the information is available only after accumulating 72 bits, one from each frame, the application will get a valid pointer only after successful accumulation is done.</p> <p>When there is no copyright identification in the stream this API returns a NULL pointer.</p> <p>Also, when the accumulation is in progress and no prior valid identifier is available, this API returns a NULL pointer.</p> <p>The return value may not be valid, if there is any frame decoding error.</p> <p>This API is available only in <code>mp3mch_dec</code>.</p>

Example

```
char * p_copyright_info;
res = (*api_func)(api_obj,
                  XA_API_CMD_GET_CONFIG_PARAM,
                  XA_MP3DEC_CONFIG_PARAM_MCH_COPYRIGHT_ID_PTR,
                  (pVOID) &p_copyright_info);
```

Errors

Common API Errors.
XA_API_FATAL_MEM_ALLOC
`pv_value` is NULL

4. Introduction to the Example Test Bench

The supplied test bench consists of the following files:

- Test bench source files in `test/src`
 - `xa_mp3_dec_error_handler.c`
 - `xa_mp3_dec_sample_testbench.c`
 - `id3_tag_decode.c`
- Optional post processing test bench source files
 - See `readme.txt` in `test/build`
- Test bench include files in `test/include`
 - `id3_tag_decode.h`
- Makefile to build the executable in `test/build`
 - `makefile_testbench_sample`
- Sample parameter file to use during run in `test/build`
 - `paramfilesimple.txt`

4.1 Making the Executable

To build the application, follow these steps:

Go to `test/build`.

Enter:

```
xt-make -f makefile_testbench_sample clean <lib>
```

Where,

<lib> is mp2, mp3 or mp3mch

This will build the example decoder application `xa_<lib>_dec_test`

Note:

- Optional post processing can be built from the test bench source files. See `readme.txt` in `test/build`
- If you have source code distribution, you must build the <lib> library before you can build the test-bench.

You can build the library by following these steps:

1. Go to the build directory.

2. Enter:

```
$xt-make clean <lib> install
```

This will build the <lib> library and copy it to the lib directory.

4.2 Usage

The sample application executable can be run with direct command line options or with a parameter file.

The command line usage is as follows:

```
xt-run xa_<lib>_dec_test \
    -ifile:<infile> -ofile:<outfile> \
    [-pcmsz:<pcmbitwidth>] \
    [-crc:<crc_check>]
    [-mch:<mch_enable>]
    [-nonstd:<nonstd_enable>]
```

Where

<infile> is the name of the input MPEG audio file.

<outfile> is the name of the output file.

<pcmbitwidth> is the PCM bit-width which can be either 16 or 24 bits.

<crc_check> is 0 to disable or 1 to enable CRC validation.

<mch_enable> is 0 to disable or 1 to enable multi-channel decoding (mp3mch_dec only).

<nonstd_enable> is 0 to disable (default) or 1 to enable the standard validity checks for streams. The following command-line options are specific to error concealment (not supported by default).

```
-dabmp2:<dabmp2_enable>
-numch:<numch>
-numsamps_perch:<numsamps_perch>

-num_mute_frames:<num_mute_frames>
-num_rampdown_samps:<num_rampdown_samps>
-num_rampup_samps:<num_rampup_samps>
```

```
-alpha0x:<alpha>
```

```
-beta0x:<beta>
```

```
-force_mute:<force_mute>Where
```

<numch> Number of PCM channels, can be 1 or 2.

<numsamps_perch> Number of PCM samples per channel, can be <= 1152

<num_mute_frames> Number of frames to continue mute state during concealment phase

<num_rampdown_samps> Number of samples to apply ramp-down while entering concealment phase

<num_rampup_samps> Number of samples to apply ramp-up while exiting concealment phase

<alpha> Ramp down scale factor in 1.31 format
<beta> Ramp up scale factor in 1.31 format
<force_mute> 0 to disable, 1 to enable soft muting.
When set to 1, error concealment will forcefully activate and continue till this flag is set to zero

If no command line argument is given, the application reads the commands from the parameter file `paramfilesimple.txt` in the same directory as the executable.

The syntax for writing into the `paramfilesimple.txt` file is as follows:

```
@Start
@Input_path <path to be prepended to all input filenames>
@Output_path <path to be prepended to all output filenames>
<command line 1>
<command line 2>
....
@Stop
```

The MP3 Decoder can be run for multiple test files using different command lines. The syntax for command lines in the parameter file is the same as the syntax for specifying options on the command line to the test bench program.

-
- | | |
|-------------|---|
| Note | Generally, 16-bit output is used for applications. |
| Note | All the <code>@<command></code> s should be at the first column of a line except the <code>@New_line</code> command. |
| Note | All the <code>@<command></code> s are case sensitive. If the command line in the parameter file has to be broken to two parts on two different lines use the <code>@New_line</code> command. For example:

<pre><command line part 1> @New_line <command line part 2></pre> |
| Note | Blank lines will be ignored. |
| Note | Individual lines can be commented out using <code>"/"</code> at the beginning of the line. |
-

4.3 ID3 Decoding Example

Part of the MP3 decoder example test bench is a decoder for the ID3 container format. This container is used to carry information about the content of the encoded audio, which is added to the bitstream. There are two popular versions: ID3v1 and ID3v2. This section gives an introduction to the formats.

ID3v1

ID3v1 is placed towards the end of the MP3 file. To make it easy to detect, a fixed size of 128 bytes was chosen. The tag has the structure as shown in [Table 4-1: ID3v1 Structure](#) on page 76.

Table 4-1: ID3v1 Structure

Field	Size (in Bytes)
"TAG"	3
Song title	30
Artist	30
Album	30
Year	4
Comment	30
Genre	1

The first three bytes are always "TAG" and is the identification that this is an ID3 tag. The easiest way to decode an ID3v1 tag is to look for the word "TAG" 128 bytes from the end of a file.

ID3v2

ID3v2 is a general tagging format for audio, which makes it possible to store meta-data about the audio inside the audio file itself. The ID3 tag described in this document is mainly targeted at files encoded with MPEG-1/2 layer I, MPEG-1/2 layer II, MPEG-1/2 layer III and MPEG-2.5, but may work with other types of encoded audio or as a standalone format for audio meta-data.

ID3v2 is designed to be as flexible and expandable as possible to meet any new metadata information needs that might arise. To achieve this flexibility, ID3v2 is constructed as a container for several information blocks, called frames, whose format need not be known to the software that encounters them. At the start of every frame is a unique and predefined identifier, a size descriptor that allows software to skip unknown frames, and a flags field.

The overall tag structure for ID3v2 is as shown in [Table 4-2: ID3v2 Structure](#) on page 77.

Table 4-2: ID3v2 Structure Header (10 bytes)
Extended Header
Frames (variable length)
Padding
(variable length, OPTIONAL)
Footer (10 bytes, OPTIONAL)

5. Reference

- [1] *ISO/IEC 11172-3 Information technology -- Coding of moving pictures and associated audio for digital storage media at up to about 1,5 Mbit/s -- Part 3: Audio (MPEG-1)*
- [2] *ISO/IEC 13818-3 Information technology -- Generic coding of moving pictures and associated audio information -- Part 3: Audio (MPEG-2)*
- [3] *ETSI EN 300 401 V1.4.1 Radio Broadcasting Systems; Digital Audio Broadcasting (DAB) to mobile, portable and fixed receivers*