COMPREHENSIVE TECHNICAL SPECIFICATIONS - WEEKOOK V2

Project: Weekook - Cuisine à Domicile Platform **Environment**: Development
Date: 2026-02-18 (mise à jour 2026-10-28)
Tech Stack: React 18 + TypeScript + Vite 6 + Express.js + Prisma + MySQL

TABLE OF CONTENTS

1. PRISMA SCHEMA
2. DATABASE MODELS
3. BACKEND - SERVER ROUTES
4. ZOD VALIDATION SCHEMAS
5. MIDDLEWARE
6. CONFIGURATION & UTILITIES
7. EMAIL SYSTEM
8. FRONTEND ROUTES
9. API CLIENT & AUTH
10. ENVIRONMENT VARIABLES
11. PACKAGE DEPENDENCIES

PRISMA SCHEMA

File: `prisma/schema.prisma`

```
generator client {
  provider = "prisma-client-js"
}

datasource db {
  provider = "mysql"
  url      = env("DATABASE_URL")
}

// User model - All users (customers + kookers)
model User {
  id              Int       @id @default(autoincrement())
  email           String    @unique
  pendingEmail    String?   @map("pending_email")      // Email en attente de
confirmation
  emailVerified   Boolean   @default(true) @map("email_verified")  // false après
inscription jusqu'à vérification
  password        String
  firstName       String    @map("first_name")
  lastName        String    @map("last_name")
  phone           String?
  avatar          String?
  role            String    @default("user")  // "user", "kooker", "admin",
"suspended"
```

```
  isAdmin         Boolean   @default(false) @map("is_admin")
  createdAt       DateTime  @default(now()) @map("created_at")
  updatedAt       DateTime  @updatedAt @map("updated_at")

  kookerProfile        KookerProfile?
  userProfile          UserProfile?
  bookings             Booking[]        @relation("UserBookings")
  reviews              Review[]
  favorites            Favorite[]
  sentMessages         Message[]        @relation("SentMessages")
  receivedMessages     Message[]        @relation("ReceivedMessages")
  reviewsReceived      Review[]         @relation("ReviewsReceived")
  passwordResetTokens  PasswordResetToken[]

  @@map("users")
}

// Kooker professional profile
model KookerProfile {
  id              Int       @id @default(autoincrement())
  userId          Int       @unique @map("user_id")
  bio             String?   @db.Text
  specialties     Json?     // Array of specialty strings
  type            Json?     // Array of types: ["KOOK", "COURS"]
  city            String?
  address         String?
  experience      String?
  rating          Float     @default(0)
  reviewCount     Int       @default(0) @map("review_count")
  featured        Boolean   @default(false)
  verified        Boolean   @default(false)
  isCompany       Boolean   @default(false) @map("is_company")
  active          Boolean   @default(true)
  latitude        Float?    // Interne : calculé par le serveur depuis address +
city, jamais exposé
  longitude       Float?
  serviceRadiusKm Int       @default(30) @map("service_radius_km")  // Zone
d'intervention (km) autour de l'adresse
  stripeAccountId          String?   @map("stripe_account_id")
  stripeOnboardingComplete Boolean   @default(false)
@map("stripe_onboarding_complete")
  createdAt       DateTime  @default(now()) @map("created_at")
  updatedAt       DateTime  @updatedAt @map("updated_at")

  user            User      @relation(fields: [userId], references: [id])
  services        Service[]
  availabilities  Availability[]
  bookingsReceived Booking[] @relation("KookerBookings")
  reviewsReceived Review[]  @relation("KookerReviews")
  favoritedBy     Favorite[]
  testimonials    Testimonial[]
```

```
  @@map("kooker_profiles")
}

// User hosting profile (for hosting services at their place)
model UserProfile {
  id                  Int       @id @default(autoincrement())
  userId              Int       @unique @map("user_id")

  // Address
  address             String?
  addressComplement   String?   @map("address_complement")
  city                String?
  postalCode          String?   @map("postal_code")
  country             String?   @default("France")

  // Access
  accessCode          String?   @map("access_code")
  floor               String?
  intercom            String?
  parkingInfo         String?   @db.Text @map("parking_info")

  // Kitchen
  stoveType           String?   @map("stove_type")  // "gaz", "induction",
"électrique", "mixte"
  hasOven             Boolean   @default(false) @map("has_oven")
  hasDishwasher       Boolean   @default(false) @map("has_dishwasher")
  tableCapacity       Int?      @map("table_capacity")
  kitchenNotes        String?   @db.Text @map("kitchen_notes")

  // Dietary preferences
  dietaryRestrictions Json?     @map("dietary_restrictions")  // Array
  allergies           Json?     // Array

  // Notes for kooker
  hostingNotes        String?   @db.Text @map("hosting_notes")

  updatedAt           DateTime  @updatedAt @map("updated_at")

  user                User      @relation(fields: [userId], references: [id],
onDelete: Cascade)

  @@map("user_profiles")
}

// Kooker specialty type (reference data)
model KookerSpecialty {
  id              Int       @id @default(autoincrement())
  name            String    @unique
  icon            String?
  createdAt       DateTime  @default(now()) @map("created_at")

  @@map("kooker_specialties")
```

```
}

// Service offered by kooker (menu item)
model Service {
  id              Int       @id @default(autoincrement())
  kookerProfileId Int       @map("kooker_profile_id")
  title           String
  description     String?   @db.Text
  type            Json      // ["KOOK"] or ["COURS"] stored as JSON
  priceInCents    Int       @map("price_in_cents")
  durationMinutes Int       @map("duration_minutes")
  minGuests           Int?      @map("min_guests")
  maxGuests           Int       @default(1) @map("max_guests")
  active              Boolean   @default(true)
  allergens           Json?
  constraints         Json?
  specialty           Json?
  prepTimeMinutes     Int?      @map("prep_time_minutes")
  ingredientsIncluded Boolean   @default(false) @map("ingredients_included")
  equipmentProvided   Boolean   @default(false) @map("equipment_provided")
  ingredientsList                Json?     @map("ingredients_list")
  ingredientsBaseServings        Int?      @map("ingredients_base_servings")
  ingredientsPricePerGuestInCents Int?
@map("ingredients_price_per_guest_in_cents")
  ingredientsDefaultSource       String    @default("client")
@map("ingredients_default_source")  // "client" or "kooker"
  equipmentKooker                Json?     @map("equipment_kooker")
  extraGuestPriceInCents Int?   @map("extra_guest_price_in_cents")  // For COURS
only
  koursDifficulty     String?   @map("kours_difficulty")  // For COURS
  koursLocation       String?   @map("kours_location")    // For COURS
  createdAt       DateTime  @default(now()) @map("created_at")
  updatedAt       DateTime  @updatedAt @map("updated_at")

  kookerProfile   KookerProfile @relation(fields: [kookerProfileId], references:
[id])
  images          ServiceImage[]
  menuItems       MenuItem[]
  bookings        Booking[]
  messages        Message[]

  @@map("services")
}

// Service images gallery
model ServiceImage {
  id              Int       @id @default(autoincrement())
  serviceId       Int       @map("service_id")
  url             String
  alt             String?
  sortOrder       Int       @default(0) @map("sort_order")
  isCardImage     Boolean   @default(false) @map("is_card_image")
```

```
  createdAt       DateTime  @default(now()) @map("created_at")

  service         Service   @relation(fields: [serviceId], references: [id],
onDelete: Cascade)

  @@map("service_images")
}

// Menu item (part of a service)
model MenuItem {
  id              Int       @id @default(autoincrement())
  serviceId       Int       @map("service_id")
  category        String
  name            String
  description     String?
  sortOrder       Int       @default(0) @map("sort_order")

  service         Service   @relation(fields: [serviceId], references: [id],
onDelete: Cascade)

  @@map("menu_items")
}

// Booking - Reservation
model Booking {
  id              Int       @id @default(autoincrement())
  userId          Int       @map("user_id")
  kookerProfileId Int       @map("kooker_profile_id")
  serviceId       Int       @map("service_id")
  date            DateTime
  startTime       String    @map("start_time")  // HH:MM format
  endTime         String?   @map("end_time")
  guests          Int       @default(1)
  totalPriceInCents Int     @map("total_price_in_cents")
  status          String    @default("pending")  // "pending", "confirmed",
"awaiting_confirmation", "completed", "cancelled"
  notes           String?   @db.Text
  ingredientsSource String  @default("client") @map("ingredients_source")  //
"client" or "kooker"
  stripePaymentIntentId String? @map("stripe_payment_intent_id")
  paymentStatus   String    @default("none") @map("payment_status")  // "none",
"pending_authorization", "authorized", "captured", "refunded", "cancelled"
  awaitingConfirmationAt DateTime? @map("awaiting_confirmation_at")
  reminderSentAt1 DateTime? @map("reminder_sent_at_1")
  reminderSentAt2 DateTime? @map("reminder_sent_at_2")
  reminderSentAt3 DateTime? @map("reminder_sent_at_3")
  kookerReminderSentAt1 DateTime? @map("kooker_reminder_sent_at_1")
  kookerReminderSentAt2 DateTime? @map("kooker_reminder_sent_at_2")
  kookerReminderSentAt3 DateTime? @map("kooker_reminder_sent_at_3")
  createdAt       DateTime  @default(now()) @map("created_at")
  updatedAt       DateTime  @updatedAt @map("updated_at")
```

```
  user            User      @relation("UserBookings", fields: [userId], references:
[id])
  kookerProfile   KookerProfile @relation("KookerBookings", fields:
[kookerProfileId], references: [id])
  service         Service   @relation(fields: [serviceId], references: [id])
  payments        Payment[]
  reviews         Review[]

  @@map("bookings")
}

// Payment tracking
model Payment {
  id                    Int       @id @default(autoincrement())
  bookingId             Int       @map("booking_id")
  stripePaymentIntentId String    @map("stripe_payment_intent_id")
  type                  String    // "authorization", "capture", "refund",
"cancellation", "transfer"
  amountInCents         Int       @map("amount_in_cents")
  commissionInCents     Int?      @map("commission_in_cents")
  stripeTransferId      String?   @map("stripe_transfer_id")
  status                String    // "pending", "succeeded", "failed"
  metadata              Json?
  createdAt             DateTime  @default(now()) @map("created_at")

  booking               Booking   @relation(fields: [bookingId], references: [id])

  @@map("payments")
}

// Reviews / Ratings
model Review {
  id              Int       @id @default(autoincrement())
  userId          Int       @map("user_id")
  kookerProfileId Int       @map("kooker_profile_id")
  bookingId       Int?      @map("booking_id")
  type            String    @default("user_to_kooker")  // "user_to_kooker",
"kooker_to_user"
  targetUserId    Int?      @map("target_user_id")  // For kooker_to_user reviews
  rating          Int       // 1-5
  comment         String?   @db.Text
  status          String    @default("pending")  // "pending", "approved",
"rejected"
  createdAt       DateTime  @default(now()) @map("created_at")

  user            User      @relation(fields: [userId], references: [id])
  kookerProfile   KookerProfile @relation("KookerReviews", fields:
[kookerProfileId], references: [id])
  booking         Booking?  @relation(fields: [bookingId], references: [id])
  targetUser      User?     @relation("ReviewsReceived", fields: [targetUserId],
references: [id])
```

```
  @@map("reviews")
}

// Favorites
model Favorite {
  id              Int       @id @default(autoincrement())
  userId          Int       @map("user_id")
  kookerProfileId Int       @map("kooker_profile_id")
  createdAt       DateTime  @default(now()) @map("created_at")

  user            User      @relation(fields: [userId], references: [id])
  kookerProfile   KookerProfile @relation(fields: [kookerProfileId], references:
[id])

  @@unique([userId, kookerProfileId])
  @@map("favorites")
}

// Availability slots for kookers
model Availability {
  id              Int       @id @default(autoincrement())
  kookerProfileId Int       @map("kooker_profile_id")
  date            DateTime
  startTime       String    @map("start_time")  // HH:MM format
  endTime         String    @map("end_time")
  isAvailable     Boolean   @default(true) @map("is_available")
  createdAt       DateTime  @default(now()) @map("created_at")

  kookerProfile   KookerProfile @relation(fields: [kookerProfileId], references:
[id])

  @@map("availabilities")
}

// Internal messaging
model Message {
  id                  Int       @id @default(autoincrement())
  senderId            Int       @map("sender_id")
  receiverId          Int       @map("receiver_id")
  content             String    @db.Text
  read                Boolean   @default(false)
  kookerRecipientId   Int?      @map("kooker_recipient_id")  // For filtering by
kooker
  bookingId           Int?      @map("booking_id")           // Associated booking
  serviceId           Int?      @map("service_id")           // Associated service
  createdAt           DateTime  @default(now()) @map("created_at")

  sender          User      @relation("SentMessages", fields: [senderId],
references: [id])
  receiver        User      @relation("ReceivedMessages", fields: [receiverId],
references: [id])
  service         Service?  @relation(fields: [serviceId], references: [id])
```

```
  @@map("messages")
}

// System configuration
model Config {
  id        Int      @id @default(autoincrement())
  key       String   @unique
  value     String   @db.Text  // Stored as JSON string
  updatedAt DateTime @updatedAt @map("updated_at")

  @@map("configs")
}

// Messages du formulaire de contact (consultés dans l'admin)
model ContactMessage {
  id        Int      @id @default(autoincrement())
  name      String
  email     String
  subject   String?
  message   String   @db.Text
  userId    Int?     @map("user_id")
  read      Boolean  @default(false)
  createdAt DateTime @default(now()) @map("created_at")

  @@map("contact_messages")
}

// Testimonials for homepage
model Testimonial {
  id              Int       @id @default(autoincrement())
  kookerProfileId Int?      @map("kooker_profile_id")
  authorName      String    @map("author_name")
  authorRole      String?   @map("author_role")
  content         String    @db.Text
  rating          Int       @default(5)
  featured        Boolean   @default(false)
  createdAt       DateTime  @default(now()) @map("created_at")

  kookerProfile   KookerProfile? @relation(fields: [kookerProfileId], references:
[id])

  @@map("testimonials")
}

// Password reset tokens
model PasswordResetToken {
  id        Int      @id @default(autoincrement())
  userId    Int      @map("user_id")
  token     String   @unique
  expiresAt DateTime @map("expires_at")
  used      Boolean  @default(false)
```

```
  createdAt DateTime @default(now()) @map("created_at")

  user      User     @relation(fields: [userId], references: [id], onDelete:
Cascade)

  @@map("password_reset_tokens")
}

// Email verification and email change tokens
model EmailToken {
  id        Int      @id @default(autoincrement())
  userId    Int      @map("user_id")
  token     String   @unique
  type      String   // "verify" | "change_email"
  expiresAt DateTime @map("expires_at")
  used      Boolean  @default(false)
  createdAt DateTime @default(now()) @map("created_at")

  user      User     @relation(fields: [userId], references: [id], onDelete:
Cascade)

  @@map("email_tokens")
}

// Error logs
model ErrorLog {
  id         Int      @id @default(autoincrement())
  message    String   @db.Text
  stack      String?  @db.LongText
  route      String?
  method     String?
  statusCode Int?     @map("status_code")
  userId     Int?     @map("user_id")
  createdAt  DateTime @default(now()) @map("created_at")

  @@map("error_logs")
}

// Page load performance logs
model PageViewLog {
  id         Int      @id @default(autoincrement())
  page       String
  loadTimeMs Int      @map("load_time_ms")
  userId     Int?     @map("user_id")
  createdAt  DateTime @default(now()) @map("created_at")

  @@map("page_view_logs")
}
```

DATABASE MODELS

Model	Purpose	Key Fields
User	All platform users	id, email, password (bcrypt), firstName, lastName, phone, avatar, role, isAdmin
KookerProfile	Professional kooker information	userId, bio, specialties (JSON array, liste admin), type (JSON), city, address, serviceRadiusKm, latitude/longitude (internes, calculés), rating, reviewCount, verified, stripeAccountId
UserProfile	Hosting information for users	userId, address, city, kitchen details, dietary restrictions, allergies
Service	Offering (KOOK/COURS)	kookerProfileId, title, type, priceInCents, durationMinutes, maxGuests, ingredients info, equipment
ServiceImage	Images for services	serviceId, url, isCardImage, sortOrder
MenuItem	Menu items in service	serviceId, category, name, description
Booking	Reservation	userId, kookerProfileId, serviceId, date, startTime, status, totalPriceInCents, paymentStatus
Payment	Payment audit trail	bookingId, stripePaymentIntentId, type, amountInCents, status
Review	User ratings	userId, kookerProfileId, rating (1-5), comment, status (pending/approved)
Favorite	Bookmarked kookers	userId, kookerProfileId (unique constraint)
Availability	Kooker availability slots	kookerProfileId, date, startTime, endTime, isAvailable
Message	Messaging	senderId, receiverId, serviceId, content, read
Testimonial	Homepage testimonials	kookerProfileId, authorName, content, rating, featured
PasswordResetToken	Password recovery	userId, token, expiresAt, used
EmailToken	Email verification & change confirmation	userId, token (unique), type ("verify"|"change_email"), expiresAt, used
Config	System configuration	key, value (JSON)
ContactMessage	Formulaire de contact	name, email, subject, message, read, createdAt

ErrorLog	Server error tracking	message, stack, route, statusCode, userId
PageViewLog	Performance tracking	page, loadTimeMs, userId

BACKEND - SERVER ROUTES

AUTH ROUTES (`/api/v1/auth`)

POST `/register`

- **Rate Limit**: 50 req/15 min
- **Validation**: `registerSchema`
- **Body**:

```
{
  "email": "user@example.com",
  "password": "string (min 8 chars)",
  "firstName": "string",
  "lastName": "string"
}
```

- **Returns**: User object with kookerProfileId (or null)
- **Status Codes**: 201 (success), 409 (email exists), 400 (validation)

POST `/login`

- **Rate Limit**: 50 req/15 min
- **Validation**: `loginSchema`
- **Body**:

```
{
  "email": "user@example.com",
  "password": "string"
}
```

- **Returns**: User object with kookerProfileId
- **Sets Cookie**: `token` (httpOnly, secure, sameSite:strict, maxAge: 2h)
- **Status Codes**: 200 (success), 401 (invalid credentials), 400 (validation)

POST `/logout`

- **Returns**: `{ success: true, data: { message: "..." } }`

GET `/me` **(Protected)**

- **Returns**: Current user object with kookerProfileId
- **Status Codes**: 200, 401 (unauthorized)

POST `/forgot-password`

- **Rate Limit**: 5 req/15 min
- **Body**: `{ "email": "string" }`
- **Logic**: Generates 32-byte reset token, expires in 1 hour

- **Email Sent**: `sendPasswordResetEmail()`
- **Returns**: Always `{ success: true }` (never reveals if email exists)
- **Status Codes**: 200

POST `/reset-password`

- **Validation**: `resetPasswordSchema`
- **Body**: `{ "token": "string", "password": "string (min 8)" }`
- **Logic**: Verifies token, hashes password with bcrypt (10 rounds), marks token as used
- **Status Codes**: 200, 400 (invalid/expired token)

GET `/verify-email` (Email verification after registration)

- **Query**: `?token=<string>`
- **Logic**: Validates `EmailToken` (type="verify", not used, not expired) → sets `emailVerified=true`, marks token as used, issues JWT cookie
- **Redirects**: To `/` or `redirect` param on success
- **Status Codes**: 302 (redirect), 400 (invalid/expired token)

POST `/resend-verification` (Resend verification email)

- **Rate Limit**: 5 req / 15 min
- **Body**: `{ "email": "string" }` (or taken from session if authenticated)
- **Logic**: If account exists and `emailVerified=false` → generates new `EmailToken` (type="verify"), sends email
- **Returns**: Always `{ success: true }` (never reveals if email exists)
- **Status Codes**: 200

USERS ROUTES — EMAIL CHANGE

GET `/api/v1/users/confirm-email-change`

- **Query**: `?token=<string>`
- **Logic**: Validates `EmailToken` (type="change_email", not used, not expired) → sets `user.email = user.pendingEmail`, clears `pendingEmail`, marks token as used, issues new JWT cookie
- **Status Codes**: 302 (redirect to profile), 400 (invalid/expired token)

KOOKERS ROUTES (`/api/v1/kookers`)

GET `/` (Search with filters)

- **Query Params**:
  - `q` : Full-text search (name, bio, city, specialties, services)
  - `type` : Filter by type (KOOK/COURS) - checks service types
  - `specialty` : Filter by specialty array
  - `city` : Filter by city (database level if no `q`, JS level if `q`)
  - `minPrice` / `maxPrice` : Price range in euros (stored in cents)
  - `difficulty` : Course difficulty filter
  - `page` : 1-based pagination (default 1)
  - `limit` : Items per page (1-50, default 12)
- **Returns**: Paginated kookers with active services, featured/rating order
- **Response**:

```
{
  "success": true,
  "data": {
    "kookers": [...],
    "pagination": { "page": 1, "limit": 12, "total": 100, "totalPages": 9 }
  }
}
```

GET `/dashboard/stats` (Protected, Kooker Required)

- **Returns**:

```
{
  "totalBookings": 42,
  "pendingBookings": 3,
  "totalRevenue": 125000,  // in cents
  "avgRating": 4.5,
  "totalReviews": 28
}
```

GET `/:id` (Kooker Profile Detail)

- **Returns**: Complete kooker profile with:
  - user info (firstName, lastName, avatar, phone, createdAt)
  - services (active only) with images, menuItems
  - reviews (user_to_kooker, approved only)
  - availabilities (future only)
  - confirmedSlots (upcoming bookings with status)
- **Status Codes**: 200, 404 (not found), 400 (invalid ID)

GET `/profile/me` (Protected, Kooker Required)

- **Returns**: profil complet du kooker connecté + `user` (firstName, lastName, email, phone, avatar), adresse incluse ; sans `latitude`, `longitude`, `stripeAccountId`
- Fonctionne aussi pour un profil non validé (`active: false`) — contrairement à `GET /:id`
- Utilisé par l'onglet Profil du dashboard kooker
- **Status Codes**: 200, 401, 403 (not kooker), 404

POST `/become` (Protected, Create Kooker Profile)

- **Validation**: `becomeKookerSchema`
- **Body**:

```
{
  "bio": "string (optional)",
  "specialties": ["string array"],
  "type": ["KOOK" or "COURS"],
  "city": "string",
  "address": "string (optional)",
  "serviceRadiusKm": "number 1–200 (optional, défaut 30)",
  "experience": "string (optional)",
```

```
  "isCompany": "boolean (optional)"
}
```

- **Spécialités** : doivent appartenir à `configs.specialties` → sinon 400 *"Spécialité non proposée : X. Choisissez dans la liste."*
- **Position** : calculée par le serveur depuis `address` + `city` (`geocodeKookerLocation`) ; aucune coordonnée acceptée en entrée ni renvoyée
- **Creates**: KookerProfile with active=false
- **Updates**: User role to "kooker"
- **Invalidates**: Auth cache
- **Returns**: KookerProfile object
- **Status Codes**: 201, 409 (already kooker), 400 (validation)

PUT `/profile` (Protected, Kooker Required)

- **Validation**: `updateKookerProfileSchema`
- **Body**: Any subset of: bio, specialties, type, city, address, serviceRadiusKm, experience, isCompany
- **Logic**:
  - `specialties` vérifiées contre la liste admin (les valeurs déjà présentes sur le profil restent acceptées)
  - `address` ou `city` envoyé → position recalculée par le serveur (valeur non envoyée = valeur actuelle)
- **Returns**: Updated KookerProfile (sans latitude/longitude)
- **Status Codes**: 200, 403 (not kooker), 400 (validation)

SERVICES ROUTES (`/api/v1/services`)

GET `/search` (Search services — public)

- **Params**: `q` , `type` , `specialty` , `address` , `city` , `minPrice` , `maxPrice` , `difficulty` , `featured` , `date` , `page` (défaut 1), `limit` (défaut 12)
- **Filtres**:
  - Uniquement services `active: true` appartenant à un kooker `active: true`
  - `q` : recherche texte sur titre, description, prénom/nom kooker, spécialités kooker (requête SQL `LOWER(CAST(specialties AS CHAR)) LIKE %q%` → partiel, insensible à la casse)
  - `type` : `array_contains: [type]` sur le tableau JSON `type` du service
  - `specialty` : `array_contains` sur `kookerProfile.specialties` **OU** sur `service.specialty`
  - `address` : adresse de la prestation (texte ≤ 200), localisée par le serveur (`geocodeAddress` , BAN, score ≥ 0,5, cache 500) ; kookers actifs tels que `haversine(adresse, kooker) ≤ service_radius_km` . Adresse introuvable → `services: [] + addressNotFound: true` . Aucune distance ni coordonnée renvoyée
  - `city` : sur `kookerProfile.city` (sous-chaîne) — compatibilité, non utilisé par l'interface
  - `minPrice` / `maxPrice` : sur `priceInCents` (euros → centimes)
  - `difficulty` : sur `koursDifficulty` (COURS uniquement)
  - `featured` : `kookerProfile.featured = true`
  - `date` (YYYY-MM-DD) : filtre disponibilité — retourne uniquement les services dont le kooker a une disponibilité ce jour-là
- **Include**: images (isCardImage prioritaire), kookerProfile (id, city, rating, reviewCount, featured, verified, user)

- **Tri**: `kookerProfile.featured DESC` puis `kookerProfile.rating DESC`
- **Réponse**: `{ success, data: { services[], addressNotFound?: true, pagination: { page, limit, total, totalPages } } }`
- **Status Codes**: 200

> ⚠️ *Cette route est déclarée **avant** `/:id` dans le fichier pour éviter que "search" soit capturé comme un ID.*

GET `/kooker/:id` (Get all services for kooker)

- **Returns**: Array of services with images and menuItems
- **Ordering**: createdAt DESC

GET `/:id` (Get single service detail)

- **Returns**: Service with images, menuItems, kookerProfile (user details)
- **Status Codes**: 200, 404

POST `/` (Protected, Kooker Required, Create Service)

- **Validation**: `createServiceSchema`
- **Body**:

```
{
  "title": "string",
  "description": "string (optional)",
  "type": ["KOOK" or "COURS"],
  "priceInCents": 5000,  // e.g., 50 EUR
  "durationMinutes": 120,  // 0 pour un KOOK (durée désactivée en MVP)
  "minGuests": 1,
  "maxGuests": 6,
  "allergens": ["array"],
  "constraints": ["array"],
  "specialty": ["array"],
  "prepTimeMinutes": 30,
  "ingredientsIncluded": false,
  "equipmentProvided": true,
  "ingredientsList": [{ "name": "s", "quantity": "s", "unit": "s" }],
  "ingredientsBaseServings": 4,
  "ingredientsPricePerGuestInCents": 1000,
  "ingredientsDefaultSource": "client",
  "equipmentKooker": ["array"],
  "extraGuestPriceInCents": 500,  // For COURS
  "kcoursDifficulty": "débutant",  // For COURS
  "coursLocation": "chez moi",    // For COURS
  "menuItems": [{ "category": "s", "name": "s", "description": "s" }],
  "images": ["url1", "url2"]
}
```

- **Spécialités** : `specialty` doit appartenir à `configs.specialties` → sinon 400
- **Creates**: Service + ServiceImages + MenuItems
- **Returns**: Service with images and menuItems
- **Status Codes**: 201, 403 (not kooker), 400 (validation)

PUT `/card-image/:imageId` (Protected, Kooker Required)

- **Logic**: Sets one image as card image (clears others for this kooker)
- **Returns**: `{ "imageId": 123 }`
- **Status Codes**: 200, 403 (not owner), 404 (image not found)

PUT `/:id` (Protected, Kooker Required, Update Service)

- **Validation**: `updateServiceSchema` (all fields optional)
- **Logic**:
  - Verifies ownership
  - `specialty` vérifiée contre la liste admin (valeurs déjà présentes sur l'offre acceptées)
  - Replaces menuItems if provided
  - Preserves isCardImage flag on images if URL matches
  - If no card image previously, first image becomes card image
- **Returns**: Updated service with images and menuItems
- **Status Codes**: 200, 403 (not owner), 404, 400 (validation)

DELETE `/:id` (Protected, Kooker Required)

- **Logic**: Deletes service (cascade deletes images, menuItems via FK)
- **Status Codes**: 200, 403, 404

BOOKINGS ROUTES (`/api/v1/bookings`)

GET `/my` (Protected, Get user's bookings)

- **Returns**: Array of bookings with service, kookerProfile (user details), reviews
- **Ordering**: date DESC
- **Includes**: reviews (user_to_kooker only)

GET `/kooker` (Protected, Kooker Required, Get received bookings)

- **Returns**: Array of bookings for this kooker with user details, service
- **Ordering**: date DESC

GET `/:id` (Protected, Booking owner or kooker only)

- **Returns**: Complete booking with service details, kookerProfile, user
- **Status Codes**: 200, 403 (access denied), 404

POST `/` (Protected, Create Booking)

- **Validation**: `createBookingSchema`
- **Body**:

```
{
  "serviceId": 123,
  "date": "2026-03-01",
  "startTime": "19:00",
  "guests": 6,
  "notes": "optional notes",
  "ingredientsSource": "client"  // or "kooker"
}
```

- **Logic**:
  - Validates date is not in past

    - Checks service exists and is active
    - Verifies guests <= maxGuests
    - Auto-calculates price:
        - **COURS**: base + (guests-6) * extraGuestPriceInCents (if >6)
        - **KOOK**: base * guests
        - **Ingredients**: +ingredientsPricePerGuestInCents * guests if ingredientsSource="kooker"
    - Checks kooker has Stripe account + onboarding complete
    - Creates Stripe PaymentIntent (manual_capture)
    - Creates Payment audit record
- **Returns**: `{ booking, clientSecret }`
- **Status Codes**: 201, 400 (validation/past date), 404 (service not found)

POST `/:id/confirm-payment` (Protected, Booking owner)

- **Logic**:
    - Validates date not in past (cancels booking if so)
    - Verifies PaymentIntent status = requires_capture
    - Updates paymentStatus to "authorized"
    - Sends notifications: sendBookingRequestToKooker + system message
- **Returns**: `{ status: "authorized" }`
- **Status Codes**: 200, 400 (wrong payment status), 404

PUT `/:id/confirm-completion` (Protected, Booking owner)

- **Logic**:
    - Requires status = "awaiting_confirmation"
    - Sets status = "completed"
    - Calls executeStripeTransfer() to move funds to kooker
    - Sends emails and system message
- **Status Codes**: 200, 400 (wrong status), 404

PUT `/:id` (Protected, User if pending or Kooker if not completed/cancelled)

- **Validation**: `updateBookingDetailsSchema`
- **Body**: date, startTime, guests, notes (all optional)
- **Logic**:
    - User can edit only if pending
    - Kooker can edit if not completed/cancelled
    - Recalculates price if guests change (for KOOK type)
    - Sends modification emails with change summary
- **Returns**: Updated booking
- **Status Codes**: 200, 400, 403, 404

PUT `/:id/status` (Protected, Kooker Required)

- **Validation**: `updateBookingStatusSchema` (status: "confirmed" or "cancelled")
- **Logic**:
    - Validates booking date not in past
    - **If confirmed**: Stripe capture payment
    - **If cancelled**: Stripe cancel/refund
    - **If completed**: Stripe transfer to kooker
    - Sends notifications

- **Status Codes**: 200, 400 (wrong status/past date), 404

PUT `/:id/cancel` (Protected, Owner or Kooker)

- **Logic**:
  - Prevents cancellation if already cancelled/completed
  - Handles Stripe cancellation/refund
  - Sends notifications to both parties
- **Status Codes**: 200, 400, 404

REVIEWS ROUTES (`/api/v1/reviews`)

GET `/kooker/:id` (Get approved reviews for kooker)

- **Returns**: Array of reviews (type=user_to_kooker, status=approved) with user details
- **Ordering**: createdAt DESC

GET `/booking/:id` (Protected)

- **Returns**: All reviews for a booking
- **Status Codes**: 200, 401, 404

POST `/` (Protected, Create user-to-kooker review)

- **Validation**: `createReviewSchema`
- **Body**:

```
{
  "kookerProfileId": 123,
  "bookingId": 456,  // optional
  "rating": 5,
  "comment": "string"
}
```

- **Logic**:
  - Prevents self-review
  - If bookingId: verifies booking is completed, checks no existing review on booking
  - If no bookingId: checks no existing review per user per kooker
  - Creates review with status = "pending" (requires admin approval)
  - Sends `sendNewReviewPendingToAdmins()`
  - **Rating is NOT updated on profile until admin approves**
- **Returns**: Review object with status="pending"
- **Status Codes**: 201, 400, 409 (duplicate)

POST `/kooker-to-user` (Protected, Kooker Required)

- **Validation**: `createKookerReviewSchema`
- **Body**:

```
{
  "bookingId": 456,
  "rating": 5,
  "comment": "string"
}
```

- **Logic**:
  - Verifies booking belongs to this kooker
  - Verifies booking is completed
  - Kooker can rate independently — no prerequisite on client's review
  - Checks kooker hasn't already reviewed this booking
  - Creates review with status = "pending" (admin moderation required)
  - Does NOT affect kooker's rating/reviewCount
- **Returns**: Review object
- **Status Codes**: 201, 400, 404, 409

FAVORITES ROUTES (`/api/v1/favorites`)

GET `/` (Protected)

- **Returns**: User's favorites with kookerProfile (user, active services)
- **Ordering**: createdAt DESC

POST `/:kookerId` (Protected, Add favorite)

- **Logic**: Upsert (idempotent - return existing if already favorited)
- **Returns**: Favorite object
- **Status Codes**: 201, 404 (kooker not found)

DELETE `/:kookerId` (Protected)

- **Status Codes**: 200, 404

AVAILABILITY ROUTES (`/api/v1/availability`)

GET `/kooker/:id` (Get kooker's future availabilities)

- **Returns**: Array of availabilities (date >= today) ordered by date/startTime
- **Status Codes**: 200, 400 (invalid ID)

PUT `/` (Protected, Kooker Required, Batch upsert)

- **Body**:

```
{
  "availabilities": [
    { "date": "2026-03-01", "startTime": "19:00", "endTime": "22:00",
"isAvailable": true }
  ]
}
```

- **Logic**:
  - Deletes all future availabilities for this kooker
  - Creates new ones from request
- **Returns**: Array of newly created availabilities
- **Status Codes**: 200, 400

MESSAGES ROUTES (`/api/v1/messages`)

GET `/unread-count` (Protected)

- **Returns**: `{ count: 5 }`

GET `/conversations` (Protected)

- **Logic**:
  - Loads last 500 messages involving this user
  - Groups by partner + serviceId
  - Counts unread per conversation
  - Sorts by lastMessage date DESC
- **Returns**: Array of conversations with user, lastMessage, unreadCount, service

GET `/conversation/:userId` (Protected, Optional ?serviceId query)

- **Logic**:
  - Fetches messages between current and other user (optionally filtered by serviceId)
  - Marks all received messages as read
  - Both operations in parallel
- **Returns**: Array of messages ordered by createdAt ASC
- **Status Codes**: 200, 400 (invalid userID)

POST `/` (Protected, Send message)

- **Validation**: `sendMessageSchema`
- **Body**:

```
{
  "receiverId": 123,
  "content": "message text",
  "serviceId": 456,
  "kookerRecipientId": 789  // optional
}
```

- **Logic**:
  - Verifies receiver and service exist
  - Creates message
  - Sends email notification (with 5-min cooldown per recipient)
- **Returns**: Message with sender and receiver details
- **Status Codes**: 201, 404 (recipient/service not found), 400

DELETE `/conversation/:userId` (Protected, Optional ?serviceId query)

- **Logic**: Deletes all messages with userId (optionally filtered by serviceId)
- **Status Codes**: 200, 400

DELETE `/:id` (Protected)

- **Logic**: Only sender or receiver can delete
- **Status Codes**: 200, 403, 404

REVIEWS ROUTES - ADMIN (`/api/v1/admin/reviews`)

GET `/reviews` (Protected, Admin Required)

- **Query params**: `?status=pending|approved|rejected` , `?type=user_to_kooker|kooker_to_user` (optional), `page` , `limit`
- **Returns**: Paginated reviews of both types with user, kookerProfile, and targetUser details

- **Default**: all types returned if `?type` is omitted

PUT `/reviews/:id/status` (Protected, Admin Required)

- **Body**: `{ "status": "approved" | "rejected" }`
- **Logic**:
  - **If approved**: status → `approved` ; kooker rating recalculated **only for `user_to_kooker`** reviews
  - **If rejected**: review deleted ; kooker rating recalculated **only for `user_to_kooker`** reviews
  - `kooker_to_user` reviews never affect kooker's rating/reviewCount
- **Status Codes**: 200, 400, 404

DELETE `/reviews/:id` (Protected, Admin Required)

- **Logic**: Deletes review ; recalculates kooker rating **only if `user_to_kooker`**
- **Status Codes**: 200, 404

TESTIMONIALS ROUTES (`/api/v1/testimonials`)

GET `/` (Get featured testimonials)

- **Returns**: Array of featured testimonials (featured=true) with kookerProfile
- **Ordering**: createdAt DESC

POST `/` (Protected, Submit testimonial)

- **Body**: `{ "authorName": "s", "authorRole": "s", "content": "s", "rating": 5 }`
- **Validation**: content >= 10 chars, rating 1-5
- **Creates**: Testimonial with featured=false (requires admin to feature)
- **Status Codes**: 201, 400 (validation)

USERS ROUTES (`/api/v1/users`)

PUT `/profile` (Protected)

- **Validation**: `updateUserProfileSchema`
- **Body**: firstName, lastName, phone, email (all optional)
- **Logic**:
  - Checks email uniqueness if changed
  - Re-issues JWT if email changed (to keep cookie in sync)
- **Returns**: Updated user object
- **Status Codes**: 200, 409 (email taken), 400

PUT `/avatar` (Protected)

- **Body**: `{ "avatar": "url" }`
- **Returns**: Updated user
- **Status Codes**: 200, 400

GET `/hosting-profile` (Protected)

- **Returns**: UserProfile or null

PUT `/hosting-profile` (Protected)

- **Validation**: `updateHostingProfileSchema`
- **Body**: address, city, postalCode, kitchen details, dietary restrictions, allergies, hostingNotes (all optional)

- **Logic**: Upsert (create if not exists, update if exists)
- **Returns**: UserProfile
- **Status Codes**: 200, 400

UPLOAD ROUTES (`/api/v1/upload`)

POST `/` (Protected, Upload single file)

- **Middleware**: multer (5MB limit, JPEG/PNG/WebP/GIF only)
- **Logic**: Stores file with `${Date.now()}-${randomString}.ext` naming
- **Returns**:

```
{
  "success": true,
  "data": {
    "url": "/uploads/1234567-abc123.jpg",
    "filename": "1234567-abc123.jpg",
    "mimetype": "image/jpeg",
    "size": 102400
  }
}
```

- **Status Codes**: 201, 400 (no file/wrong type)

CONTACT ROUTES (`/api/v1/contact`)

POST `/` (Public)

- **Validation**: `createContactMessageSchema`
- **Rate limit**: 5 req / 15 min par IP
- **Body**: `{ "name": "string ≤100", "email": "email", "subject": "string ≤200 (optional)", "message": "string 1-5000" }`
- **Creates**: ContactMessage (`read = false`)
- **Status Codes**: 201, 400 (validation), 429

GEO ROUTES (`/api/v1/geo`)

Autocomplétion via les API publiques françaises (`server/src/lib/geo.ts`) : `geo.api.gouv.fr/communes` et `data.geopf.fr/geocodage/search` (timeout 8 s, une nouvelle tentative). Format d'une suggestion : `{ label, city, postalCode }` — **sans coordonnées**.

GET `/cities?q=` (Public)

- Nom de commune (≥ 2 caractères, tri par population) ou code postal à 5 chiffres → jusqu'à 6 communes (champ ville des formulaires kooker)

GET `/addresses?q=` (Public)

- Adresse (≥ 3 caractères, autocomplétion BAN) → jusqu'à 6 adresses (adresse de la prestation dans la recherche)

ADMIN ROUTES (`/api/v1/admin`)

GET `/config/public` (Public - no auth needed)

- **Returns**: Configuration for forms (commissionKours, commissionKook, specialties, units, etc.)

GET `/stats` (Protected, Admin Required)

- **Returns**: `{ userCount, kookerCount, bookingCount, revenueInCents }`

GET `/users` (Protected, Admin Required)

- **Query**: search, role, page, limit
- **Returns**: Paginated users with kooker profile info

PUT `/users/:id` (Protected, Admin Required)

- **Body**: role, suspended, isAdmin
- **Returns**: Updated user

DELETE `/users/:id` (Protected, Admin Required)

GET `/kookers` (Protected, Admin Required)

- **Query**: search, page, limit
- **Returns**: Paginated kookers with counts

PUT `/kookers/:id` (Protected, Admin Required)

- **Body**: featured, verified, active
- **Returns**: Updated kooker

GET `/reviews/kooker/:id` (Protected, Admin Required)

PUT `/reviews/:id/status` (Protected, Admin Required)

- **Recalculates kooker rating on approval**

DELETE `/reviews/:id` (Protected, Admin Required)

GET `/bookings` (Protected, Admin Required)

- **Query**: status, page, limit
- **Returns**: Paginated bookings

GET `/services` (Protected, Admin Required)

- **Returns**: Paginated services

GET `/testimonials` (Protected, Admin Required)

PUT `/testimonials/:id` (Protected, Admin Required)

DELETE `/testimonials/:id` (Protected, Admin Required)

GET `/contact-messages` (Protected, Admin Required)

- **Returns**: Tous les ContactMessage, `createdAt DESC`

PUT `/contact-messages/:id` (Protected, Admin Required)

- **Body**: `{ "read": boolean }`

DELETE `/contact-messages/:id` (Protected, Admin Required)

GET `/config` (Protected, Admin Required)

- **Returns**: All configuration keys/values

PUT `/config/:key` (Protected, Admin Required)

- **Body**: `{ "value": any }`
- **Upserts**: Config entry

GET `/kpis` (Protected, Admin Required)

- **Query**: period (day|week|month)
- **Returns**: Revenue, users, bookings, kookers with delta vs previous period

GET `/business-charts` (Protected, Admin Required)

- **Returns**: 12-week acquisition, booking status breakdown, top kookers, platform health, recent bookings

GET `/tech-stats` (Protected, Admin Required)

- **Returns**: DB ping time, table counts, upload folder size, error logs, page timings

---

STRIPE ROUTES (`/api/v1/stripe`)

GET `/config` (Public)

- **Returns**: `{ "publishableKey": "pk_..." }` (`STRIPE_PUBLISHABLE_KEY`) — utilisée par Stripe.js côté client

POST `/connect/onboard` (Protected, Kooker Required)

- **Logic**:
  - Type de compte selon `kookerProfile.isCompany` : `company` ou `individual`
  - Pas de compte Stripe → création d'un compte **Express** (FR, MCC 5812, capacités `card_payments` + `transfers`, metadata `kookerProfileId`) et enregistrement de `stripeAccountId`
  - Compte existant dont le `business_type` ne correspond plus → nouveau compte créé, `stripeOnboardingComplete` remis à `false`
  - Génère un lien d'onboarding (`refresh_url` = `/kooker-dashboard?stripe=refresh` , `return_url` = `/kooker-dashboard?stripe=return`)
- **Returns**: `{ "url": "https://connect.stripe.com/..." }`
- **Status Codes**: 200, 403 (not kooker), 503 (Stripe non configuré)

GET `/connect/status` (Protected, Kooker Required)

- **Returns**: `{ "connected": bool, "chargesEnabled": bool, "payoutsEnabled": bool, "onboardingComplete": bool }`
- Sans compte Stripe (ou Stripe non configuré) → tout à `false`
- Si `charges_enabled && payouts_enabled` et pas encore enregistré → `stripeOnboardingComplete = true` + tentative d'auto-validation du kooker (`tryAutoValidateKooker`)

POST `/webhook` (Public - no auth)

- **Body**: brut (`express.raw` , déclaré avant le parser JSON)
- **Signature Verification**: header `stripe-signature` + `STRIPE_WEBHOOK_SECRET` → 400 si absent ou invalide
- **Handles**:
  - `payment_intent.amount_capturable_updated` → booking `paymentStatus` `pending_authorization` → `authorized`
  - `payment_intent.payment_failed` → booking `paymentStatus = failed` , `status = cancelled`

    - `account.updated` (charges + payouts actifs) → `stripeOnboardingComplete = true` + auto-validation du kooker
- **Returns**: `{ "received": true }` (erreurs de traitement journalisées, réponse 200 quand même)

METRICS ROUTES (`/api/v1/metrics`)

POST `/page-view` (Public - no auth)

- **Body**: `{ "page": "string (tronqué à 100)", "loadTimeMs": number, "userId": number (optional) }`
- **Creates**: PageViewLog (temps de chargement affichés dans Admin → tech-stats)
- **Returns**: `{ "success": true }` — toujours, même en cas d'erreur (fire-and-forget) ; 400 si `page` ou `loadTimeMs` manquant
- Appelée par le hook client `usePageTiming`

ZOD VALIDATION SCHEMAS

Auth Schemas (`server/src/schemas/auth.ts`)

```
registerSchema = z.object({
  email: z.string().email('Email invalide'),
  password: z.string().min(8, 'Le mot de passe doit contenir au moins 8
caracteres'),
  firstName: z.string().min(1, 'Le prenom est requis'),
  lastName: z.string().min(1, 'Le nom est requis'),
});

loginSchema = z.object({
  email: z.string().email('Email invalide'),
  password: z.string().min(1, 'Le mot de passe est requis'),
});

forgotPasswordSchema = z.object({
  email: z.string().email('Email invalide'),
});

resetPasswordSchema = z.object({
  token: z.string().min(1, 'Token requis'),
  password: z.string().min(8, 'Le mot de passe doit contenir au moins 8
caractères'),
});
```

Booking Schemas (`server/src/schemas/booking.ts`)

```
createBookingSchema = z.object({
  serviceId: z.number({ required_error: 'serviceId est requis' }),
  date: z.string({ required_error: 'La date est requise' }),
  startTime: z.string({ required_error: "L'heure de debut est requise" }),
  guests: z.number().optional().default(1),
```

```
  notes: z.string().optional(),
  ingredientsSource: z.enum(['client', 'kooker']).optional().default('client'),
});

updateBookingStatusSchema = z.object({
  status: z.enum(['confirmed', 'cancelled'], {
    required_error: 'Le statut est requis',
    invalid_type_error: 'Statut invalide',
  }),
});

updateBookingDetailsSchema = z.object({
  date: z.string().regex(/^\d{4}-\d{2}-\d{2}$/, 'Format date invalide (YYYY-MM-
DD)').optional(),
  startTime: z.string().regex(/^\d{2}:\d{2}$/, 'Format heure invalide
(HH:MM)').optional(),
  guests: z.number().int().min(1).max(200).optional(),
  notes: z.string().max(2000).nullable().optional(),
});
```

Kooker Schemas (`server/src/schemas/kooker.ts`)

```
becomeKookerSchema = z.object({
  bio: z.string().optional(),
  specialties: z.array(z.string()),
  type: z.array(z.string()),
  city: z.string().min(1, 'La ville est requise'),
  experience: z.string().optional(),
  isCompany: z.boolean().optional(),
  address: z.string().optional(),
  phone: phoneSchema,
  serviceRadiusKm,
});

// Zone d'intervention en km autour de l'adresse (#82) — aucune coordonnée acceptée
serviceRadiusKm = z.number().int().min(1).max(200).optional();

updateKookerProfileSchema = z.object({
  bio: z.string().optional(),
  specialties: z.array(z.string()).optional(),
  type: z.array(z.string()).optional(),
  city: z.string().optional(),
  experience: z.string().optional(),
  address: z.string().optional(),
  isCompany: z.boolean().optional(),
  serviceRadiusKm,
});
// Les valeurs de `specialties` sont en plus vérifiées dans la route
// contre la liste admin (assertAllowedSpecialties, voir CONFIGURATION & UTILITIES)

updateUserProfileSchema = z.object({
```

```
  firstName: z.string().optional(),
  lastName: z.string().optional(),
  phone: z.string().optional(),
  email: z.string().email('Email invalide').optional(),
});

updateHostingProfileSchema = z.object({
  address: z.string().optional(),
  addressComplement: z.string().optional(),
  city: z.string().optional(),
  postalCode: z.string().optional(),
  country: z.string().optional(),
  accessCode: z.string().optional(),
  floor: z.string().optional(),
  intercom: z.string().optional(),
  parkingInfo: z.string().optional(),
  stoveType: z.enum(['gaz', 'induction', 'électrique', 'mixte']).optional(),
  hasOven: z.boolean().optional(),
  hasDishwasher: z.boolean().optional(),
  tableCapacity: z.number().int().min(1).max(100).optional(),
  kitchenNotes: z.string().optional(),
  dietaryRestrictions: z.array(z.string()).optional(),
  allergies: z.array(z.string()).optional(),
  hostingNotes: z.string().optional(),
});
```

Service Schemas (`server/src/schemas/service.ts`)

```
const menuItemSchema = z.object({
  category: z.string(),
  name: z.string(),
  description: z.string().optional(),
});

const ingredientItemSchema = z.object({
  name: z.string(),
  quantity: z.string(),
  unit: z.string(),
});

createServiceSchema = z.object({
  title: z.string().min(1, 'Le titre est requis'),
  description: z.string().optional(),
  type: z.array(z.string()).min(1, 'Au moins un type est requis'),
  priceInCents: z.number().min(0, 'Le prix doit etre positif'),
  durationMinutes: z.number().min(0), // 0 pour les KOOK (durée désactivée en MVP)
  minGuests: z.number().optional(),
  maxGuests: z.number().optional().default(1),
  allergens: z.array(z.string()).optional(),
  constraints: z.array(z.string()).optional(),
  specialty: z.array(z.string()).optional(),
```

```
  prepTimeMinutes: z.number().optional(),
  ingredientsIncluded: z.boolean().optional(),
  equipmentProvided: z.boolean().optional(),
  ingredientsList: z.array(ingredientItemSchema).optional(),
  ingredientsBaseServings: z.number().int().min(1).optional(),
  ingredientsPricePerGuestInCents: z.number().int().min(0).optional(),
  ingredientsDefaultSource: z.enum(['client', 'kooker']).optional(),
  equipmentKooker: z.array(z.string()).optional(),
  extraGuestPriceInCents: z.number().min(0).optional(),
  koursDifficulty: z.string().optional(),
  koursLocation: z.string().optional(),
  menuItems: z.array(menuItemSchema).optional(),
  images: z.array(z.string()).optional(),
});

updateServiceSchema = z.object({
  title: z.string().min(1).optional(),
  description: z.string().optional(),
  type: z.array(z.string()).optional(),
  priceInCents: z.number().min(0).optional(),
  durationMinutes: z.number().min(0).optional(),
  minGuests: z.number().optional(),
  maxGuests: z.number().optional(),
  active: z.boolean().optional(),
  allergens: z.array(z.string()).optional(),
  constraints: z.array(z.string()).optional(),
  specialty: z.array(z.string()).optional(),
  prepTimeMinutes: z.number().optional(),
  ingredientsIncluded: z.boolean().optional(),
  equipmentProvided: z.boolean().optional(),
  ingredientsList: z.array(ingredientItemSchema).optional(),
  ingredientsBaseServings: z.number().int().min(1).optional(),
  ingredientsPricePerGuestInCents: z.number().int().min(0).optional(),
  ingredientsDefaultSource: z.enum(['client', 'kooker']).optional(),
  equipmentKooker: z.array(z.string()).optional(),
  extraGuestPriceInCents: z.number().min(0).optional(),
  koursDifficulty: z.string().optional(),
  koursLocation: z.string().optional(),
  menuItems: z.array(menuItemSchema).optional(),
  images: z.array(z.string()).optional(),
});
```

Review Schemas (`server/src/schemas/review.ts`)

```
createReviewSchema = z.object({
  kookerProfileId: z.number({ required_error: 'kookerProfileId est requis' }),
  bookingId: z.number().optional(),
  rating: z.number().min(1, 'La note minimum est 1').max(5, 'La note maximum est
5'),
  comment: z.string().optional(),
});
```

```
createKookerReviewSchema = z.object({
  bookingId: z.number({ required_error: 'bookingId est requis' }),
  rating: z.number().min(1, 'La note minimum est 1').max(5, 'La note maximum est
5'),
  comment: z.string().optional(),
});
```

Contact Schemas (`server/src/schemas/contact.ts`)

```
createContactMessageSchema = z.object({
  name: z.string().trim().min(1, 'Le nom est requis').max(100),
  email: z.string().trim().email('Email invalide').max(255),
  subject: z.string().trim().max(200).optional(),
  message: z.string().trim().min(1, 'Le message est requis').max(5000),
});
```

Message Schemas (`server/src/schemas/message.ts`)

```
sendMessageSchema = z.object({
  receiverId: z.number({ required_error: 'receiverId est requis' }),
  content: z.string().min(1, 'Le contenu du message est requis'),
  kookerRecipientId: z.number().optional(),
  serviceId: z.number({ required_error: 'serviceId est requis' }),
});
```

MIDDLEWARE

Auth Middleware (`server/src/middleware/auth.ts`)

```
// Auth cache: TTL 60s, avoids 1 DB query per request
const AUTH_CACHE_TTL = 60_000;
const authCache = new Map<number, { data: ...; expiresAt: number }>();

async function authenticate(req, res, next):
  - Retrieves token from cookies
  - Verifies JWT (throws if invalid)
  - Checks cache first (60s TTL)
  - Falls back to DB query: user.findUnique()
  - Implements sliding session:
    * If token age > 30 min: issue fresh token (extends absolute 7-day session)
    * Otherwise: refresh cookie expiry (reset 2h inactivity timer)
  - Sets req.user with: userId, email, role, isAdmin, kookerProfileId
  - Returns 401 on failure

function requireKooker(req, res, next):
  - Checks req.user.kookerProfileId exists
  - Returns 403 "Acces reserve aux kookers" (authenticated but insufficient role)
```

```
function requireAdmin(req, res, next):
  - Checks req.user.isAdmin === true
  - Returns 403 "Acces reserve aux administrateurs" (authenticated but insufficient
role)

// Note: 401 = not authenticated (no/invalid JWT), 403 = authenticated but wrong
role

function invalidateAuthCache(userId):
  - Called after user profile/role changes
  - Clears cache entry so next request refetches from DB
```

Validation Middleware (`server/src/middleware/validate.ts`)

```
function validate(schema: ZodSchema):
  - Calls schema.safeParse(req.body)
  - Returns 400 + fieldErrors if invalid
  - Sets req.body = result.data if valid
  - Logs errors to console for debugging
```

Error Handler Middleware (`server/src/middleware/errorHandler.ts`)

```
function errorHandler(err, req, res, next):
  - If AppError: returns status + message as JSON
  - Otherwise (unexpected):
    * Logs to console
    * Creates ErrorLog entry (fire-and-forget)
    * Returns generic 500 error
```

Rate Limit Middleware (`server/src/middleware/rateLimit.ts`)

```
function rateLimit(maxRequests: number = 5, windowMs: number = 15*60*1000):
  - In-memory tracking by IP
  - Returns 429 if exceeded
  - Window resets after windowMs
  - ⚠️ Compteur partagé entre toutes les routes limitées (une seule Map par IP)

Utilisé sur : auth (login, register, forgot-password, resend-verification) et `POST
/contact` (5 / 15 min).
```

Upload Middleware (`server/src/middleware/upload.ts`)

```
multer config:
  - Storage: diskStorage to /uploads folder
  - Filename: ${Date.now()}-${random-string}.ext
  - File filter: JPEG, PNG, WebP, GIF only
```

```
  - Limit: 5MB per file
  - Error message: "Type de fichier non autorise..."
```

CONFIGURATION & UTILITIES

Env Config (`server/src/config/env.ts`)

```
export const env = {
  PORT: 3001,
  JWT_SECRET: "...",
  NODE_ENV: "development" | "validation" | "production",
  CORS_ORIGIN: "http://localhost:5173",
  COOKIE_DOMAIN: "localhost",
  RESEND_API_KEY: "re_...",
  APP_URL: "https://dev.weekook.com",
  STRIPE_SECRET_KEY: "sk_test_...",
  STRIPE_PUBLISHABLE_KEY: "pk_test_...",
  STRIPE_WEBHOOK_SECRET: "whsec_...",
};
```

JWT Utilities (`server/src/utils/jwt.ts`)

```
const JWT_MAX_AGE = '7d';  // Absolute session max
const INACTIVITY_TIMEOUT_MS = 1 * 60 * 60 * 1000;  // 1 hour
const TOKEN_REFRESH_THRESHOLD_S = 30 * 60;  // Refresh if >30min old

interface TokenPayload {
  userId: number;
  email: string;
  iat?: number;  // Issued at
  exp?: number;  // Expiration
}

function signToken(payload: { userId, email }): string
  - Signs with HS256
  - Expiry: 7 days

function verifyToken(token: string): TokenPayload
  - Throws on invalid/expired
```

Error Classes (`server/src/utils/errors.ts`)

```
class AppError extends Error {
  constructor(message: string, statusCode: number = 500)

class UnauthorizedError extends AppError {
  statusCode: 401
```

```
class NotFoundError extends AppError {
  statusCode: 404

class ValidationError extends AppError {
  statusCode: 400

class ForbiddenError extends AppError {
  statusCode: 403
```

Specialties (`server/src/utils/specialties.ts`)

```
assertAllowedSpecialties(values: string[] | undefined, existing: unknown = []):
Promise<void>
  - Liste autorisée = configs.specialties + valeurs déjà enregistrées (existing)
  - Lance AppError 400 "Spécialité non proposée : X. Choisissez dans la liste."
sinon
  - Utilisé par POST /kookers/become, PUT /kookers/profile, POST /services, PUT
/services/:id
```

Geo (`server/src/lib/geo.ts`)

```
suggestCities(query): Promise<PlaceSuggestion[]>       // communes, sans coordonnées
suggestAddresses(query): Promise<PlaceSuggestion[]>    // adresses BAN, sans
coordonnées
geocodeAddress(address, expectedCity?): Promise<Coordinates | null>
  // BAN, score ≥ 0,5 ; expectedCity : résultat dans cette commune (comparaison du
nom,
  // la BAN renvoie les codes d'arrondissement pour Paris/Lyon/Marseille) ; cache
500
geocodeKookerLocation(address, city): Promise<Coordinates | null>
  // commune via la ville → adresse dans cette commune, sinon centre de la commune
backfillKookerCoordinates(): Promise<void>             // au démarrage, kookers sans
position
```

Tâches au démarrage (`server/src/app.ts`)

1. `seedConfig()` — valeurs de config par défaut
2. `normalizeKookerSpecialties()` — convertit en listes JSON les `specialties` stockées en texte (`JSON_TYPE = 'STRING'`)
3. Après `listen` : `backfillKookerCoordinates()` en arrière-plan

EMAIL SYSTEM

Email Functions (`server/src/lib/email.ts`)

All emails use Resend API + lazy initialization (only creates client if RESEND_API_KEY set).

Email Cooldown: 5 minutes per recipient (in-memory map).

Key Functions:

- **sendPasswordResetEmail**(userEmail, userName, resetUrl)
  - Subject: "Réinitialisation de votre mot de passe Weekook"
  - Link valid 1 hour
- **sendBookingRequestToKooker**(kookerEmail, kookerName, clientName, serviceName, date, startTime, guests, totalPriceInCents)
  - Subject: `Nouvelle réservation de ${clientName} — ${serviceName}`
  - Info box: Prestation, Date, Heure, Convives, Montant
- **sendBookingConfirmedToUser**(userEmail, userName, kookerName, serviceName, date, startTime, guests, totalPriceInCents)
  - Subject: `Réservation confirmée — ${serviceName} avec ${kookerName}`
- **sendBookingCancelledToUser**(userEmail, userName, kookerName, serviceName, date)
  - Subject: `Réservation annulée — ${serviceName}`
- **sendBookingCancelledToKooker**(kookerEmail, kookerName, clientName, serviceName, date)
- **sendBookingModifiedToKooker**(kookerEmail, kookerName, clientName, serviceName, changes: string, bookingId)
  - changes formatted as bullet list
- **sendBookingModifiedToUser**(userEmail, userName, kookerName, serviceName, changes, bookingId)
- **sendPendingReminderToKooker1/2/3**(...)
  - Reminder emails (0h, 24h, 48h after pending)
- **sendBookingExpiredToUser/Kooker**(...)
  - Auto-cancelled after 72h no response
- **sendConfirmationRequestToUser**(userEmail, userName, kookerName, serviceName, date, startTime, bookingId)
  - Request user confirms prestation happened
- **sendConfirmationReminder1/2ToUser**(...)
  - Reminder 24h and 36h after prestation
- **sendAutoConfirmationToUser**(...)
  - Auto-validated after 48h
- **sendCompletionToKooker**(kookerEmail, kookerName, clientName, serviceName, date, totalPriceInCents)
  - Subject: `Paiement en cours — ${serviceName}`
- **sendNewReviewPendingToAdmins**(reviewerName, kookerName, rating, comment, kookerProfileId)
  - Notifies all admin users

- Stars display (★☆)

FRONTEND ROUTES

Router Configuration (`client/src/router/index.tsx`)

All pages except login/reset-password are wrapped with PageLayout (navbar + footer). Protected routes require authentication + redirect to /connexion if not logged in. Admin routes require authentication + isAdmin=true + redirect to /tableau-de-bord otherwise.

Path	Component	Protection	Purpose
`/`	HomePage	Public	Hero, featured services (ServiceCard), testimonials, FAQ
`/recherche`	SearchPage	Public	Search & filter services (ServiceCard) — appel `GET /services/search`
`/kooker/:id`	KookerProfilePage	Public	Public kooker profile + services + reviews
`/prestation/:id`	ServiceDetailPage	Public	Détail d'une prestation : galerie, description, prix, encart kooker, CTA réserver
`/tarification`	PricingPage	Public	Pricing info (retirée du header et du footer)
`/a-propos`	AboutPage	Public	About page
`/avantages`	BenefitsPage	Public	Benefits page
`/confiance`	TrustPage	Public	Trust & guarantee page
`/faq`	FaqPage	Public	FAQ page
`/connexion`	LoginPage	Public	Login/Register split-screen
`/verifier-email`	VerifyEmailPage	Public	Email verification after registration
`/confirmer-email`	ConfirmEmailChangePage	Public	Email change confirmation
`/contact`	ContactPage	Public	Contact form → `POST /contact`
`/reinitialiser-mot-de-passe`	ResetPasswordPage	Public	Password reset form
`/tableau-de-bord`	UserDashboardPage	Protected	User bookings, favorites
`/devenir-kooker`	BecomeKookerPage	Protected	Form to become kooker

`/kooker-dashboard`	KookerDashboardPage	Protected	Kooker stats, bookings, services, planning
`/kooker-dashboard/menu/nouveau`	CreateMenuPage	Protected	Create new service
`/kooker-dashboard/menu/:id/editer`	EditMenuPage	Protected	Edit service
`/reservation`	BookingPage	Protected	Booking confirmation flow
`/reservation/:id`	BookingDetailPage	Protected	Booking detail + confirm/cancel
`/messagerie`	MessagesPage	Protected	Messaging interface
`/mon-profil`	UserProfilePage	Protected	Edit user profile + hosting info
`/admin`	AdminLayout	Admin Protected	Admin dashboard frame
`/admin/utilisateurs`	AdminUsersPage	Admin	User management
`/admin/kookers`	AdminKookersPage	Admin	Kooker management
`/admin/reservations`	AdminBookingsPage	Admin	Booking management
`/admin/services`	AdminServicesPage	Admin	Service management
`/admin/temoignages`	AdminTestimonialsPage	Admin	Testimonials management
`/admin/avis`	AdminReviewsPage	Admin	Review moderation (pending/approved/rejected
`/admin/faq`	AdminFaqPage	Admin	FAQ management
`/admin/messages-contact`	AdminContactMessagesPage	Admin	Messages du formulaire de contact
`/admin/configuration`	AdminConfigPage	Admin	System config
`*`	NotFoundPage	Public	404 page

Composants partagés liés

Composant	Rôle
`components/common/PlaceAutocomplete.tsx`	Champ avec suggestions : `kind="cities"` (`GET /geo/cities`, formulaires kooker) ou `kind="addresses"` (`GET /geo/addresses`, recherche) ; exporte `SERVICE_RADIUS_OPTIONS` = [5, 10, 20, 30, 50, 100]
`components/common/SpecialtyPicker.tsx`	Choix des spécialités parmi `GET /admin/config/public` ; valeurs hors liste affichées « hors liste », retirables uniquement

`lib/utils.ts` → `hasDuration(type, minutes)`	Durée affichée uniquement pour les COURS avec durée > 0

API CLIENT & AUTH

API Client (`client/src/lib/api.ts`)

```
const BASE_URL = '/api/v1';

interface ApiResponse<T> {
  success: boolean;
  data?: T;
  error?: string;
  details?: Record<string, string[]>;  // Zod validation errors
}

async function request<T>(method, path, body?): Promise<ApiResponse<T>>
  - Credentials: include (sends cookies)
  - Content-Type: application/json
  - Throws on HTTP error (after parsing response)

export const api = {
  get: <T>(path) => request('GET', path),
  post: <T>(path, body?) => request('POST', path, body),
  put: <T>(path, body?) => request('PUT', path, body),
  delete: <T>(path) => request('DELETE', path),
  upload: <T>(path, formData) => fetch + FormData (no JSON header),
};
```

Auth Context (`client/src/contexts/AuthContext.tsx`)

```
interface User {
  id: number;
  email: string;
  firstName: string;
  lastName: string;
  phone?: string;
  avatar?: string;
  role: string;  // "user", "kooker", "admin", "suspended"
  isAdmin?: boolean;
  kookerProfileId?: number | null;
}

interface AuthContextType {
  user: User | null;
  isLoading: boolean;
  login: (email, password) => Promise<User>;
  register: (data) => Promise<void>;
  logout: () => Promise<void>;
```

```
  refreshUser: () => Promise<void>;
}

function AuthProvider({ children }):
  - useEffect: calls refreshUser() on mount
  - setIsLoading(false) after initial check
  - Provides context to children

export function useAuth():
  - Returns AuthContextType
  - Throws if used outside AuthProvider
```

ENVIRONMENT VARIABLES

`.env.example`

```
# Base de données MySQL
DATABASE_URL="mysql://USER:PASSWORD@HOST:3306/DATABASE_NAME"

# JWT Secret (générer une clé unique par environnement)
JWT_SECRET="change-me-with-a-strong-secret"

# Port du serveur Express
PORT=3001

# Environnement
NODE_ENV=development  # development | validation | production

# CORS - URL du frontend
CORS_ORIGIN=http://localhost:5173

# Cookie domain
COOKIE_DOMAIN=localhost

# Stripe (paiements)
STRIPE_SECRET_KEY=sk_test_...
STRIPE_PUBLISHABLE_KEY=pk_test_...
STRIPE_WEBHOOK_SECRET=whsec_...

# Resend (emails transactionnels)
RESEND_API_KEY=re_...

# URL de l'application (utilisée dans les liens des emails)
APP_URL=https://dev.weekook.com
```

PACKAGE DEPENDENCIES

Root `package.json`

```
{
  "workspaces": ["client", "server", "shared"],
  "scripts": {
    "dev": "concurrently npm:dev:server npm:dev:client",
    "dev:client": "npm run dev --workspace=client",
    "dev:server": "npm run dev --workspace=server",
    "build": "npm run build --workspace=client && npm run build --workspace=server",
    "db:migrate": "npx prisma migrate dev --schema=prisma/schema.prisma",
    "db:seed": "npx tsx prisma/seed.ts",
    "db:push": "npx prisma db push --schema=prisma/schema.prisma",
    "db:generate": "npx prisma generate --schema=prisma/schema.prisma"
  },
  "devDependencies": {
    "concurrently": "^8.2.2",
    "typescript": "^5.4.5",
    "tsx": "^4.7.1",
    "prisma": "^5.11.0"
  },
  "dependencies": {
    "@prisma/client": "^5.11.0"
  }
}
```

Server `package.json`

Dependencies:

- `@prisma/client` ^5.11.0 - ORM
- `bcrypt` ^5.1.1 - Password hashing
- `cookie-parser` ^1.4.6 - Cookie middleware
- `cors` ^2.8.5 - CORS middleware
- `dotenv` ^16.4.5 - Environment variables
- `express` ^4.18.2 - Web framework
- `helmet` ^7.1.0 - Security headers
- `jsonwebtoken` ^9.0.2 - JWT signing/verification
- `multer` ^1.4.5-lts.1 - File upload
- `node-cron` ^4.2.1 - Scheduled tasks
- `resend` ^6.9.3 - Email API
- `stripe` ^20.4.1 - Payment processing
- `zod` ^3.22.4 - Input validation

DevDependencies:

- Various @types packages
- `tsx` ^4.7.1 - TypeScript executor
- `typescript` ^5.4.5

Scripts:

- `npm run dev` - Run with tsx watch
- `npm run build` - TypeScript compilation
- `npm start` - Run compiled dist/app.js

Client `package.json`

Key Dependencies:

- `react` ^18.3.1
- `react-router-dom` ^6.22.3 - Routing
- `@radix-ui/*` - 27+ headless UI components
- `@stripe/react-stripe-js` ^5.6.1 - Stripe integration
- `react-hook-form` ^7.55.0 - Form handling
- `tailwindcss` ^4.0.0 - Styling
- `recharts` ^2.15.2 - Charts
- `sonner` ^2.0.3 - Toast notifications
- `framer-motion` ^11.0.0 - Animations
- `lucide-react` ^0.487.0 - Icons

DevDependencies:

- `vite` ^6.3.5 - Build tool
- `@vitejs/plugin-react-swc` ^3.10.2 - Fast React transformation
- `typescript` ^5.4.5
- `tailwindcss` ^4.0.0

Scripts:

- `npm run dev` - Vite dev server (port 5173)
- `npm run build` - TypeScript + Vite build
- `npm run preview` - Preview production build

Vite Config:

- Plugins: React SWC, Tailwind CSS
- Alias: `@` -> `src/`
- Proxy: `/api` and `/uploads` to `http://localhost:3001`
- Build target: esnext

SUMMARY

Weekook V2 is a full-stack booking platform for culinary services using:

- **Frontend**: React 18 + TypeScript + Vite 6 + Tailwind CSS 4 + Radix UI + Stripe.js
- **Backend**: Express.js + Prisma ORM + MySQL
- **Auth**: JWT in httpOnly cookies with sliding sessions (2h inactivity, 7d absolute max)
- **Payments**: Stripe (manual capture, transfers to kooker on completion)
- **Validation**: Zod schemas on both client input validation + server enforcement
- **Email**: Resend API with templates for bookings, password resets, reviews
- **Admin**: Comprehensive dashboard for KPIs, user management, content moderation

85 API endpoints (décompte des routes déclarées dans `server/src/routes/*.ts`, au 2026-10-28) :

Préfixe	Nb	Couverture
`/auth`	8	register, login, logout, me, forgot/reset password, vérification email

`/kookers`	6	recherche, profil public, profil du kooker connecté, stats dashboard, devenir kooker, profil
`/services`	7	recherche (adresse / zone d'intervention), CRUD, image de carte
`/bookings`	9	cycle de vie complet avec Stripe
`/reviews`	4	user→kooker, kooker→user, consultation
`/messages`	6	messagerie interne + notifications email
`/favorites`	3	liste, ajout, retrait
`/availability`	2	lecture, mise à jour batch
`/testimonials`	2	lecture, soumission
`/users`	5	profil, avatar, profil d'accueil, changement d'email
`/upload`	1	upload de fichier
`/geo`	2	autocomplétion communes et adresses
`/contact`	1	formulaire de contact public
`/stripe`	4	config publique, Connect onboarding, statut, webhook
`/metrics`	1	temps de chargement des pages
`/admin`	24	config, stats, KPIs, graphiques, utilisateurs, kookers, avis, réservations, services, témoignages, messages de contact

Key Features:

- Rate limiting on auth endpoints
- Auth cache (60s TTL)
- Sliding sessions with token refresh
- Price in cents (stored/computed)
- Duration in minutes
- JSON fields for flexible arrays (specialties, types, allergens) — toujours des listes natives
- Spécialités limitées à la liste admin (UI + serveur)
- Accessibility (Radix UI, keyboard navigation)
- Responsive design (Tailwind responsive utilities)
- Error logging to DB
- Performance page view tracking

End of Technical Specifications Document