

Day 7 - Dataset Receipt & Initial Inspection

Dataset Description :

- Dataset Shape : 399 Rows and 6 columns are available
- Column Description :
 - binary bit R → Received bit (after detection)
 - Binary bit S → Sent/Transmitted bit (Target Label)
 - Analog value → ADC reading (Feature)
 - Analog Voltage → Converted ADC voltage (Feature)
 - NTU → Turbidity level (Feature)
 - S No → Just index (drop it)
- Dataset size : 12 Kb

S No	binary bit	Binary bit	Analog value	Analog Voltage	NTU
1	1	1	125	0.610351563	1-2NTU
2	0	0	101	0.493164063	1-2NTU
3	1	1	123	0.600585938	1-2NTU
4	0	0	101	0.493164063	1-2NTU
5	0	0	95	0.463867188	1-2NTU
6	0	0	99	0.483398438	1-2NTU
7	1	1	142	0.693359375	1-2NTU
8	0	0	97	0.473632813	1-2NTU
9	0	0	98	0.478515625	1-2NTU
10	0	0	98	0.478515625	1-2NTU

Input Features:

- Analog value
- Analog Voltage
- NTU

Target:

- Binary bit S

Unncessary Feature :

- S.no - No use
- Binary bit R we need correct bit which is binary bit s

