

Inter-Subject Correlation of Heart Rate and Attention Modulation

Roberto Antonello 47891A

Abstract

This project focuses on analyzing heart-rate synchrony across individuals to verify if it's modulated by attentional state while watching educational videos. The goal is therefore to replicate a couple of results from Pérez et al. (2021) [1] using data from a newer dataset: the Brain, Body and Behavior Dataset (BBBD) [2].

To achieve this, heart-rate fluctuations were extracted from raw ECG recordings and compared across subjects using ISC-HR (inter-subject correlation of heart-rate).

A hypothesis test with a FDR correction is used to establish statistical significance of the obtained results. ISC-HR is then compared between attentive and distracted conditions through a paired statistical test across all five stimuli.

Hypothesis test and descriptive statistics are employed to analyze synchrony patterns and to detect the effect of attention across stimuli.

The results provide a statistically grounded replication of ISC-HR modulation by attention, discussed in relation to the original paper's finding on which this project is based.

1 Introduction

Heart rate is often treated as a purely autonomic signal, reflecting internal physiological states such as arousal or stress.

A recent study suggest that heart-rate fluctuations can be driven by external stimuli. When multiple individuals are exposed to the same narrative content, their heart rates tend to fluctuate in a similar way.

This phenomenon is known as inter-subject correlation of heart-rate (ISC-HR).

Pérez et al. (2021) [1] proposed that these heart-rate fluctuations are modulated by conscious, attentive processing of the stimulus.

This project aims to replicate two of the main results reported by the analyzed paper.

- ISC-HR is statistically significant across subjects exposed to the same stimulus (R1).
- Synchrony is modulated by attentional state, being higher when subjects are attentive than when they are distracted (R2).

This work uses data from the Brain, Body and Behavior Dataset (BBBD) [2], which is a more recent dataset that includes similar experiments to the original study.

2 Related Work

The original paper [1] computes ISC-HR by correlating each subject’s instantaneous heart-rate fluctuations against the rest of the group, averaging the resulting pairwise correlations in Fisher-Z space, and testing significance via a circular-shift permutation procedure with False Discovery Rate (FDR) correction. The study reports three main findings across four experiments.

The first one (R1) shows that heart-rate fluctuations synchronize across subjects listening to the same auditory narrative, with 17 of 27 subjects having statistically significant ISC-HR.

The second result (R2) shows this synchrony is systematically higher when subjects attend to a stimulus than when they are distracted.

The third result (R3) shows that ISC-HR predicts subsequent memory recall performance for the narrative content, suggesting that the measure reflects conscious engagement rather than an autonomic response to sensory input.

The fourth experiment applies ISC-HR to patients with disorders of consciousness, showing reduced synchrony relative to healthy controls and framing ISC-HR as a potential prognostic marker in a clinical setting.

As already anticipated, this project replicates only R1 and R2 using an experiment equivalent to the original study’s experiment 2.

3 Dataset

This project uses Experiment 2 of the BBBD dataset [2], which contains recordings of ECG, EEG, eye-tracking, and respiration during educational video viewing.

In experiment 2, 31 subjects watch five educational videos, each one viewed twice by the same subject: attentively the first time, distracted by performing a secondary task (silently counting backward) the second time.

BBBD’s data descriptor [2] explicitly states that the ECG data provided for this experiment are not newly collected, but are the same recordings originally published

in Pérez et al., 2021 [1].

ECG preprocessing documentation [2] states that R-wave peaks were detected automatically and then manually corrected. This project instead detects R-peaks directly from the raw ECG signal using an automated procedure, without using BBBD’s provided peak timestamps and without manual review.

This choice was made in order to reproduce and understand the original study’s methodology.

Not every subject has a usable recording for every (subject, session, stimulus) combination. Missing files are skipped automatically, so the number of subjects analyzed varies slightly across stimuli and conditions.

4 Methodology

This chapter describes the full process from raw ECG signals to the statistical tests used to replicate R1 and R2.




Fig. 1 Full processing pipeline from raw ECG signal to the statistical tests to replicate R1 and R2.

4.1 Signal preprocessing

Raw ECG signals are first high-pass filtered to remove baseline drift, then a notch filter is used to suppress power-line interference. The first high-pass filter used a 0.5 Hz cutoff, in order to preserve the faster fluctuations corresponding to heartbeats while attenuating baseline drift.

The notch filter targets 60 Hz, which is the frequency of electrical interference from the power supply. Considering the dataset’s 128 Hz sampling rate, the Nyquist

limit is therefore 64 Hz. This places 60 Hz close to this edge. Thus the effect of the second filter is marginal.

R-peaks are detected by using an adaptive amplitude threshold. The chosen value is $3 \times$ standard deviations of the filtered signal. This is combined with a 0.3s temporal distance between consecutive detections.

Instantaneous heart rate was computed as the inverse of successive R-R intervals $\frac{60}{RR}$ (BPM), where RR is the time interval between two consecutive R-peaks. Then it's resampled onto a common 4Hz grid via interpolation to allow comparison across subjects.

Subjects whose mean heart rate fell outside a plausible range (40-160 BPM) were automatically excluded from further analysis in order to improve the quality of the results.

4.2 ISC-HR computation

In order to compute ISC-HR, all subjects' interpolated HR series were truncated to their shortest common length and arranged into a matrix of pairwise Pearson correlations.

Each subject's ISC-HR was computed as the Fisher-Z average of their correlation with every other subject in the group, excluding self-correlation. This is followed by the inverse Fisher-Z transform.

da Hypothesis-Test-R1-Note.pdf Sezione 1: Fisher-Z, Step 3-5 del paper

4.3 Hypothesis test

permutazione circolare, Benjamini-Hochberg

4.4 Attention modulation

da R2-Attention-Modulation-Note.pdf: correlazione a riferimento fisso, esclusione dell'auto-correlazione, Shapiro-Wilk + t-test/Wilcoxon.

4.5 Implementation choices

(opzionale, se vuoi una tabella riassuntiva) — QC, i parametri non specificati dal paper, tutti già tracciati nei documenti

5 Results

Qui attingi principalmente da Final-Results-R1-R2-Discussion.pdf, che è già scritto quasi in forma di risultati/discussione:

5.1 Input validation

5.2 R1 on all combinations of (session, stimulus)

5.3 Significant stimulus

5.4 Stimulus 02 case

6 Discussion

Confronto con le cifre del paper (con le cautele che abbiamo già scritto), limiti dichiarati (niente ANOVA completa, sensibilità all'interpolazione non testata, scelte QC/esclusione non specificate dal paper), interpretazione del pattern generale.

7 Conclusion

Cosa hai dimostrato, cosa resta aperto (R3, metodo esatto per test multipli, ecc.).

8. References

Paper Pérez et al., documentazione BBBD/Zenodo, eventuali librerie citate.

Declarations

Ai Usage Disclaimer: parts of this project have been realized with the assistance of ChatGPT(model GPT-5.3) and Claude(model Sonnet 4.6) for the following types of tasks:

- Reviewing and refining text during the writing of this report.
- Collecting ideas about results analysis.
- Generation of Python code to support the development.

Every content generated by AI has been reviewed and tested by the author.

References

- [1] P. Pérez, J. Madsen, L. Banellis, B. Türker, F. Raimondo, V. Perlberg, M. Valente, M.-C. Niérat, L. Puybasset, L. Naccache, T. Similowski, D. Cruse, L. C. Parra, and J. D. Sitt. Conscious processing of narrative stimuli synchronizes heart rate between individuals. *Cell Reports*, 36(11):109692, 2021.
- [2] J. Madsen, N. Kuppa, and L. C. Parra. The Brain, Body, and Behavior Dataset (BBBD): Multimodal Recordings during Educational Videos. *Scientific Data*, 13:920, 2026.