

┌ 1

Give an algorithm for MCP of running time  $O(m \log \log m)$ .

*Solution.*

**The pseudocode of the algorithm is in the next page.**

The correctness of the algorithm comes from below. First, we initialize our  $c^*$  candidates to be all capacities of the edges in  $G$ . Then, in each iteration, we divide it into many divisions of approximately the same size in order, and test which division  $c^*$  is in. Finally, there will be only one candidate left, and the only candidate is  $c^*$ .

Now we'll analyze the running time. Note that using median-of-medians algorithm to find the median of a set  $S$  has running time  $O(|S|)$ . In "Loop 2" of function MCP, we find the median of  $S_1, \dots, S_k$  in  $2^d$  iterations. Note that there is an invariant equation  $\sum_{i=1}^k |S_k| = |C|$ . So finding the median requires  $O(|C| \cdot 2^d)$  in total. The GETDIVISION function may need to add all the edges into the graph in the worst case. Testing the connectivity will use  $O(m)$  time in total if we record a set of reachable vertices as described in Exercise 1. So the running time of GETDIVISION is  $O(m)$ .

We now prove that  $|C| \cdot 2^d = O(m)$  by induction. Initially,  $|C| = m$  and  $d = 0$ . It obviously holds. Suppose  $|C_{old}| \cdot 2^{d_{old}} = O(m)$ . We have  $|C_{new}| = O(|C_{old}| \cdot (\frac{1}{2})^{2^{d_{old}}})$ ,  $d_{new} = d_{old} + 2^{d_{old}}$ . So  $|C_{new}| \cdot 2^{d_{new}} = O(m)$ .

Now we know that a single iteration of "Loop 1" takes time  $O(m)$ . Note that  $2^d < m$ . Since  $d$  increases exponentially, "Loop 1" will iterate  $O(\log^* m)$  times. Finally, we get the running time is  $O(m \log^* m)$ . Obviously this algorithm has a better running time than  $O(m \log \log m)$ ,  $O(m \log \log \log m)$ ,  $O(m \log \log \log \log m)$  when  $m$  is sufficiently large.  $\square$

┌ 2

Give an algorithm for MCP that runs in  $O(m \log \log \log m)$ ? How about  $O(m \log \log \log \log m)$ ? How far can you get?

*Solution.* See Problem 2.  $\square$

---

**Algorithm 1** An algorithm for MCP problem.

---

```

function MCP( $V, E = \{e_1, e_2, \dots, e_m\}, c$ )
     $C \leftarrow \{e_1, \dots, e_m\}$ 
     $oldEdges \leftarrow \emptyset$ 
     $d \leftarrow 0$ 
    while there are multiple capacities of the edges in  $C$  do ▷ Loop 1
         $divisions \leftarrow [C]$  ▷ Let  $divisions$  be a list only containing the set  $C$ .
        for  $i = 1$  to  $2^d$  do ▷ Loop 2
            Let  $S_1, S_2, \dots, S_k$  denote the edge sets in  $divisions$  in order, i.e., representing  $divisions$  as  $[S_1, \dots, S_k]$ .
            Use median-of-medians algorithm  $k$  times to find the median capacity of the capacities of the edges in
            each set. Denote them as  $m_1, m_2, \dots, m_k$  respectively. (If there are two, choose the larger one.)
             $newDivisions \leftarrow []$  ▷ Let  $newDivisions$  be an empty list.
            for  $j = 1$  to  $k$  do ▷ Loop 3
                Append  $\{s \in S_j : c(s) \geq m_j\}$  to  $newDivisions$ .
                Append  $\{s \in S_j : c(s) < m_j\}$  to  $newDivisions$ .
            end for
             $divisions \leftarrow newDivisions$ 
        end for
         $C, oldEdges \leftarrow \text{GETDIVISION}(divisions, oldEdges)$ 
         $d \leftarrow 2^d + d$ 
    end while
    return the capacity of the edges in  $C$ 
end function

function GETDIVISION( $divisions, oldEdges$ ) ▷ Using the algorithm of exercise 1.
     $G \leftarrow (V, oldEdges)$ 
    for  $div$  in  $divisions$  in the order of the list do
        Add all edges in  $div$  to  $G$ .
        if  $t$  is now reachable from  $s$  then
            return  $div, oldEdges$ 
        else
             $oldEdges \leftarrow oldEdges \cup div$ 
        end if
    end for
end function

```

---