AI-Driven Closed-Loop Precision Spraying for Real-Time Application Optimization

ABE 598 Digital Agriculture · Final Project Report (milestone M5, December 9, 2026)
Team CoverageVision AI · Emery Brewer (remote) · Junjie Ao · Kinjalk Parth

Built October 20, 2026 from the results files in the repository. Items marked **TEAM TO CONFIRM** need a team member's check before submission.

1 Summary

We built the closed loop of the proposal end to end and evaluated it inside a physics-informed simulator: a learned coverage model with a calibrated interval, a constrained setting selector, a water-sensitive-paper (WSP) renderer, classical (B0) and U-Net (B1) card readers, a fast loop that corrects the next segment and a slow loop that corrects the model between passes. **The closed-loop criterion is met against a fair oracle** that knows the hidden mismatch but not the per-card noise: the fast + slow loop recovers 96% [80, 107] of the open-loop-to-oracle gap at +4.1% [+2.8, +5.5] volume (target ≥ 50%, ≤ +10%). Against the midterm's card-aware oracle the volume half is missed (+17.2% [+15.4, +19.0]), because that oracle sees noise no controller can know. The model (2.84 pp MAE, ridge 3.32 pp), the selector (97.0% success at lower drift than the matched fixed setting) and card reading on our own cards (B0 1.44 pp, B1 0.20 pp MAE) meet their targets. On out-of-generator cards B1 drops to 1.74 pp and 88.3% class agreement (target 90%), and the real-card criterion is blocked by restricted data. Four extensions were tested and none is adopted by default: travel speed is inconclusive (a small open-loop drift gain, no closed-loop CI), boom height (alone or with speed) trades success for drift and volume, a wind forecaster lowers forecast error but not coverage failures, and a physics-first hybrid predictor is not better than pure ML in the loop. All results are simulator-internal.

2 System as Built

Sprayers commit to settings before they see how weather and machine state change the deposit, and standard water-sensitive-paper (WSP) checks report problems only after the sprayer has passed. The proposal closes that loop: before each field segment a model predicts coverage and drift for every candidate setting, a selector picks the setting that meets the coverage requirement C_{req} at the lowest predicted drift and volume, the sprayer applies it, computer vision reads the coverage actually achieved from a WSP card, and the error corrects the next segments (fast loop) and the model between passes (slow loop). Without spray trials this semester, the whole loop runs in a physics-informed simulator with injected hidden mismatch (wind gusts, canopy interception, nozzle wear) that the model never sees.

The loop follows the proposal (Figure 1). Modules exchange versioned records defined in `contracts.py` (schema 1.2: optional travel speed and boom height added to the 1.0 setting). `loop.py` runs a 40-segment pass under six policies (`open`, `fast`, `fast_slow`, fair `oracle`, card-aware `oracle_card`, `best_fixed`) and logs one row per segment. All extensions are opt-in and default off; with them off, results are bit-identical to the baseline. The code base is 8,430 lines of Python with 288 test functions; the full suite (402 tests after parametrization) passes on the final machine (32 logical cores, RTX 5070 Ti).




Figure 1. CoverageVision loop as implemented, with source modules. Border color marks the module lead (orange Emery, green Junjie, blue Kinjalk, grey shared). Black arrows: forward pass for segment k; blue arrows: fast loop (bias b to the selector) and slow loop (coverage offset on the frozen model, refit between passes).

3 Components

3.1 Nozzle catalog

`data/catalog/nozzles.csv` holds 316 chart rows for five families (TP65 50, XR 72, DGX40 24, ULD 80, 3D 90; 43 family-size combinations). `catalog.py` interpolates flow along $Q \propto \sqrt{P}$, recomputes GPA at 20 in spacing, and generates 547 candidate settings on a 5 psi grid. The validator reports 0 violations on four checks (square-root law, sampled GPA cells, droplet class monotone in pressure, ranges). Compromises: TP65 droplet class uses the 80° column (D3), DGX40 contributes flow only (D4), ULD and 3D rows come from manufacturer sheets [12], spray angles are nominal (D5).

3.2 Simulator

The simulator composes first-order relationships and is not a validated drift model. Flow follows $Q = Q_{ref}\sqrt{(P/P_{ref})}$, application rate GPA = 5940·GPM/(MPH·W) [4]. The volume spectrum is log-normal with VMD set by the ASABE S572.3 class [3]. Terminal velocity uses a Schiller–Naumann drag correlation [9]; evaporation follows the d^2 law [10] with Stull's wet-bulb approximation [11]. Droplets leave the nozzle at $v_0 = 0.6\sqrt{(2P/\rho_w)}$ and relax toward V_t under linear drag (D10); size bins displaced over 0.5 m cross-track are drift. Coverage uses a Boolean (Poisson) model [5],

$$C = 1 - \exp(-N\cdot E[\pi s^2/4]/A), \quad s = SF\cdot d, \quad SF \sim U[1.6, 2.2] \text{ per card [6]}, \quad d \geq 50\ \mu m.$$

The per-card spread factor SF is the irreducible noise that recurs throughout this report: it is drawn when the card is sprayed, so no controller can know it in advance. Hidden mismatch (AR(1) gusts, canopy interception, nozzle wear) is set by one level (none, low, med, high) and never seen by the model. Tests cover the anchors in Table 1, monotone trends (Figure 2), the Boolean formula against Monte Carlo placement, and seeded determinism.

Table 1. Physical anchors checked by tests (values computed from the code at build time; drift at 15 GPA, 2 m/s crosswind, H = 0.5 m, 25 °C, 50% RH, 40 psi, mean of 6 seeds). Plausibility checks, not field validation.

Quantity	Reference or accepted band	Simulator
Terminal velocity, 20 µm droplet (m/s)	0.012 ± 25%	0.012
Terminal velocity, 100 µm droplet (m/s)	0.265 ± 25%	0.248
Terminal velocity, 200 µm droplet (m/s)	0.7 ± 25%	0.707
Terminal velocity, 400 µm droplet (m/s)	1.8 ± 25%	1.610
Drift fraction, fine spray (F), 2 m/s crosswind	10% to 35%	30%
Drift fraction, medium spray (M), 2 m/s crosswind	2% to 15%	8%
Drift fraction, coarse spray (C), 2 m/s crosswind	below 5%	1%




Figure 2. Simulator trends. (a) Coverage rises with application rate and falls for coarser classes at equal volume. (b) Drift against crosswind. (c) Drift rises with boom height. (d) For a 90 µm spray, coverage falls with temperature and rises with humidity.

3.3 Dataset and predictive model

Dataset v1 has 50,000 simulator rows: Latin-hypercube conditions over the operating ranges, settings drawn uniformly from the 547 candidates, no hidden mismatch. Features are raw conditions, wind as cross- and along-track components, catalog-derived flow, VMD and angle, and physics features (wet-bulb depression, H/V_t, $|U_{cross}|H/V_t$, GPA/VMD). We compare ridge, random forest and LightGBM [15]; the interval comes from quantile LightGBM with conformal calibration [16]. Splits are a random 80/20 hold-out and three grouped splits withholding wind above 5 m/s, the 3D family, and the hot-dry regime. LightGBM reaches a coverage MAE of 2.84 pp on the random hold-out (target 3 pp) against 3.32 pp for ridge and 3.23 pp for random forest, and is the best model on every split. Its 80% prediction interval covers 80.0% of held-out rows with mean width 9.0 pp. Scoring all 547 candidates takes 9.3 ms (median) and a 50,000-row refit takes 2.3 s, so the selector can run for every segment.

Table 2. Coverage MAE (pp) on held-out data against sampled outcomes; bold marks the best model. "vs expected" is LightGBM's MAE against noise-free expected coverage. Target: MAE ≤ 3 pp and below ridge.

Split	Ridge	Random forest	LightGBM	LightGBM vs expected	Drift MAE (fraction)	Shift MAE (mm)
Random 80/20	3.32	3.23	**2.84**	0.64	0.0030	3.4
Wind > 5 m/s withheld	3.41	3.38	**2.83**	0.84	0.0051	8.3
3D family withheld	3.42	3.57	**2.98**	0.90	0.0072	12.2
Hot-dry withheld	3.16	3.17	**2.80**	0.67	0.0034	3.6

The 3 pp target sits close to a floor set by the simulator. Because of the per-card spread factor no model can beat 2.76 pp against sampled outcomes; LightGBM's 2.84 pp is 0.09 pp above it, and against the noise-free expectation its MAE is 0.64 pp (ridge 1.82 pp). Withholding regimes barely moves coverage error (2.80 to 2.98 pp) but raises drift error from 0.0030 to 0.0051 (wind above 5 m/s withheld) and shift error from 3.4 to 8.3 mm, so drift estimates are least reliable at high wind. 5 of 5 sensitivity sweeps pass; they check direction, not magnitude.




Figure 3. LightGBM against simulator on held-out rows: four outputs on the random split (top), coverage on the withheld regimes (bottom left three) and coverage MAE by split and model (bottom right; dotted: 3 pp target).

3.4 Selector and scenarios

The selector implements Eq. (2) of the proposal: it scores every catalog candidate, keeps those with $C + b - m \geq C_{\text{req}}$, and minimizes $\lambda \cdot \text{drift}_n + (1 - \lambda) \cdot \text{volume}_n$ (min-max normalized over the feasible set; $\lambda = 0.6$). The margin m is the lower half-width of the prediction interval, floored at 1.5 pp; if nothing is feasible it returns the highest-coverage setting and flags the segment. The scenario library generates 40-segment passes with AR(1) wind and gust bursts, rotating wind direction, diurnal temperature and humidity, and back-and-forth headings, in six presets (`calm_morning`, `gusty_afternoon`, `hot_dry`, `crosswind_shift`, `marginal_limits`, `inversion_evening`); the parameters are plausible regime choices, not measured weather statistics.

Table 3. Selector against fixed settings on 200 random no-mismatch scenarios at $C_{\text{req}} = 30\%$ (success = share with true coverage ≥ C_{req}). The learned model selects and the simulator scores; all 547 candidates are scored per call. Single draw per scenario, no CI.

Policy	Success (%)	Mean drift (fraction)	Mean volume (GPA)	Time per selection (ms)
Selector, learned model (spray)	**97.0**	**0.0131**	**24.8**	**19.8**
Lowest-drift fixed setting with matching success: XR 15 @ 45 psi	98.0	0.0167	47.5	–
Best fixed setting overall: TP65 15 @ 55 psi	100.0	0.0171	52.5	–
Selector, simulator as model, no interval (`oracle`)	38.5	0.0106	17.3	557.7

The selector meets the requirement in 97.0% of the 200 scenarios (target ≥ 90%). The lowest-drift fixed setting with matching success (XR 15 @ 45 psi, 98%) has drift 0.0167 against 0.0131 (21% lower for the selector) and applies 47.5 GPA against 24.8. One selection takes 20 ms. Without a prediction interval (simulator as model, 1.5 pp margin floor only) success falls to 38.5%: the per-card spread factor is noise no model can predict, so the margin must come from a calibrated interval (Figure 4).




Figure 4. Mean drift against mean volume as λ varies (0, 0.3, 0.6, 1.0). Green: learned model selects; blue: simulator selects and scores; square: best fixed setting.

3.5 WSP renderer and public data

The renderer turns the droplets on a card into an RGB image and an exact mask (76 × 26 mm, 600 dpi). Each detectable droplet leaves an area-preserving elliptical stain of diameter $SF \cdot d$; degradations (warp, illumination, blur, noise, JPEG) come in `scanner` and `phone` profiles (Figure 5). Over 100 undegraded cards, mask coverage matches the analytic Boolean value to a mean absolute 0.14 pp. The Simões et al. record [7] provides 300 synthetic cards with polygon labels (CC BY 4.0; 635,839 droplets; coverage 1.5% to 41.0%, mean 13.0%), which we use as an out-of-generator test.

3.6 Post-spray verification

B0 is a classical pipeline: card detection with perspective correction, illumination flattening, an (R−B) stain channel thresholded with Otsu's method [2,17], opening, and a distance-transform watershed for stain counts and Dv0.1/0.5/0.9. B1 is a U-Net with a lightweight pretrained encoder [8] that segments stains on tiles; coverage is the stained share of the mask. Both flag saturated cards. Coverage, not stain counts, is the quantity the loop uses: count errors are large for both readers wherever stains touch.

Table 4. Card-reading accuracy by true-coverage band on the 180 held-out cards of our renderer and on the 300 Simões et al. synthetic cards (out-of-generator; no card above 50%). Coverage MAE and signed bias in pp, three-class agreement, mean stain-mask IoU. Targets: MAE ≤ 2 pp, agreement ≥ 90%. Source: `results/verification_eval.json`.

Verifier	Cards	True coverage	n	MAE (pp)	Bias (pp)	Class agreement (%)	IoU
B0 classical	own renderer	0-15%	46	0.70	+0.69	91.3	0.820
B0 classical	own renderer	15-30%	44	0.97	+0.86	95.5	0.846
B0 classical	own renderer	30-50%	44	0.77	-0.47	97.7	0.861
B0 classical	own renderer	50+%	46	3.28	-3.28	100.0	0.886
B0 classical	**own renderer**	**all**	**180**	**1.44**	**-0.57**	**96.1**	**0.853**
B0 classical	Simões synthetic	0-15%	221	2.44	+0.63	94.6	0.829
B0 classical	Simões synthetic	15-30%	63	2.40	-2.12	73.0	0.873
B0 classical	Simões synthetic	30-50%	16	6.44	-6.44	25.0	0.807
B0 classical	**Simões synthetic**	**all**	**300**	**2.65**	**-0.33**	**86.3**	**0.837**
B1 U-Net	own renderer	0-15%	46	0.08	-0.07	100.0	0.922
B1 U-Net	own renderer	15-30%	44	0.18	-0.12	100.0	0.926
B1 U-Net	own renderer	30-50%	44	0.24	-0.08	97.7	0.933
B1 U-Net	own renderer	50+%	46	0.28	+0.25	100.0	0.951
B1 U-Net	**own renderer**	**all**	**180**	**0.20**	**-0.00**	**99.4**	**0.933**
B1 U-Net	Simões synthetic	0-15%	221	1.06	-1.06	100.0	0.891
B1 U-Net	Simões synthetic	15-30%	63	2.82	-2.82	63.5	0.861
B1 U-Net	Simões synthetic	30-50%	16	6.83	-6.83	25.0	0.801
B1 U-Net	**Simões synthetic**	**all**	**300**	**1.74**	**-1.74**	**88.3**	**0.880**

B1 is the full model now. The U-Net was trained on a GPU (checkpoint epoch 27, val Dice 0.969, amp=bf16, 840 training cards); the midterm's 6-epoch CPU checkpoint is retired. On our renderer's test cards B1 reaches 0.20 pp MAE and 99.4% agreement against 1.44 pp and 96.1% for B0. B0's error concentrates above 50% coverage, where stains merge (3.28 pp, bias -3.28 pp); B1 stays at or below 0.28 pp in every band.

Outside the generator both readers lose accuracy, and B1 loses more than its own-card numbers suggest. On the Simões cards B1 has 1.74 pp MAE (bias -1.74 pp, every band underread) and B0 2.65 pp. Class agreement is 88.3% (B1) and 86.3% (B0), below the 90% target. The misses sit at 15 to 50% coverage: in the 30–50% band (16 cards) B1 underreads by 6.83 pp and agrees on the class for 25% of cards; in the 15–30% band (63 cards) by 2.82 pp with 63% agreement. Underreading near a class limit reports a card as worse than it is, which is the safe direction for re-treatment but would make the fast loop spray more. The Simões cards use an inferred pixel scale (no dpi is published) and contain no card above 41% coverage.




Figure 5. Left: synthetic cards from our renderer, 5% to 76% true coverage, scanner and phone profiles. Middle: B0 coverage against true coverage on the 180 held-out renderer cards (shaded: ±2 pp). Right: B1 (GPU-trained) on the same cards; this panel comes from the GPU-host evaluation (`results/b1_synthetic.json`, MAE 0.17 pp), the table from the local re-evaluation. Lines mark the 15% and 30% class limits.

Runtime: met. Controlled timing on the project laptop (30 renderer cards, minimum of 3 calls after warm-up) gave B0 median 0.18 s, p95 0.26 s, and B1 median 0.82 s, p95 1.09 s, maximum 1.33 s, while other experiments loaded the CPU. Contention can only slow a reader down, so these are upper bounds for that laptop and already inside the 2 s target. The same protocol on the final desktop (AMD Ryzen 9 9950X 16-Core Processor (desktop; 16 cores / 32 logical), lightly loaded, B1 forced to CPU) gives B0 median 0.11 s, p95 0.15 s, and B1 median 0.41 s, p95 0.52 s, maximum 0.55 s (single call without the minimum of 3: B1 p95 0.55 s, maximum 0.67 s). This shows the readers' cost without contention; it is a desktop, not a laptop number. Source: `results/b1_idle_retime.json`.

Real annotated cards: blocked. The two annotated real cards (2,754 droplets) and the pre-annotated real squares are in Zenodo record 14010262, whose files are restricted (D9). The tile evaluation is implemented and runs as soon as the files are placed under `data/external/simoes2025/real/`; access has to be requested through Zenodo (draft email: `reports/email_draft_simoes.md`) **TEAM TO CONFIRM whether the request was sent**. The real-card criterion (≤ 5 pp) is therefore untested.

4 Closed-Loop Results

Setup. The grid (`experiments/closed_loop.py`) runs six policies (`open`, `fast`, `fast_slow`, fair `oracle`, card-aware `oracle_card`, `best_fixed`) over four presets (`calm_morning`, `crosswind_shift`, `gusty_afternoon`, `hot_dry`), four hidden-mismatch levels (none, low, med, high) and 20 seeds, 40 segments per pass at C_{req} = 30%. The model is the learned `SprayModel`; the verifier is *noisy* (true coverage plus Gaussian error with the per-band bias and spread of B0). `fast_slow` runs five consecutive passes and the fifth is scored. Every policy sees the same hidden realization, so all comparisons are paired. Gap recovery is (policy − open)/(oracle − open) in the share of segments meeting C_{req}; volume overhead is mean GPA relative to the oracle. Criterion numbers pool low, med and high mismatch; brackets are 95% paired-bootstrap CIs over seeds.

Two changes since the midterm, both fixed before the evaluation grid ran. (1) *Fair oracle* (D15). The midterm oracle also saw the WSP spread factor of each card, which is drawn when the card is sprayed and which no controller can know; it needed no safety margin. The fair oracle (`loop.FairOracleModel`) knows the hidden mismatch of each segment exactly (gust state, canopy interception, nozzle wear) but not the spread factor, predicts at the mean spread factor, takes the exact 10% quantile as its lower bound, and selects with the same margin rule as the learned model. It measures perfect knowledge of the mismatch under the same risk policy. The midterm oracle is kept as `oracle_card`, an unreachable bound: the fair oracle itself uses +12.6% [+11.2, +13.9] more volume than `oracle_card` (+9.8% [+8.9, +10.5] with no mismatch). (2) *Slow loop redesign* (D16). The midterm slow loop refit LightGBM on the measured cards with record weight 30 and made things worse. The new slow loop (`feedback.ResidualCorrectedModel`) freezes the offline model and refits, after every pass, an additive coverage offset on all verified cards so far, per fast-loop regime and shrunk by empirical Bayes toward a global offset and toward 0 (prior sd 5 pp). The interval is shifted, never narrowed. Slow-loop variants were compared only on dev seeds 100–109, disjoint from the evaluation seeds 0–19.

Table 5. Closed-loop criterion (proposal Table 1), learned model, 20 seeds, low + med + high mismatch pooled. Source: `results/closed_loop_summary.md`.

Criterion	Reference	Policy	Recovery (95% CI)	Volume vs oracle (95% CI)	Verdict
≥ 50% gap recovery, ≤ +10% volume	fair oracle	fast + slow	96% [80, 107]	+4.1% [+2.8, +5.5]	**met** (both CIs clear)
	fair oracle	fast	69% [44, 82]	+1.4% [+0.2, +2.7]	met on point estimate; recovery CI crosses 50%
	card-aware oracle (bound)	fast + slow	63% [46, 73]	+17.2% [+15.4, +19.0]	missed on volume
	card-aware oracle (bound)	fast	46% [24, 57]	+14.2% [+12.4, +15.9]	missed

The closed-loop criterion is met against the fair oracle. The fast + slow loop recovers 96% [80, 107] of the open-to-oracle gap at +4.1% [+2.8, +5.5] volume; both CIs clear their targets. The fast loop alone recovers 69% [44, 82] at +1.4% [+0.2, +2.7], which meets 50% only on the point estimate; its weakest preset is `hot_dry` (55% [4, 73]). With the mismatch-free physics as the model (`oracle_nominal`) the picture is the same: fast 71% [48, 82] at +0.2% [-1.0, +1.4], fast + slow 93% [80, 102] at +2.8% [+1.6, +4.0]. Against `oracle_card` the volume half stays missed (+17.2% [+15.4, +19.0]), for the structural reason above.

Caveats that bound the result. The pooled gap is only 8.3 pp (none 0.2, low 0.9, med 7.5, high 16.6 pp): the open loop's interval margin already protects it at low mismatch, so the criterion is informative only at med and high, where fast + slow recovers 102% [84, 116] and 104% [96, 112]. Recovery above 100% means the policy met C_{req} slightly more often than the fair oracle, paid for with volume (+6.4% [+4.8, +8.3] at high mismatch); the oracle limits information, not reliability. The verdict depends on the oracle's risk level: with a stricter fair oracle (q = 0.05, met 0.983) recovery falls to 53% [30, 65] (fast) and 74% [56, 83] (fast + slow, volume +0.7% [-0.5, +2.1]), still meeting the criterion with less margin. Per preset, fast + slow recovers 89% to 102%.




Figure 6. Share of segments meeting C_{req} (true outcome) against hidden-mismatch level, learned model: all presets pooled (left) and per preset; mean and 95% CI over 20 seeds. Green: fair oracle; light blue: card-aware oracle (unreachable bound).

Table 6. Share of segments meeting C_{req} by policy and hidden-mismatch level (learned model; mean ± 95% CI over 20 seeds, presets pooled).

policy	none	low	med	high
open	0.964 ± 0.011	0.958 ± 0.018	0.884 ± 0.051	0.781 ± 0.078
fast	0.950 ± 0.011	0.942 ± 0.011	0.937 ± 0.013	0.918 ± 0.019
fast_slow	0.951 ± 0.011	0.948 ± 0.011	0.961 ± 0.011	0.954 ± 0.015
oracle	0.965 ± 0.012	0.967 ± 0.009	0.959 ± 0.012	0.947 ± 0.016
oracle_card	1.000 ± 0.000	1.000 ± 0.000	1.000 ± 0.000	1.000 ± 0.000
best_fixed	0.826 ± 0.025	0.843 ± 0.032	0.758 ± 0.058	0.659 ± 0.082




Figure 7. One pass (`gusty_afternoon`, med mismatch, seed 0, learned model). Top: raw and bias-corrected prediction, card readings and true coverage under the fast loop, open loop and fast + slow loop. Bottom: bias applied to each segment.




Figure 8. Mean applied volume and drift fraction by mismatch level (top: learned model; bottom: `oracle_nominal`). The card-aware oracle (light blue) sprays less than any policy that cannot see the card noise, including the fair oracle (green).

The slow loop removes the systematic error but not the variance. At high mismatch the mean residual (measured minus model in use) goes from -6.02 pp in pass 1 to 0.03 pp in pass 2, and the residual MSE from 73.3 to 45.2 pp^2. The within-pass residual variance does not fall: it stays between 27.0 and 31.9 pp^2 in every pass at every mismatch level, including none (high: 27.4 in pass 1, 29.6 in pass 5; Figure 9). It is set by the per-card spread factor and the per-segment gust, which no offset can remove. The proposal expected it to shrink pass after pass; it does not, and we report that as a negative result. In the ablation cell (`gusty_afternoon`, med, 20 seeds) the residual offset meets 0.966 with 98% [80, 125] recovery; the midterm refit meets 0.832 with -89% [-308, -16] (record weight 30) and 0.905 with 12% [-107, 53] (weight 1).




Figure 9. Slow loop over five consecutive passes, learned model, all presets: residual variance, residual MSE, mean residual, share meeting C_{req} and volume per pass, by mismatch level (mean and 95% CI over 20 seeds). Pass 1 has no offset yet.

Ablations (fast loop, `gusty_afternoon`, med mismatch, fair oracle). Smoothing α = 0.1 / 0.3 / 0.6 recovers 47% / 63% / 39%; a global bias recovers 79% against 63% for per-regime biases, at +3.4% against +2.1% volume. All CIs overlap. Rendered-card verifiers (5 seeds) give 46% [-67, 78] (B0) and 46% [-100, 76] (B1): too few seeds to separate them from the noisy verifier. Retreat flags were never raised, so re-treatment is untested.

Table 7. Ablations, learned model, `gusty_afternoon`, med mismatch, reference = fair oracle.

group	variant	seeds	met	gap recovery	volume vs oracle
alpha	alpha=0.1	20	0.930 ± 0.028	47% [28, 60]	−1.4% [−2.6, −0.2]
alpha	alpha=0.3	20	0.941 ± 0.018	63% [32, 79]	+2.1% [+0.8, +3.5]
alpha	alpha=0.6	20	0.924 ± 0.016	39% [−38, 64]	+3.5% [+1.7, +5.3]
warmup	warmup=0	20	0.946 ± 0.017	70% [39, 88]	+2.3% [+0.9, +3.8]
warmup	warmup=2	20	0.941 ± 0.018	63% [32, 79]	+2.1% [+0.8, +3.5]
warmup	warmup=4	20	0.934 ± 0.024	53% [24, 69]	+1.1% [−0.1, +2.5]
bias scope	per-regime bias	20	0.941 ± 0.018	63% [32, 79]	+2.1% [+0.8, +3.5]
bias scope	global bias	20	0.952 ± 0.010	79% [43, 97]	+3.4% [+1.5, +5.5]
verifier	verifier=perfect	20	0.933 ± 0.019	51% [−7, 72]	+0.6% [−0.8, +2.1]
slow loop	slow loop: residual offset, per regime (default; 5 passes, final pass)	20	0.966 ± 0.016	98% [80, 125]	+5.2% [+4.1, +6.5]
slow loop	slow loop: residual offset, global only (5 passes, final pass)	20	0.964 ± 0.016	95% [77, 120]	+5.2% [+4.1, +6.5]
slow loop	slow loop: legacy LightGBM refit, record weight 1 (5 passes, final pass)	20	0.905 ± 0.018	12% [−107, 53]	−1.8% [−3.2, −0.2]

slow loop	slow loop: legacy LightGBM refit, record weight 30 (5 passes, final pass)	20	0.832 ± 0.030	−89% [−308, −16]	−7.5% [−8.7, −6.2]
verifier	verifier=b0 (rendered, 5 seeds)	5	0.885 ± 0.084	46% [−67, 78]	−0.7% [−3.5, +1.8]
verifier	verifier=b1 (rendered, 5 seeds)	5	0.885 ± 0.064	46% [−100, 76]	−0.1% [−2.9, +2.6]

4.1 Demonstration




Figure 10. Demo app (midterm screenshot): scenario `gusty_afternoon`, high mismatch, fast policy, segment 15 of 40, with chosen setting, selector reasoning, rendered card and the coverage values.

The Streamlit app `app/main.py` runs a pass segment by segment and shows every decision: conditions, the chosen setting and why (feasible candidates, top-5 ranking), the rendered card with the reader's mask, and predicted, corrected, measured and true coverage. The **Field run** tab runs one pass under a chosen preset, mismatch level, control strategy (`open`, `fast`, `fast_slow` with a table of what the slow loop learned between passes, fair `oracle`, `oracle_card`, `best_fixed`) and card reader (classical, U-Net, noisy), with animated field and card replays. **Compare strategies** runs several strategies on the same hidden realization. **How the simulator works** shows the physics for a chosen nozzle. A sidebar expander, **Advanced controller options**, exposes the extensions of Section 5 as opt-in controls (travel speed, boom height, wind forecast `last` / `ewma` / `ar1` / `ar1+gust`), on the same grids as the evaluation scripts; all are off by default and leave the run bit-identical when off (D17).

Browser check. Checked on 2026-10-19 with headless Chrome over CDP against the live app: all six strategies and the perfect, classic and noisy readers ran; play/pause, speeds, scrubber, hover and click-to-seek and the end-of-run summary work; `fast_slow` shows the learning-between-passes table and the card replay is consistent for every strategy at med and high mismatch; the Compare tab, Spray lab and nozzle explorer render. A full 40-card pass with the U-Net reader takes about 30 s on the idle desktop CPU. Five display bugs found in the check were fixed; the app tests pass.

5 Extensions

Four extensions beyond the proposal were built as opt-in options and evaluated with paired comparisons on the same seeds and 95% paired-bootstrap CIs. None is adopted by default: three are negative results, and travel speed is inconclusive.

5.1 Travel speed as a controlled setting

Design (D11, schema 1.1). `Setting.travel_speed_kmh` is optional; when the selector option `speed_options_kmh` is set it chooses a grid speed within ±25% of the segment's current speed and inside the spec range. Application rate scales as GPA ∝ 1/speed. Default off; with it off every result is bit-identical.

Result: inconclusive, not adopted. On the 200 paired no-mismatch scenarios of the boom-height evaluation (the `speed` variant, grid 8–28 km/h in 4 km/h steps, same seeds as `off`), the learned selector's success changes by +0.0 pp [-2.0, +2.0] and drift by -0.0010 [-0.0018, -0.0001] (volume 24.78 to 23.71 GPA); with the mismatch-free physics as the selector model, success -0.5 pp [-2.0, +1.0], drift -0.0015 [-0.0027, -0.0005]. On that grid the open-loop evidence meets the adoption rule (success holds, drift falls). Two things keep it off by default. (1) With the 2 km/h grid that D11 ships and the app uses, the learned selector's open-loop success falls from 0.935 to 0.900 (`results/speed_control_eval.md`, band 0.25, single draw, no CI). (2) There is no closed-loop evidence with a CI: the only closed-loop run is a pilot (med mismatch, 4 presets, 3 seeds, no CI) in which the fast loop met C_{req} in 0.917 of segments with speed control against 0.954 without, at 23.02 against 24.19 GPA, too small to support a conclusion. A paired 20-seed closed-loop run on the shipped grid would settle it.

5.2 Boom height as a controlled setting

Design (D12, schema 1.2). `Setting.boom_height_m` is optional and combinable with speed. Candidate heights lie inside the spec range (0.30–0.75 m), within ±25% of the canopy-following set point, and above a per-family minimum from fan overlap, $H \geq 1.3 \cdot S/(2\tan(\theta/2))$, because the uniform-field simulator does not model striping at low height. Default off.

Result: no benefit with the deployable models; default off. In the no-mismatch open loop, height control alone *raises* drift (nominal model +0.0033 [+0.0010, +0.0057], learned +0.0027 [+0.0005, +0.0049]) at unchanged success. Here the nominal model is the simulator's own expected physics, so this is not a misprediction: the selector's λ trade-off spends the height freedom on volume (21.42 against 24.83 GPA, nominal). Speed + height in the open loop lowers drift (nominal -0.0029 [-0.0049, -0.0011], learned -0.0029 [-0.0042, -0.0015]), but success falls with the nominal model (-2.0 pp [-4.0, -0.5]) and is unclear with the learned one (-0.5 pp [-2.5, +1.5]). In the closed loop (`oracle_nominal` model, perfect verifier, 4 presets × 10 seeds) the fast loop with height control meets C_{req} less often (-1.6 pp [-2.4, -0.9] med, -1.6 pp [-2.6, -0.6] high); speed + height loses more (-2.9 pp [-3.6, -2.1], -3.4 pp [-4.4, -2.4]) while lowering volume (-2.59 [-3.09, -2.11], -2.81 [-3.34, -2.32] GPA); its drift change is -0.0021 [-0.0045, +0.0003] at med (CI includes 0) and -0.0035 [-0.0066, -0.0005] at high. With the fair oracle, which knows the hidden mismatch, height alone cuts drift (-0.0036 [-0.0052, -0.0019] med, -0.0060 [-0.0075, -0.0046] high) with no detectable loss in success (-0.5 pp [-1.2, +0.3], -0.2 pp [-0.9, +0.5]). The drift benefit therefore appears only with the fair oracle under mismatch; with the nominal and learned models the selector spends height mainly on volume. The data do not isolate the cause beyond that.

Table 8. Boom height and travel speed in the closed loop (`oracle_nominal` model, perfect verifier, 4 presets × 10 seeds; differences vs `off` with 95% paired-bootstrap CIs; `oracle` = fair oracle). Source: `results/boom_control_eval.md`.

policy / mismatch / variant	met	GPA	drift	Δ met	Δ drift	Δ GPA
fast/med/off	0.934	24.13	0.0158	-	-	-
fast/med/height	0.918	21.93	0.0146	−0.0162 [−0.0244, −0.0087]	−0.0012 [−0.0039, +0.0015]	−2.2026 [−2.7893, −1.6413]

fast/med/speed+height	0.905	21.54	0.0137	−0.0287 [−0.0362, −0.0206]	−0.0021 [−0.0045, +0.0003]	−2.5927 [−3.0943, −2.1093]
fast/high/off	0.924	25.71	0.0198	-	-	-
fast/high/height	0.907	23.67	0.0165	−0.0162 [−0.0262, −0.0062]	−0.0033 [−0.0062, −0.0005]	−2.0419 [−2.4612, −1.6292]
fast/high/speed+height	0.889	22.90	0.0163	−0.0344 [−0.0444, −0.0244]	−0.0035 [−0.0066, −0.0005]	−2.8117 [−3.3392, −2.3181]
oracle/med/off	0.956	24.15	0.0153	-	-	-
oracle/med/height	0.951	22.66	0.0117	−0.0050 [−0.0125, +0.0031]	−0.0036 [−0.0052, −0.0019]	−1.4932 [−1.8344, −1.1782]
oracle/med/speed+height	0.934	22.08	0.0121	−0.0213 [−0.0313, −0.0113]	−0.0032 [−0.0049, −0.0014]	−2.0698 [−2.4444, −1.7341]
oracle/high/off	0.949	25.69	0.0190	-	-	-
oracle/high/height	0.948	24.39	0.0130	−0.0019 [−0.0087, +0.0050]	−0.0060 [−0.0075, −0.0046]	−1.2959 [−1.5151, −1.0848]
oracle/high/speed+height	0.922	23.85	0.0124	−0.0269 [−0.0369, −0.0175]	−0.0066 [−0.0082, −0.0051]	−1.8317 [−2.0603, −1.6110]

5.3 Short-horizon wind forecaster

Design (D13). The selector plans each segment with the wind read at its start, but the plant applies a hidden AR(1) gust. An opt-in forecaster (`forecast.py`; statistics only) predicts the gust ratio of the next segment from an anemometer that observes the realized wind of completed segments with sd 0.3 m/s noise, never the upcoming one. Arms: `last`, `ewma`, `ar1` (online shrunk least squares), `ar1+gust` and `nominal+gust` (plan with forecast + 1 sd), and `gust_oracle`, which reads the plant's gust and bounds any forecaster. Grid: 4 mismatch levels × 4 presets × 20 seeds, paired against forecaster-off on the same passes. Defaults were fixed on dev seeds 100–103. Default off; with it off results are bit-identical.

Result: negative. No forecaster raises the share of segments meeting C_{req}. AR(1) cuts the wind error by -0.059 m/s [-0.085, -0.033] in the fast loop (off: 0.558 m/s) and -0.099 m/s [-0.130, -0.068] in fast + slow, but success changes by -0.0 pp [-0.3, +0.3] and -0.2 pp [-0.4, +0.1]. The 3-seed pilot had suggested an error cut of about 0.18 m/s; it did not hold. The gust-aware arms cost about half a percent of volume for no gain, and `nominal+gust`, which widens the wind margin without any forecast, does the same. The bound explains it: `gust_oracle` changes success by -0.5 pp [-0.9, -0.1] (fast) and -0.3 pp [-0.6, -0.0] (fast + slow). A 30% stronger wind moves the coverage of the chosen settings by only 0.07 to 0.18 pp, so the selector's margin already absorbs gust risk, and the remaining shortfall comes from canopy interception, nozzle wear and card noise, which a wind forecast cannot see.




Figure 11. Left: example pass (`gusty_afternoon`, high mismatch, seed 0): realized wind, nominal reading, AR(1) forecast and gust-aware planning wind. Middle and right: change in share meeting C_{req} and in volume against forecaster-off by mismatch level (filled: fast loop; open: fast + slow; 95% paired CI).

Table 9. Wind forecaster arms, learned model, noisy verifier, low + med + high mismatch and all presets pooled. Δ = arm minus forecaster-off on the same passes, 95% paired-bootstrap CI. Source: `results/forecast_eval.json`.

Loop	Arm	Met	Δ met	Δ volume	Wind MAE (m/s)	Δ wind MAE
fast	off (reference)	0.940	-	-	0.558	-
fast	`last`	0.935	−0.5 pp [−0.9, −0.1]	−0.6% [−0.8, −0.3]	0.561	+0.002 m/s [−0.040, +0.046]
fast	`ewma`	0.938	−0.1 pp [−0.4, +0.2]	−0.2% [−0.4, +0.1]	0.516	−0.042 m/s [−0.082, −0.002]
fast	`ar1`	0.940	−0.0 pp [−0.3, +0.3]	+0.0% [−0.2, +0.2]	0.499	−0.059 m/s [−0.085, −0.033]
fast	`ar1+gust`	0.940	−0.0 pp [−0.4, +0.3]	+0.6% [+0.4, +0.7]	0.499	−0.059 m/s [−0.085, −0.033]
fast	`nominal+gust`	0.941	+0.1 pp [−0.1, +0.4]	+0.6% [+0.4, +0.7]	0.558	+0.000 m/s [+0.000, +0.000]
fast	`gust_oracle`	0.935	−0.5 pp [−0.9, −0.1]	−0.5% [−0.7, −0.2]	0.000	−0.558 m/s [−0.605, −0.511]
fast	*fair oracle (ref.)*	0.958				
fast + slow	off (reference)	0.960	-	-	0.558	-
fast + slow	`last`	0.956	−0.3 pp [−0.6, −0.1]	−0.3% [−0.6, −0.0]	0.561	+0.002 m/s [−0.040, +0.046]
fast + slow	`ewma`	0.959	−0.1 pp [−0.3, +0.2]	−0.1% [−0.3, +0.1]	0.516	−0.042 m/s [−0.082, −0.002]
fast + slow	`ar1`	0.958	−0.2 pp [−0.4, +0.1]	−0.1% [−0.3, +0.1]	0.459	−0.099 m/s [−0.130, −0.068]
fast + slow	`ar1+gust`	0.959	−0.1 pp [−0.4, +0.2]	+0.4% [+0.2, +0.6]	0.459	−0.099 m/s [−0.130, −0.068]
fast + slow	`nominal+gust`	0.959	−0.0 pp [−0.2, +0.2]	+0.6% [+0.4, +0.7]	0.558	+0.000 m/s [+0.000, +0.000]
fast + slow	`gust_oracle`	0.957	−0.3 pp [−0.6, −0.0]	−0.3% [−0.6, −0.1]	0.000	−0.558 m/s [−0.605, −0.511]
fast + slow	*fair oracle (ref.)*	0.958				

5.4 Physics-first hybrid predictor

Design (D14). `PhysicsResidualModel` predicts with a physics base (the simulator's equations without hidden mismatch, at the mean spread factor) plus a strongly regularized LightGBM residual and a conformalized interval. Because the plant is the simulator, an exact physics base is circular; the honest test uses misspecified bases (evaporation, drift threshold, spread factor and VMD each off by 10 to 30%). Default model stays `spray`.

Offline and in the selector the hybrid repairs a wrong physics base. The learned residual removes 94 to 99% of the misspecification's excess coverage and drift error (four splits, both presets). Coverage MAE against the expected coverage falls from 4.30 / 4.84 pp (physics alone, optimistic / pessimistic) to 0.31 / 0.30 pp, against 0.64 pp for `SprayModel`. In the selector test misspecified physics alone meets C_{req} in 44.0% of scenarios, the hybrid on the same wrong base in 93.5%, `SprayModel` in 92.5%.

In the closed loop the hybrid is not better than pure ML. With med + high mismatch (20 seeds, noisy verifier; fair oracle met 0.953 ± 0.014 at 25.9 GPA) the hybrid on a wrong base is 0.6 to 1.1 pp below `SprayModel` in every policy (CIs exclude zero) at 1.4 to 1.8% less volume. Its gap recovery with `fast_slow`, +98% [+88, +106], is not distinguishable from `SprayModel`'s +104% [+93, +113] (overlapping CIs; not tested paired) and meets the proposal criterion (+3.3% [+2.1, +4.5] volume). Misspecified physics alone collapses in the open loop (0.296 met against 0.822 for the hybrid) but reaches 0.978 after five passes of the slow loop, by spraying +9.7% [+8.5, +10.9] more than the fair oracle: the slow-loop offset absorbs a smooth physics bias. The exact-base hybrid, the circular upper bound, is not better than `SprayModel` either (-1.4 [-1.8, -1.0] pp with `fast_slow`). Recommendation: keep `SprayModel`; use the hybrid when a trusted physics model exists but is wrong by 10 to 30%.

Table 10. Hybrid predictor in the closed loop, med + high mismatch pooled, 20 seeds, noisy verifier. Gap recovery uses each model's own open loop; volume against the fair oracle; Δ met against `SprayModel` on the same seeds (95% paired-bootstrap CI). The exact-base row is circular. Source: `results/hybrid_eval.md`.

model	policy	met	volume (GPA)	gap recovery	volume vs oracle	Δ met vs spray (pp)
SprayModel (pure ML)	open	0.833 ± 0.064	23.5	-	−9.1% [−12.5, −5.2]	-
SprayModel (pure ML)	fast	0.927 ± 0.015	26.3	+79% [+63, +88]	+1.5% [+0.2, +2.9]	-
SprayModel (pure ML)	fast_slow	0.957 ± 0.012	27.2	+104% [+93, +113]	+5.1% [+3.8, +6.7]	-
hybrid (exact base)	fast_slow	0.943 ± 0.015	26.4	+93% [+84, +100]	+2.1% [+0.9, +3.4]	−1.4 [−1.8, −1.0]
physics only, misspecified (optimistic)	open	0.296 ± 0.094	22.2	-	−14.3% [−17.7, −10.6]	−53.7 [−57.8, −48.6]
physics only, misspecified (optimistic)	fast	0.854 ± 0.029	25.2	+85% [+82, +87]	−2.6% [−4.8, −0.3]	−7.3 [−9.1, −5.6]
physics only, misspecified (optimistic)	fast_slow	0.978 ± 0.010	28.4	+104% [+102, +105]	+9.7% [+8.5, +10.9]	+2.1 [+1.7, +2.5]
hybrid, misspecified base (optimistic)	open	0.822 ± 0.068	23.2	-	−10.4% [−13.8, −6.6]	−1.1 [−1.7, −0.5]
hybrid, misspecified base (optimistic)	fast	0.921 ± 0.015	25.8	+76% [+58, +85]	−0.2% [−1.4, +1.0]	−0.6 [−1.2, −0.2]
hybrid, misspecified base (optimistic)	fast_slow	0.950 ± 0.013	26.7	+98% [+88, +106]	+3.3% [+2.1, +4.5]	−0.7 [−1.1, −0.3]

6 Final Scorecard

Table 11 lists every success criterion of the proposal (Table 1, targets quoted verbatim; the verification criterion is split into its parts) and the four extensions. Of 15 rows, 8 are met, 1 partial, 1 missed, 1 blocked by data access, 3 are extensions evaluated with a negative result, 1 is an extension with inconclusive evidence, and 0 wait for an input. The same table, as text, is in `results/scorecard.md`. **met**: target satisfied (inside the simulator); **partial**: some sub-targets met; **missed**; **blocked**: outside dependency; **done-negative**: evaluated, negative result, not adopted; **inconclusive, not adopted**: evidence too weak either way.

Table 11. Final scorecard. Fair oracle = reference; card-aware oracle = unreachable bound. Brackets are 95% paired-bootstrap CIs.

Criterion	Target (proposal Table 1, verbatim)	Result (95% CI where one exists)	Status	Source
End-to-end demonstration	A simulated field pass runs from prediction to correction without manual steps, and every decision is logged and visualized.	`python -m coverageai.e2e --real`: 40-segment pass with rendered cards and B0 in 33 s, mean abs(measured - true) 0.57 pp (midterm measurement); every segment logged as a SegmentLog row. Streamlit app checked in a browser: all strategies and readers run, every decision is shown.	**met**	midterm e2e run; `app/main.py` browser check
Simulator and dataset	Outputs follow the encoded trends (coverage rises with volume; drift rises with wind speed, release height, and fine-droplet share) across the M1 operating ranges.	36 simulator tests pass, including a monotone sweep for each trend and the physical anchors; full suite 402 tests pass.	**met**	`tests/test_simulator.py`
Predictive model	Coverage MAE ≤ 3 pp on held-out conditions and lower than a linear baseline's; error reported on held-out condition regimes; sensitivity checks pass.	LightGBM 2.84 pp (random split) vs ridge 3.32 pp; 2.83, 2.98, 2.80 pp on three withheld regimes; 5/5 sensitivity checks pass; noise floor 2.76 pp. No CI (single hold-out).	**met**	`results/model_v1.json`

Parameter selection	With no injected mismatch, selected settings meet C_{req} in ≥ 90% of scenarios at lower drift risk than the best fixed setting with the same success rate.	97.0% of 200 scenarios; drift 0.0131 vs 0.0167 and 24.8 vs 47.5 GPA for the matched fixed setting (XR 15 @ 45 psi, 98%). No CI.	**met**	`results/selector_eval.json`
Verification: MAE, own synthetic cards	Coverage MAE ≤ 2 pp on synthetic cards.	B0 1.44 pp, B1 0.20 pp (180 held-out renderer cards).	**met**	`results/verification_eval.json`
Verification: class agreement, own synthetic cards	Three-class agreement ≥ 90% on synthetic cards.	B0 96.1%, B1 99.4%.	**met**	`results/verification_eval.json`
Verification: Simoes synthetic cards (out-of-generator)	Same synthetic targets: MAE ≤ 2 pp, agreement ≥ 90%.	B0 2.65 pp / 86.3%; B1 1.74 pp / 88.3%. B1 underreads every band; 30-50% band (16 cards) bias −6.83 pp.	**partial**	`results/verification_eval.json`
Verification: speed	≤ 2 s per card on a laptop CPU.	Laptop, busy CPU (upper bound): B0 p95 0.26 s; B1 p95 1.09 s, max 1.33 s (30 cards). Desktop re-time, light load (not a laptop): B0 p95 0.15 s; B1 p95 0.52 s, max 0.55 s.	**met**	`results/verification_eval.json` (timing); `results/b1_idle_retime.json`
Verification: real cards	Coverage MAE ≤ 5 pp on real cards.	Untested: the annotated real cards (Zenodo 14010262) are restricted; evaluation code is ready.	**blocked**	D9; `results/verification_summary.md`
Closed loop (fair oracle)	Under injected mismatch, recovers ≥ 50% of the open-loop-to-oracle gap in requirement-met segments, using ≤ 10% more volume than the oracle (20 seeds, 95% CI).	fast + slow: 96% [80, 107] recovery, +4.1% [+2.8, +5.5] volume. fast: 69% [44, 82] (CI crosses 50%), +1.4% [+0.2, +2.7].	**met**	`results/closed_loop_summary.md`
Closed loop (card-aware oracle, unreachable bound)	Same criterion against `oracle_card`, which also sees the per-card spread factor.	fast + slow: 63% [46, 73] recovery, +17.2% [+15.4, +19.0] volume. The fair oracle itself uses +12.6% [+11.2, +13.9] more volume than `oracle_card`.	**missed**	`results/closed_loop_summary.md`
Extension: travel speed (D11)	No proposal target. Adopt by default only if success holds and drift or volume falls.	Coarse grid (8-28 km/h in 4 km/h steps), 200 paired scenarios, learned selector: success +0.0 pp [−2.0, +2.0], drift −0.0010 [−0.0018, −0.0001]; nominal: success −0.5 pp [−2.0, +1.0], drift −0.0015 [−0.0027, −0.0005]. Shipped 2 km/h grid, open loop, learned: success 0.935 to 0.900 (single draw, no CI). Closed loop: pilot only (3 seeds, no CI), fast met 0.954 to 0.917. Not adopted: no closed-loop CI.	**inconclusive, not adopted**	`results/boom_control_eval.md` (speed variant); `results/speed_control_eval.md`
Extension: boom height (D12)	No proposal target. Same adoption rule.	Open loop, height alone: drift +0.0027 [+0.0005, +0.0049] (learned). Closed loop, fast, speed+height: met −2.9 pp [−3.6, −2.1] (med), −3.4 pp [−4.4, −2.4] (high), GPA −2.59 [−3.09, −2.11] (med). Fair oracle, height alone: drift −0.0060 [−0.0075, −0.0046] (high), met −0.2 pp [−0.9, +0.5].	**done-negative**	`results/boom_control_eval.md`
Extension: wind forecaster (D13)	No proposal target. Adopt only if it raises the share meeting C_{req}.	AR(1): wind MAE −0.059 m/s [−0.085, −0.033] (fast), success −0.0 pp [−0.3, +0.3]; fast + slow −0.2 pp [−0.4, +0.1]. Bound `gust_oracle`: −0.5 pp [−0.9, −0.1] (fast).	**done-negative**	`results/forecast_eval.json`, `results/forecast_eval.md`
Extension: hybrid physics + ML predictor (D14)	No proposal target. Adopt only if better than `SprayModel` in the closed loop.	Misspecified base, fast_slow: 0.950 met vs 0.957 (−0.7 [−1.1, −0.3] pp), recovery +98% [+88, +106] vs +104% [+93, +113], volume −1.8% [−2.1, −1.5] vs SprayModel.	**done-negative**	`results/hybrid_eval.md`

7 Negative Results

1. **Prediction-error variance does not shrink pass after pass.** The slow loop removes the mean residual (high mismatch: −6.02 pp in pass 1, 0.03 pp in pass 2), but the within-pass residual variance stays at 27.0 to 31.9 pp^2 in every pass and at every mismatch level, including none. Per-card spread-factor noise and per-segment gusts are irreducible for an offset correction.
2. **B1 is less safe outside the generator than on our own cards.** MAE 0.20 pp and 99.4% class agreement on renderer cards, but 1.74 pp (bias −1.74 pp) and 88.3% on the Simoes synthetic cards; class agreement misses 90% for both readers. Real-card accuracy is

unknown.

3. **The wind forecaster does not help.** AR(1) lowers the wind error (−0.059 m/s [−0.085, −0.033]) but not coverage failures (−0.0 pp [−0.3, +0.3]); even a perfect gust forecast gives −0.5 pp [−0.9, −0.1].
4. **Boom height (alone or with speed) trades success for drift and volume.** In the fast loop speed + height cuts volume (−2.81 [−3.34, −2.32] GPA, high) but meets C_{req} less often (−2.9 pp [−3.6, −2.1] med, −3.4 pp [−4.4, −2.4] high). Height alone raises drift in the open loop (+0.0027 [+0.0005, +0.0049], learned model). Speed alone changes success by +0.0 pp [−2.0, +2.0].
5. **The hybrid predictor is not better than pure ML in the closed loop**: −0.7 [−1.1, −0.3] pp met against `SprayModel` with `fast_slow`, and the exact-base (circular) hybrid is not better either.
6. **The midterm slow loop hurt.** Refitting LightGBM on the cards with record weight 30 gave −89% [−308, −16] recovery (met 0.832); it narrowed the interval while fitting card noise. Replaced by the residual offset (D16).
7. **The volume target is unreachable against the card-aware oracle.** The fair oracle itself uses +12.6% [+11.2, +13.9] more volume than `oracle_card`; fast + slow is at +17.2% [+15.4, +19.0].
8. **The fast loop alone does not clear the recovery target with confidence**: 69% [44, 82], weakest on `hot_dry` (55% [4, 73]).
9. **Rendered-card verifiers are inconclusive in the loop**: 5 seeds give 46% [−67, 78] (B0) and 46% [−100, 76] (B1) recovery. Retreatment flags were never raised, so that path is untested.

8 Limitations

- **Simulator-internal and partly circular.** Plant, training data, renderer and hidden mismatch come from one hand-built simulator, fit to published trends, not a validated drift model. The experiments test whether the control logic behaves as designed when the model is wrong in a known, low-dimensional way; they do not measure field efficacy. The mismatch is injected by us and is of the kind the bias and offset are built to absorb (a coverage offset that persists over a pass, with a mean that persists across passes). Inversions, boom roll, nozzle clogging and card-placement error are not tested. Scenarios are a synthetic generator, not weather records. The hybrid's exact physics base is the plant itself, so its exact-base rows are an upper bound.
- **The oracle defines the result.** Against the fair oracle the closed-loop criterion is met; against the card-aware oracle it is missed on volume, because that oracle sees the per-card spread factor; the fair oracle itself uses +12.6% [+11.2, +13.9] more volume than it. With a stricter fair oracle (q = 0.05) recovery shrinks but the criterion still holds. The fair-oracle definition and its q = 0.1 risk level were fixed before the grid ran.
- **No real annotated cards.** The two annotated real cards are in a restricted Zenodo record (D9). The real-card criterion (≤ 5 pp) is untested, and sim-to-real transfer of B0 and B1 is unmeasured; the proposal cites a drop from 57.06% to 40.81% for YOLOv8 from synthetic to real cards [7].
- **Out-of-generator class agreement is missed.** On the Simões synthetic cards B1 reaches 1.74 pp MAE but 88.3% class agreement (B0: 2.65 pp, 86.3%), against a 90% target. Both underread at 15–50% coverage, where few cards exist, and the Simões pixel scale is inferred.
- **The default loop verifier is a noise model.** The closed-loop grid uses perfect coverage plus Gaussian error calibrated to B0, which omits heavy-tailed failures and domain shift; the rendered-card runs have only 5 seeds.
- **Same class, same physics.** Spray angle and pattern overlap are not modeled (beyond the boom-height overlap constraint), so families with the same droplet class and flow are indistinguishable to the selector.

9 Key Decisions

The decision log (`Docs/decisions.md`) holds 17 entries, each resolving an ambiguity or recording a design choice. D1–D5 fix conventions and catalog gaps; D6 deferred speed control; D7–D8 record the compressed schedule and the Python toolchain; D9 reports the real-card criterion as untested rather than estimating it; D10 adds nozzle exit velocity so medium droplets no longer drift implausibly (87% to 8% at 2 m/s). After the midterm: D11 and D12 add travel speed and boom height as optional settings; D13 the wind forecaster; D14 the hybrid predictor; D15 the fair oracle as the reference of the closed-loop criterion; D16 the residual-offset slow loop that replaced the LightGBM refit; D17 the app's opt-in controller options. Each post-midterm entry records its evaluation verdict.

10 Project Management and Contributions

Tools follow the proposal: a GitHub repository with review before merge, a Microsoft Teams channel, the decision log and an AI-use log (19 entries). After the midterm the M3–M4 work (B1 GPU training, slow-loop redesign, fair oracle and the full closed-loop rerun) was completed, and the four extensions were added and evaluated. The real-card evaluation remains blocked by data access.

Table 12. Contributions. Modules implemented by AI agents are owned and reviewed by the named member.

Member	Responsibilities	Work completed
Emery Brewer (remote)	System specification, physics relationships, scenario rationale, selector ownership, domain validation.	Authored the parameter specification and early simulations that define `spec.yaml` and the simulator physics; owner of the catalog, scenario library and selector. **TEAM TO CONFIRM** review of the speed and boom-height relationships (D11, D12) and the domain-validation text.
Junjie Ao	Simulator and dataset pipeline; predictive model ownership.	Owner of the simulator, dataset v1 and the `SprayModel` (LightGBM with conformal interval, baselines, grouped-split evaluation) and of the hybrid predictor evaluation (D14). **TEAM TO CONFIRM** his own authoring and review.
Kinjalk Parth	WSP renderer; verification; feedback and loop; integration and experiments; orchestration of AI-assisted work.	Contracts, decision log, renderer, B0, B1 (GPU training), Simões loader, feedback (fast loop, residual slow loop), loop harness with fair oracle, closed-loop grid, forecaster and extension experiments, Streamlit app, this report; review and merge of all work packages.

11 AI-Use Disclosure

The course permits AI use, and this project uses it heavily. Plans, contracts, simulator, catalog transcription, model, selector, scenarios, renderer, both verifiers, feedback, loop, experiments, app, tests and this report were produced by Claude models (Claude Opus as orchestrator and reviewer, Claude Sonnet and Opus models as implementation agents) under the team's direction; 19 sessions are recorded in `Docs/ai_usage_log.md` (Appendix A). Team members set the scope, resolve ambiguities in the decision log, review the modules they own, and are responsible for every claim here. Numbers are read from results files at build time; the only typed numbers are the midterm end-to-end run, the test-suite count and the app run time from the browser check, each with its source in `reports/final/build.py`.

References

1. A. S. Felsot, J. B. Unsworth, J. B. H. J. Linders, G. Roberts, D. Rautman, C. Harris, and E. Carazo. Agrochemical spray drift; assessment and mitigation—A review. *J. Environ. Sci. Health, Part B*, 46(1):1–23, 2011.
2. H. Zhu, M. Salyani, and R. D. Fox. A portable scanning system for evaluation of spray deposit distribution. *Computers and Electronics in Agriculture*, 76:38–43, 2011. doi:10.1016/j.compag.2011.01.003.
3. ANSI/ASABE S572.3. Spray Nozzle Classification by Droplet Spectra. ASABE, St. Joseph, MI, 2020.
4. Kansas State University Research and Extension. Droplet Size Calibration: A New Approach to Effective Spraying. Publication MF2869.
5. E. Cerruto, S. Failla, D. Longo, and G. Manetto. Simulation of water sensitive papers for spray analysis. *CIGR Journal*, 18(4), 2016.
6. E. Cerruto, G. Manetto, D. Longo, S. Failla, and R. Papa. A model to estimate the spray deposit by simulated water sensitive papers. *Crop Protection*, 124:104861, 2019. doi:10.1016/j.cropro.2019.104861.
7. I. Simões, A. J. Sousa, A. Baltazar, and F. Santos. Spray quality assessment on water-sensitive paper comparing AI and classical computer vision methods. *Agriculture*, 15(3):261, 2025. doi:10.3390/agriculture15030261; data: doi:10.5281/zenodo.13995950.
8. Q. Gao, M. Sozzi, and F. Marinello. U-Net-based semantic segmentation and concave point detection for adhesive droplets on water-sensitive paper. University of Padova research record, 2025. hdl:11577/3569369.
9. L. Schiller and A. Naumann. Über die grundlegenden Berechnungen bei der Schwerkraftaufbereitung. *Z. Ver. Dtsch. Ing.*, 77:318–320, 1933.
10. R. E. Williamson and E. D. Threadgill. A simulation for the dynamics of evaporating spray droplets in agricultural spraying. *Trans. ASAE*, 17(2):254–261, 1974.
11. R. Stull. Wet-bulb temperature from relative humidity and air temperature. *J. Appl. Meteorol. Climatol.*, 50(11):2267–2269, 2011. doi:10.1175/JAMC-D-11-0143.1.
12. TeeJet Technologies, Spray Nozzles Catalog 51A (TP, XR, DGX rate charts); Hypro (Pentair), ULD and 3D nozzle sales sheets.
13. University of Nebraska–Lincoln Extension. Temperature, humidity and evaporation of spray droplets, G1773.
14. U.S. EPA. Mitigation menu measure descriptions. epa.gov/pesticides/mitigation-menu-measure-descriptions.
15. G. Ke et al. LightGBM: a highly efficient gradient boosting decision tree. *Advances in Neural Information Processing Systems* 30, 2017.
16. Y. Romano, E. Patterson, and E. J. Candès. Conformalized quantile regression. *Advances in Neural Information Processing Systems* 32, 2019.
17. N. Otsu. A threshold selection method from gray-level histograms. *IEEE Trans. Systems, Man, and Cybernetics*, 9(1):62–66, 1979.

References [1]–[8] reuse the proposal's [1], [2], [8], [10], [11], [14], [9], [12]; the rest are sources used in the code or project documents. **TEAM TO CONFIRM references [9]–[11] and [15]–[17]**

Appendix A: AI Usage Log

Reproduced from `Docs/ai_usage_log.md` at build time (19 sessions).

Date	Work package	Model	Output
2026-10-18	Plan, WP-00	Claude Opus 5.5	PLAN.md, contracts, spec.yaml, units, mocks, smoke test
2026-10-18	WP-11	Claude Sonnet 5.5	selector.py (constrained selector, best_fixed_setting), experiments/eval_selector.py, tests/test_selector.py
2026-10-18	WP-12	Claude Sonnet	Scenario library (scenarios.py: six presets, AR(1) wind with gusts, random_conditions), plot script, Docs/scenarios.md, tests
2026-10-18	WP-01	Claude Sonnet	Nozzle catalog: data/catalog/nozzles.csv (316 rows, 5 families; Hypro rows from official Pentair PDFs), gpa_checks.csv, experiments/validate_catalog.py, catalog.py (load/derive/candidates), tests/test_catalog.py
2026-10-18	WP-06	Claude Sonnet	feedback.py (eq. 3 bias, per-regime, warm-up, clip), loop.py (run_pass, oracle wrapper, slow loop, logs/summary), e2e rewired to loop, tests
2026-10-18	WP-05	Claude Sonnet 5.5	Zenodo investigation of the Simoes 2025 dataset, `vision/real_data.py` loader (download, YOLOv8-polygon rasterization, tiling, summary CLI), tests, example figure, decision D9, draft email to authors
2026-10-18	WP-02	Claude Sonnet 5.5	physics/ (droplets, evaporation, drift, coverage), simulator.py (SpraySimulator, begin_pass, simulate_batch), tests/test_simulator.py, experiments/sim_trends.py + figure
2026-10-18	WP-03	Claude Sonnet	vision/render.py synthetic WSP renderer (vectorized rasterizer, scanner/phone degradations), stratified dataset CLI, tests/test_render.py, example figure
2026-10-18	WP-02b	Claude Sonnet 5.5	Exit-velocity + linear-drag relaxation in physics/drift.py (decision D10), anchor tests, refreshed sim_trends.png
2026-10-18	WP-10	Claude Sonnet	Dataset generator (experiments/make_dataset.py, results/dataset_v1.md), model/features.py, model/predictor.py (SprayModel LightGBM + CQR interval, ridge/RF baselines), experiments/train_eval_model.py, results/model_v1.json, parity and sensitivity figures, tests/test_model.py
2026-10-18/19	WP-20/21	Claude Sonnet 5.5	integration.py (build_modules, NominalPhysicsModel, NoisyVerifier), vectorized oracle (simulator.simulate_candidates/nominal_arrays), loop pass-state + measure_outcome hooks, e2e --real, experiments/closed_loop.py (grid, ablations, figures, summary), results/closed_loop*, tests/test_integration.py
2026-10-18	WP-04	Claude Sonnet 5.5	vision/classical.py ClassicalVerifier B0 (ROI quad + perspective, flatten, Otsu/fixed threshold, watershed stains, Dv), vision/simple_cards.py test-card generator, experiments/eval_classical.py (WP-03 dataset aware), tests/test_classical.py, results/b0_synthetic.json + parity plot
2026-10-18	WP-40	Claude Sonnet 5.5	Midterm report draft: reports/midterm/template.html, build.py (fills numbers from results/*.json, copies figures, renders PDF via headless Edge), midterm_report.html/.pdf
2026-10-18	WP-22	Claude Sonnet	Streamlit demo (app/main.py, app/charts.py), coverageai/app_logic.py (module adapter, pass wrapper, KPIs, field strip, nozzle explorer helpers), .streamlit theme, experiments/demo_screenshots.py (headless Chrome CDP + static fallback), tests/test_app_logic.py
2026-10-18	WP-13	Claude Sonnet	vision/unet.py (U-Net B1: pairing, augmentation, train, tiled UNetVerifier, eval CLI), vision/toy_data.py, tests/test_unet.py, notebooks/train_unet_colab.ipynb; CPU toy run only
2026-10-18	WP-40b	Claude Sonnet 5.5	Midterm report update with all results: selector (spray vs oracle), B1 CPU-checkpoint rows and idle timing, closed-loop section parsed from closed_loop_summary.md, demo section, status table, corrected schedule and Zenodo wording, build.py changes (cropped figures, B1 loader)
2026-10-19	Handoff (NEXT_STEPS 1-5)	Claude Opus 5.5 (orchestrator, final report), Claude Sonnet 5.5 (eval, app, timing agents), Claude Haiku 5.5 (text fix)	New-machine setup (CUDA torch), full forecaster grid (negative result, D13) and hybrid closed loop (D14) with verdicts, eval_forecast.py syntax fix, boom-height verdict (D12), D15/D16 rows, app browser check with 5 fixes and opt-in speed/boom/forecast controls, B1 idle re-timing (results/b1_idle_retime.json), final report (reports/final/), results/scorecard.md, README/NEXT_STEPS refresh
2026-10-19	WP-40c	Claude Opus 5.5	Midterm report, complete version: reports/midterm/build.py + template.html re-derived from reports/final (midterm framing, rubric section order, contribution table with next milestones, analysis and next-steps sections, team confirmations applied, U-Net training wording), separate reports/midterm/scorecard.md; regenerated data/synthetic/v1 (1200 cards, seed 0); midterm_report.html/.pdf
2026-10-20	README media	Claude Opus 5.5	experiments/readme_media.py (renders the app's field-run and spray-lab canvases in headless Chrome with set animation times, WSP card frames with B0 masks, ffmpeg GIFs); Docs/media/ field_run.gif, spray_lab.gif, nozzle_compare.gif, wsp_cards.gif, app_field_run.png; README hero, loop diagram (mermaid), "See it in action" and "Results at a glance" sections