

Team Notebook

July 29, 2023

Contents

| | | | | | | | | |
|----------|-------------------------------|----------|----------|-------------------------------|-----------|----------|---------------------------------|-----------|
| 1 | Strings | 2 | 4.8 | sweep | 10 | 6.7 | segment-tree-lazy | 18 |
| 1.1 | AhoCorasick | 2 | 4.9 | theorems | 11 | 6.8 | segment-tree | 19 |
| 1.2 | Manacher | 2 | 5 | graph | 11 | 6.9 | sparse-table | 19 |
| 1.3 | PalindromicTree | 2 | 5.1 | bellman-ford | 11 | 6.10 | unordered-map | 19 |
| 1.4 | PrefixFunction | 3 | 5.2 | dijkstra | 11 | 7 | math | 20 |
| 1.5 | SuffixArray | 3 | 5.3 | dinic | 11 | 7.1 | arithmetic | 20 |
| 1.6 | SuffixAutomaton | 5 | 5.4 | floyd-warshall | 12 | 7.2 | bigint | 20 |
| 2 | dp | 6 | 5.5 | heavy-light | 12 | 7.3 | crt | 21 |
| 2.1 | convex-hull-trick | 6 | 5.6 | hungarian | 12 | 7.4 | discrete-log | 21 |
| 2.2 | divide-and-conquer | 6 | 5.7 | kuhn | 13 | 7.5 | gauss | 22 |
| 3 | generate_pdf | 6 | 5.8 | lca | 13 | 7.6 | matrix | 22 |
| 4 | geo2d | 7 | 5.9 | maxflow-mincost | 14 | 7.7 | mod | 22 |
| 4.1 | circle | 7 | 5.10 | push-relabel | 14 | 7.8 | poly | 23 |
| 4.2 | convex-hull | 7 | 5.11 | strongly-connected-components | 15 | 7.9 | primes | 25 |
| 4.3 | delaunay | 8 | 5.12 | two-sat | 15 | 7.10 | segment | 26 |
| 4.4 | halfplane-intersect | 9 | 6 | implementation | 15 | 7.11 | theorems | 26 |
| 4.5 | line | 9 | 6.1 | dsu | 15 | 8 | strings_{martin} | 26 |
| 4.6 | point | 10 | 6.2 | fenwick-tree | 16 | 8.1 | hash | 26 |
| 4.7 | polygon | 10 | 6.3 | mo | 16 | 8.2 | hash2d | 27 |
| | | | 6.4 | persistent-segment-tree-lazy | 16 | 8.3 | kmp | 28 |
| | | | 6.5 | persistent-segment-tree | 17 | 8.4 | palin | 28 |
| | | | 6.6 | search | 17 | 8.5 | sufarr | 28 |

1 Strings

1.1 AhoCorasick

```
#include<bits/stdc++.h>
using namespace std;

const int K = 26;
struct Vertex {
    int next[K];
    int leaf = 0;
    int leaf_id = -1;
    int p = -1;
    char pch;
    int link = -1;
    int exit = -1;
    int cnt = -1;
    int go[K];

    Vertex(int p=-1, char ch='$') : p(p), pch(ch) {
        fill(begin(next), end(next), -1);
        fill(begin(go), end(go), -1);
    }
};

vector<Vertex> t(1);

void add(string &s, int id) {
    int v = 0;
    for (char ch : s) {
        int c = ch - 'a';
        if (t[v].next[c] == -1) {
            t[v].next[c] = t.size();
            t.emplace_back(v, ch);
        }
        v = t[v].next[c];
    }
    t[v].leaf++;
    t[v].leaf_id = id;
}

int go(int v, char ch);

int get_link(int v) {
    if (t[v].link == -1) {
        if (v == 0 || t[v].p == 0)
            t[v].link = 0;
        else
            t[v].link = go(get_link(t[v].p), t[v].pch);
    }
}
```

```
        return t[v].link;
    }

    int go(int v, char ch) {
        int c = ch - 'a';
        if (t[v].go[c] == -1) {
            if (t[v].next[c] != -1)
                t[v].go[c] = t[v].next[c];
            else
                t[v].go[c] = v == 0 ? 0 : go(get_link(v), ch);
        }
        return t[v].go[c];
    }

    int next_match(int v)
    {
        if (t[v].exit == -1)
        {
            if (t[get_link(v)].leaf)
                t[v].exit = get_link(v);
            else
                t[v].exit = v == 0 ? 0 : next_match(get_link(v));
        }
        return t[v].exit;
    }

    int cnt_matches(int v)
    {
        if (t[v].cnt == -1)
            t[v].cnt = v == 0 ? 0 : t[v].leaf + cnt_matches(
                get_link(v));
        return t[v].cnt;
    }
}
```

1.2 Manacher

```
#include<bits/stdc++.h>
using namespace std;
#define rep(i, n) for (int i = 0; i < (int)n; i++)
#define repx(i, a, b) for (int i = (int)a; i < (int)b; i++)

// odd[i] : length of the longest palindrome centered at i
// even[i] : length of the longest palindrome centered
//            between i and i+1
void manacher(string &s, vector<int> &odd, vector<int> &even)
{
    string t = "$#";
    for(char c: s)
        t += c + string("#");
```

```
    t += "^";
    int n = t.size();
    vector<int> p(n);
    int l = 1, r = 1;
    repx(i, 1, n-1) {
        p[i] = max(0, min(r - i, p[l + (r - i)]));
        while(t[i - p[i]] == t[i + p[i]]) {
            p[i]++;
        }
        if (i + p[i] > r) {
            l = i - p[i], r = i + p[i];
        }
    }
    repx(i, 2, n-2) {
        if(i%2) even.push_back(p[i]-1);
        else odd.push_back(p[i]-1);
    }
}
```

1.3 PalindromicTree

```
#include<bits/stdc++.h>
using namespace std;
#define rep(i, n) for (int i = 0; i < (int)n; i++)
#define repx(i, a, b) for (int i = (int)a; i < (int)b; i++)

struct Node {
    int len;           // length of substring
    int edge[26];      // insertion edge for all characters a-z
    int link;          // the Maximum Palindromic Suffix Node
                      // for the current Node
    int i;             // (optional) start index of current Node
    int cnt = 1;       // (optional) number of occurrences of
                      // this substring
    Node(){ fill(begin(edge), end(edge), -1); }
};

struct EerTree { // Palindromic Tree
    vector<Node> t; // tree
    int curr;      // current node

    EerTree(string &s) {
        t.resize(2);
        t.reserve(s.size()+2); // (optional) maximum size of
        // tree
        t[0].len = -1;         // root 1
        t[0].link = 0;
        t[1].len = 0;          // root 2
        t[1].link = 0;
```

```

curr = 1;
rep(i, s.size()) insert(i, s); // construct tree

// (optional) calculate number of occurrences of each
// node
for(int i = t.size()-1; i > 1; i--)
    t[t[i].link].cnt += t[i].cnt;
}

void insert(int i, string &s) {
    int tmp = curr;
    while (i - t[tmp].len < 1 || s[i] != s[i-t[tmp].len-1])
        tmp = t[tmp].link;

    if(t[tmp].edge[s[i]-'a'] != -1){
        curr = t[tmp].edge[s[i]-'a']; // node already
        exists
        t[curr].cnt++; // (optional)
        increase cnt
        return;
    }

    curr = t[tmp].edge[s[i]-'a'] = t.size(); // create
    new node
    t.emplace_back();

    t[curr].len = t[tmp].len + 2; // set length
    t[curr].i = i - t[curr].len + 1; // (optional) set
    start index

    if (t[curr].len == 1) { // set suffix link
        t[curr].link = 1;
    } else {
        tmp = t[tmp].link;
        while (i-t[tmp].len < 1 || s[i] != s[i-t[tmp].len-1])
            tmp = t[tmp].link;
        t[curr].link = t[tmp].edge[s[i]-'a'];
    }
}

int main()
{
    string s = "abcbab";
    EerTree pt(s); // construct palindromic tree
    repx(i, 2, pt.t.size()) // list all distinct palindromes
    {
        cout << i-1 << " ";
    }
}

```

```

repx(j, pt.t[i].i, pt.t[i].i + pt.t[i].len)
    cout << s[j];
    cout << " " << pt.t[i].cnt << endl;
}

return 0;
}

```

1.4 PrefixFunction

```

#include<bits/stdc++.h>
using namespace std;
#define rep(i, n) for (int i = 0; i < (int)n; i++)
#define repx(i, a, b) for (int i = (int)a; i < (int)b; i++)

vector<int> prefix_function(string s) {
    int n = s.size();
    vector<int> pi(n);
    repx(i, 1, n) {
        int j = pi[i-1];
        while (j > 0 && s[i] != s[j])
            j = pi[j-1];
        if (s[i] == s[j])
            j++;
        pi[i] = j;
    }
    return pi;
}

vector<vector<int>> aut;
void compute_automaton(string s) {
    s += '#';
    int n = s.size();
    vector<int> pi = prefix_function(s);
    aut.assign(n, vector<int>(26));
    rep(i, n) {
        rep(c, 26) {
            int j = i;
            while (j > 0 && 'a' + c != s[j])
                j = pi[j-1];
            if ('a' + c == s[j])
                j++;
            aut[i][c] = j;
        }
    }
}

```

1.5 SuffixArray

```

#include<bits/stdc++.h>
using namespace std;
#define LOG2(X) ((unsigned) (8*sizeof (unsigned long long) -
    __builtin_clzll((X)) - 1))
#define rep(i, n) for (int i = 0; i < (int)n; i++)
#define repx(i, a, b) for (int i = (int)a; i < (int)b; i++)

struct SuffixArray {
    int n; vector<int> C, R, R_, sa, sa_, lcp;
    inline int gr(int i) { return i < n ? R[i] : 0; } // sort
    suffixes
    //inline int gr(int i) { return R[i%n]; } // sort
    cyclic shifts
    void csort(int maxv, int k) {
        C.assign(maxv + 1, 0); rep(i, n) C[gr(i + k)]++;
        repx(i, 1, maxv + 1) C[i] += C[i - 1];
        for (int i = n - 1; i >= 0; i--) sa[--C[gr(sa[i] + k)]] = sa[i];
        sa.swap(sa_);
    }
    void getSA(vector<int>& s) {
        R = R_ = sa = sa_ = vector<int>(n); rep(i, n) sa[i] = i;
        sort(sa.begin(), sa.end(), [&s](int i, int j) {
            return s[i] < s[j]; });
        int r = R[sa[0]] = 1;
        repx(i, 1, n) R[sa[i]] = (s[sa[i]] != s[sa[i - 1]]) ?
            ++r : r;
        for (int h = 1; h < n && r < n; h <= 1) {
            csort(r, h); csort(r, 0); r = R_[sa[0]] = 1;
            repx(i, 1, n) {
                if (R[sa[i]] != R[sa[i - 1]] || gr(sa[i] + h)
                    != gr(sa[i - 1] + h)) r++;
                R_[sa[i]] = r;
            }
            R.swap(R_);
        }
    }
    void getLCP(vector<int> &s) { // only works with suffixes
        (not cyclic shifts)
        lcp.assign(n, 0); int k = 0;
        rep(i, n) {
            int r = R[i] - 1;
            if (r == n - 1) { k = 0; continue; }
            int j = sa[r + 1];
            while (i + k < n && j + k < n && s[i + k] == s[j + k]) k++;
            lcp[r] = k; if (k) k--;
        }
    }
}

```

```

}
SuffixArray(vector<int> &s) { n = s.size(); getSA(s);
    getLCP(s); constructLCP(); }

/* ----- Optional ----- */
vector<vector<int>> T;
void constructLCP() {
    T.assign(LOG2(n)+1, lcp);
    for(int k = 1; (1<<k) <= n; ++k)
        for(int i = 0; i + (1<<k) <= n; ++i)
            T[k][i] = min(T[k-1][i], T[k-1][i+(1<<(k-1))]);
}
// get LCP of suffix starting at i and suffix starting at
// j
int queryLCP(int i, int j) {
    if(i == j) return n-i;
    i = R[i]-1; j = R[j]-1;
    if(i > j) swap(i, j);
    ll k = LOG2(j-i);
    return min(T[k][i], T[k][j-(1<<k)]);
}
// compare substring of length len1 starting at i
// with substring of length len2 starting at j
bool cmp(int i, int len1, int j, int len2) {
    if(queryLCP(i, j) >= min(len1, len2))
        return (len1 < len2);
    else
        return (R[i] < R[j]);
}
};

vector<int> suffix_array;
vector<vector<int>> C;
int n;

void sort_cyclic_shifts(string s) {
    s += "$";
    n = s.size();
    const int alphabet = 256;
    vector<int> p(n), c(n), cnt(max(alphabet, n), 0);
    for (int i = 0; i < n; i++)
        cnt[s[i]]++;
    for (int i = 1; i < alphabet; i++)
        cnt[i] += cnt[i-1];
    for (int i = 0; i < n; i++)
        p[--cnt[s[i]]] = i;
    c[p[0]] = 0;
    int classes = 1;
    for (int i = 1; i < n; i++) {
        if (s[p[i]] != s[p[i-1]])

```

```

            classes++;
            c[p[i]] = classes - 1;
        }
        C.emplace_back(c.begin(), c.end());
        vector<int> pn(n), cn(n);
        for (int h = 0; (1 << h) < n; ++h) {
            for (int i = 0; i < n; i++) {
                pn[i] = p[i] - (1 << h);
                if (pn[i] < 0)
                    pn[i] += n;
            }
            fill(cnt.begin(), cnt.begin() + classes, 0);
            for (int i = 0; i < n; i++)
                cnt[c[pn[i]]]++;
            for (int i = 1; i < classes; i++)
                cnt[i] += cnt[i-1];
            for (int i = n-1; i >= 0; i--)
                p[--cnt[c[pn[i]]]] = pn[i];
            cn[p[0]] = 0;
            classes = 1;
            for (int i = 1; i < n; i++) {
                pair<int, int> cur = {c[p[i]], c[(p[i] + (1 << h)) % n]};
                pair<int, int> prev = {c[p[i-1]], c[(p[i-1] + (1 << h)) % n]};
                if (cur != prev)
                    ++classes;
                cn[p[i]] = classes - 1;
            }
            c.swap(cn);
            C.emplace_back(c.begin(), c.end());
        }
        p.erase(p.begin());
        suffix_array = p;
    }

vector<int> lcp_construction(string &s, vector<int> &p) {
    int n = s.size();
    vector<int> rank(n);
    rep(i, n) rank[p[i]] = i;

    int k = 0;
    vector<int> lcp(n-1, 0);
    rep(i, n) {
        if (rank[i] == n - 1) {
            k = 0;
            continue;
        }
        int j = p[rank[i] + 1];
        while (i + k < n && j + k < n && s[i+k] == s[j+k])

```

```

            k++;
            lcp[rank[i]] = k;
            if (k)
                k--;
        }
        return lcp;
    }

bool compare1(int i, int j, int l) {
    int k = LOG2(l);
    pair<int, int> a = {C[k][i], C[k][(i+1-(1 << k))%n]};
    pair<int, int> b = {C[k][j], C[k][(j+1-(1 << k))%n]};
    return a >= b;
}

bool compare2(int i, int j, int l) {
    int k = LOG2(l);
    pair<int, int> a = {C[k][i], C[k][(i+1-(1 << k))%n]};
    pair<int, int> b = {C[k][j], C[k][(j+1-(1 << k))%n]};
    return a <= b;
}

pair<int, int> find(int i, int len)
{
    int l = 0, r = suffix_array.size()-1;
    while(l != r)
    {
        int mid = (l+r)/2;
        if(compare1(suffix_array[mid], i, len))
            r = mid;
        else
            l = mid+1;
    }
    int left = l;

    l = 0, r = suffix_array.size()-1;
    while(l != r)
    {
        int mid = (l+r+1)/2;
        if(compare2(suffix_array[mid], i, len))
            l = mid;
        else
            r = mid-1;
    }
    int right = r;

    if(!compare1(suffix_array[left], i, len)) return {-1, -1};
    if(!compare2(suffix_array[right], i, len)) return
        {-1, -1};
}

```

```

    if(left > right) return {-1,-1};

    return {left, right};
}

```

1.6 SuffixAutomaton

```

#include<bits/stdc++.h>
using namespace std;
#define rep(i, n) for (int i = 0; i < (int)n; i++)
#define repx(i, a, b) for (int i = (int)a; i < (int)b; i++)

struct SuffixAutomaton {
    vector<map<char,int>> edges; // edges[i] : the labeled
        edges from node i
    vector<int> link;           // link[i] : the suffix link
        of i
    vector<int> length;         // length[i] : the length of
        the longest string in the ith class
    vector<int> cnt;            // cnt[i] : number of
        occurrences of each string in the ith class
    vector<int> paths;          // paths[i] : number of paths
        on the automaton starting from i
    vector<bool> terminal;      // terminal[i] : true if i is
        a terminal state
    vector<int> first_pos;
    vector<int> last_pos;
    int last;                  // the index of the
        equivalence class of the whole string

    SuffixAutomaton(string s) {
        edges.push_back(map<char,int>());
        link.push_back(-1);
        length.push_back(0);
        last = 0;

        rep(i, s.size()) { // construct r
            edges.push_back(map<char,int>());
            length.push_back(i+1);
            link.push_back(0);
            int r = edges.size() - 1;
            int p = last; // add edges to r and find p with
                link to q
            while(p >= 0 && !edges[p].count(s[i])) {
                edges[p][s[i]] = r;
                p = link[p];
            }
            if(p != -1) {
                int q = edges[p][s[i]];

```

```

                if(length[p] + 1 == length[q]) {
                    link[r] = q; // we do not have to split q,
                        just set the correct suffix link
                } else { // we have to split, add q'
                    edges.push_back(edges[q]); // copy edges
                        of q
                    length.push_back(length[p] + 1);
                    link.push_back(link[q]); // copy parent of
                        q
                    int qq = edges.size()-1;
                    link[q] = qq; // add qq as the new parent
                        of q and r
                    link[r] = qq;
                    while(p >= 0 && edges[p][s[i]] == q) { //
                        move short classes polling to q to
                        poll to q'
                        edges[p][s[i]] = qq;
                        p = link[p];
                    }
                }
            }
            last = r;
        }

        /* ----- Optional ----- */

        // mark terminal nodes
        terminal.assign(edges.size(), false);
        int p = last;
        while(p > 0) {
            terminal[p] = true;
            p = link[p];
        }

        // precompute match count
        cnt.assign(edges.size(), -1);
        cnt_matches(0);

        // precompute number of paths (substrings) starting
            from state
        paths.assign(edges.size(), -1);
        cnt_paths(0);

        first_pos.assign(edges.size(), -1);
        get_first_pos(0);

        last_pos.assign(edges.size(), -1);
        get_last_pos(0);
    }
}

```

```

int cnt_matches(int state) {
    if(cnt[state] != -1) return cnt[state];
    int ans = terminal[state];
    for(auto edge : edges[state])
        ans += cnt_matches(edge.second);
    return cnt[state] = ans;
}

int cnt_paths(int state) {
    if(paths[state] != -1) return paths[state];
    int ans = state == 0 ? 0 : 1; // without repetition (
        counts diferent substrings)
    // int ans = state == 0 ? 0 : cnt[state]; // with
        repetition
    for(auto edge : edges[state])
        ans += cnt_paths(edge.second);
    return paths[state] = ans;
}

int get_first_pos(int state) {
    if(first_pos[state] != -1) return first_pos[state];
    int ans = 0;
    for(auto edge : edges[state])
        ans = max(ans, get_first_pos(edge.second)+1);
    return first_pos[state] = ans;
}

int get_last_pos(int state) {
    if(last_pos[state] != -1) return last_pos[state];
    int ans = terminal[state] ? 0 : INT_MAX; //fix
    for(auto edge : edges[state])
        ans = min(ans, get_last_pos(edge.second)+1);
    return last_pos[state] = ans;
}

string get_k_substring(int k) // 0-indexed
{
    string ans;
    int state = 0;
    while(true)
    {
        int curr = state == 0 ? 0 : 1; // without
            repetition (counts diferent substrings)
        // int curr = state == 0 ? 0 : cnt[state]; // with
            repetition
        if(curr > k) return ans;
        k -= curr;

        for(auto edge : edges[state]) {
            if(paths[edge.second] <= k) {

```

```

        k -= paths[edge.second];
    } else {
        ans += edge.first;
        state = edge.second;
        break;
    }
}
}
};

```

2 dp

2.1 convex-hull-trick

```

#include "../common.h"

const ll INF = LLONG_MAX;

struct Line {
    mutable ll a, b, c;

    bool operator<(Line r) const { return a < r.a; }
    bool operator<(ll x) const { return c < x; }
};

// dynamically insert 'a*x + b' lines and query for maximum
// at any x
// all operations have complexity O(log N)
// UNTESTED
struct LineContainer : multiset<Line, less<>> {

    ll div(ll a, ll b) {
        return a / b - ((a ^ b) < 0 && a % b);
    }

    bool isect(iterator x, iterator y) {
        if (y == end()) return x->c = INF, 0;
        if (x->a == y->a) x->c = x->b > y->b ? INF : -INF;
        else x->c = div(y->b - x->b, x->a - y->a);
        return x->c >= y->c;
    }

    void add(ll a, ll b) {
        // a *= -1, b *= -1 // for min
        auto z = insert({a, b, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
    }
};

```

```

        if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->c >= y->c) isect(x, erase(y));
    }

    ll query(ll x) {
        if (empty()) return -INF; // INF for min
        auto l = *lower_bound(x);
        return l.a * x + l.b;
        // return -l.a * x - l.b; // for min
    }
};

```

2.2 divide-and-conquer

```

#include "../common.h"

const ll INF = 1e18;

// for every index i assign an optimal index j, such that
// cost(i, j) is
// minimal for every i. the property that if i2 >= i1 then
// j2 >= j1 is
// exploited (monotonic condition).
//
// calculate optimal index for all indices in range [l, r)
// knowing that
// the optimal index for every index in this range is within
// [optl, optr).
//
// time: O(N log N)
void calc(vector<int> &opt, int l, int r, int optl, int optr) {
    if (l == r) return;
    int i = (l + r) / 2;
    ll optc = INF;
    int optj;
    repx(j, optl, optr) {
        ll c = i + j; // cost(i, j)
        if (c < optc) optc = c, optj = j;
    }
    opt[i] = optj;
    calc(opt, l, i, optl, optj + 1);
    calc(opt, i + 1, r, optj, optr);
}

```

3 generate_pdf

```

#!/usr/bin/env python3

import subprocess
import os
code_dir = "code"

def get_sections():
    sections = []
    section_name = None
    with open('contents.txt', 'r') as f:
        for line in f:
            if '#' in line: line = line[:line.find('#')]
            line = line.strip()
            if len(line) == 0: continue
            if line[0] == '[':
                if section_name is not None:
                    sections.append((section_name, subsections))
                    section_name = line[1:-1]
                    subsections = []
                else:
                    tmp = line.split('\t', 1)
                    if len(tmp) == 1:
                        raise ValueError('Subsection parse error: %s' % line)
                    filename = tmp[0]
                    subsection_name = tmp[1]
                    if subsection_name is None:
                        raise ValueError('Subsection given without section')
                    subsections.append((filename, subsection_name))
            return sections

def get_style(filename):
    ext = filename.lower().split('.')[1]
    if ext in ['c', 'cc', 'cpp', 'h']:
        return 'cpp'
    elif ext in ['java']:
        return 'java'
    elif ext in ['py']:
        return 'py'
    else:
        return 'txt'

# TODO: check if this is everything we need
def texify(s):
    #s = s.replace('\n', '\\\n')

```

```

#s = s.replace('"', '\\\\"')
return s

def get_tex(sections):
    tex = ''
    for (section_name, subsections) in sections:
        tex += '\\section{%s}\n' % texify(section_name)
        for (filename, subsection_name) in subsections:
            tex += '\\subsection{%s}\n' % texify(
                subsection_name)
            tex += '\\raggedbottom\\lstinputlisting[style=%s
                ]{%s/%s}\n' % (get_style(filename), code_dir,
                filename)
            tex += '\\hrulefill\n'
            tex += '\n'
    return tex

if __name__ == "__main__":
    sections = get_sections()
    tex = get_tex(sections)
    with open('contents.tex', 'w') as f:
        f.write(tex)
    latexmk_options = ["latexmk", "-pdf", "notebook.tex"]
    subprocess.call(latexmk_options)
    remove_files = ["notebook.fls", "notebook.aux", "notebook
        .fdb_latexmk",
        "notebook.log", "notebook.out", "notebook.toc"]
    for file in remove_files:
        if os.path.exists(file):
            os.remove(file)

```

4 geo2d

4.1 circle

```

#include "line.cpp"
#include "point.cpp"

struct C {
    P o;
    T r;

    C(P o, T r) : o(o), r(r) {}
    C() : C(P(), T()) {}

    // intersects the circle with a line, assuming they
    intersect

```

```

// the intersections are sorted with respect to the
// direction of the
// line
pair<P, P> line_inter(L l) const {
    P c = l.closest_to(o);
    T c2 = (c - o).magsq();
    P e = sqrt(max(r * r - c2, T())) * l.d.unit();
    return {c - e, c + e};
}

// checks whether the given line collides with the circle
// negative: 2 intersections
// zero: 1 intersection
// positive: 0 intersections
// UNTESTED but very simple
T line_collide(L l) const {
    T c2 = (l.closest_to(o) - o).magsq();
    return c2 - r * r;
}

// calculates the two intersections between two circles
// the circles must intersect in one or two points!
// REALLY UNTESTED
pair<P, P> inter(C h) const {
    P d = h.o - o;
    T c = (r * r - h.r * h.r) / d.magsq();
    return h.line_inter({(1 + c) / 2 * d, d.rot()});
}

// check if the given circles intersect
bool collide(C h) const {
    return (h.o - o).magsq() <= (h.r + r) * (h.r + r);
}

// get one of the two tangents that cross through the
// point
// the point must not be inside the circle
// a = -1: cw (relative to the circle) tangent
// a = 1: ccw (relative to the circle) tangent
P point_tangent(P p, T a) const {
    T c = r * r / p.magsq();
    return o + c * (p - o) - a * sqrt(c * (1 - c)) * (p -
        o).rot();
}

// get one of the 4 tangents between the two circles
// a = 1: exterior tangents
// a = -1: interior tangents (requires no area overlap)
// b = 1: ccw tangent
// b = -1: cw tangent

```

```

// the line origin is on this circumference, and the
// direction
// is a unit vector towards the other circle
L tangent(C c, T a, T b) const {
    T dr = a * r - c.r;
    P d = c.o - o;
    P n = (d * dr + b * d.rot() * sqrt(d.magsq() - dr *
        dr)).unit();
    return {o + n * r, -b * n.rot()};
}

// find the circumcircle of the given **non-degenerate**
// triangle
static C thru_points(P a, P b, P c) {
    L l((a + b) / 2, (b - a).rot());
    P p = l.intersection(L((a + c) / 2, (c - a).rot()));
    return {p, (p - a).mag()};
}

// find the two circles that go through the given point,
// are tangent
// to the given line and have radius 'r'
// the point-line distance must be at most 'r'!
// the circles are sorted in the direction of the line
static pair<C, C> thru_point_line_r(P a, L t, T r) {
    P d = t.d.rot().unit();
    if (d * (a - t.o) < 0) d = -d;
    auto p = C(a, r).line_inter({t.o + d * r, t.d});
    return {{p.first, r}, {p.second, r}};
}

// find the two circles that go through the given points
// and have
// radius 'r'
// the circles are sorted by angle with respect to the
// first point
// the points must be at most at distance 'r'!
static pair<C, C> thru_points_r(P a, P b, T r) {
    auto p = C(a, r).line_inter({(a + b) / 2, (b - a).rot
        ()});
    return {{p.first, r}, {p.second, r}};
}
};

```

4.2 convex-hull

```

#include "point.cpp"

```

```
// get the convex hull with the least amount of vertices for
// the given set
// of points
// probably misbehaves if points are not all distinct!
vector<P> convex_hull(vector<P> &ps) {
    int N = ps.size(), n = 0, k = 0;
    if (N <= 2) return ps;
    rep(i, N) if (make_pair(ps[i].y, ps[i].x) < make_pair(ps[
        k].y, ps[k].x)) k = i;
    swap(ps[k], ps[0]);
    sort(++ps.begin(), ps.end(), [&](P l, P r) {
        T x = (r - l) / (ps[0] - l), d = (r - l) * (ps[0] - l
        ));
        return x > 0 || x == 0 && d < 0;
    });

    vector<P> H;
    for (P p : ps) {
        while (n >= 2 && (H[n - 1] - p) / (H[n - 2] - p) >=
            0) H.pop_back(), n--;
        H.push_back(p), n++;
    }
    return H;
}
```

4.3 delaunay

```
#include "point.cpp"

const T INF = 1e18;

typedef ll lll; // if all coordinates are < 2e4
// typedef __int128_t lll; // if on a 64-bit platform

struct Q {
    Q *rot, *o;
    P p = {INF, INF};
    bool mark;
    P &F() { return r()->p; }
    Q *r() { return rot->rot; }
    Q *prev() { return rot->o->rot; }
    Q *next() { return r()->prev(); }
};

T cross(P a, P b, P c) {
    return (b - a) / (c - a);
}

bool circ(P p, P a, P b, P c) { // is p in the circumcircle?
```

```
    lll p2 = p.magsq(), A = a.magsq() - p2,
        B = b.magsq() - p2, C = c.magsq() - p2;
    return cross(p, a, b) * C + cross(p, b, c) * A + cross(p,
        c, a) * B > 0;
}

Q *makeEdge(Q *H, P orig, P dest) {
    Q *r = H ? H : new Q{new Q{new Q{0}}}};
    H = r->o;
    r->r()->r() = r;
    repx(i, 0, 4) r = r->rot, r->p = {INF, INF}, r->o = i & 1
        ? r : r->r();
    r->p = orig;
    r->F() = dest;
    return r;
}

void splice(Q *a, Q *b) {
    swap(a->o->rot->o, b->o->rot->o);
    swap(a->o, b->o);
}

Q *connect(Q *H, Q *a, Q *b) {
    Q *q = makeEdge(H, a->F(), b->p);
    splice(q, a->next());
    splice(q->r(), b);
    return q;
}

pair<Q *, Q *> rec(Q *H, const vector<P> &s) {
    if (s.size() <= 3) {
        Q *a = makeEdge(H, s[0], s[1]), *b = makeEdge(H, s
            [1], s.back());
        if (s.size() == 2) return {a, a->r()};
        splice(a->r(), b);
        auto side = cross(s[0], s[1], s[2]);
        Q *c = side ? connect(H, b, a) : 0;
        return {side < 0 ? c->r() : a, side < 0 ? c : b->r()
        };
    }

    #define J(e) e->F(), e->p
    #define valid(e) (cross(e->F(), J(base)) > 0)
    Q *A, *B, *ra, *rb;
    int half = s.size() / 2;
    tie(ra, A) = rec(H, {s.begin(), s.end() - half});
    tie(B, rb) = rec(H, {s.begin() + s.size() - half, s.end()
        });
    while ((cross(B->p, J(A)) < 0 && (A = A->next())) ||
        (cross(A->p, J(B)) > 0 && (B = B->r()->o)))
```

```

    ;
    Q *base = connect(H, B->r(), A);
    if (A->p == ra->p) ra = base->r();
    if (B->p == rb->p) rb = base;

#define DEL(e, init, dir) \
    Q *e = init->dir; \
    if (valid(e)) \
        while (circ(e->dir->F(), J(base), e->F())) { \
            Q *t = e->dir; \
            splice(e, e->prev()); \
            splice(e->r(), e->r()->prev()); \
            e->o = H; \
            H = e; \
            e = t; \
        }
    for (;;) {
        DEL(LC, base->r(), o);
        DEL(RC, base, prev());
        if (!valid(LC) && !valid(RC)) break;
        if (!valid(LC) || (valid(RC) && circ(J(RC), J(LC))))
            base = connect(H, RC, base->r());
        else
            base = connect(H, base->r(), LC->r());
    }
    return {ra, rb};
#undef J
#undef valid
#undef DEL
}

// there must be no duplicate points
// returns no triangles in the case of all collinear points
// produces counter-clockwise triangles ordered in triples
// maximizes the minimum angle across all triangulations
// the euclidean mst is a subset of these edges
// O(N log N)
vector<P> triangulate(vector<P> pts) {
    sort(pts.begin(), pts.end(), [](P a, P b) {
        return make_pair(a.x, a.y) < make_pair(b.x, b.y);
    });
    assert(unique(pts.begin(), pts.end()) == pts.end());
    if (pts.size() < 2) return {};
    Q *H = 0;
    Q *e = rec(H, pts).first;
    vector<Q *> q = {e};
    int qi = 0;
    while (cross(e->o->F(), e->F(), e->p) < 0) e = e->o;
#define ADD \
    { \
        \
    }
```



```

Q *c = e; \
do { \
    c->mark = 1; \
    pts.push_back(c->p); \
    q.push_back(c->r()); \
    c = c->next(); \
} while (c != e); \
}
ADD;
pts.clear();
while (qi < (int)q.size())
    if (!(e = q[qi++])>mark) ADD;
return pts;
#undef ADD
}

```

4.4 halfplane-intersect

```

#include "line.cpp"
#include "point.cpp"

const T INF = 1e9;

// obtain the convex polygon that results from intersecting
// the given list
// of halfplanes, represented as lines that allow their left
// side
// assumes the halfplane intersection is bounded
vector<P> halfplane_intersect(vector<L> &H) {
    L bb(P(-INF, -INF), P(INF, 0));
    rep(k, 4) H.push_back(bb), bb.o = bb.o.rot(), bb.d = bb.d
        .rot();

    sort(begin(H), end(H), [](L a, L b) { return a.d.angcmp(b
        .d) < 0; });
    deque<L> q;
    int n = 0;
    rep(i, H.size()) {
        while (n >= 2 && H[i].side(q[n - 1].intersection(q[n
            - 2])) > 0)
            q.pop_back(), n--;
        while (n >= 2 && H[i].side(q[0].intersection(q[1])) >
            0)
            q.pop_front(), n--;
        if (n > 0 && H[i].parallel(q[n - 1])) {
            if (H[i].d * q[n - 1].d < 0) return {};
            if (H[i].side(q[n - 1].o) > 0) q.pop_back(), n--;
            else continue;
        }
    }
}

```

```

    q.push_back(H[i]), n++;
}

while (n >= 3 && q[0].side(q[n - 1].intersection(q[n -
    2])) > 0)
    q.pop_back(), n--;
while (n >= 3 && q[n - 1].side(q[0].intersection(q[1])) >
    0)
    q.pop_front(), n--;
if (n < 3) return {};

vector<P> ps(n);
rep(i, n) ps[i] = q[i].intersection(q[(i + 1) % n]);
return ps;
}

```

4.5 line

```

#include "point.cpp"

// a segment or an infinite line
// does not handle point segments correctly!
struct L {
    P o, d;

    L() : o(), d() {}
    L(P o, P d) : o(o), d(d) {}

    // UNTESTED
    L(P ab, T c) : d(ab.rot()), o(ab * -c / ab.magsq()) {}
    pair<P, T> line_eq() { return {-d.rot(), d.rot() * o}; }

    // returns a number indicating which side of the line the
    // point is in
    // negative: left
    // positive: right
    T side(P r) const { return (r - o) / d; }

    // returns the intersection coefficient
    // in the range [0, d / r.d]
    // if d / r.d is zero, the lines are parallel
    T inter(L r) const { return (r.o - o) / r.d; }

    // get the single intersection point
    // lines must not be parallel
    P intersection(L r) const { return o + d * inter(r) / (d
        / r.d); }

    // check if lines are parallel

```

```

bool parallel(L r) const { return abs(d / r.d) <= EPS; }

// check if segments intersect
bool seg_collide(L r) const {
    T z = d / r.d;
    if (abs(z) <= EPS) {
        if (abs(side(r.o)) > EPS) return false;
        T s = (r.o - o) * d, e = s + r.d * d;
        if (s > e) swap(s, e);
        return s <= d * d + EPS && e >= -EPS;
    }
    T s = inter(r), t = -r.inter(*this);
    if (z < 0) s = -s, t = -t, z = -z;
    return s >= -EPS && s <= z + EPS && t >= -EPS && t <=
        z + EPS;
}

// full segment intersection
// produces a point segment if the intersection is a
// point
// however it **does not** handle point segments as input
// !
bool seg_inter(L r, L *out) const {
    T z = d / r.d;
    if (abs(z) <= EPS) {
        if (abs(side(r.o)) > EPS) return false;
        if (r.d * d < 0) r = {r.o + r.d, -r.d};
        P s = o * d < r.o * d ? r.o : o;
        P e = (o + d) * d < (r.o + r.d) * d ? o + d : r.o
            + r.d;
        if (s * d > e * d) return false;
        return *out = L(s, e - s), true;
    }
    T s = inter(r), t = -r.inter(*this);
    if (z < 0) s = -s, t = -t, z = -z;
    if (s >= -EPS && s <= z + EPS && t >= -EPS && t <= z
        + EPS)
        return *out = L(o + d * s / z, P()), true;
    return false;
}

// check if the given point is on the segment
bool point_on_seg(P r) const {
    if (abs(side(r)) > EPS) return false;
    if ((r - o) * d < -EPS) return false;
    if ((r - o - d) * d > EPS) return false;
    return true;
}

```

```
// get the point in this line that is closest to a given
// point
P closest_to(P r) const {
    P dr = d.rot();
    return r + (o - r) * dr * dr / d.magsq();
}
};
```

4.6 point

```
#include "../common.h"

typedef ll T;
const T EPS = 0;

struct P {
    T x, y;

    P(T x, T y) : x(x), y(y) {}
    P() : P(0, 0) {}

    friend ostream &operator<<(ostream &s, const P &r) {
        return s << r.x << " " << r.y;
    }
    friend istream &operator>>(istream &s, P &r) { return s
        >> r.x >> r.y; }

    P operator+(P r) const { return {x + r.x, y + r.y}; }
    P operator-(P r) const { return {x - r.x, y - r.y}; }
    P operator*(T r) const { return {x * r, y * r}; }
    P operator/(T r) const { return {x / r, y / r}; }
    P operator-() const { return {-x, -y}; }
    friend P operator*(T l, P r) { return {l * r.x, l * r.y};
    }

    P rot() const { return {-y, x}; }
    T operator*(P r) const { return x * r.x + y * r.y; }
    T operator/(P r) const { return rot() * r; }

    T magsq() const { return x * x + y * y; }
    T mag() const { return sqrt(magsq()); }
    P unit() const { return *this / mag(); }

    bool half() const { return abs(y) <= EPS && x < -EPS || y
        < -EPS; }
    T angcmp(P r) const {
        int h = (int)half() - r.half();
        return h ? h : r / *this;
    }
};
```

```
bool operator==(P r) const { return abs(x - r.x) <= EPS
    && abs(y - r.y) <= EPS; }

double angle() const { return atan2(y, x); }
static P from_angle(double a) { return {cos(a), sin(a)};
    }
};
```

4.7 polygon

```
#include "point.cpp"

// get the area of a simple polygon in ccw order
// returns negative area for cw polygons
T area(const vector<P> &ps) {
    int N = ps.size();
    T a = 0;
    rep(i, N) a += (ps[i] - ps[0]) / (ps[(i + 1) % N] - ps[i]
        );
    return a / 2;
}

// checks whether a point is inside a simple polygon
// returns -1 if inside, 0 if on border, 1 if outside
// O(N)
// UNTESTED
int in_poly(const vector<P> &ps, P p) {
    int N = ps.size(), w = 0;
    rep(i, N) {
        P s = ps[i] - p, e = ps[(i + 1) % N] - p;
        if (s == P()) return 0;
        if (s.y == 0 && e.y == 0) {
            if (min(s.x, e.x) <= 0 && 0 <= max(s.x, e.x))
                return 0;
        } else {
            bool b = s.y < 0;
            if (b != (e.y < 0)) {
                T z = s / e;
                if (z == 0) return 0;
                if (b == (z > 0)) w += b ? 1 : -1;
            }
        }
    }
    return w ? -1 : 1;
}

// check if a point is in a convex polygon
struct InConvex {
```

```
vector<P> ps;
T ll, lh, rl, rh;
int N, m;

// preprocess polygon
// O(N)
InConvex(const vector<P> &p) : ps(p), N(ps.size()), m(0)
{
    assert(N >= 2);
    rep(i, N) if (ps[i].x < ps[m].x) m = i;
    rotate(ps.begin(), ps.begin() + m, ps.end());
    rep(i, N) if (ps[i].x > ps[m].x) m = i;
    ll = lh = ps[0].y, rl = rh = ps[m].y;
    for (P p : ps) {
        if (p.x == ps[0].x) ll = min(ll, p.y), lh = max(
            lh, p.y);
        if (p.x == ps[m].x) rl = min(rl, p.y), rh = max(
            rh, p.y);
    }
    InConvex() {}

    // check if point belongs in polygon
    // returns -1 if inside, 0 if on border, 1 if outside
    // O(log N)
    int in_poly(P p) {
        if (p.x < ps[0].x || p.x > ps[m].x) return 1;
        if (p.x == ps[0].x) return p.y < ll || p.y > lh;
        if (p.x == ps[m].x) return p.y < rl || p.y > rh;
        int r = upper_bound(ps.begin(), ps.begin() + m, p,
            [](P a, P b) { return a.x < b.x; }) - ps.begin()
            ;
        T z = (ps[r - 1] - ps[r]) / (p - ps[r]);
        if (z >= 0) return !z;
        r = upper_bound(ps.begin() + m, ps.end(), p, [](P a,
            P b) { return a.x > b.x; }) - ps.begin();
        z = (ps[r - 1] - ps[r % N]) / (p - ps[r % N]);
        if (z >= 0) return !z;
        return -1;
    }
};
```

4.8 sweep

```
#include "point.cpp"

// iterate over all pairs of points
// 'op' is called with all ordered pairs of different
// indices '(i, j)'
```

```
// additionally, the 'ps' vector is kept sorted by signed
// distance
// to the line formed by 'i' and 'j'
// for example, if the vector from 'i' to 'j' is pointing
// right,
// the 'ps' vector is sorted from smallest 'y' to largest 'y'

// note that, because the 'ps' vector is sorted by signed
// distance,
// 'j' is always equal to 'i + 1'
// this means that the amount of points to the left of the
// line is always 'N - i'
template <class OP>
void all_pair_points(vector<P> &ps, OP op) {
    int N = ps.size();
    sort(ps.begin(), ps.end(), [](P a, P b) {
        return make_pair(a.y, a.x) < make_pair(b.y, b.x);
    });
    vector<pair<int, int>> ss;
    rep(i, N) rep(j, N) if (i != j) ss.push_back({i, j});
    stable_sort(ss.begin(), ss.end(), [&](auto a, auto b) {
        return (ps[a.second] - ps[a.first]).angle_lt(ps[b.
            second] - ps[b.first]);
    });
    vector<int> p(N);
    rep(i, N) p[i] = i;
    for (auto [i, j] : ss) {
        op(p[i], p[j]);
        swap(ps[p[i]], ps[p[j]]);
        swap(p[i], p[j]);
    }
}
```

4.9 theorems

```
// Pick's theorem
//
// For a simple polygon with integer vertices, the
// following relationship holds:
//
//  $A = I + B / 2 - 1$ 
//
// A: Area of the polygon
// I: Integer points strictly inside the polygon
// B: Integer points on the boundary of the polygon
```

5 graph

5.1 bellman-ford

```
#include "../common.h"

const ll INF = 1e18;

struct Edge {
    int u, v;
    ll w;
};

// find distance from source node to all nodes.
// supports negative edge weights.
// returns true if a negative cycle is detected.
//
// time: O(V E)
bool bellman_ford(int N, int s, vector<Edge> &E, vector<ll>
    &D, vector<int> &P) {
    P.assign(N, -1), D.assign(N, INF), D[s] = 0;
    rep(i, N - 1) {
        bool f = true;
        rep(ei, E.size()) {
            auto &e = E[ei];
            ll n = D[e.u] + e.w;
            if (D[e.u] < INF && n < D[e.v]) D[e.v] = n, P[e.v]
                = ei, f = false;
        }
        if (f) return false;
    }
    return true;
}
```

5.2 dijkstra

```
#include "../common.h"

const ll INF = 1e18;

// calculate shortest distances from a source node to every
// other node in
// O(E log V). requires an array of size N to store results.
void dijkstra(const vector<vector<pair<ll, int>>> &G, vector
    <ll> &D, int src) {
    priority_queue<pair<ll, int>> q;
    D.assign(G.size(), INF);
    D[src] = 0, q.push({0, src});
```

```
while (!q.empty()) {
    auto [d, u] = q.top();
    d = -d, q.pop();
    if (d > D[u]) continue;
    for (auto [w, v] : G[u])
        if (d + w < D[v]) {
            D[v] = d + w;
            q.push({-D[v], v});
        }
}
```

5.3 dinic

```
#include "../common.h"

const ll INF = 1e18;

struct Edge {
    int u, v;
    ll c, f = 0;
};

// maximum flow algorithm.
//
// time: O(E V^2)
// O(E V^(2/3)) / O(E sqrt(E)) unit capacities
// O(E sqrt(V)) unit networks (hopcroft-
// karp)
//
// unit network: c in {0, 1} and forall v, len(incoming(v))
// <= 1 or len(outgoing(v)) <= 1
//
// min-cut: find all nodes reachable from the source in the
// residual graph
struct Dinic {
    int N, s, t;
    vector<vector<int>> G;
    vector<Edge> E;
    vector<int> lvl, ptr;

    Dinic() {}
    Dinic(int N, int s, int t) : N(N), s(s), t(t), G(N) {}

    void add_edge(int u, int v, ll c) {
        G[u].push_back(E.size());
        E.push_back({u, v, c});
        G[v].push_back(E.size());
        E.push_back({v, u, 0});
    }
}
```

```

}

11 push(int u, ll p) {
    if (u == t || p <= 0) return p;
    while (ptr[u] < G[u].size()) {
        int ei = G[u][ptr[u]++];
        Edge &e = E[ei];
        if (lvl[e.v] != lvl[u] + 1) continue;
        ll a = push(e.v, min(e.c - e.f, p));
        if (a <= 0) continue;
        e.f += a, E[ei ^ 1].f -= a;
        return a;
    }
    return 0;
}

11 maxflow() {
    ll f = 0;
    while (true) {
        // bfs to build levels
        lvl.assign(N, -1);
        queue<int> q;
        lvl[s] = 0, q.push(s);
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (int ei : G[u]) {
                Edge &e = E[ei];
                if (e.c - e.f <= 0 || lvl[e.v] != -1)
                    continue;
                lvl[e.v] = lvl[u] + 1, q.push(e.v);
            }
        }
        if (lvl[t] == -1) break;

        // dfs to find blocking flow
        ptr.assign(N, 0);
        while (ll ff = push(s, INF)) f += ff;
    }
    return f;
}
};

```

5.4 floyd-warshall

```
#include "../common.h"
```

```
const ll INF = 1e18;
```

```

// calculate distances between every pair of nodes in O(V^3)
// time and O(V^2)
// memory.
// requires an NxN array to store results.
// works with negative edges, but not negative cycles.
void floyd(const vector<vector<pair<int, ll>>> &G, vector<
vector<ll>> &dists) {
    int N = G.size();
    rep(i, N) rep(j, N) dists[i][j] = i == j ? 0 : INF;
    rep(i, N) for (auto edge : G[i]) dists[i][edge.first] =
        edge.second;
    rep(k, N) rep(i, N) rep(j, N) {
        dists[i][j] = min(dists[i][j], dists[i][k] + dists[k]
            [j]);
    }
}

```

5.5 heavy-light

```
#include "../common.h"
```

```

struct Hld {
    vector<int> P, H, D, pos, top;

    Hld() {}
    void init(vector<vector<int>> &G) {
        int N = G.size();
        P.resize(N), H.resize(N), D.resize(N), pos.resize(N),
            top.resize(N);
        D[0] = -1, dfs(G, 0);
        int t = 0;
        rep(i, N) if (H[P[i]] != i) {
            int j = i;
            while (j != -1) {
                top[j] = i, pos[j] = t++;
                j = H[j];
            }
        }
    }
}

```

```

int dfs(vector<vector<int>> &G, int i) {
    int w = 1, mw = 0;
    D[i] = D[P[i]] + 1, H[i] = -1;
    for (int c : G[i]) {
        if (c == P[i]) continue;
        P[c] = i;
        int sw = dfs(G, c);
        if (sw > mw) H[i] = c, mw = sw;
        w += sw;
    }
}

```

```

}
return w;
}

template <class OP>
void path(int u, int v, OP op) {
    while (top[u] != top[v]) {
        if (D[top[u]] > D[top[v]]) swap(u, v);
        op(pos[top[v]], pos[v] + 1);
        v = P[top[v]];
    }
    if (D[u] > D[v]) swap(u, v);
    op(pos[u], pos[v] + 1); // value on vertex
    // op(pos[u]+1, pos[v] + 1); // value on path
}

```

```

// segment tree
template <class T, class S>
void update(S &seg, int i, T val) {
    seg.update(pos[i], val);
}

```

```

// segment tree lazy
template <class T, class S>
void update(S &seg, int u, int v, T val) {
    path(u, v, [&](int l, int r) { seg.update(l, r, val);
    });
}

```

```

template <class T, class S>
T query(S &seg, int u, int v) {
    T ans = 0;
    // neutral element
    path(u, v, [&](int l, int r) { ans += seg.query(l, r)
        ; }); // query op
    return ans;
}
};

```

5.6 hungarian

```
#include "../common.h"
```

```
const ll INF = 1e18;
```

```

// find a maximum gain perfect matching in the given
// bipartite complete graph.
// input: gain matrix (G_{xy} = benefit of joining vertex x
// in set X with vertex

```

```
// y in set Y).
// output: maximum gain matching in members 'xy[x]' and 'yx[y]'.
// runtime: O(N^3)
struct Hungarian {
    int N, qi, root;
    vector<vector<ll>> gain;
    vector<int> xy, yx, p, q, slackx;
    vector<ll> lx, ly, slack;
    vector<bool> S, T;

    void add(int x, int px) {
        S[x] = true, p[x] = px;
        rep(y, N) if (lx[x] + ly[y] - gain[x][y] < slack[y]) {
            slack[y] = lx[x] + ly[y] - gain[x][y], slackx[y] = x;
        }
    }

    void augment(int x, int y) {
        while (x != -2) {
            yx[y] = x;
            swap(xy[x], y);
            x = p[x];
        }
    }

    void improve() {
        S.assign(N, false), T.assign(N, false), p.assign(N, -1);
        qi = 0, q.clear();
        rep(x, N) if (xy[x] == -1) {
            q.push_back(root = x), p[x] = -2, S[x] = true;
            break;
        }
        rep(y, N) slack[y] = lx[root] + ly[y] - gain[root][y], slackx[y] = root;

        while (true) {
            while (qi < q.size()) {
                int x = q[qi++];
                rep(y, N) if (lx[x] + ly[y] == gain[x][y] && !T[y]) {
                    if (yx[y] == -1) return augment(x, y);
                    T[y] = true, q.push_back(yx[y]), add(yx[y], x);
                }
            }
        }
    }
};
```

```
ll d = INF;
rep(y, N) if (!T[y]) d = min(d, slack[y]);
rep(x, N) if (S[x]) lx[x] -= d;
rep(y, N) if (T[y]) ly[y] += d;
rep(y, N) if (!T[y]) slack[y] -= d;

rep(y, N) if (!T[y] && slack[y] == 0) {
    if (yx[y] == -1) return augment(slackx[y], y);
    T[y] = true;
    if (!S[yx[y]]) q.push_back(yx[y]), add(yx[y], slackx[y]);
}
}
}

Hungarian(vector<vector<ll>> g) : N(g.size()), gain(g), xy(N, -1), yx(N, -1), lx(N, -INF), ly(N), slack(N), slackx(N) {
    rep(x, N) rep(y, N) lx[x] = max(lx[x], ly[y]);
    rep(i, N) improve();
};
```

5.7 kuhn

```
#include "../common.h"

// get a maximum cardinality matching in a bipartite graph.
// input: adjacency lists.
// output: matching (in 'mt' member).
// runtime: O(V E)
struct Kuhn {
    int N, size;
    vector<vector<int>> G;
    vector<bool> seen;
    vector<int> mt;

    bool visit(int i) {
        if (seen[i]) return false;
        seen[i] = true;
        for (int to : G[i])
            if (mt[to] == -1 || visit(mt[to])) {
                mt[to] = i;
                return true;
            }
        return false;
    }
};
```

```
return true;
}
return false;
}

Kuhn(vector<vector<int>> adj) : G(adj), N(G.size()), mt(N, -1) {
    rep(i, N) {
        seen.assign(N, false);
        size += visit(i);
    }
};
```

5.8 lca

```
#include "../common.h"

// calculates the lowest common ancestor for any two nodes
// in O(log N) time,
// with O(N log N) preprocessing
struct Lca {
    int L;
    vector<vector<int>> up;
    vector<pair<int, int>> time;

    Lca() {}
    void init(const vector<vector<int>> &G) {
        int N = G.size();
        L = N <= 1 ? 0 : 32 - __builtin_clz(N - 1);
        up.resize(L + 1);
        rep(l, L + 1) up[l].resize(N);
        time.resize(N);
        int t = 0;
        visit(G, 0, 0, t);
        rep(l, L) rep(i, N) up[l + 1][i] = up[l][up[l][i]];
    }

    void visit(const vector<vector<int>> &G, int i, int p, int &t) {
        up[0][i] = p;
        time[i].first = t++;
        for (int edge : G[i]) {
            if (edge == p) continue;
            visit(G, edge, i, t);
        }
        time[i].second = t++;
    }
};
```

```

bool is_anc(int up, int dn) {
    return time[up].first <= time[dn].first &&
           time[dn].second <= time[up].second;
}

int get(int i, int j) {
    if (is_anc(i, j)) return i;
    if (is_anc(j, i)) return j;
    int l = L;
    while (l >= 0) {
        if (is_anc(up[l][i], j))
            l--;
        else
            i = up[l][i];
    }
    return up[0][i];
}
};

```

5.9 maxflow-mincost

```

// untested

#include "../common.h"

const ll INF = 1e18;

struct Edge {
    int u, v;
    ll c, w, f = 0;
};

// find the minimum-cost flow among all maximum-flow flows.
//
// time: O(F V E)          F is the maximum flow
//      O(V E + F E log V) if bellman-ford is replaced by
//      johnson
struct Flow {
    int N, s, t;
    vector<vector<int>> G;
    vector<Edge> E;
    vector<ll> d;
    vector<int> p;

    Flow() {}
    Flow(int N, int s, int t) : N(N), s(s), t(t), G(N) {}

    void add_edge(int u, int v, ll c, ll w) {
        G[u].push_back(E.size());

```

```

        E.push_back({u, v, c, w});
        G[v].push_back(E.size());
        E.push_back({v, u, 0, -w});
    }

    void calcdists() {
        // replace bellman-ford with johnson for better time
        d.assign(N, INF);
        p.assign(N, -1);
        d[s] = 0;
        rep(i, N - 1) rep(ei, E.size()) {
            Edge &e = E[ei];
            ll n = d[e.u] + e.w;
            if (d[e.u] < INF && e.c - e.f > 0 && n < d[e.v])
                d[e.v] = n, p[e.v] = ei;
        }
    }

    ll maxflow() {
        ll ff = 0;
        while (true) {
            calcdists();
            if (p[t] == -1) break;

            ll f = INF;
            int cur = t;
            while (p[cur] != -1) {
                Edge &e = E[p[cur]];
                f = min(f, e.c - e.f);
                cur = e.u;
            }

            int cur = t;
            while (p[cur] != -1) {
                E[p[cur]].f += f;
                E[p[cur] ^ 1].f -= f;
            }

            ff += f;
        }
        return ff;
    }
};

```

5.10 push-relabel

```

#include "../common.h"

const ll INF = 1e18;

```

```

// maximum flow algorithm.
// to run, use 'maxflow()'.
//
// time: O(V^2 sqrt(E)) <= O(V^3)
// memory: O(V^2)
struct PushRelabel {
    vector<vector<ll>> cap, flow;
    vector<ll> excess;
    vector<int> height;

    PushRelabel() {}
    void resize(int N) { cap.assign(N, vector<ll>(N)); }

    // push as much excess flow as possible from u to v.
    void push(int u, int v) {
        ll f = min(excess[u], cap[u][v] - flow[u][v]);
        flow[u][v] += f;
        flow[v][u] -= f;
        excess[v] += f;
        excess[u] -= f;
    }

    // relabel the height of a vertex so that excess flow may
    // be pushed.
    void relabel(int u) {
        int d = INT32_MAX;
        rep(v, cap.size()) if (cap[u][v] - flow[u][v] > 0) d
            = min(d, height[v]);
        if (d < INF) height[u] = d + 1;
    }

    // get the maximum flow on the network specified by 'cap'
    // with source 's'
    // and sink 't'.
    // node-to-node flows are output to the 'flow' member.
    ll maxflow(int s, int t) {
        int N = cap.size(), M;
        flow.assign(N, vector<ll>(N));
        height.assign(N, 0), height[s] = N;
        excess.assign(N, 0), excess[s] = INF;
        rep(i, N) if (i != s) push(s, i);

        vector<int> q;
        while (true) {
            // find the highest vertices with excess
            q.clear(), M = 0;
            rep(i, N) {

```

```

        if (excess[i] <= 0 || i == s || i == t)
            continue;
        if (height[i] > M) q.clear(), M = height[i];
        if (height[i] >= M) q.push_back(i);
    }
    if (q.empty()) break;
    // process vertices
    for (int u : q) {
        bool relab = true;
        rep(v, N) {
            if (excess[u] <= 0) break;
            if (cap[u][v] - flow[u][v] > 0 && height[u]
                > height[v])
                push(u, v), relab = false;
        }
        if (relab) {
            relabel(u);
            break;
        }
    }
}

ll f = 0;
rep(i, N) f += flow[i][t];
return f;
}
};

```

5.11 strongly-connected-components

```
#include "../common.h"
```

```

// compute strongly connected components.
// time:  $O(V + E)$ , memory:  $O(V)$ 
//
// after building:
// comp = map from vertex to component (components are
//         toposorted, root first, leaf last)
// N = number of components
// G = condensation graph (component DAG)
//
// byproducts:
// vgi = transposed graph
// order = reverse topological sort (leaf first, root last)
//
// others:
// vn = number of vertices
// vg = original vertex graph
struct Scc {

```

```

    int vn, N;
    vector<int> order, comp;
    vector<vector<int>> vg, vgi, G;

    void toposort(int u) {
        if (comp[u] return;
        comp[u] = -1;
        for (int v : vg[u]) toposort(v);
        order.push_back(u);
    }

    bool carve(int u) {
        if (comp[u] != -1) return false;
        comp[u] = N;
        for (int v : vgi[u]) {
            carve(v);
            if (comp[v] != N) G[comp[v]].push_back(N);
        }
        return true;
    }

    Scc() {}
    Scc(vector<vector<int>> &g) : vn(g.size()), vg(g), comp(
        vn), vgi(vn), G(vn), N(0) {
        rep(u, vn) toposort(u);
        rep(u, vn) for (int v : vg[u]) vgi[v].push_back(u);
        invrep(i, vn) N += carve(order[i]);
    }
};

```

5.12 two-sat

```

#include "../common.h"
#include "strongly_connected_components.cpp"

// calculate the solvability of a system of logical
// equations, where every equation is of the form 'a or b'
//
// 'neg': get negation of 'u'
// 'then': 'u' implies 'v'
// 'any': 'u' or 'v'
// 'set': 'u' is true
//
// after 'solve' ( $O(V+E)$ ) returns true, 'sol' contains one
// possible solution.
// determining all solutions is  $O(V \cdot E)$  hard (requires
// computing reachability in a DAG).
struct TwoSat {
    int N;

```

```

    vector<vector<int>> G;
    Scc scc;
    vector<bool> sol;

    TwoSat(int n) : N(n), G(2 * n), sol(n) {}
    TwoSat() {}

    int neg(int u) { return (u + N) % (2 * N); }
    void then(int u, int v) { G[u].push_back(v), G[neg(v)].
        push_back(neg(u)); }
    void any(int u, int v) { then(neg(u), v); }
    void set(int u) { G[neg(u)].push_back(u); }

    bool solve() {
        scc = Scc(G);
        rep(u, N) if (scc.comp[u] == scc.comp[neg(u)]) return
            false;
        rep(u, N) sol[u] = (scc.comp[u] > scc.comp[neg(u)]);
        return true;
    }
};

```

6 implementation

6.1 dsu

```
#include "../common.h"
```

```

struct Dsu {
    vector<int> p, r;

    // initialize the disjoint-set-union to all unitary sets
    void reset(int N) {
        p.resize(N), r.assign(N, 0);
        rep(i, N) p[i] = i;
    }

    // find the leader node corresponding to node 'i'
    int find(int i) {
        if (p[i] != i) p[i] = find(p[i]);
        return p[i];
    }

    // perform union on the two sets that 'i' and 'j' belong
    // to
    void unite(int i, int j) {
        i = find(i), j = find(j);
        if (i == j) return;

```

```

    if (r[i] > r[j]) swap(i, j);
    if (r[i] == r[j]) r[j] += 1;
    p[i] = j;
}
};

```

6.2 fenwick-tree

```

#include "../common.h"

template <class T>
struct Ft {
    vector<T> t;

    T neutral() { return 0; }

    Ft() {}
    Ft(int N) : t(N + 1, neutral()) {}

    T query(int r) {
        r = min(r, N);
        T x = 0; // neutral
        for (; r > 0; r -= r & -r)
            x = x + t[r];
        return x;
    }

    T query(int l, int r) { return query(r) - query(l); }

    void update(int i, T x) {
        for (i++;)
    }
};

```

6.3 mo

```

#include "../common.h"

struct Query {
    int l, r, idx;
};

// answer segment queries using only 'add(i)', 'remove(i)'
// and 'get()'
// functions.
//
// complexity: O((N + Q) * sqrt(N) * F)
// N = length of the full segment

```

```

// Q = amount of queries
// F = complexity of the 'add', 'remove' functions
template <class A, class R, class G, class T>
void mo(vector<Query> &queries, vector<T> &ans, A add, R
    remove, G get) {
    int Q = queries.size(), B = (int)sqrt(Q);
    sort(queries.begin(), queries.end(), [&](Query &a, Query
        &b) {
        return make_pair(a.l / B, a.r) < make_pair(b.l / B, b
            .r);
    });
    ans.resize(Q);

    int l = 0, r = 0;
    for (auto &q : queries) {
        while (r < q.r) add(r), r++;
        while (l > q.l) l--, add(l);
        while (r > q.r) r--, remove(r);
        while (l < q.l) remove(l), l++;
        ans[q.idx] = get();
    }
}

```

6.4 persistent-segment-tree-lazy

```

#include "../common.h"

template <class T>
struct Node {
    T x, lz;
    int l = -1, r = -1;
};

template <class T>
struct Pstl {
    int N;
    vector<Node<T>> a;
    vector<int> head;

    T qneut() { return 0; }
    T merge(T l, T r) { return l + r; }
    T uneut() { return 0; }
    T accum(T u, T x) { return u + x; }
    T apply(T x, T lz, int l, int r) { return x + (r - l) *
        lz; }

    int build(int vl, int vr) {
        if (vr - vl == 1) a.push_back({qneut(), uneut()}); //
            node construction
    }
}

```

```

    else {
        int vm = (vl + vr) / 2, l = build(vl, vm), r =
            build(vm, vr);
        a.push_back({merge(a[l].x, a[r].x), uneut(), l, r
            }); // query merge
    }
    return a.size() - 1;
}

T query(int l, int r, int v, int vl, int vr, T acc) {
    if (l >= vr || r <= vl) return qneut();
    // query neutral
    if (l <= vl && r >= vr) return apply(a[v].x, acc, vl,
        vr); // update op
    acc = accum(acc, a[v].lz);
    // update merge
    int vm = (vl + vr) / 2;
    return merge(query(l, r, a[v].l, vl, vm, acc), query(
        l, r, a[v].r, vm, vr, acc)); // query merge
}

int update(int l, int r, T x, int v, int vl, int vr) {
    if (l >= vr || r <= vl || r <= 1) return v;
    a.push_back(a[v]);
    v = a.size() - 1;
    if (l <= vl && r >= vr) {
        a[v].x = apply(a[v].x, x, vl, vr); // update op
        a[v].lz = accum(a[v].lz, x); // update merge
    } else {
        int vm = (vl + vr) / 2;
        a[v].l = update(l, r, x, a[v].l, vl, vm);
        a[v].r = update(l, r, x, a[v].r, vm, vr);
        a[v].x = merge(a[a[v].l].x, a[a[v].r].x); //
            query merge
    }
    return v;
}

Pstl() {}
Pstl(int N) : N(N) { head.push_back(build(0, N)); }

T query(int t, int l, int r) {
    return query(l, r, head[t], 0, N, uneut()); // update
        neutral
}

int update(int t, int l, int r, T x) {
    return head.push_back(update(l, r, x, head[t], 0, N))
        , head.size() - 1;
}
};

```


6.5 persistent-segment-tree

```
#include "../common.h"

// usage:
// Pst<Node<ll>> pst;
// pst = {N};
// int newtime = pst.update(time, index, value);
// Node<ll> result = pst.query(newtime, left, right);

template <class T>
struct Node {
    T x;
    int l = -1, r = -1;

    Node() : x(0) {}
    Node(T x) : x(x) {}
    Node(Node a, Node b, int l = -1, int r = -1) : x(a.x + b.x), l(l), r(r) {}
};

template <class U>
struct Pst {
    int N;
    vector<U> a;
    vector<int> head;

    int build(int vl, int vr) {
        if (vr - vl == 1) a.push_back(U()); // node construction
        else {
            int vm = (vl + vr) / 2, l = build(vl, vm), r = build(vm, vr);
            a.push_back(U(a[l], a[r], l, r)); // query merge
        }
        return a.size() - 1;
    }

    U query(int l, int r, int v, int vl, int vr) {
        if (l >= vr || r <= vl) return U(); // query neutral
        if (l <= vl && r >= vr) return a[v];
        int vm = (vl + vr) / 2;
        return U(query(l, r, a[v].l, vl, vm), query(l, r, a[v].r, vm, vr)); // query merge
    }

    int update(int i, U x, int v, int vl, int vr) {
        a.push_back(a[v]);
        v = a.size() - 1;
        if (vr - vl == 1) a[v] = x; // update op
    }
};
```

```
    else {
        int vm = (vl + vr) / 2;
        if (i < vm) a[v].l = update(i, x, a[v].l, vl, vm);
        else a[v].r = update(i, x, a[v].r, vm, vr);
        a[v] = U(a[v].l, a[v].r, a[v].l, a[v].r);
        // query merge
    }
    return v;
}

Pst() {}
Pst(int N) : N(N) { head.push_back(build(0, N)); }

U query(int t, int l, int r) {
    return query(l, r, head[t], 0, N);
}

int update(int t, int i, U x) {
    return head.push_back(update(i, x, head[t], 0, N)),
        head.size() - 1;
}
};
```

6.6 search

```
#include "common.h"

// search x in a[i]
//
// first a[i] > x: upper_bound(a, x)
// first a[i] >= x: lower_bound(a, x)
// last a[i] < x: --lower_bound(a, x)
// last a[i] <= x: --upper_bound(a, x)

// note: searching for the largest [l, r] such that f(l) > a
// & f(r) < b where
// [a, b] is a range in f() space may result in negative [l, r] ranges.

// searches for a value in an [l, r] range (both inclusive).
//
// the 'isleft(m)' function evaluates whether 'm' is
// strictly to the left of the
// target value.
int binsearch_left(int l, int r, bool isleft(int)) {
    while (l != r) {
        int m = (l + r) / 2;
        if (isleft(m)) {
            l = m + 1;
        }
    }
}
```

```
    } else {
        r = m;
    }
    return l;
}

// searches for a value in an [l, r] range (both inclusive).
//
// the 'isright(m)' function evaluates whether 'm' is
// strictly to the right of
// the target value.
//
// note the '+1' when computing 'm', which avoids infinite
// loops.
// the only difference with 'binsearch_left' is how the
// evaluation function is
// specified. both are functionally identical.
int binsearch_right(int l, int r, bool isright(int)) {
    while (l != r) {
        int m = (l + r + 1) / 2;
        if (isright(m)) {
            r = m - 1;
        } else {
            l = m;
        }
    }
    return l;
}

// continuous ternary (golden section) search.
//
// searches for a minimum value of the given unimodal
// function (monotonic
// positive derivative).
template <typename T, typename U>
pair<T, U> ctersearch(int iter, T l, T r, U f(T)) {
    const T INVG = 0.61803398874989484820;

    T m = l + (r - l) * INVG;
    U lv = f(l), rv = f(r), mv = f(m);
    rep(i, iter) {
        T x = l + (m - l) * INVG;
        U xv = f(x);
        if (xv > mv) l = r, lv = rv, r = x, rv = xv;
        else r = m, rv = mv, m = x, mv = xv;
    }
    return {m, mv};
}
```

6.7 segment-tree-lazy

```
#include "../common.h"

// 0-based, inclusive-exclusive
// usage:
// Stl3<ll> a;
// a = {N};
template <class T>
struct Stl3 {
    // immediate, lazy
    vector<pair<T, T>> a;

    T qneutral() { return 0; }
    T merge(T l, T r) { return l + r; }
    T unneutral() { return 0; }
    void update(pair<T, T> &u, T val, int l, int r) { u.first
        += val * (r - l), u.second += val; }

    Stl3() {}
    Stl3(int N) : a(4 * N, {qneutral(), unneutral()}) {} //
        node neutral

    void push(int v, int vl, int vm, int vr) {
        update(a[2 * v], a[v].second, vl, vm); // node update
        update(a[2 * v + 1], a[v].second, vm, vr); // node
            update
        a[v].second = unneutral(); // update
            neutral
    }

    // query for range [l, r)
    T query(int l, int r, int v = 1, int vl = 0, int vr = -1)
    {
        if (vr == -1) vr = a.size() / 4;
        if (l <= vl && r >= vr) return a[v].first; // query
            op
        if (l >= vr || r <= vl) return qneutral(); // query
            neutral
        int vm = (vl + vr) / 2;
        push(v, vl, vm, vr);
        return merge(query(l, r, 2 * v, vl, vm), query(l, r,
            2 * v + 1, vm, vr)); // item merge
    }

    // update range [l, r) using val
    void update(int l, int r, T val, int v = 1, int vl = 0,
        int vr = -1) {
        if (vr == -1) vr = a.size() / 4;
        if (l >= vr || r <= vl || r <= 1) return;

```

```
        if (l <= vl && r >= vr) update(a[v], val, vl, vr); //
            node update
        else {
            int vm = (vl + vr) / 2;
            push(v, vl, vm, vr);
            update(l, r, val, 2 * v, vl, vm);
            update(l, r, val, 2 * v + 1, vm, vr);
            a[v].first = merge(a[2 * v].first, a[2 * v + 1].
                first); // node merge
        }
    }
};

struct Node {
    ll x, lazy;

    Node() : x(neutral()), lazy(0) {} // query neutral,
        update neutral
    Node(ll x_) : Node() { x = x_; }
    Node(Node &l, Node &r) : Node() { refresh(l, r); } //
        node merge construction
    void refresh(Node &l, Node &r) { x = merge(l.x, r.x); } //
        node merge

    void update(ll val, int l, int r) { x += val * (r - l),
        lazy += val; } // update-query, update accumulate
    ll take() {
        ll z = 0; // update neutral
        swap(lazy, z);
        return z;
    }

    ll query() { return x; }
    static ll neutral() { return 0; } // query
        neutral
    static ll merge(ll l, ll r) { return l + r; } // query
        merge
};

template <class T, class Node>
struct Stl {
    vector<Node> node;

    void reset(int N) { node.assign(4 * N, {}); } // node
        neutral

    void build(const vector<T> &a, int v = 1, int vl = 0, int
        vr = -1) {
        node.resize(4 * a.size(), vr == -1 ? node.size()
            / 4 : vr;

```

```
        if (vr - vl == 1) {
            node[v] = {a[vl]}; // node construction
            return;
        }
        int vm = (vl + vr) / 2;
        build(a, 2 * v, vl, vm);
        build(a, 2 * v + 1, vm, vr);
        node[v] = {node[2 * v], node[2 * v + 1]}; // node
            merge construction
    }

    void push(int v, int vl, int vm, int vr) {
        T lazy = node[v].take(); // update neutral
        node[2 * v].update(lazy, vl, vm); // node update
        node[2 * v + 1].update(lazy, vm, vr); // node update
    }

    // query for range [l, r)
    T query(int l, int r, int v = 1, int vl = 0, int vr = -1)
    {
        if (vr == -1) vr = node.size() / 4;
        if (l <= vl && r >= vr) return node[v].query(); //
            query op
        if (l >= vr || r <= vl) return Node::neutral(); //
            query neutral
        int vm = (vl + vr) / 2;
        push(v, vl, vm, vr);
        return Node::merge(query(l, r, 2 * v, vl, vm), query(
            l, r, 2 * v + 1, vm, vr)); // item merge
    }

    // update range [l, r) using val
    void update(int l, int r, T val, int v = 1, int vl = 0,
        int vr = -1) {
        if (vr == -1) vr = node.size() / 4;
        if (l >= vr || r <= vl || r <= 1) return;
        if (l <= vl && r >= vr) node[v].update(val, vl, vr);
            // node update
        else {
            int vm = (vl + vr) / 2;
            push(v, vl, vm, vr);
            update(l, r, val, 2 * v, vl, vm);
            update(l, r, val, 2 * v + 1, vm, vr);
            node[v].refresh(node[2 * v], node[2 * v + 1]); //
                node merge
        }
    }
};
};
```

6.8 segment-tree

```
#include "../common.h"

// usage:
// St<Node<ll>> st;
// st = {N};
// st.update(index, new_value);
// Node<ll> result = st.query(left, right);

template <class T>
struct Node {
    T x;
    Node() : x(0) {}
    Node(T x) : x(x) {}
    Node(Node a, Node b) : x(a.x + b.x) {}
};

template <class U>
struct St {
    vector<U> a;

    St() {}
    St(int N) : a(4 * N, U()) {} // node neutral

    // query for range [l, r)
    U query(int l, int r, int v = 1, int vl = 0, int vr = -1)
    {
        if (vr == -1) vr = a.size() / 4;
        if (l <= vl && r >= vr) return a[v]; // item
            construction
        int vm = (vl + vr) / 2;
        if (l >= vr || r <= vl) return U();
        // item neutral
        return U(query(l, r, 2 * v, vl, vm), query(l, r, 2 *
            v + 1, vm, vr)); // item merge
    }

    // set element i to val
    void update(int i, U val, int v = 1, int vl = 0, int vr =
        -1) {
        if (vr == -1) vr = a.size() / 4;
        if (vr - vl == 1) a[v] = val; // item update
        else {
            int vm = (vl + vr) / 2;
            if (i < vm) update(i, val, 2 * v, vl, vm);
            else update(i, val, 2 * v + 1, vm, vr);
            a[v] = U(a[2 * v], a[2 * v + 1]); // node merge
        }
    }
};
```

```
};
```

6.9 sparse-table

```
#include "../common.h"

// handle immutable range maximum queries (or any idempotent
// query) in O(1)
template <class T>
struct Sparse {
    vector<vector<T>> st;

    T op(T a, T b) { return max(a, b); }

    Sparse() {}

    void reset(int N) { st = {vector<T>(N)}; }
    void set(int i, T val) { st[0][i] = val; }

    // O(N log N) time
    // O(N log N) memory
    void init() {
        int N = st[0].size();
        int npot = N <= 1 ? 1 : 32 - __builtin_clz(N);
        st.resize(npot);
        repx(i, 1, npot) rep(j, N + 1 - (1 << i)) st[i].
            push_back(
                op(st[i - 1][j], st[i - 1][j + (1 << (i - 1))]]);
        // query op
    }

    // query maximum in the range [l, r) in O(1) time
    // range must be nonempty!
    T query(int l, int r) {
        int i = 31 - __builtin_clz(r - l);
        return op(st[i][l], st[i][r - (1 << i)]); // query op
    }
};
```

6.10 unordered-map

```
#include "../common.h"

// hackproof rng
static mt19937 rng(chrono::steady_clock::now().
    time_since_epoch().count());
```

```
// deterministic rng
uint64_t splitmix64(uint64_t *x) {
    uint64_t z = (*x += 0x9e3779b97f4a7c15);
    z = (z ^ (z >> 30)) * 0xbf58476d1ce4e5b9;
    z = (z ^ (z >> 27)) * 0x94d049bb133111eb;
    return z ^ (z >> 31);
}

// hackproof unordered map hash
struct Hash {
    size_t operator()(const ll &x) const {
        static const uint64_t RAND =
            chrono::steady_clock::now().time_since_epoch().
                count();
        uint64_t z = x + RAND + 0x9e3779b97f4a7c15;
        z = (z ^ (z >> 30)) * 0xbf58476d1ce4e5b9;
        z = (z ^ (z >> 27)) * 0x94d049bb133111eb;
        return z ^ (z >> 31);
    }
};

// hackproof unordered_map
template <class T, class U>
using umap = unordered_map<T, U, Hash>;

// hackproof unordered_set
template <class T>
using uset = unordered_set<T, Hash>;

// an unordered map with small integer keys that avoids
// hashing, but allows O(N)
// iteration and clearing, with N being the amount of items
// (not the maximum
// key).
template <class T>
struct Map {
    int N;
    vector<bool> used;
    vector<int> keys;
    vector<T> vals;

    Map() : N(0) {}
    // O(C)
    void recap(int C) {
        C += 1, used.resize(C), keys.resize(C), vals.resize(C);
    }

    // O(1)
    T &operator[](int k) {
```

```

    if (!used[k]) used[k] = true, keys[N++] = k, vals[k]
        = T();
    return vals[k];
}

// O(N)
void clear() {
    while (N) used[keys[--N]] = false;
}

// O(N)
template <class OP>
void iterate(OP op) {
    rep(i, N) op(keys[i], vals[keys[i]]);
}
};

```

7 math

7.1 arithmetic

```

#include "../common.h"

// floor(log2(n)) without precision loss
inline int floor_log2(int n) { return n <= 1 ? 0 : 31 -
    __builtin_clz(n); }
// ceil(log2(n)) without precision loss
inline int ceil_log2(int n) { return n <= 1 ? 0 : 32 -
    __builtin_clz(n - 1); }

inline ll floordiv(ll a, ll b) {
    return a / b - ((a ^ b) < 0 && a % b);
}

inline ll ceildiv(ll a, ll b) {
    return a / b + ((a ^ b) >= 0 && a % b);
}

// a^e through binary exponentiation.
ll binexp(ll a, ll e) {
    ll res = 1; // neutral element
    while (e) {
        if (e & 1) res = res * a; // multiplication
        a = a * a;                // multiplication
        e >>= 1;
    }
    return res;
}

```

7.2 bigint

```

#include "../common.h"

using u32 = uint32_t;
using u64 = uint64_t;

// signed bigint
struct bigint {
    vector<u32> digits;
    u32 neg;

    bigint() : neg(0) {}
    bigint(ll x) : digits{lo(x), hi(x)}, neg(x < 0 ? ~0 : 0)
        { this->trim(); }
    bigint(vector<u32> d) : digits(d), neg(0) {}

    static u32 lo(u64 dw) { return (u32)dw; }
    static u32 hi(u64 dw) { return (u32)(dw >> 32); }

    // remove leading zeros from representation
    void trim() {
        while (digits.size() && digits.back() == neg) digits.
            pop_back();
    }

    void add(const bigint &rhs, u32 c = 0) {
        int ls = digits.size();
        int rs = rhs.digits.size();
        rep(i, max(ls, rs)) {
            if (i >= ls) digits.push_back(neg);
            u64 r = (u64)digits[i] + (i < rs ? rhs.digits[i]
                : rhs.neg) + c;
            digits[i] = lo(r), c = hi(r);
        }
        u64 ec = (u64)c + neg + rhs.neg;
        neg = ((hi(ec) ^ neg ^ rhs.neg) & 1 ? ~0 : 0);
        if (lo(ec) != neg) digits.push_back(lo(ec));
    }

    bigint &operator+=(const bigint &rhs) {
        this->add(rhs);
        return *this;
    }

    bigint &operator+=(u32 rhs) {
        this->add({}, rhs);
        return *this;
    }
}

```

```

void negate() {
    rep(i, digits.size()) digits[i] = ~digits[i];
    neg = ~neg;
    this->add({}, 1);
}

bigint negated() const {
    bigint out = *this;
    out.negate();
    return out;
}

bigint &operator-=(const bigint &rhs) {
    this->negate();
    *this += rhs;
    this->negate();
    return *this;
}

bigint &operator*=(bigint &rhs) {
    static bigint lhs;
    swap(*this, lhs), digits.clear(), neg = 0;
    u32 r = rhs.neg, s = 0;
    if (lhs.neg) s ^= lhs.neg, lhs.negate();
    if (rhs.neg) s ^= rhs.neg, rhs.negate();
    rep(j, rhs.digits.size()) {
        u64 c = 0;
        int ls = digits.size();
        int rs = lhs.digits.size();
        repx(i, j, max(ls, rs + j)) {
            if (i >= ls) digits.push_back(0);
            u64 r =
                (u64)digits[i] +
                (u64)(i - j < rs ? lhs.digits[i - j] : 0)
                * rhs.digits[j] +
                c;
            digits[i] = lo(r), c = hi(r);
        }
        if (c != 0) digits.push_back(c);
    }
    if (r) rhs.negate();
    if (s) negate();
    return *this;
}

bigint &operator/=(bigint &rhs) {
    divmod(rhs);
    return *this;
}

```

```

bigint &operator%=(bigint &rhs) {
    *this = divmod(rhs);
    return *this;
}

int divmod_trunc(int rhs) {
    u32 s = (rhs < 0 ? ~0 : 0) ^ this->neg, q = abs(rhs);
    u64 r = 0;
    if (this->neg) this->negate();
    invrep(i, digits.size()) {
        r = (r << 32) | digits[i];
        digits[i] = r / q, r %= q;
    }
    if (s) {
        this->negate();
        return -(int)r;
    }
    return (int)r;
}

// compares 'this' with 'rhs'
// 'this < rhs': -1
// 'this == rhs': 0
// 'this > rhs': 1
int cmp(const bigint &rhs) const {
    if (neg && !rhs.neg) return -1;
    if (!neg && rhs.neg) return 1;
    int ls = digits.size(), rs = rhs.digits.size();
    invrep(i, max(ls, rs)) {
        u32 l = i < ls ? digits[i] : neg;
        u32 r = i < rs ? rhs.digits[i] : rhs.neg;
        if (l < r) return -1;
        if (l > r) return 1;
    }
    return 0;
}

bool operator==(const bigint &rhs) const { return cmp(rhs) == 0; }
bool operator!=(const bigint &rhs) const { return cmp(rhs) != 0; }
bool operator<(const bigint &rhs) const { return cmp(rhs) == -1; }
bool operator>=(const bigint &rhs) const { return cmp(rhs) != -1; }
bool operator>(const bigint &rhs) const { return cmp(rhs) == 1; }
bool operator<=(const bigint &rhs) const { return cmp(rhs) != 1; }

```

```

friend ostream &operator<<(ostream &s, const bigint &self) {
    if (self == bigint()) return s << "0";
    bigint x = self;
    if (x.neg) {
        x.negate();
        s << "-";
    }
    vector<int> digs;
    while (x != bigint()) digs.push_back(x.divmod_trunc(10));
    invrep(i, digs.size()) s << digs[i];
    return s;
}

// truncating division and modulo
bigint divmod(bigint &rhs) {
    assert(rhs != bigint());
    u32 sr = rhs.neg, s = neg ^ rhs.neg;
    if (neg) negate();
    if (sr) rhs.negate();
    bigint l = 0, r = *this, x;
    r += 1u;
    while (l != r) {
        bigint m = l;
        m += r;
        rep(i, m.digits.size()) m.digits[i] =
            (m.digits[i] >> 1) |
            (i + 1 < m.digits.size() ? m.digits[i + 1] <<
                31 : 0);
        x = m, x *= rhs;
        if (x <= *this) {
            l = (m += 1);
        } else {
            r = m;
        }
    }
    l -= 1, swap(l, *this);
    r = *this, r *= rhs, l -= r;
    trim(), l.trim();
    if (sr) rhs.negate();
    if (s) negate(), l.negate();
    return l;
}
};

```

7.3 crt

```

#define NOMAIN_BIGINT
#include "mod.cpp"

pair<ll, ll> solve_crt(const vector<pair<ll, ll>> &eqs) {
    ll a0 = eqs[0].first, p0 = eqs[0].second;
    rep(x, 1, eqs.size()) {
        ll a1 = eqs[x].first, p1 = eqs[x].second;
        ll k1, k0;
        ll d = ext_gcd(p1, p0, k1, k0);
        a0 -= a1;
        if (a0 % d != 0) return {-1, -1};
        p0 = p0 / d * p1;
        a0 = a0 / d * k1 % p0 * p1 % p0 + a1;
        a0 = (a0 % p0 + p0) % p0;
    }
    return {a0, p0};
}

```

7.4 discrete-log

```

#include "../common.h"
#include "../implementation/unordered_map.cpp"
#include "mod.cpp"

// discrete logarithm log_a(b).
// solve b ^ x = a (mod M) for the smallest x.
// returns -1 if no solution is found.
//
// time: O(sqrt(M))
ll dlog(ll a, ll b, ll M) {
    ll k = 1, s = 0;
    while (true) {
        ll g = __gcd(b, M);
        if (g <= 1) break;
        if (a == k) return s;
        if (a % g != 0) return -1;
        a /= g, M /= g, s += 1, k = b / g * k % M;
    }
    ll N = sqrt(M) + 1;

    umap<ll, ll> r;
    rep(q, N + 1) {
        r[a] = q;
        a = a * b % M;
    }

    ll bN = binexp(b, N, M), bNp = k;
    rep(x, 1, N + 1) {
        bNp = bNp * bN % M;
    }
}

```

```

        if (r.count(bNp)) return N * p - r[bNp] + s;
    }
    return -1;
}

```

7.5 gauss

```

#include "../common.h"

const double EPS = 1e-9;

// solve a system of equations.
// complexity: O(min(N, M) * N * M)
//
// 'a' is a list of rows
// the last value in each row is the result of the equation
// return values:
// 0 -> no solutions
// 1 -> unique solution, stored in 'ans'
// -1 -> infinitely many solutions, one of which is stored
//      in 'ans'
// UNTESTED
int gauss(vector<vector<double>> a, vector<double> &ans) {
    int N = a.size(), M = a[0].size() - 1;

    vector<int> where(M, -1);
    for (int j = 0, i = 0; j < M && i < N; j++) {
        int sel = i;
        repx(k, i, N) if (abs(a[k][j]) > abs(a[sel][j])) sel = k;
        if (abs(a[sel][j]) < EPS) continue;
        repx(k, j, M + 1) swap(a[sel][k], a[i][k]);
        where[j] = i;

        rep(k, N) if (k != i) {
            double c = a[k][j] / a[i][j];
            repx(l, j, M + 1) a[k][l] -= a[i][l] * c;
        }
        i++;
    }

    ans.assign(M, 0);
    rep(i, M) if (where[i] != -1) ans[i] = a[where[i]][M] / a[where[i]][i];
    rep(i, N) {
        double sum = 0;
        rep(j, M) sum += ans[j] * a[i][j];
        if (abs(sum - a[i][M]) > EPS) return 0;
    }
}

```

```

    rep(i, M) if (where[i] == -1) return -1;
    return 1;
}

```

7.6 matrix

```

#include "../common.h"

using T = ll;

struct Mat {
    int N, M;
    vector<vector<T>> v;

    Mat(int n, int m) : N(n), M(m), v(N, vector<T>(M)) {}
    Mat(int n) : Mat(n, n) { rep(i, N) v[i][i] = 1; }

    vector<T> &operator[](int i) { return v[i]; }

    Mat operator*(Mat &r) {
        assert(M == r.N);
        int n = N, m = r.M, p = M;
        Mat a(n, m);
        rep(i, n) rep(j, m) {
            a[i][j] = T(); // neutral
            rep(k, p) a[i][k] = a[i][j] + v[i][k] * r[k][j]; // mul, add
        }
        return a;
    }

    Mat binexp(ll e) {
        assert(N == M);
        Mat a = *this, res(N); // neutral
        while (e) {
            if (e & 1) res = res * a; // mul
            a = a * a; // mul
            e >>= 1;
        }
        return res;
    }

    friend ostream &operator<<(ostream &s, Mat &a) {
        rep(i, a.N) {
            rep(j, a.M) s << a[i][j] << " ";
            s << endl;
        }
    }
}

```

```

        return s;
    }
};

```

7.7 mod

```

#include "../common.h"

ll binexp(ll a, ll e, ll M) {
    assert(e >= 0);
    ll res = 1 % M;
    while (e) {
        if (e & 1) res = res * a % M;
        a = a * a % M;
        e >>= 1;
    }
    return res;
}

ll multinv(ll a, ll M) { return binexp(a, M - 2, M); }

// calculate gcd(a, b).
// also, calculate x and y such that:
// a * x + b * y == gcd(a, b)
//
// time: O(log min(a, b))
// (ignoring complexity of arithmetic)
ll ext_gcd(ll a, ll b, ll &x, ll &y) {
    if (b == 0) {
        x = 1, y = 0;
        return a;
    }
    ll d = ext_gcd(b, a % b, y, x);
    y -= a / b * x;
    return d;
}

// compute inverse with any M.
// a and M must be coprime for inverse to exist!
ll multinv_euc(ll a, ll M) {
    ll x, y;
    ext_gcd(a, M, x, y);
    return x;
}

// multiply two big numbers (~10^18) under a large modulo,
// without resorting to
// bigints.
ll bigmul(ll x, ll y, ll M) {

```

```

    ll z = 0;
    while (y) {
        if (y & 1) z = (z + x) % M;
        x = (x << 1) % M, y >>= 1;
    }
    return z;
}

struct Mod {
    int a;
    static const int M = 1e9 + 7;

    Mod(ll aa) : a((aa % M + M) % M) {}

    Mod operator+(Mod rhs) const { return (a + rhs.a) % M; }
    Mod operator-(Mod rhs) const { return (a - rhs.a + M) % M; }
    Mod operator-() const { return Mod(0) - *this; }
    Mod operator*(Mod rhs) const { return (ll)a * rhs.a % M; }

    Mod operator+=(Mod rhs) { return *this = *this + rhs; }
    Mod operator-=(Mod rhs) { return *this = *this - rhs; }
    Mod operator*=(Mod rhs) { return *this = *this * rhs; }

    Mod bigmul(ll big) const { return ::bigmul(a, big, M); }

    Mod binexp(ll e) const { return ::binexp(a, e, M); }
    // Mod multinv() const { return ::multinv(a, M); } //
    // prime M
    // Mod multinv() const { return ::multinv_euc(a, M); } //
    // possibly composite M
};

// dynamic modulus
struct DMod {
    int a, M;

    DMod(ll aa, ll m) : M(m), a((aa % m + m) % m) {}

    DMod operator+(DMod rhs) const { return {(a + rhs.a) % M, M}; }
    DMod operator-(DMod rhs) const { return {(a - rhs.a + M) % M, M}; }
    DMod operator-() const { return DMod(0, M) - *this; }
    DMod operator*(DMod rhs) const { return {(ll)a * rhs.a % M, M}; }

    DMod operator+=(DMod rhs) { return *this = *this + rhs; }
    DMod operator-=(DMod rhs) { return *this = *this - rhs; }

```

```

    DMod operator*=(DMod rhs) { return *this = *this * rhs; }

    DMod bigmul(ll big) const { return ::bigmul(a, big, M); }

    DMod binexp(ll e) const { return ::binexp(a, e, M); }
    DMod multinv() const { return ::multinv(a, M); } //
    // prime M
    // DMod multinv() const { return ::multinv_euc(a, M); } //
    // possibly composite M
};

```

7.8 poly

```

#include "../common.h"

#define NOMAIN_MOD
#include "mod.cpp"

using cd = complex<double>;
const double PI = acos(-1);

// compute the DFT of a power-of-two-length sequence.
// if 'inv' is true, computes the inverse DFT.
//
// the DFT of a polynomial  $A(x) = A_0 + A_1x + A_2x^2 + \dots + A_nx^n$  is the array
// of the polynomial  $A$  evaluated in all  $n$ th roots of unity:
//  $[A(w_0), A(w_1), A(w_2), \dots, A(w_{n-1})]$ , where  $w_0 = 1$  and  $w_1$  is the  $n$ th
// principal root of unity.
void fft(vector<cd> &a, bool inv) {
    int N = a.size(), k = 0;
    assert(N == 1 << __builtin_ctz(N));

    rep(i, N) {
        int b = N >> 1;
        while (k & b) k ^= b, b >>= 1;
        k ^= b;
        if (i < k) swap(a[i], a[k]);
    }

    for (int l = 2; l <= N; l <= 1) {
        double ang = 2 * PI / l * (inv ? -1 : 1);
        cd w1(cos(ang), sin(ang));
        for (int i = 0; i < N; i += l) {
            cd w(1);

```

```

            repx(j, 0, l / 2) {
                cd u = a[i + j], v = a[i + j + l / 2] * w;
                a[i + j] = u + v;
                a[i + j + l / 2] = u - v;
                w *= w1;
            }
        }
    }

    if (inv)
        for (cd &x : a) x /= N;
}

const ll MOD = 7340033, ROOT = 5, ROOTPOW = 1 << 20;

void find_root_of_unity(ll M) {
    ll c = M - 1, k = 0;
    while (c % 2 == 0) c /= 2, k += 1;

    // find proper divisors of  $M - 1$ 
    vector<int> divs;
    repx(d, 1, c) {
        if (d * d > c) break;
        if (c % d == 0) rep(i, k + 1) divs.push_back(d << i);
    }
    rep(i, k) divs.push_back(c << i);

    // find any primitive root of  $M$ 
    ll G = -1;
    repx(g, 2, M) {
        bool ok = true;
        for (int d : divs) ok &= (binexp(g, d, M) != 1);
        if (ok) {
            G = g;
            break;
        }
    }
    assert(G != -1);

    ll w = binexp(G, c, M);
    cerr << M << " = c * 2^k + 1" << endl;
    cerr << " c = " << c << endl;
    cerr << " k = " << k << endl;
    cerr << "w^(2^k) == 1" << endl;
    cerr << " w = " << w << endl;
}

// compute the DFT of a power-of-two-length sequence, modulo
// a special prime
// number with principal root.

```



```
//
// the modulus _must_ be a prime number with an Nth root of
// unity, where N is a
// power of two. the FFT can only be performed on arrays of
// size <= N.
void ntt(vector<ll> &a, bool inv) {
    int N = a.size(), k = 0;
    assert(N == 1 << __builtin_ctz(N) && N <= ROOTPOW);
    rep(i, N) a[i] = (a[i] % MOD + MOD) % MOD;

    repx(i, 1, N) {
        int b = N >> 1;
        while (k & b) k ^= b, b >>= 1;
        k ^= b;
        if (i < k) swap(a[i], a[k]);
    }

    for (int l = 2; l <= N; l <= 1) {
        ll w1 = inv ? multinv(ROOT, MOD) : ROOT;
        for (ll i = ROOTPOW; i > 1; i >= 1) w1 = w1 * w1 % MOD;
        for (int i = 0; i < N; i += 1) {
            ll w = 1;
            repx(j, 0, l / 2) {
                ll u = a[i + j], v = a[i + j + l / 2] * w % MOD;
                a[i + j] = (u + v) % MOD;
                a[i + j + l / 2] = (u - v + MOD) % MOD;
                w = w * w1 % MOD;
            }
        }

        ll ninv = multinv(N, MOD);
        if (inv)
            for (ll &x : a) x = x * ninv % MOD;
    }

    void convolve(vector<ll> &a, vector<ll> b, int n) {
        n = 1 << (32 - __builtin_clz(2 * n - 1));
        a.resize(n), b.resize(n);
        ntt(a, false), ntt(b, false);
        rep(i, n) a[i] *= b[i];
        ntt(a, true), ntt(b, true);
    }

    using T = ll;
    T pmul(T a, T b) { return a * b % MOD; }
    T padd(T a, T b) { return (a + b) % MOD; }
    T psub(T a, T b) { return (a - b + MOD) % MOD; }
```

```
T pinv(T a) { return multinv(a, MOD); }

struct Poly {
    vector<T> a;

    Poly() {}
    Poly(T c) : a(c) { trim(); }
    Poly(vector<T> c) : a(c) { trim(); }

    void trim() {
        while (!a.empty() && a.back() == 0) a.pop_back();
    }
    int deg() const { return a.empty() ? -1000000 : a.size() - 1; }
    Poly sub(int l, int r) const {
        r = min(r, (int)a.size()); l = min(l, r);
        return vector<T>(a.begin() + l, a.begin() + r);
    }
    Poly trunc(int n) const { return sub(0, n); }
    Poly shl(int n) const {
        Poly out = *this;
        out.a.insert(out.a.begin(), n, 0);
        return out;
    }
    Poly rev(int n, bool r = false) const {
        Poly out(*this);
        if (r) out.a.resize(max(n, (int)a.size()));
        reverse(out.a.begin(), out.a.end());
        return out.trunc(n);
    }

    Poly &operator+=(const Poly &rhs) {
        auto &b = rhs.a;
        a.resize(max(a.size(), b.size()));
        rep(i, b.size()) a[i] = padd(a[i], b[i]); // add
        trim();
        return *this;
    }
    Poly &operator-=(const Poly &rhs) {
        auto &b = rhs.a;
        a.resize(max(a.size(), b.size()));
        rep(i, b.size()) a[i] = psub(a[i], b[i]); // sub
        trim();
        return *this;
    }
    Poly &operator*=(const Poly &rhs) {
        int n = deg() + rhs.deg() + 1;
        if (n <= 0) return *this = Poly();
        n = 1 << (n <= 1 ? 0 : 32 - __builtin_clz(n - 1));
        vector<T> b = rhs.a;
```

```
a.resize(n), b.resize(n);
        ntt(a, false), ntt(b, false); // fft
        rep(i, a.size()) a[i] = pmul(a[i], b[i]); // mul
        ntt(a, true), trim(); // invfft
        return *this;
    }
    Poly inv(int n) const {
        assert(deg() >= 0);
        Poly ans = pinv(a[0]); // inverse
        int b = 1;
        while (b < n) {
            Poly C = (ans * trunc(2 * b)).sub(b, 2 * b);
            ans -= (ans * C).trunc(b).shl(b);
            b *= 2;
        }
        return ans.trunc(n);
    }

    Poly operator+(const Poly &rhs) const { return Poly(*this) += rhs; }
    Poly operator-(const Poly &rhs) const { return Poly(*this) -= rhs; }
    Poly operator*(const Poly &rhs) const { return Poly(*this) *= rhs; }

    pair<Poly, Poly> divmod(const Poly &b) const {
        if (deg() < b.deg()) return {Poly(), *this};
        int d = deg() - b.deg() + 1;
        Poly D = (rev(d) * b.rev(d).inv(d)).trunc(d).rev(d, true);
        return {D, *this - D * b};
    }
    Poly operator/(const Poly &b) const { return divmod(b).first; }
    Poly operator%(const Poly &b) const { return divmod(b).second; }
    Poly &operator/=(const Poly &b) { return *this = divmod(b).first; }
    Poly &operator%=(const Poly &b) { return *this = divmod(b).second; }

    T eval(T x) {
        T y = 0;
        invrep(i, a.size()) y = padd(pmul(y, x), a[i]); // add, mul
        return y;
    }
    Poly &build(vector<Poly> &tree, vector<T> &x, int v, int l, int r) {
        if (l == r) return tree[v] = vector<T>{-x[l], 1};
```



```

    int m = (1 + r) / 2;
    return tree[v] = build(tree, x, 2 * v, 1, m) *
        build(tree, x, 2 * v + 1, m + 1, r);
}
void subeval(vector<Poly> &tree, vector<T> &x, vector<T>
    &y, int v, int l,
        int r) {
    if (l == r) {
        y[l] = eval(x[l]);
        return;
    }
    int m = (1 + r) / 2;
    (*this % tree[2 * v]).subeval(tree, x, y, 2 * v, 1, m
    );
    (*this % tree[2 * v + 1]).subeval(tree, x, y, 2 * v +
    1, m + 1, r);
}
// evaluate m points in  $O(k (\log k)^2)$  with  $k = \max(n, m)$ 
vector<T> multieval(vector<T> &x) {
    int N = x.size();
    if (deg() < 0) return vector<T>(N, 0);
    vector<Poly> tree(4 * N);
    build(tree, x, 1, 0, N - 1);
    vector<T> y(N);
    subeval(tree, x, y, 1, 0, N - 1);
    return y;
}

friend ostream &operator<<(ostream &s, const Poly &p) {
    s << "(";
    bool first = true;
    rep(i, p.a.size()) {
        if (p.a[i] == 0) continue;
        if (!first) s << " + ";
        s << p.a[i];
        if (i > 0) s << " x";
        if (i > 1) s << "^" << i;
        first = false;
    }
    s << ")";
    return s;
}
};

#ifdef NOMAIN_POLY

int main() {
    Poly p1({1, 4});
    Poly p2({-3, 2});

```

```

    Poly p3({12, 12, 12, 1});
    Poly p4({128, 40, 29, 2, 0});

    cout << p1 << " * " << p2 << " = " << p1 * p2 << endl;

    vector<ll> xs = {-4, -3, -2, -1, 0, 1, 2, 3, 4};
    for (ll &x : xs) x = (x % MOD + MOD) % MOD;
    vector<ll> ys = p2.multieval(xs);
    cout << "P(x) = " << p2 << endl;
    cout << "x -> P(x):" << endl;
    rep(i, xs.size()) { cout << " " << xs[i] << " -> " << ys[
        i] << endl; }

    cerr << endl;
    find_root_of_unity(7340033);

    cerr << endl;
    find_root_of_unity(998244353);
}
#endif

```

7.9 primes

```

#include "../common.h"

// counts the divisors of a positive integer in  $O(\sqrt{n})$ 
ll count_divisors(ll x) {
    ll divs = 1, i = 2;
    for (ll divs = 1, i = 2; x > 1; i++) {
        if (i * i > x) {
            divs *= 2;
            break;
        }
        for (ll d = divs; x % i == 0; x /= i) divs += d;
    }
    return divs;
}

// gets the prime factorization of a number in  $O(\sqrt{n})$ 
vector<pair<ll, int>> factorize(ll x) {
    vector<pair<ll, int>> f;
    for (ll k = 2; x > 1; k++) {
        if (k * k > x) {
            f.push_back({x, 1});
            break;
        }
        int n = 0;
        while (x % k == 0) x /= k, n++;
    }
}

```

```

        if (n > 0) f.push_back({k, n});
    }
    return f;
}

// iterate over all divisors of a number.
//
// divisor count upper bound:  $n^{(1.07 / \ln \ln n)}$ 
template <class OP>
void divisors(ll x, OP op) {
    auto facts = factorize(x);
    vector<int> f(facts.size());
    while (true) {
        ll y = 1;
        rep(i, f.size()) rep(j, f[i]) y *= facts[i].first;
        op(y);

        int i;
        for (i = 0; i < f.size(); i++) {
            f[i] += 1;
            if (f[i] <= facts[i].second) break;
        }
        if (i == f.size()) break;
    }
}

// computes euler totative function  $\phi(x)$ , counting the
// amount of integers in
//  $[1, x]$  that are coprime with  $x$ .
//
// time:  $O(\sqrt{x})$ 
ll phi(ll x) {
    ll phi = 1, k = 2;
    for (; x > 1; k++) {
        if (k * k > x) {
            phi *= x - 1;
            break;
        }
        ll k1 = 1, k0 = 0;
        while (x % k == 0) x /= k, k0 = k1, k1 *= k;
        phi *= k1 - k0;
    }
    return phi;
}

// computes primality up to  $N$ .
// considers 0 and 1 prime.
//  $O(N \log N)$ 
void sieve(int N, vector<bool> &prime) {
    prime.assign(N + 1, true);
}

```

```

    repx(n, 2, N + 1) if (prime[n]) for (int k = 2 * n; k <=
        N; k += n) prime[k] = false;
}

```

7.10 segment

```

#include "../common.h"

// in-place segment intersection.
void intersect(pair<int, int>& a, pair<int, int> b) {
    a = {max(a.first, b.first), min(a.second, b.second)};
}

// in-place segment "union".
// finds the shortest segment that contains both 'a' and 'b'
// '.
//
// for [a, b) segments: change > to >= and <= to <
void unite(pair<int, int>& a, pair<int, int> b) {
    if (a.first > a.second)
        a = b;
    else if (b.first <= b.second)
        a = {min(a.first, b.first), max(a.second, b.second)};
}

// segment containment.
//
// [a, b] in [c, d]
// subset or equal: a >= c && b <= d || a > b
// proper subset: a > c && b < d || a > b && c <= d
//
// [a, b) in [c, d)
// subset or equal: a >= c && b <= d || a >= b
// proper subset: a > c && b < d || a >= b && c < d
bool is_subset(pair<int, int> sub, pair<int, int> sup) {
    return sub.first >= sup.first && sub.second <= sup.second
        ||
        sub.second < sub.first;
}

bool is_subset_proper(pair<int, int> sub, pair<int, int> sup) {
    return sub.first > sup.first && sub.second < sup.second
        ||
        sub.second < sub.first && sup.first <= sup.second;
}

```

7.11 theorems

```

// Burnside lemma
//
// For a set X, with members x in X, and a group G, with
// operations g in G, where g(x): X -> X.
// F_g is the set of x which are fixed points of g (ie. {
// x in X / g(x) = x }).
// The number of orbits (connected components in the
// graph formed by assigning each x a node and
// a directed edge between x and g(x) for every g) is
// called M.
// M = the average of the fixed points of all g = (|F_g1|
// + |F_g2| + ... + |F_gn|) / |G|
//
// If x are images and g are simmetries, then M
// corresponds to the amount of objects, |G|
// corresponds to the amount of simmetries, and F_g
// corresponds to the amount of simmetrical
// images under the simmetry g.
//
// Rational root theorem
//
// All rational roots of the polynomials with integer
// coefficients:
//
// a0 * x^0 + a1 * x^1 + a2 * x^2 + ... + an * x^n = 0
//
// If these roots are represented as p / q, with p and q
// coprime,
// - p is an integer factor of a0
// - q is an integer factor of an
//
// Note that if a0 = 0, then x = 0 is a root, the
// polynomial can be divided by x and the theorem
// applies once again.
//
// Legendre's formula
//
// Considering a prime p, the largest power p^k that
// divides n! is given by:
//
// k = floor(n/p) + floor(n/p^2) + floor(n/p^3) + ...
//
// Which can be computed in O(log n / log p) time

```

8 strings_{martin}

8.1 hash

```

#include "../common.h"

// compute substring hashes in O(1).
// hashes are compatible between different strings.
struct Hash {
    ll HMOD;
    int N;
    vector<int> h;
    vector<int> p;

    Hash() {}
    // O(N)
    Hash(const string& s, ll HMOD_ = 1000003931)
        : N(s.size() + 1), HMOD(HMOD_), p(N), h(N) {
        static const ll P =
            chrono::steady_clock::now().time_since_epoch().
            count() % (1 << 29);
        p[0] = 1;
        rep(i, N - 1) p[i + 1] = p[i] * P % HMOD;
        rep(i, N - 1) h[i + 1] = (h[i] + (ll)s[i] * p[i]) %
            HMOD;
    }

    // O(1)
    pair<ll, int> get(int i, int j) { return {(h[j] - h[i] +
        HMOD) % HMOD, i}; }

    bool cmp(pair<ll, int> x0, pair<ll, int> x1) {
        int d = x0.second - x1.second;
        ll& lo = d < 0 ? x0.first : x1.first;
        lo = lo * p[abs(d)] % HMOD;
        return x0.first == x1.first;
    }
};

// compute hashes in multiple prime modulus simultaneously,
// to reduce the chance
// of collisions.
struct HashM {
    int N;
    vector<Hash> sub;

    HashM() {}
    // O(K N)

```

```

HashM(const string& s, const vector<ll>& mods) : N(mods.
    size()), sub(N) {
    rep(i, N) sub[i] = Hash(s, mods[i]);
}

// O(K)
vector<pair<ll, int>> get(int i, int j) {
    vector<pair<ll, int>> hs(N);
    rep(k, N) hs[k] = sub[k].get(i, j);
    return hs;
}

bool cmp(const vector<pair<ll, int>>& x0, const vector<
    pair<ll, int>>& x1) {
    rep(i, N) if (!sub[i].cmp(x0[i], x1[i])) return false
        ;
    return true;
}

bool cmp(int i0, int j0, int i1, int j1) {
    rep(i, N) if (!sub[i].cmp(sub[i].get(i0, j0),
        sub[i].get(i1, j1))) return
        false;

    return true;
}
};

#ifdef NOMAIN_HASH

int main() {
    const vector<ll> HMOD = {1000001237, 1000003931};
    // 01234567890123456789012
    string s = "abracadabra abracadabra";
    HashM h(s, HMOD);
    rep(i0, s.size() + 1) repx(j0, i0, s.size() + 1) rep(i1,
        s.size() + 1)
        repx(j1, i1, s.size() + 1) {
        bool eq = h.cmp(h.get(i0, j0), h.get(i1, j1));
        bool eq2 = s.substr(i0, j0 - i0) == s.substr(i1, j1 -
            i1);
        if (eq != eq2) {
            cout << " hash says strings \"" << s.substr(i0,
                j0 - i0) << "\" "
                << (eq ? "==" : "!=") << " \"" << s.substr(i1,
                    j1 - i1)
                << "\" but in reality they are " << (eq2 ? "
                    ==": "!=")
                << endl;
        }
    }
}

```

```

}

```

```

#endif

```

8.2 hash2d

```

#include "../common.h"

```

```

using Hash = pair<ll, int>;

```

```

struct Block {
    int x0, y0, x1, y1;
};

```

```

struct Hash2d {
    ll HMOD;
    int W, H;
    vector<int> h;
    vector<int> p;

    Hash2d() {}
    Hash2d(const string& s, int W_, int H_, ll HMOD_ =
        1000003931)
        : W(W_ + 1), H(H_ + 1), HMOD(HMOD_) {
        static const ll P =
            chrono::steady_clock::now().time_since_epoch().
                count() % (1 << 29);
        p.resize(W * H);
        p[0] = 1;
        rep(i, W * H - 1) p[i + 1] = p[i] * P % HMOD;
        h.assign(W * H, 0);
        repx(y, 1, H) repx(x, 1, W) {
            ll c = (ll)s[(y - 1) * (W - 1) + x - 1] * p[y * W
                + x] % HMOD;
            h[y * W + x] = (HMOD + h[y * W + x - 1] + h[(y -
                1) * W + x] -
                h[(y - 1) * W + x - 1] + c) %
                HMOD;
        }
    }

    bool isout(Block s) {
        return s.x0 < 0 || s.x0 >= W || s.x1 < 0 || s.x1 >= W
            || s.y0 < 0 ||
                s.y0 >= H || s.y1 < 0 || s.y1 >= H;
    }
}

```

```

Hash get(Block s) {

```

```

    return {(2 * HMOD + h[s.y1 * W + s.x1] - h[s.y1 * W +
        s.x0] -
        h[s.y0 * W + s.x1] + h[s.y0 * W + s.x0]) %
        HMOD,
        s.y0 * W + s.x0};
}

```

```

bool cmp(Hash x0, Hash x1) {
    int d = x0.second - x1.second;
    ll& lo = d < 0 ? x0.first : x1.first;
    lo = lo * p[abs(d)] % HMOD;
    return x0.first == x1.first;
}
};

```

```

struct Hash2dM {
    int N;
    vector<Hash2d> sub;

    Hash2dM() {}
    Hash2dM(const string& s, int W, int H, const vector<ll>&
        mods)
        : N(mods.size()), sub(N) {
        rep(i, N) sub[i] = Hash2d(s, W, H, mods[i]);
    }
}

```

```

bool isout(Block s) { return sub[0].isout(s); }

```

```

vector<Hash> get(Block s) {
    vector<Hash> hs(N);
    rep(i, N) hs[i] = sub[i].get(s);
    return hs;
}

```

```

bool cmp(const vector<Hash>& x0, const vector<Hash>& x1)
{
    rep(i, N) if (!sub[i].cmp(x0[i], x1[i])) return false
        ;
    return true;
}

```

```

bool cmp(Block s0, Block s1) {
    rep(i, N) if (!sub[i].cmp(sub[i].get(s0), sub[i].get(
        s1))) return false;
    return true;
}
};

```

```

#ifdef NOMAIN_HASH2D

```

```
const vector<ll> HMOD = {1000002649, 1000000933, 1000003787,
    1000002173};
```

```
int main() {}
```

```
#endif
```

8.3 kmp

```
#include "common.h"
```

```
// compute the prefix function for string 's':
// for every character substring [0 : i] (both inclusive),
// compute the longest proper prefix that
// is also a suffix.
```

```
// O(N)
```

```
//
```

```
// computing 'prefunc' on a string of the type 'www#ttttttt'
// 'will give for
```

```
// every 't' the amount of characters from 'w' that match (
// ie. search for the
// string 'w' inside the string 't').
```

```
void prefunc(const string &s, vector<int> &p)
```

```
{
```

```
    int N = s.size(), j;
    p.resize(N), p[0] = 0;
    repx(i, 1, N)
```

```
{
```

```
    for (j = p[i - 1]; j > 0 && s[j] != s[i];)
        j = p[j - 1];
    p[i] = j + (s[j] == s[i]);
```

```
}
```

```
}
```

8.4 palin

```
#include "../common.h"
```

```
// find maximal palindromes (and therefore all palindromes)
// in O(n).
```

```
// returns a vector of positions, with one position for
// every character and in
```

```
// between characters.
```

```
//
```

```
// a b c c c
```

```
// 0 1 2 3 4 5 6 7 8
```

```
// 1 0 1 0 1 2 3 2 1
```

```
void manacher(const string& s, vector<int>& p) {
```

```
    int N = s.size(), P = 2 * N - 1;
```

```
    p.assign(P, 0);
```

```
    int l = 0, r = -1;
```

```
    rep(i, P) {
```

```
        int d = (r >= i ? min(p[l + r - i], r - i + 2) : i %
            2);
```

```
        while (i - d >= 0 && i + d < P && s[(i - d) / 2] == s
            [(i + d) / 2])
```

```
            d += 2;
```

```
        p[i] = d;
```

```
        if (i + d - 2 > r) l = i - d + 2, r = i + d - 2;
```

```
    }
```

```
    rep(i, P) p[i] -= 1;
```

```
}
```

```
#ifndef NOMAIN_PALIN
```

```
void test(const string& s) {
```

```
    vector<int> p;
```

```
    manacher(s, p);
```

```
    cout << "palindromes of string \"" << s << "\":" << endl;
```

```
    rep(i, p.size()) {
```

```
        for (int k = i % 2; k < p[i]; k += 2) {
            cout << " \"" << s.substr((i - k) / 2, k + 1) <<
                "\"\n" << endl;
```

```
        }
```

```
    }
```

```
}
```

```
int main() {
```

```
    test("hello");
```

```
    test("abracadabra");
```

```
    test("abcba");
```

```
    test("abba");
```

```
    test("cada");
```

```
}
```

```
#endif
```

8.5 sufarr

```
#include "../common.h"
```

```
// build the suffix array
```

```
// suffixes are sorted, with each suffix represented by its
// starting position
```

```
vector<int> suffixarray(const string& s) {
```

```
    int N = s.size() + 1; // optional: include terminating
    NUL
```

```
    vector<int> p(N), p2(N), c(N), c2(N), cnt(256);
```

```
    rep(i, N) cnt[s[i]] += 1;
```

```
    repx(b, 1, 256) cnt[b] += cnt[b - 1];
```

```
    rep(i, N) p[--cnt[s[i]]] = i;
```

```
    repx(i, 1, N) c[p[i]] = c[p[i - 1]] + (s[p[i]] != s[p[i -
        1]]);
```

```
    for (int k = 1; k < N; k <= 1) {
```

```
        int C = c[p[N - 1]] + 1;
```

```
        cnt.assign(C + 1, 0);
```

```
        for (int& pi : p) pi = (pi - k + N) % N;
```

```
        for (int c1 : c) cnt[c1 + 1] += 1;
```

```
        rep(i, C) cnt[i + 1] += cnt[i];
```

```
        rep(i, N) p2[cnt[c[p[i]]]++] = p[i];
```

```
        c2[p2[0]] = 0;
```

```
        repx(i, 1, N) c2[p2[i]] =
```

```
            c2[p2[i - 1]] + (c[p2[i]] != c[p2[i - 1]] ||
```

```
                c[(p2[i] + k) % N] != c[(p2[i - 1]
                    + k) % N]);
```

```
        swap(c, c2), swap(p, p2);
```

```
    }
```

```
    p.erase(p.begin()); // optional: erase terminating NUL
    return p;
```

```
}
```

```
// build the lcp
```

```
// 'lcp[i]' represents the length of the longest common
// prefix between suffix i
```

```
// and suffix i+1 in the suffix array 'p'. the last element
// of 'lcp' is zero by
```

```
// convention
```

```
vector<int> makeLcp(const string& s, const vector<int>& p) {
```

```
    int N = p.size(), k = 0;
```

```
    vector<int> r(N), lcp(N);
```

```
    rep(i, N) r[p[i]] = i;
```

```
    rep(i, N) {
```

```
        if (r[i] + 1 >= N) {
```

```
            k = 0;
```

```
            continue;
```

```
        }
```

```
        int j = p[r[i] + 1];
```

```
        while (i + k < N && j + k < N && s[i + k] == s[j + k
            ]) k += 1;
```

```
        lcp[r[i]] = k;
```

```
        if (k) k -= 1;
```

```
    }
```

```

    return lcp;
}

#ifdef NOMAIN_SUFARR

void test(const string& s) {
    cout << "suffix array for string \"" << s << "\" (length
        " << s.size()
        << "):" << endl;
}

```

```

vector<int> sa = suffixarray(s);
vector<int> lcp = makelcp(s, sa);
rep(i, sa.size()) {
    int j = sa[i];
    if (i > 0) cout << " " << lcp[i - 1] << endl;
    cout << " \"" << s.substr(j) << "\"" << endl;
}

```

```

int main() {
    test("hello");
    test("abracadabra");
}

#endif

```
