

Spring Boot Annotations Cheat Sheet with Examples and Notes

1. @SpringBootApplication

- Example:

```
@SpringBootApplication
```

```
public class MyApp { public static void main(String[] args) { SpringApplication.run(MyApp.class, args); } }
```

- Note: Use at the main class to enable auto-configuration and component scanning.

2. @RestController

- Example:

```
@RestController
```

```
public class MyController { @GetMapping("/hello") public String hello() { return "Hello"; } }
```

- Note: Use for REST APIs where responses are JSON or XML.

3. @RequestMapping

- Example:

```
@RequestMapping("/api")
```

```
public String api() { return "API Endpoint"; }
```

- Note: Use to map HTTP requests at the class or method level.

4. @GetMapping / @PostMapping

- Example:

```
@GetMapping("/users")
```

```
public List<User> getUsers() { return userService.getAllUsers(); }
```

- Note: Use for HTTP GET, POST, PUT, DELETE methods for clarity.

5. @Autowired

- Example:

```
@Autowired
```

```
private UserService userService;
```

- Note: Use for dependency injection to automatically inject beans.

6. @Service

- Example:

@Service

```
public class UserService { public List<User> getAllUsers() { return null; } }
```

- Note: Use for service layer classes containing business logic.

7. @Repository

- Example:

@Repository

```
public interface UserRepository extends JpaRepository<User, Long> {}
```

- Note: Use for DAO classes interacting with the database.

8. @Component

- Example:

@Component

```
public class MyComponent { public void doSomething() {} }
```

- Note: Use for general-purpose Spring-managed components.

9. @Entity

- Example:

@Entity

```
public class User { @Id @GeneratedValue private Long id; private String name; }
```

- Note: Use for database entity classes.

10. @Table

- Example:

@Table(name="users")

```
public class User {}
```

- Note: Use to define table mapping for an entity.

11. @Id

- Example:

@Id private Long id;

- Note: Use to define primary key field.

12. @GeneratedValue

- Example:

@GeneratedValue(strategy=GenerationType.IDENTITY) private Long id;

- Note: Use for auto-generating primary key values.

13. @Value

- Example:

@Value("\${app.name}") private String appName;

- Note: Use to inject values from application.properties.

14. @Configuration

- Example:

@Configuration

```
public class AppConfig { @Bean public MyBean myBean() { return new MyBean(); } }
```

- Note: Use to define configuration classes.

15. @Bean

- Example:

@Bean

```
public MyBean myBean() { return new MyBean(); }
```

- Note: Use to declare Spring beans.

16. @EnableAutoConfiguration

- Example:

@EnableAutoConfiguration

```
public class App {}
```

- Note: Use to let Spring Boot configure beans automatically.

17. @ComponentScan

- Example:

```
@ComponentScan(basePackages="com.example")
```

```
public class App {}
```

- Note: Use to specify packages for component scanning.