Merkle Tree

Merkle Tree

The Merkle tree is a robust data structure employed in computer science and cryptography to efficiently establish the integrity and authenticity of data within expansive datasets.

Constructing a Merkle tree involves recursively hashing pairs of data until only a solitary hash, referred to as the Merkle root, remains. The tree's leaves represent the original data, while each internal node represents the hash of its two child nodes.

The Merkle root serves as a means to verify data integrity. A party can substantiate that a specific data element is part of the tree by presenting a path from the leaf node to the root, accompanied by the hashes of each node along the path. The verifier can then compute the root by hashing the provided data and hashes, subsequently comparing it to the expected root.

Merkle Tree




Figure: Merkle Tree with 8 leaf nodes

Structure of Merkle Tree

Leaf nodes: The leaf nodes are the bottom layer of a Merkle tree and represent the individual pieces of data that will be included in the tree. In the context of blockchain, the leaf nodes represent the individual transactions that will be hashed and included in the Merkle tree.

Hash function: The hash function is used to transform the data in the leaf nodes into fixed size hashes.

Parent nodes: The parent nodes are created by hashing pairs of leaf nodes together. Each parent node represents the hash of its two children, and this process is repeated recursively until there is only one node left – the root node.

Root node: The root node is the top-level node of a Merkle tree and represents the hash of all the data included in the tree. The root node is included in the block header in the context of blockchain.

Branch Nodes: The branch nodes are the intermediate nodes between the leaf nodes and the root node. They represent the hash of their two children and are used to verify the authenticity of a particular piece of data in the Merkle tree.

Merkle Tree Creation

Prepare the data: The first step is to prepare the data you want to include in the tree. The data are usually divided into fixed-size blocks, and each block is assigned a unique identifier, such as a hash.

Build the bottom layer: In this step, you take each block of data and hash it to create a leaf node. The leaf nodes are then grouped into pairs, and the hash of each pair is calculated to create a new node.

Build the next layer: In the next layer, you repeat step 2, but this time you calculate the hash of each pair of nodes from the previous layer. You continue this process until there is only one node left, which is the root of the tree.

Store the tree: The Merkle tree can be stored in several ways, such as a flat array or a binary tree. Each node in the tree is assigned a unique identifier, which can be used to verify the authenticity of the data.

Verify data: To verify the authenticity of a block of data, you need to provide the leaf node hash, as well as the hashes of all the nodes on the path from the leaf node to the root. The verifier can then recalculate the root hash and compare it to the expected value. If the hashes match, the data are considered authentic.

Role of Merkle Tree in Blockchain

When a new block is added to a blockchain, it contains a list of all the transactions that have occurred since the previous block. These transactions are combined and hashed together to create a Merkle tree. The root of the Merkle tree is then included in the block header, along with other important information, such as the timestamp and the previous block hash. By including the Merkle tree root in the block header, the blockchain can ensure the following:

Data integrity: The Merkle tree provides a way to verify that all transactions in a block are valid and have not been tampered with. By providing the hash of each transaction in the block, a verifier can easily calculate the Merkle root hash and compare it to the root hash included in the block header. If the hashes match, it can be assumed that all the transactions are valid and have not been modified.

Role of Merkle Tree in Blockchain

Scalability: The Merkle tree allows for efficient and scalable verification of transactions. Instead of having to verify each transaction individually, the Merkle tree allows a verifier to quickly verify an entire block by only checking a handful of hashes.

Tamper resistance: Because a Merkle tree is built using a hash function, it is difficult to modify the transactions in a block without changing the Merkle root hash. This means that once a block has been added to a blockchain, it is extremely difficult to modify or delete any of the transactions in that block.

Merkle Proof

A Merkle proof, also known as a Merkle path or a Merkle authentication path, is a proof that demonstrates the membership or non-membership of an element in a Merkle tree data structure. Merkle proofs are widely used in distributed systems, such as blockchain technology, to efficiently verify the integrity of data without having to download the entire dataset.

Proof of Membership

To prove membership of a particular transaction in a Merkle tree, a proof must be provided that includes the hash values of the nodes on the path from the transaction to the root of the Merkle tree.

1. Assume there is a Merkle tree with four transactions, labeled A, B, C, and D, and the root hash of the tree is represented by H.
2. Say we want to prove that transaction C is included in the Merkle tree.

Merkle Proof

3. To prove this, we need to provide a proof that includes the hash values of the nodes on the path from transaction C to the root of the Merkle tree.
4. In this case, the path from C to the root of the tree includes the hashes of transactions B and D and the root H.
5. The proof of membership for transaction C would therefore include the hashes of transactions B and D, as well as the root hash H.
6. A verifier can then use these hash values to reconstruct the path from transaction C to the root H and verify that the hash of C matches the hash stored in the Merkle tree.
7. If the hash values match, the verifier can be confident that transaction C is included in the Merkle tree and, therefore, in the blockchain.
8. This process of proving membership in a Merkle tree blockchain is secure because any tampering with the transactions in the Merkle tree would result in a different root hash, and the proof would not be valid.

Applications of Merkle Trees

Cryptocurrencies: Cryptocurrencies such as Bitcoin and Ethereum use Merkle trees to verify the validity of transactions. Each block in the blockchain contains a Merkle tree of all the transactions in a block, and the root of the tree is included in the block header. This allows nodes in the network to easily verify the authenticity of the transactions in a block.

Content-addressable storage: Content-addressable storage systems, such as the InterPlanetary File System (IPFS), use Merkle trees to verify the integrity of stored content. Each file is split into chunks, and a Merkle tree is constructed from the hashes of the chunks. The root of the tree is then used as the content's address, allowing the content to be retrieved and verified from any node in the network.

Distributed systems: Distributed systems often use Merkle trees to verify the consistency of replicated data across multiple nodes. Each node stores a Merkle tree of the data it holds, and these trees are compared to ensure that all nodes have the same data.

Data storage: Merkle trees are also used in data storage systems, such as the ZFS filesystem. ZFS uses Merkle trees to verify the integrity of stored data, allowing it to detect and correct errors in the storage media.