

Programing Basic Knowledge L^AT_EX

Rayhanul Islam Mukul

15 December 2022

Contents

1	Data Structure	5
1.1	Array	5
1.2	Stack	6
1.3	Queue	7
1.4	Priority Queue	7
1.5	DeQueue	7
2	Standard Template Library (STL)	9
2.1	Map	9
2.2	Vector Pair	10
2.3	Pointer	11
2.4	Set	12
2.5	Multiset	12
2.6	String	13
2.6.1	String manipulation (e.g. reverse, replace, split):	13
2.6.2	String compression (e.g. Run-length encoding, Huffman coding):	13
2.6.3	String hashing:	14
2.6.4	String sorting (e.g. radix sort):	14
2.6.5	String comparison:	15
2.6.6	Palindrome detection:	15
2.7	Big Mod	17
2.8	Binary Exponentiation Power	18
2.9	Sieve Prime Factorization	19
2.10	Binary Search	20
2.11	Dynamic Programing	21
2.12	Euclidean Algorithm	22
2.13	Lamda Function	23
2.14	Bitwise Operation	24
3	Graph Theoury	25
3.1	Knuth–Morris–Pratt (KMP)	25
3.2	Rabin Karp Algorithm	27
3.3	Breadth First Search (BFS)	29
3.4	Depth First Search (DFS)	30
3.5	Dijkstra’s Algorithm	31
3.6	Graham Scan Algorithm	32
3.7	Meet in the middle	35
4	Common Mistakes in Competitive Programming	37
4.0.1	Mistake 1	37

Chapter 1

Data Structure

Topic

- Arrays
- Linked Lists
- Stacks
- Queues
- Trees
- Heaps
- Hash table
- Graphs

1.1 Array

Code 1.1: Array of C++ programming language

```
int arr[10] = {1, 12, 3, 24, 35, 16};  
sort(arr, arr+10, [](int i, int j){  
    return i > j;  
});
```

1.2 Stack

LIFO = Last in First Out

Code 1.2: Stack of C++ programming language

```
stack <int> mystack;    // push, pop, top, empty : O(1)
mystack.push(10);
mystack.pop();
mystack.empty();
```

1.3 Queue

FIFO = First in First Out

Code 1.3: Queue of C++ programming language

```
queue <int> myqueue;
myqueue.push(10);           //Enqueue (push): 0(1) - inserting
myqueue.pop();              //Dequeue (pop): 0(1) - removing
int front = myqueue.front(); //Front (front): 0(1) - accessing
int back = myqueue.back();
int size = myqueue.size();  //0(1)
bool empty = myqueue.empty(); //Empty (empty): 0(1) - checking
```

1.4 Priority Queue

Code 1.4: Priority Queue of C++ programming language

```
priority_queue<int> myPriorityQueue;
myPriorityQueue.push(30);           //0(log n)
myPriorityQueue.pop();              //0(log n)
int highestPriority = myPriorityQueue.top(); //0(1)
```

```
priority_queue <int, vector<int>, greater<int>> myPriorityQueue; //0(log n)
```

```
if (myPriorityQueue.empty()) {
    // the priority queue is empty
}
```

1.5 DeQueue

Code 1.5: Priority Queue of C++ programming language

```
deque <int> mydeque;
mydeque.push_back(10);           //Insertion (push_back, push_front): 0(1)
mydeque.push_front(20);
mydeque.pop_front();             //Deletion (pop_back, pop_front): 0(1)
mydeque.pop_back();
```

```
mydeque.erase(mydeque.begin()); //Insertion/Deletion (insert, erase): 0(n)
mydeque.insert(mydeque.begin(), 10);
int frontElement = mydeque.front();
int backElement = mydeque.back();
bool empty = mydeque.empty();
mydeque.clear();
```


Chapter 2

Standard Template Library (STL)

Topic

- Containers: vector, deque, list, set, multiset, map, multimap
- Iterators:
- Algorithms:
- Function:
- Function adapters:

2.1 Map

Code 2.1: Map

```
map <string, int> myMap;  
myMap["meow"] = 1;           //Insertion, Deletion, Search: O(log n)  
myMap.insert({"meeow", 2});  
myMap.erase("meow");  
for(auto it = myMap.begin(); it != myMap.end(); it++){  
    cout << it->first << " " << it->second << endl;  
}
```

```
if(myMap.count("meow")){  
    // key exists  
}
```

```
map <int, vector <int>> myMap;  
map <int, vector <int>> :: iterator it;  
for(it = myMap.begin(); it != myMap.end(); it++){  
    sort(it->second.begin(), it->second.end());  
}  
for(auto it1 : myMap){  
    x = it1.first;  
    for(int i = 0; i < myMap[x].size(); i++){  
        cout << myMap[x][i] << gap;  
    }  
}
```

2.2 Vector Pair

Code 2.2: Pair

```
pair <int, int> myPair;  
myPair = make_pair(1, 2);
```

```
vector <pair <int, int>> vecPair;  
vecPair.push_back(make_pair(1, 2));           //Access, insert O(1)  
sort(vecPair.begin(), vecPair.end());         //sort O(n log n)  
for(int i = 0; i < vecPair.size(); i++){      //Find element: O(log n) Bin_Sear  
    cout << vecPair[i].first << gap << vecPair[i].second << endl;  
}
```

```
vector <pair <int, int>> vecPair[1000];  
vecPair[0].pb({5, 2});                        // Creating a tuple: O(1)  
vecPair[0].pb({2, 3});  
sort(vecPair[0].begin(), vecPair[0].end());  
for(auto [u, w] : vecPair[0]){                //Comparing two tuples: O(n)  
    cout << u << gap << w << endl;  
}
```

2.3 Pointer

Code 2.3: Pointer

```
#include <bits/stdc++.h>
using namespace std;
void call(int *x){
    *x = 20;
    cout << "*x : " << *x << endl;
}
int main(){
    int n = 10;
    call(&n);
    cout << "n : " << n << endl;

    int a = 10, b = 20;
    vector <int*> v;
    v.push_back(&a);
    v.push_back(&b);
    *v[0] += 1;
    cout << "a : " << a << endl;

    return 0;
}
```

2.4 Set

Code 2.4: Set

```
set <int> mySet;      // Insert, Delete, Find in: O(logN)
mySet.insert(1);
mySet.erase(1);
for(auto it: mySet) cout << it << gap; // Traverse in: O(NlogN)
int numOccurrences = mySet.count(1);    // Count in O(logN)
int minValue = *mySet.begin();          // Minimum in O(1)
int maxValue = *mySet.rbegin();         // Maximum in O(1)
if(mySet.find(1) != mySet.end()) cout << "Found" << endl; // Find in O(logN)
```

2.5 Multiset

```
multiset <int> myMultiset; // Insert, Delete, Find in: O(logN)
myMultiset.insert(1);
myMultiset.erase(1);
for(auto it: myMultiset) cout << it << gap; // Traverse in: O(NlogN)
int numOccurrences = myMultiset.count(1);    // Count in O(logN)
int minValue = *myMultiset.begin();          // Minimum in O(1)
int maxValue = *myMultiset.rbegin();         // Maximum in O(1)
if(myMultiset.find(1) != myMultiset.end()){
    cout << "Found" << endl;                // Find in O(logN)
}
```

2.6 String

Code 2.5: Transform

```
transform(s.begin(), s.end(), s.begin(), ::tolower); // O(n), n = length
transform(s.begin(), s.end(), s.begin()+1, ::toupper);
```

Code 2.6: String concatenation

```
string str1 = "Hello", str2 = "World";
string str3 = str1 + str2;           //Time Complexity: O(m+n)
```

Code 2.7: Substring extraction

```
string str1 = "Hello World";        //Complexity is: O(K), k is length
string s1 = str1.substr(0, 7);       //0 = index_start , 7 = length
```

Code 2.8: String search

```
string str1 = "Hello World";
string find = "Wor";                //O(n*m), where n = str1.size(), m = find.size()
int pos = str1.find(find);
if(pos != string::npos){
    cout << "Found at " << pos << endl;
}
```

2.6.1 String manipulation (e.g. reverse, replace, split):

Code 2.9: String manipulation

```
#include <iostream>
#include <string>

int main() {
    std::string str = "Hello World";
    std::reverse(str.begin(), str.end());
    std::cout << str << std::endl;
    return 0;
}
```

2.6.2 String compression (e.g. Run-length encoding, Huffman coding):

Code 2.10: String compression

```
#include <iostream>
#include <string>

std::string runLengthEncoding(std::string str) {
    std::string result;
    int count = 1;
    for (int i = 1; i < str.length(); i++) {
        if (str[i] == str[i - 1]) {
            count++;
        } else {
            result += str[i - 1] + std::to_string(count);
            count = 1;
        }
    }
}
```

```
    result += str[str.length() - 1] + std::to_string(count);
    return result;
}

int main() {
    std::string str = "aaaabbcccdde";
    std::cout << runLengthEncoding(str) << std::endl;
    return 0;
}
```

2.6.3 String hashing:

Code 2.11: String hashing

```
#include <iostream>
#include <string>

int hashFunction(std::string str) {
    int hash = 0;
    for (char c : str) {
        hash = hash + c;
    }
    return hash % 10;
}

int main() {
    std::string str = "Hello World";
    std::cout << hashFunction(str) << std::endl;
    return 0;
}
```

2.6.4 String sorting (e.g. radix sort):

Code 2.12: String sorting

```
#include <iostream>
#include <vector>
#include <string>

int getMaxLength(const std::vector<std::string> &arr) {
    int maxLength = 0;
    for (const std::string &s : arr) {
        maxLength = std::max(maxLength, (int)s.length());
    }
    return maxLength;
}

void countingSort(std::vector<std::string> &arr, int position) {
    std::vector<std::vector<std::string>> buckets(256);
    for (const std::string &s : arr) {
        int index = (position < s.length()) ? (int)s[position] : 0;
        buckets[index].push_back(s);
    }
    int k = 0;
    for (const std::vector<std::string> &bucket : buckets) {
        for (const std::string &s : bucket) {
            arr[k++] = s;
        }
    }
}
```

```

}

void radixSort(std::vector<std::string> &arr) {
    int maxLength = getMaxLength(arr);
    for (int position = maxLength - 1; position >= 0; position--) {
        countingSort(arr, position);
    }
}

int main() {
    std::vector<std::string> arr = {"caterpillar", "bee", "ant", "dog", "cat"};
    radixSort(arr);
    for (std::string s : arr) {
        std::cout << s << " ";
    }
    std::cout << std::endl;
    return 0;
}

```

2.6.5 String comparison:

Code 2.13: String comparison

```

#include <iostream>
#include <string>

int main() {
    std::string s1 = "hello";
    std::string s2 = "world";
    if (s1 == s2) {
        std::cout << "The strings are equal." << std::endl;
    } else if (s1 < s2) {
        std::cout << "s1 is less than s2." << std::endl;
    } else {
        std::cout << "s1 is greater than s2." << std::endl;
    }
    return 0;
}

```

2.6.6 Palindrome detection:

Code 2.14: Palindrome detection

```

#include <iostream>
#include <string>

bool isPalindrome(const std::string &s) {
    int start = 0;
    int end = (int)s.length() - 1;
    while (start < end) {
        if (s[start] != s[end]) {
            return false;
        }
        start++;
        end--;
    }
    return true;
}

```

```
int main() {  
    std::string s = "racecar";  
    if (isPalindrome(s)) {  
        std::cout << "The string is a palindrome." << std::endl;  
    } else {  
        std::cout << "The string is not a palindrome." << std::endl;  
    }  
    return 0;  
}
```


2.7 Big Mod

Code 2.15: Big Mode

```
#include <bits/stdc++.h>
using namespace std;
#define ll long long int
int power(ll a, ll b, ll mod){
    if(b == 0) return 1%mod;
    ll tmp = power(a, b/2, mod);
    ll result =( tmp*tmp)%mod;
    if(b%2 == 1) result = (result*a) % mod;
    return result;
}
int main(){
    cout << power(5, 5, 10) << endl;
    return 0;
}
```

2.8 Binary Exponentiation Power

Code 2.16: Binary Exponentiation

```
#include <bits/stdc++.h>
using namespace std;
const int MOD = 1e9 + 7;
int power(int a, int b){
    int res = 1;
    while(b > 0){
        if(b%2 == 1){
            res = res * a;
            res %= MOD;
            b--;
        }
        a = a * a;
        a %= MOD;
        b /= 2;
    }
    return res;
}
int main(){
    int a = 2, b = 3;
    cout << power(a, b) << endl;

    return 0;
}
```

2.9 Sieve Prime Factorization

Code 2.17: Sieve-Prime Factorization

```
const int n = 1000000
bool prime[1000000];
vector<int> p;
void sieve(int n){
    for(ll i = 3; i*i <= n; i+=2){
        if(prime[i] == false){
            for(ll j = i*i; j <= n; j+=i)prime[j] = true;
        }
    }
    p.push_back(2);
    for(int i = 3; i <= n; i+=2) if(prime[i] == false) p.push_back(i);
    for(int i = 0; i < p.size(); i++) cout << p[i] << " ";
}
```

2.10 Binary Search

Code 2.18: Binary Search

```
#include <bits/stdc++.h>
using namespace std;
const int MOD = 1e9 + 7;
int binary_search(int arr[], int size, int item){
    int left = 0, right = size - 1, mid;
    while(left <= right){
        mid = left + (right - left)/2;
        if(arr[mid] == item) return mid;
        if(arr[mid] < item) left = mid + 1;
        else right = mid - 1;
    }
    return -1;
}
int main(){
    int arr[10] = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
    int ans = binary_search(arr, 10, 8);
    if(ans){
        cout << "Index of : " << ans << endl;
    }
    else cout << "Not found it" << endl;

    return 0;
}
```

2.11 Dynamic Programing

Code 2.19: Fibonacci Series

```
#include <bits/stdc++.h>
using namespace std;
int dp[105];
int f(int n){
    if(n == 0) return 0;
    if(n == 1) return 1;
    if(dp[n] >= 0) return dp[n];
    dp[n] = f(n-1) + f(n-2);
    return dp[n];
}
int main(){
    for(int i = 0; i < 105; i++) dp[i] = -1;
    cout << f(7) << endl;
}
```

2.12 Euclidean Algorithm

Code 2.20: Euclidean Algorithm GCD LCM

```
#include <bits/stdc++.h>
using namespace std;
int gcd(int a, int b) {
    if (a == 0) return b;
    return gcd(b % a, a);
}
int main(){
    int a = 4, b = 10;
    int lcm = a*b/(__gcd(a, b));
    cout << lcm << " " << __gcd(a, b) << endl;

    return 0;
}
```

2.13 Lamda Function

Code 2.21: Lamda Function

```
#include <bits/stdc++.h>
using namespace std;
auto func = [] (int i, int j){
    return i+j;
};
int main(){
    cout << func(10, 20) << endl;

    return 0;
}
```

Code 2.22: Lamda Function

```
#include <bits/stdc++.h>
using namespace std;
function <int(int)> fib = [](int i){
    if(i <= 1) return 1;
    return fib(i-1) + fib(i-2);
};
int main(){
    cout << fib(5) << endl;

    return 0;
}
```

2.14 Bitwise Operation

Code 2.23: Bitwise Operation

```
Bitwise XOR:
  5 = 0 1 0 1
  6 = 0 1 1 0
  5^6 = 0 0 1 1
Left Shift: left_shift * 2
  x << = 0 1 1 0 1 0 1 1
x << 2 = 1 1 0 1 0 1 0 0
Right Shift: Right_shift / 2
  x >> = 0 1 1 0 1 0 1 1
x >> 2 = 0 0 0 1 1 0 1 0
```


Chapter 3

Graph Theoury

3.1 Knuth–Morris–Pratt (KMP)

KMP time complexity: $O(n+m)$. where, n = length of text, m = length of pattern

Code 3.1: KMP Algorithm

```
vector <int> createTemArray(string pattern){
    vector <int> lps(pattern.size());
    int ind = 0;
    for(int i = 1; i < pattern.size();){
        if(pattern[i] == pattern[ind]){
            lps[i] = ind + 1;
            ind++; i++;
        }
        else{
            if(ind != 0) ind = lps[ind - 1];
            else{
                lps[i] = ind;
                i++;
            }
        }
    }
    return lps;
}

void kmp(string pattern, string text){
    vector <int> lps = createTemArray(pattern);
    int i = 0, j = 0;    // i for text, j for pattern
    while(i < text.size()){
        if(text[i] == pattern[j]){
            i++; j++;
        }
        else{
            if(j != 0) j = lps[j-1];
            else i++;
        }
        if(j == pattern.size()){
            cout << "Pattern found at index " << i - j << endl;
            j = lps[j-1];    // for overlapping pattern
        }
    }
}

void solve(int tt){
    string pattern = "abc";
    string text = "ababcababcabc";
    kmp(pattern, text);
}
```

}

3.2 Rabin Karp Algorithm

Rabin Karp time complexity: $O(n+m)$. where, n = length of text, m = length of pattern

Code 3.2: Rabin Karp Algorithm

```
void Rabinkarp(string pattern, string text){
    int m = pattern.length();
    int n = text.length();
    int q = INT_MAX;
    int x = 11;          // typically prime - multiplier
    int x_m = 1;         // x^(m-1) used for next hash computation
    int hash_p = 0, hash_t = 0;
    for(int i = 0; i < m - 1; i++){
        x_m = (x_m * x) % q;
    }
    // compute hash for pattern and first window of text
    for(int i = 0; i < m; i++){
        hash_p = (x * hash_p + pattern[i]) % q;
        hash_t = (x * hash_t + text[i]) % q;
    }
    for(int i = 0; i <= n - m; i++){
        if(hash_p == hash_t){ // check for character by character match
            /*bool flag = true;
            for(int j = 0; j < m; j++){
                if(text[i + j] != pattern[j]){
                    flag = false;
                    break;
                }
            }
            if(flag){
                cout << "Pattern found at index " << i << endl;
            }*/
            cnt++;
        }
        //if it was not last window, then continue hash computation
        if(i < n - m){
            hash_t = (x * (hash_t - text[i] * x_m) + text[i + m]) % q;
            if(hash_t < 0){
                hash_t += q;
            }
        }
    }
}

void solve(int tt){
    string pattern = "abc";
    string text = "ababcababcabc";
    Rabinkarp(pattern, text);
}
```

```
int Hash(const string &s, int m, int B, int M){
    int h = 0, power = 1;
    for(int i = m-1; i >= 0; i--){
        h = (h + (s[i] * power) % M) % M;
        h = h % M;
        power = (power * B) % M;
    }
    return h;
}

int Rabinkarp(const string &text, const string &pattern){
    int n = text.size();
```

```

int m = pattern.size();
if(n < m) return -1;
if(m == 0 || n == 0) return -1;
int B = 347, M = MOD;
int power = 1;
for(int i = 1; i < m; i++) power = (power * B) % M; // Calculate B^m-1
// Find hash value of fisrt m characters of text
// Find hash value of pattern[0...m-1]
int hash_text = Hash(text, m, B, M);
int hash_pattern = Hash(pattern, m, B, M);

if(hash_text == hash_pattern) return 0;
for(int i = m; i < n; i++){
    // Update Rolling Hash
    hash_text = (hash_text - (text[i-m] * power) % M) % M;
    hash_text = (hash_text + M) % M;
    hash_text = (hash_text * B) % M;
    hash_text = (hash_text + text[i]) % M;

    if(hash_text == hash_pattern) return i-m+1;
}
return -1;
}

void solve(int tt){
    string pattern = "abc";
    string text = "abaabdabcjkhabcabca";
    cout << Rabinkarp(text, pattern) << endl; // Return First index of pattern
        in text
}

```

3.3 Breadth First Search (BFS)

BFS time complexity: $O(V + E)$ where V is no. of vertices and E is no. of edges

Code 3.3: Breadth First Search of C++ programming language

```
const int MAX = 2e5+5;
vector <int> adj[MAX];
vector <bool> vis(MAX, false);
vector <int> dis(MAX, 0);
void bfs(int s){
    queue <int> q;
    q.push(s);
    vis[s] = true;
    while(!q.empty()){
        int node = q.front();
        q.pop();
        for(auto child : adj[node]){
            if(!vis[child]){
                q.push(child);
                vis[child] = true;
                dis[child] = dis[node] + 1;
            }
        }
    }
}
void solve(int tt){
    int n, m;          // n = no. of nodes, m = no. of edges
    cin >> n >> m;
    for(int i = 1; i <= m; i++){
        int x, y;
        cin >> x >> y;
        adj[x].pb(y);
        adj[y].pb(x);
    }
    bfs(1);
    for(int i = 1; i <= n; i++){
        cout << dis[i] << gap;
    }
}
```

3.4 Depth First Search (DFS)

Code 3.4: Depth First Search of C++ programming language

```
bool vis[MAX];
vector <int> adj[MAX];
vector <int> ans;
void dfs(int node){
    if(vis[node]) return;
    ans.push_back(node);
    vis[node] = true;
    for(auto child : adj[node]){
        dfs(child);
    }
    return;
}
void solve(int tt){
    int n, m;          // n = no. of nodes, m = no. of edges
    cin >> n >> m;
    memset(vis, false, sizeof(vis));
    for(int i = 1; i <= m; i++){
        int x, y;
        cin >> x >> y;
        adj[x].pb(y);
        adj[y].pb(x);
    }
    int start; cin >> start;
    dfs(start);
    for(auto x : ans){
        cout << x << gap;
    }
}
```

3.5 Dijkstra's Algorithm

Dijkstra's Algorithm time complexity: $O(E \log V)$ where, E is the number of edges and V is the number of vertices.

Space Complexity: $O(V)$

Code 3.5: Dijkstra's algorithm of C++ programming language

```
const int N = 1e5+5;
void dijkstra(vector <vector <pair <int, int>>> &adj, int source, int n){
    vector <int> dist(N, INT_MAX);
    vector <bool> vis(N, false);
    priority_queue <pair <int, int>, vector <pair <int, int>>, greater <pair <
        int, int>>> pq;
    pq.push({0, source});
    dist[source] = 0;
    while(!pq.empty()){
        int nd = pq.top().second;
        pq.pop();
        if(vis[nd]) continue;
        vis[nd] = true;
        for(auto [v, w] : adj[nd]){
            if(dist[v] > dist[nd] + w){
                dist[v] = dist[nd] + w;
                pq.push({dist[v], v});
            }
        }
    }
    for(int i = 1; i <= n; i++){
        cout << dist[i] << gap;
    }
}
void solve(int tt){
    int n;
    cin >> n;
    vector <vector <pair <int, int>>> adj(N);
    for(int i = 1; i < n; i++){
        int u, v, w;
        cin >> u >> v >> w;
        adj[u].push_back({v, w});
        dbg(adj);
    }
    int source;
    cin >> source;
    dijkstra(adj, source, n);
}
```

3.6 Graham Scan Algorithm

Graham Scan Algorithm time complexity: $O(n \log n)$ where, n is the number of input points. In the best and average case, and $O(n^2)$ in the worst case.

Code 3.6: Graham Scan algorithm of C++ programming language

```
#include <iostream>
#include <vector>
#include <algorithm>
using namespace std;

struct Point {
    int x, y;
};

long long cross_product(Point a, Point b, Point c) {
    long long x1 = b.x - a.x;
    long long y1 = b.y - a.y;
    long long x2 = c.x - a.x;
    long long y2 = c.y - a.y;
    return x1 * y2 - x2 * y1;
}

bool compare_points(Point a, Point b) {
    return a.x < b.x || (a.x == b.x && a.y < b.y);
}

vector<Point> convex_hull(vector<Point>& points) {
    int n = points.size();
    if (n <= 1) return points;

    sort(points.begin(), points.end(), compare_points);

    vector<Point> hull;

    for (int i = 0; i < n; ++i) {
        while (hull.size() >= 2 && cross_product(hull[hull.size()-2], hull[hull.size()-1], points[i]) < 0) {
            hull.pop_back();
        }
        hull.push_back(points[i]);
    }

    int lower_hull_size = hull.size();

    for (int i = n-2; i >= 0; --i) {
        while (hull.size() > lower_hull_size && cross_product(hull[hull.size()-2], hull[hull.size()-1], points[i]) < 0) {
            hull.pop_back();
        }
        hull.push_back(points[i]);
    }

    hull.pop_back();
    return hull;
}

int main() {
    int n;
    cin >> n;
    vector<Point> points(n);
    for (int i = 0; i < n; ++i) {
        cin >> points[i].x >> points[i].y;
    }
}
```



```

vector<Point> hull = convex_hull(points);
cout << hull.size() << endl;
for (int i = 0; i < hull.size(); ++i) {
    cout << hull[i].x << " " << hull[i].y << endl;
}
return 0;
}

```

Code 3.7: Graham Scan algorithm of C++ programming language

```

class Solution {
public:
    vector<vector<int>> FindConvexHull(vector<vector<int>> &points) {
        int n = points.size();
        if(n <= 2) return vector<vector<int>> (1, vector<int> {-1});
        int leftmost = 0, mostMin = 1e9;
        for(int i = 0; i < n; ++i){
            if(points[i][0] < mostMin){
                mostMin = points[i][0];
                leftmost = i;
            }
            if(points[i][0] == mostMin && points[i][1] < points[leftmost][1]){
                leftmost = i;
            }
        }
        vector<vector<int>> hull;
        int p = leftmost;
        do{
            hull.push_back(points[p]);
            int q = (p + 1) % n;
            for(int i = 0; i < n; ++i){
                if(crossProduct(points[p], points[i], points[q]) == 2){
                    q = i;
                }
                else if(crossProduct(points[p], points[i], points[q]) == 0){
                    int64_t dist = distance(points[p], points[q], points[i]);
                    if(dist < 0) q = i;
                }
            }
            p = q;
        }while(p != leftmost);

        sort(hull.begin(), hull.end());
        return hull;
    }

private:
    int64_t crossProduct(vector<int>& a, vector<int>& b, vector<int>& c) {
        int64_t x1 = b[0] - a[0];
        int64_t y1 = b[1] - a[1];
        int64_t x2 = c[0] - a[0];
        int64_t y2 = c[1] - a[1];
        int64_t val = x1 * y2 - x2 * y1;
        if(val == 0) return 0;
        return val > 0 ? 1 : 2;
    }

    long long distance(vector<int>& a, vector<int>& b, vector<int>& c) {
        int64_t x1 = a[0] - b[0];
        int64_t y1 = a[1] - b[1];
        int64_t dist1 = (y1*y1) + (x1*x1);
        int64_t x2 = a[0] - c[0];

```

```
    int64_t y2 = a[1] - c[1];  
    int64_t dist2 = (y2*y2) + (x2*x2);  
    return dist1 - dist2;  
}  
};
```

3.7 Meet in the middle

Time Complexity: $O(2^{\frac{n}{2}} \cdot \log(2^{\frac{n}{2}}))$

Auxiliary Space: $O(2^{\frac{n}{2}})$

Code 3.8: Meet in the middle

```
void solve(int tt){
    int n, A, B;
    cin >> n >> A >> B;
    vector<int> a(n);
    for(int i = 0; i < n; i++){
        cin >> a[i];
    }
    vector<int> sum1, sum2;
    int half = n/2;
    for(int i = 0; i < (1<<half); i++){
        int sum = 0;
        for(int j = 0; j < half; j++){
            if(i & (1<<j)){
                sum += a[j];
            }
        }
        sum1.pb(sum);
    }
    for(int i = 0; i < (1<<(n-half)); i++){
        int sum = 0;
        for(int j = 0; j < (n-half); j++){
            if(i & (1<<j)){
                sum += a[j+half];
            }
        }
        sum2.pb(sum);
    }
    sor(sum1);
    int ans = 0;
    for(auto it:sum2){
        int x = A - it;
        int y = B - it;
        int l = lower_bound(sum1.begin(), sum1.end(), x) - sum1.begin();
        int r = upper_bound(sum1.begin(), sum1.end(), y) - sum1.begin();
        ans += (r-l);
    }
    cout << ans << endl;
}
```


Chapter 4

Common Mistakes in Competitive Programming

By YouKn0wWho,

4.0.1 Mistake 1

Check out the following code:

```
#include<bits/stdc++.h>
using namespace std;

int main() {
    int a = 1000'000'000,b = 1000'000'000;
    long long product = a * b;
    cout << product << '\n';
    return 0;
}
```

The output should be 10^{18} . But if you run the code, you will get a different output. Why? Overflow!

Even if you declared the product variable as long long, what's happening, in reality, is, first the compiler is multiplying a with b and then it is assigning the output to the product variable and as a and b both are int, that's why the output is also int, but 10^{18} is too much to contain for an int variable.

So how to solve this?

```
#include<bits/stdc++.h>
using namespace std;

int main() {
    int a = 1000'000'000,b = 1000'000'000;
    long long product = a * b;
    cout << product << '\n';
    return 0;
}
```

Code 4.1: Basic Knowledge of C++ programming language

```
//=====
//Basic Knowledge
//=====

cout << fixed << setprecision(10) << sum << endl; srand(clock());
value = (pow(3, 4) + 0.5)
int min = INT_MIN, max = INT_MAX;
char ch[26];
```

```
while (scanf("%s",ch) != EOF)
< input.txt > output.txt
### C & C++:
+) Loop: i) Initialization (i=0); ii) Terminate if(i<10); iii) Increment/
Decrement (i=i+1;)
+) Library Function: pow(), strlen(), strcpy(), strrev(), strupr(), strlwr(),
strcmp(), strcat()
+) int num; scanf("%4d", & num); printf("%d\n",num);
+) double num; scanf("%lf", & num); printf("sum is= %0.3lf\n",sum);
+) float num; scanf("%f", & num); printf("%f\n",num);
+) char n; scanf("%c", & n); printf("%c\n",n);
+) char str[]; int l; l = strlen(str); scanf("%s", & str); printf("%s\n",
str);
+) char s[100]; scanf("%s",s); printf("%s\n",s);
+) long long int n; scanf("%lld", &n); printf("%lld", n);
+) scanf("%[^\\n]",str);
+) fflush(stdin); gets(person[i].name);
//=====
```