

Test Case Document

Playwright automation suite — Login, Home launcher, Patient Registration, Patient Admission, the admission dashboard, and the end-to-end patient journey. 42 cases, all automated.

1. Document control

Document	Test Case Document — PMCH Healthcare ERP Test Automation
Version	1.0
Date	03 October 2026
Prepared by	QA Automation — EMSL Dev Team
Application under test	Popular Medical College and Hospital Limited — HIS ERP (Blazor / MudBlazor)
Automation framework	Playwright Test 1.63 · TypeScript · Page Object Model
Source of truth	tests/ in this repository. Every case below maps to one test() — the spec file and line are given in each row.
Results reflected	Regression run of 03 Oct 2026, 08:04 UTC (24 tests, 3 m 18 s): 23 passed, 1 failed, plus the admission dashboard suite added later the same day (7 tests, 32 s): all passed. The smoke and API suites were not part of that cycle and are marked NOT RUN .
Companion document	docs/BUG_REPORT.pdf — defects raised from this cycle, with screenshots and video.

2. Scope and environment

In scope	Authentication, module launcher, Patient Registration list and create-patient wizard, New Admission wizard (Patient / Contact Person / Advance Payment / Admission Detail), the admission dashboard — looking an admission up and printing its paperwork — host availability, and one end-to-end register-then-admit flow.
Out of scope	OPD, Pharmacy, Diagnostic, HR, Accounts and Billing modules; the ID-card print and the admission dashboard's list-level <i>Print List / Print Package List</i> buttons; what is <i>inside</i> a printed document, which is checked as a valid, non-empty PDF and no further; role-based permissions beyond the Administrator account; performance and security testing.

Environment	ERP web application over HTTPS on the hospital host (BASE_URL in .env; self-signed certificate, so ignoreHTTPSErrors is on). Live database — see the warning in section 5.
Browser	Chromium (Desktop Chrome profile) at 1920×1080, headed, one worker. Firefox and WebKit projects exist in playwright.config.ts but are commented out; mobile viewports are not enabled.
Test account	Administrator account read from ERP_USERNAME / ERP_PASSWORD. Credentials never appear in source control or in this document.
Session handling	tests/auth.setup.ts logs in once and saves the browser state to playwright/.auth/user.json. Signed-in suites reuse it; signed-out suites clear it with test.use({ storageState: { cookies: [], origins: [] } }).
Timeouts	90 s per test, 15 s per assertion, 30 s per action, 45 s per navigation — raised from the Playwright defaults because the host is slow. Three cases raise their own further (noted in their rows).

3. Legend

Priority	P1 — blocks the release if it fails (login, core patient flow). P2 — important, has a workaround. P3 — cosmetic or defensive.
Status	PASS passed in the 03 Oct 2026 run · FAIL failed, defect raised · NOT RUN not part of that cycle
Writes to live data	Rows marked WRITES leave a real record in the hospital database. Every other case is read-only.

4. Coverage summary

SUITE	SPEC FILE	CASES	PASS	FAIL	NOT RUN	SESSION
API — Health	tests/api/health.spec.ts	2	—	—	2	None
Setup — Authentication	tests/auth.setup.ts	1	1	—	—	Creates it
Smoke — Login	tests/smoke/login.smoke.spec.ts	5	—	—	5	Signed out
Smoke — Admission	tests/smoke/admission.smoke.spec.ts	4	—	—	4	Signed in
Regression — Login	tests/regression/login.regression.spec.ts	7	7	—	—	Signed out
Regression — Home	tests/regression/home.regression.spec.ts	7	7	—	—	Signed in (007 signed out)
Regression — Registration	tests/regression/registration.regression.spec.ts	6	6	—	—	Signed in
Regression — Admission	tests/regression/admission.regression.spec.ts	2	1	1	—	Signed in

SUITE	SPEC FILE	CASES	PASS	FAIL	NOT RUN	SESSION
Regression — Patient journey	tests/regression/admission.regression.spec.ts	1	1	—	—	Signed out
Regression — Admission dashboard	tests/regression/admission-dashboard.regression.spec.ts	7	7	—	—	Signed in
Total		42	30	1	11	

5. Data safety

Two cases write to the live hospital database and nothing in the suite undoes them: TC_SMK_ADM_004 stops short of the submit but fills the wizard, and TC_FLOW_001 registers a patient *and* admits them, which holds a real bed and records real advance payments. Cancelling an admission is its own workflow under **Hospital > Admission Cancel**. Run TC_FLOW_001 deliberately, and expect a Masud Rana Test-<n> patient after each run. Every other case is read-only: the registration and admission cases deliberately stop before any Confirm button, and the admission dashboard cases only search and print — a printed document changes nothing in the record it is printed from.

6. API — Health

Spec: tests/api/health.spec.ts · Project api · no browser, no session.

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_API_001 health.spec.ts:6	Health endpoint reports the host is healthy	ERP host reachable at API_URL.	1. Send GET /health with the API request context. 2. Read the status code and the response body.	GET /health	- Status is 200. - Body, trimmed, is exactly Healthy.	P1	NOT RUN
TC_API_002 health.spec.ts:13	Login page is served by the identity provider	ERP host reachable at API_URL.	1. Send GET /Account/Login. 2. Read the status code and the HTML body.	GET /Account/Login	- Status is 200. - Body contains Input.Email, proving the sign-in form rendered.	P1	NOT RUN

7. Setup — Authentication

Spec: tests/auth.setup.ts · runs before every UI project; if it fails, every signed-in case is skipped.

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_SETUP_001 auth.setup.ts:10	Log in once and persist the session for the suite	.env holds valid ERP_USERNAME / ERP_PASSWORD.	1. Open /Account/Login. 2. Enter the administrator username and password; submit. 3. Wait for the module launcher to load. 4. Save the browser storage state to disk.	Administrator account from .env	- Launcher loads with the tenant name and user role. - playwright/.auth/user.json is written and reused by every signed-in project.	P1	PASS 3.5 s

8. Smoke — Login

Spec: `tests/smoke/login.smoke.spec.ts` · signed out — the suite clears the saved session so nothing is inherited.

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_SMK_LOGIN_001 <code>login.smoke.spec.ts:12</code>	Login page renders every field	No session.	1. Open the login page. 2. Wait for the form to load. 3. Inspect each control.	—	- Username placeholder is <i>Enter your username</i>. - Password placeholder is <i>Enter your password</i>. - Submit button reads <i>Log in</i>. - Remember-me and Forgot-password are visible.	P1	NOT RUN
TC_SMK_LOGIN_002 <code>login.smoke.spec.ts:23</code>	Valid credentials land on the module launcher	No session; administrator account is active.	1. Open the login page. 2. Enter the administrator username and password; submit. 3. Wait for the launcher.	Administrator account from <code>.env</code>	- Launcher is displayed. - Tenant reads <i>Popular Medical College and Hospital</i>. - Role reads <i>Administrator</i>.	P1	NOT RUN
TC_SMK_LOGIN_003 <code>login.smoke.spec.ts:35</code>	Invalid password is rejected	No session.	1. Open the login page. 2. Enter a known username with a deliberately wrong password; submit.	<code>admin / wrong-password-on-purpose</code>	- Invalid-login error is shown. - User stays on the login page; no session is created.	P1	NOT RUN
TC_SMK_LOGIN_004 <code>login.smoke.spec.ts:42</code>	Unknown user is rejected	No session.	1. Open the login page. 2. Enter a username that does not exist with any password; submit.	<code>no-such-user-12345 / whatever</code>	- Invalid-login error is shown. - The message does not reveal whether the account exists.	P1	NOT RUN
TC_SMK_LOGIN_005 <code>login.smoke.spec.ts:49</code>	Unauthenticated visit redirects to login	No session.	1. Navigate straight to the application root <code>/</code> .	—	- URL becomes <code>/Account/Login</code>. - The login form is rendered.	P1	NOT RUN

9. Smoke — New Admission wizard

Spec: tests/smoke/admission.smoke.spec.ts · signed in on the saved session · page /hospital/patientadmission. Nothing here presses *Create Patient Admission*; the end-to-end submit is TC_FLOW_001.

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_SMK_ADM_001 admission.smoke.spec.ts:18	Wizard opens on the Patient tab with its required fields ready	Signed in as Administrator.	1. Open the New Admission wizard. 2. Wait for the page to load. 3. Inspect the Patient tab and its fields.	—	• Patient tab is active. • UHID is editable. • Full Name, Surname, Patient Mobile are editable; DOB and Blood Group are visible.	P1	NOT RUN
TC_SMK_ADM_002 admission.smoke.spec.ts:34	The four marked tabs open in order	Signed in; wizard loaded.	1. Open Patient — check Full Name rendered. 2. Open Contact Person — check Guardian Name and Relation. 3. Open Advance Payment — check Select Card, BKash Payment, Payment (Cash). 4. Open Admission Detail — check Select Department, Admitted to, Bed/Cabin.	—	• Each tab goes active when opened. • The pane behind each tab renders its own fields — a tab that switches without its fields arriving still fails.	P1	NOT RUN
TC_SMK_ADM_003 admission.smoke.spec.ts:57	A patient loads by UHID into the Patient tab	Signed in; at least one patient in the Patient Registration grid for the selected date range.	1. Open Patient Registration and read the UHID from the first grid row. 2. Open the New Admission wizard. 3. Search that UHID.	UHID read live from the grid (10+ digits)	• Full Name, Patient Mobile and DOB are all filled from the registration record — none is empty.	P1	NOT RUN

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_SMK_ADM_004 admission.smoke.spec.ts:80	The tabs take entry in order, up to the submit WRITES	Signed in; wizard loaded. Test timeout raised to 240 s.	1. Fill the Contact Person tab; confirm Guardian Name holds what was typed. 2. Fill the Advance Payment tab (card, bKash, cash). 3. Read the page's own <i>Total</i>: panel. 4. Press Next into Admission Detail; choose Department and Admitted-to. 5. Wait for the bed list to populate, pick the first real bed. 6. Search and pick an assigned doctor.	Guardian Test— <n> · Card VISA 1000, bKash 2000, Cash 3000 · HDU / HDU · doctor search Dr	• Total panel shows 6000 — the app's own sum, which is the honest proof all three amounts registered. • Bed list loads more than the placeholder option and a bed is selected. • Assigned doctor contains the searched text. • <i>Create Patient Admission</i> is enabled — and deliberately not pressed.	P1	NOT RUN

10. Regression — Login

Spec: `tests/regression/login.regression.spec.ts` · signed out. The form relies on HTML5 required rather than a server-rendered validation summary, so the empty-field cases assert constraint validity plus "the form was never submitted" instead of hunting for an error banner.

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_LOGIN_001 <code>login.regression.spec.ts:16</code>	Login page is displayed with all required elements	No session.	1. Open the login page and wait for it to load. 2. Inspect each field, the submit button and the error area.	—	- Username editable, placeholder <i>Enter your username</i>. - Password editable, <code>type="password"</code>, placeholder <i>Enter your password</i>. - Submit enabled and reads <i>Log in</i>. - Remember-me and Forgot-password visible; no error banner.	P1	PASS 1.9 s
TC_LOGIN_002 <code>login.regression.spec.ts:79</code>	Valid credentials land on the home page	No session; administrator account active.	1. Open the login page. 2. Enter the administrator username and password; submit. 3. Wait for the launcher.	Administrator account from <code>.env</code>	- Launcher loads. - Tenant reads <i>Popular Medical College and Hospital</i>; role reads <i>Administrator</i>. - No error banner.	P1	PASS 2.6 s
TC_LOGIN_003 <code>login.regression.spec.ts:32</code>	Invalid username with a valid password is rejected	No session.	1. Open the login page. 2. Enter a non-existent username with the real password; submit.	<code>no_such_user_9912</code> + real password	Invalid-login error is shown; the user is not signed in.	P1	PASS 2.2 s
TC_LOGIN_004 <code>login.regression.spec.ts:41</code>	Valid username with an invalid password is rejected	No session.	1. Open the login page. 2. Enter the real username with a wrong password; submit.	Real username + <code>WrongPass!123</code>	Invalid-login error is shown; the user is not signed in.	P1	PASS 2.3 s
TC_LOGIN_005 <code>login.regression.spec.ts:50</code>	Empty username is blocked by field validation	No session.	1. Open the login page. 2. Leave Username blank, fill Password; submit.	Username (<i>blank</i>) + real password	- Username reports a required-field constraint violation. - The form is never submitted — the browser stays on the login page.	P2	PASS 2.6 s

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_LOGIN_006 login.regression.spec.ts:60	Empty password is blocked by field validation	No session.	1. Open the login page. 2. Fill Username, leave Password blank; submit.	Real username + password (<i>blank</i>)	- Password reports a required-field constraint violation. - The form is never submitted.	P2	PASS 2.1 s
TC_LOGIN_007 login.regression.spec.ts:70	Both fields empty are blocked by field validation	No session.	1. Open the login page. 2. Submit with both fields blank.	—	- Both fields report a required-field constraint violation. - The form is never submitted.	P2	PASS 2.5 s

11. Regression — Home / module launcher

Spec: `tests/regression/home.regression.spec.ts` · signed in, except `TC_HOME_007`. The launcher is a MudBlazor shell, so module tiles are plain text nodes rather than links — they are matched exactly, because a substring match also hits the hidden language dropdown.

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_HOME_001 <code>home.regression.spec.ts:19</code>	Home page is displayed with all required elements	Signed in as Administrator.	1. Open the home page and wait for it to load. 2. Inspect the header chrome.	—	- Tenant name visible and not empty. - User name, user role and language selector all visible.	P1	PASS 2.1 s
TC_HOME_002 <code>home.regression.spec.ts:30</code>	Core ERP modules are listed on the launcher	Signed in as Administrator.	1. Open the home page. 2. Look for each core module tile by exact name.	REGISTRATION, OPD, Pharmacy, Diagnostic, HR, ACCOUNT	All six tiles are visible; the failure message names the missing module.	P1	PASS 1.8 s
TC_HOME_003 <code>home.regression.spec.ts:39</code>	Tenant is the hospital the session belongs to	Signed in as Administrator.	1. Open the home page. 2. Read the tenant name in the header.	—	Tenant matches <i>Popular Medical College and Hospital</i> (case-insensitive).	P1	PASS 1.9 s
TC_HOME_004 <code>home.regression.spec.ts:46</code>	Signed-in user context is shown	Signed in as Administrator.	1. Open the home page. 2. Read the user role and user name.	—	- Role matches <i>Administrator</i>. - User name is not empty.	P2	PASS 2.0 s
TC_HOME_005 <code>home.regression.spec.ts:54</code>	A module tile that does not exist is not rendered	Signed in as Administrator.	1. Open the home page. 2. Look for a module name that cannot exist.	NO_SUCH_MODULE_9912	No such tile is rendered — negative control proving the tile matcher is not matching everything.	P3	PASS 2.0 s
TC_HOME_006 <code>home.regression.spec.ts:61</code>	Reloading keeps the user on the launcher	Signed in as Administrator.	1. Open the home page. 2. Reload (tolerant of the host's HTTP 429 cool-off — see BUG-003). 3. Wait for the launcher again.	—	- Launcher loads again; the session is not lost. - The REGISTRATION tile is still visible.	P2	PASS 2.2 s
TC_HOME_007 <code>home.regression.spec.ts:78</code>	An unauthenticated visitor is sent to the login page	Session deliberately cleared.	1. Navigate to the home page with no session.	—	- URL becomes <code>/Account/Login</code>. - The login form renders and the tenant header is hidden — no launcher content leaks.	P1	PASS 1.9 s

12. Regression — Patient Registration

Spec: `tests/regression/registration.registration.spec.ts` · signed in. Follows the module the way a user reaches it — REGISTRATION tile on the launcher, which loads that module's menu into the left drawer, then PATIENT REGISTRATION in the drawer. Nothing here submits the create-patient wizard, because confirming a registration would leave a real patient behind on every run.

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_REG_001 <code>registration.registration.spec.ts:23</code>	REGISTRATION tile loads the module menu into the sidebar	Signed in; on the launcher.	1. Open the home page. 2. Confirm the drawer carries no PATIENT REGISTRATION link yet. 3. Click the REGISTRATION tile.	—	- Before the click: the link genuinely does not exist (count 0). - After: the REGISTRATION group and the PATIENT REGISTRATION link appear, the link pointing at <code>/hospital/newregistration</code>.	P1	PASS 4.1 s
TC_REG_002 <code>registration.registration.spec.ts:44</code>	PATIENT REGISTRATION opens the patient list	Signed in; on the launcher.	1. Click the REGISTRATION tile. 2. Click PATIENT REGISTRATION in the drawer.	—	- The patient list page loads. - URL ends with <code>/hospital/newregistration</code>.	P1	PASS 4.4 s
TC_REG_003 <code>registration.registration.spec.ts:57</code>	Patient list is displayed with all required elements	Signed in; patient list open.	1. Open the patient list. 2. Inspect the filter bar and toolbar.	—	- Show From and Show To date filters visible; Show button enabled. - Add New visible and pointing at <code>/patients/new</code>. - Search box editable.	P1	PASS 2.4 s
TC_REG_004 <code>registration.registration.spec.ts:71</code>	The grid lists patients under the expected columns	Signed in. At least one patient registered within the grid's default date range (today) — see BUG-001.	1. Open the patient list. 2. Read the header row. 3. Wait for the first data row.	Live hospital data	- Exactly six headers, in order: NAME, UHID, REG DATE, PHONE NUMBER, DOB, ACTION. - At least one data row is visible.	P1	PASS 33.8 s — slow
TC_REG_008 <code>registration.registration.spec.ts:87</code>	Add New opens the create-patient form	Signed in; patient list open.	1. Open the patient list. 2. Click Add New.	—	- The create-patient wizard loads. - URL ends with <code>/hospital/patients/new</code>.	P1	PASS 3.8 s

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_REG_009 registration.regression.spec.ts:100	The create-patient form opens on the Patient tab	Signed in; create-patient wizard open.	1. Open the create-patient wizard directly. 2. Read the aria-selected state of each tab.	—	- Patient tab is selected. - Contact Person and Corporate Client are not selected.	P2	PASS 4.1 s

ID gap. TC_REG_005, TC_REG_006 and TC_REG_007 — the grid search and row-action cases — were removed from the spec and are not currently automated. They are listed as a coverage gap in section 15; the surviving IDs were left unrenumbered so that earlier runs and defect reports still line up.

13. Regression — New Admission

Spec: `tests/regression/admission.regression.spec.ts` · signed in. The wizard admits a patient who is already registered, so the UHID is read out of the registration grid rather than hard-coded — the grid holds live hospital data and no patient in it is guaranteed to still be there next week.

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_ADM_001 <code>admission.regression.spec.ts:36</code>	New Admission opens from the Hospital module menu	Signed in; on the launcher.	1. Open the home page. 2. Open the Hospital module and find the New Admission link. 3. Click it.	Route <code>/hospital/patientadmission</code>	- The admission wizard loads. - UHID is editable and the Patient tab is active.	P1	PASS 5.0 s
TC_ADM_002 <code>admission.regression.spec.ts:51</code>	Searching a UHID loads that patient into the wizard	Signed in. At least one patient registered within the grid's default date range (today).	1. Open Patient Registration. 2. Read the UHID and the patient name from the first grid row. 3. Open the New Admission wizard. 4. Search that UHID.	UHID and name read live from the grid	- Full Name in the wizard equals the name in the grid. - Patient Mobile and DOB are filled from the registration record.	P1	FAIL 66.7 s, 2 attempts — BUG-001

14. Regression — Patient journey (end to end)

Spec: `tests/regression/admission.regression.spec.ts` · signed out, because logging in is the first thing it checks. One patient, followed the way the hospital actually takes one on. It is one test and not three because the admission wizard needs a patient who is registered and not already on a ward, and the only way to be sure of that is to have just registered them. Retries are disabled: a retry would register a second patient rather than tell us anything new.

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_FLOW_001 admission.regression.spec.ts:99	Log in, register a patient, then admit them WRITES	No session. A free bed in the target ward. Test timeout raised to 600 s; retries disabled.	1. Log in with the administrator account and reach the launcher. 2. Register the patient: open the create-patient wizard, fill the Patient tab, confirm the DOB picker wrote 4/10/1998, press Confirm Registration and capture the new Patient ID. 3. Admit them: open the New Admission wizard and search the UHID just issued. 4. Fill Contact Person, then Advance Payment; read the page's own <i>Total</i> panel. 5. Press Next into Admission Detail; fill department, ward, bed and assigned doctor. 6. Press Create Patient Admission and capture the confirmation text. 7. Verify on the ward: open Hospital > Dashboard (the admission dashboard) and search the patient name as registered; read the admission number off the row. 8. Find it by number and print: search that admission number, then press every print button in the row's Action cell, one after another, and read back the PDF each one produced.	Patient Masud Rana Test-<n>, Male, DOB 10 Apr 1998, A+, mobile 01876765454, NID 98876756757, Tangail / Bhuapur · Card VISA 1000, bKash 2000, Cash 3000 · HDU / HDU	• Login succeeds and the launcher loads. • Registration returns a Patient ID of 10 or more digits. • The wizard pulls up that exact patient — name and mobile match what was registered. • Total panel shows 6000. • The confirmation carries no <i>error / failed / invalid</i> wording. • An admission row exists on the admission dashboard: admission number of 10+ digits, carrying the patient's mobile and a bed in the ward admitted to. • Searching that admission number returns exactly one row, and it is this patient. • At least four print buttons, each producing a PDF (%PDF- header, over 1 KB).	P1	PASS 29.8 s

Deliberately not asserted: that the advance payments reach the admission. On the runs so far they did not — Hospital > Advance Dashboard carried no row for the admission this flow created, even though the wizard summed the three amounts to 6000 before the submit. The case asserts only what it can stand behind, and the gap is raised separately as **BUG-002**.

15. Regression — Admission dashboard

Spec: `tests/regression/admission-dashboard.regression.spec.ts` · signed in. Route `/hospital/patientlist-dashboard` — Hospital > **Dashboard**, the list of everyone currently admitted. This is where an admission is looked up after the fact, so the cases are the two things the page is used for: finding one admission in it, and printing that admission's paperwork. The grid holds live hospital data, so no case hard-codes an admission — each reads one out of the first row and searches for what it just read. Read-only throughout.

One trap, recorded here because it is not a defect: the NAME column prints the patient's title in front of the name (Mr Jalal Miah) but the search box matches the name as it was registered, without it. Searching a name copied straight out of the grid returns nothing; Jalal Miah returns the row. TC_ADMD_004 strips the title before searching.

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_ADMD_001 <code>admission-dashboard.regression.spec.ts:40</code>	Dashboard opens from the Hospital module menu	Signed in; on the launcher.	1. Open the home page. 2. Open the Hospital module and find the Dashboard link in the drawer. 3. Click it.	Route <code>/hospital/patientlist-dashboard</code> — the link is reached by href, because it is labelled just "Dashboard"	- The admission dashboard loads with rows in the grid. - Search is editable; <i>Print List</i> and <i>Print Package List</i> are on screen.	P1	PASS 5.3 s
TC_ADMD_002 <code>admission-dashboard.regression.spec.ts:59</code>	The grid lists admissions under the expected columns	Signed in. At least one patient admitted.	1. Open the admission dashboard. 2. Read the grid's header row. 3. Read the ADM.NO and CABINNO cell of every row on the page.	Eleven columns: ADM.NO, ADM.DATE, ADM.TIME, NAME, CABINNO, ASSIGNED DOCTOR, PHONE, ADDRESS, CABINTYPE, PACKAGE, ACTION	- Exactly those eleven headers, in that order. - No row is missing its admission number or its bed — the two every admitted patient has.	P2	PASS 3.7 s
TC_ADMD_003 <code>admission-dashboard.regression.spec.ts:79</code>	Searching an admission number finds that admission	Signed in. At least one patient admitted.	1. Open the admission dashboard and read the first row. 2. Type its admission number into Search.	Admission number read live from the grid	- Exactly one row comes back — an admission number is unique. - Its admission number and patient name are the ones read in step 1.	P1	PASS 3.3 s

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_ADMD_004 admission-dashboard.regression.spec.ts:93	Searching a patient name finds their admission	Signed in. At least one patient admitted.	1. Open the admission dashboard and read the first row. 2. Drop the title from the name (Mr Jalal Miah → Jalal Miah). 3. Type the remainder into Search.	Patient name read live from the grid	• The admission read in step 1 is among the rows returned. • Its name matches. <i>Not</i> asserted as a single row: a ward holding two patients of one name is ordinary.	P1	PASS 3.6 s
TC_ADMD_005 admission-dashboard.regression.spec.ts:111	Searching a phone number finds that admission	Signed in. Skipped if the admission at the top of the grid carries no phone number.	1. Open the admission dashboard and read the first row. 2. Type its phone number into Search.	Phone number read live from the grid	• The admission read in step 1 is among the rows returned. • Its PHONE cell is the number searched. Not a single-row assertion — a family shares a number.	P2	PASS 3.4 s
TC_ADMD_006 admission-dashboard.regression.spec.ts:125	Searching a cabin number finds the patient in that bed	Signed in. At least one patient admitted.	1. Open the admission dashboard and read the first row. 2. Type its cabin number into Search.	Cabin number read live from the grid, e.g. HDU-48	• The admission read in step 1 is among the rows returned. • Every row returned is for that bed — a bed holds one patient at a time.	P2	PASS 3.8 s

CASE ID	TITLE	PRE-CONDITIONS	TEST STEPS	TEST DATA	EXPECTED RESULT	PRI	STATUS
TC_ADMD_007 admission-dashboard.regression.spec.ts:143	Every Action print button renders a PDF	Signed in. At least one patient admitted. Test timeout raised to 240 s — four documents, the largest over a megabyte.	1. Open the admission dashboard and search the first row's admission number. 2. Press the first print button in the Action cell; wait for the tab it opens. 3. Read the document back out of the browser and close the tab. 4. Repeat for every remaining print button, one at a time, left to right.	One admission, read live from the grid. Measured on 03 Oct 2026: 1 388 783 / 643 337 / 37 660 / 643 270 bytes	• At least four print buttons, each opening its own tab. • Each tab carries a real PDF — %PDF-header, over 1 KB. • Not all four are the same file: these are different documents, and four identical ones would mean the buttons share a handler.	P1	PASS 9.4 s

How a printed document is checked. The app does not navigate to a document or download one — it builds the file in the browser and opens a tab on a `blob:` URL, which renders in the browser's own PDF viewer and has no readable page behind it. The blob belongs to the dashboard, which created it, so the test fetches that URL from the dashboard and gets the actual bytes. That is what makes "the button printed something" checkable rather than just "a tab opened" — a page that failed to render would open a tab too.

Not clicked: some rows carry a cloud-arrow-down button among the print buttons. It produced nothing observable on any row tried — no tab, no download, nothing on screen — so the print run matches on the printer icon and steps over it rather than hanging on a document that never comes. Worth a question to the module owners; it is not raised as a defect because what it is meant to do is unknown.

16. Known coverage gaps

GAP	WHY IT IS OPEN	SUGGESTED NEXT STEP
Grid search and row actions on the patient list (the old TC_REG_005–007)	Removed from the spec; the cases keyed off live data that was not stable enough to assert on.	Re-add against a patient the test registers itself, the way TC_FLOW_001 does.
Advance payment reaching the admission	Observed failing; see BUG-002. Asserting it today would make TC_FLOW_001 fail for a defect that is already tracked.	Add the assertion as soon as BUG-002 is fixed, so it guards the fix.
What is inside a printed admission document	TC_ADMD_007 checks that each Action button produces a real, non-empty PDF, not what the PDF says. Reading the text back would mean parsing it, and nothing in the suite does that today.	Add a PDF text extractor and assert the patient's name and admission number appear in each document.
The dashboard's list-level Print List / Print Package List, and the per-row cloud-arrow-down button	The two list buttons print the whole filtered page and are not tied to one admission. The cloud button produced nothing observable, and what it is meant to do is unknown.	Ask the module owners what the cloud button does, then cover all three.
Create-patient field validation (required fields, mobile/NID format, duplicate NID)	Every negative case would need the Confirm button, which writes to live data.	Needs a test tenant or a reset endpoint before it can be automated safely.
Firefox, WebKit and mobile viewports	Projects are present in the config but commented out — the host drops sessions under concurrent browsers.	Enable once the host tolerates more than one worker, or run them in separate scheduled passes.
Roles other than Administrator	Only one account is configured. Doctor, receptionist and accountant are declared as types but never exercised.	Add per-role accounts to .env and a storage state per role.
OPD, Pharmacy, Diagnostic, HR, Accounts	Out of scope for this cycle — only their tiles are checked on the launcher.	Plan per-module suites in the next cycle.

Test Case Document v1.0 · Popular Medical College & Hospital Ltd — Healthcare ERP Test Automation · 03 October 2026 · generated from docs/src/test-cases.html by `npm run docs`.