GENERAL INFORMATION:

SIMPLWINDOWS NAME:	Qsys Generic Boolean Component Control
CATEGORY:	Qsys
VERSION:	5.0.0
SUMMARY:	Controls and monitors a single boolean (on/off) control of any Q-SYS component (e.g. a mute, bypass or invert button).
GENERAL NOTES:	Inputs act on the rising edge only. BooleanState is high when the control's value is non-zero (greater than 0.1 in magnitude). ToggleBooleanState relies on BooleanState, so toggling will not work correctly until feedback has been received from the Q-SYS Core. On a momentary button, SetBooleanStateOn leaves the button on until SetBooleanStateOff is pulsed.
CRESTRON HARDWARE REQUIRED:	3 Series Processor or 4 Series Processor
SETUP OF CRESTRON HARDWARE:	Requires a Qsys Core module in the same program with a matching CoreID.
VENDOR FIRMWARE:	N/A
VENDOR SETUP:	Works with a control on any Q-SYS component; the component's Script Access must be External or All.
GENERATION:	Generated by Claude Code from SIMPL+ and SIMPL# source files

CONTROL:

[SetBooleanStateOn]	D	Pulse to set the control's value to On (1).
[SetBooleanStateOff]	D	Pulse to set the control's value to Off (0).
[ToggleBooleanState]	D	Pulse to toggle the control. The new state is the opposite of the current BooleanState feedback.

FEEDBACK:

[BooleanState]	D	High when the control is On in Q-SYS, low when Off.

PARAMETERS:

CoreID	S	Used to address this module to the Qsys Core module with the same CoreID. Default: 1
ComponentName	S	Code Name of the Q-SYS component that contains the control.
ComponentControlName	S	Name of the control within the component to be controlled.

TESTING:

SAMPLE PROGRAM:	3-Series: 3 Series Test.smw 4-Series: 4 Series Test.smw
REVISION HISTORY:	