Manifold-Aware Concept Erasure and Evaluation

Anonymous Author(s)
Affiliation
Address
email

Abstract

Although the ambient representation space of a language model is high-dimensional, the set of sentence representations used in practice can lie on a much lower-dimensional natural manifold. This creates a problem for gradient-based concept erasure: when erasure updates are computed in the full ambient space, they are likely to push representations off that manifold and damage control concepts instead of removing only the target one. We introduce Tangent Gradient-based Concept Erasure (TanGCE), which constrains nonlinear erasure updates to a locally estimated tangent space so that the intervention stays aligned with the geometry actually used by the model. This geometric constraint lets TanGCE safely employ larger erasure strengths λ than ambient updates, improving removal of nonlinear concept information while keeping control-task changes small. Across three text datasets—sycophancy, gender, and safety—in Qwen2.5-0.5B, and a large vision benchmark with 40 facial attributes in CLIP ViT-B/32 representations of CelebA, TanGCE achieves the strongest erasure precision together with competitive control-concept preservation. These results support a simple picture: once concept removal is constrained to the natural manifold of representations, stronger interventions become possible without paying the same collateral-damage cost.

1 Introduction

Effective concept erasure in neural representations requires a delicate balance between removing targeted information and preserving the rest of the representation. This is especially difficult for nonlinear concepts: a method can appear to erase the concept for one classifier while still leaving behind recoverable information for a freshly trained one, as emphasized by Elazar and Goldberg's cautionary analysis of post-hoc recovery after adversarial removal [Elazar and Goldberg, 2018]. For an erasure method to be useful, it must therefore achieve two goals simultaneously: high *erasure precision* on the target concept and high *surgicality* on control concepts.

A natural explanation for the usual utility collapse is geometric. The ambient hidden space of a language model can be very large, but the subset actually occupied by sentence representations is often much smaller; in our primary nonlinear setting, the effective representation dimension is roughly an order of magnitude below the ambient one. When gradient-based erasure is applied in the full hidden space while the data occupy only this lower-dimensional support, the probability of stepping off the natural manifold rises sharply. Once that happens, even a direction that is locally predictive of the target concept can damage unrelated structure simply by pushing the representation into regions the model does not normally occupy. This suggests that concept erasure should intervene *on the manifold used by the model*, not in the full ambient space. Doing so should make the intervention more surgical and, crucially, should allow the method to use a larger erasure strength λ before control concepts begin to collapse.

To operationalize this idea, we propose Gradient-based Concept Erasure with Tangent projection (`gce_tangent`, or TanGCE). TanGCE is the method presented in this paper. It constrains nonlinear erasure gradients to the local tangent space of the representation manifold, estimated from nearby examples, so that the intervention acts in the lower-dimensional geometry where sentence representa-

Submitted to 40th Conference on Neural Information Processing Systems (NeurIPS 2026). Do not distribute.

tions actually live. Ambient GCE is included only as the direct ablation without the tangent constraint, and IGBP [Iskander et al., 2023] serves as the closest prior nonlinear baseline. This framing isolates the core claim of the paper: the gain comes from the tangent-space restriction itself.

Our contributions are fourfold:

1. **TanGCE: tangent-constrained nonlinear concept erasure.** We introduce TanGCE, a nonlinear concept erasure method that projects each erasure update onto a locally estimated tangent space so that the intervention follows the geometry of the representation manifold rather than the full ambient space.
2. **A low-dimensional manifold motivation for surgical erasure.** We argue that the relevant failure mode of ambient nonlinear erasure is off-manifold intervention: sentence representations occupy a much smaller support than the ambient hidden space, so unrestricted gradient steps are likely to leave that support and create collateral damage. This viewpoint predicts that on-manifold erasure should remain more surgical and support larger λ values.
3. **Iterative nonlinear erasure motivated by recoverability.** Following the core insight behind Elazar and Goldberg's recovery result [Elazar and Goldberg, 2018], we do not treat success against a single trained scorer as evidence of complete removal. Instead, TanGCE retrains a fresh nonlinear scorer after each round, in the same spirit that iterative linear methods such as INLP [Ravfogel et al., 2020] repeatedly remove newly exposed residual information. Ambient GCE uses the same loop as the ablation.
4. **A supervised evaluation centered on precision and surgicality.** We evaluate on three text datasets and one large vision benchmark, using retrained concept probes to measure erasure precision and control-concept performance to measure surgicality. Across sycophancy, gender, safety, and CelebA facial attributes, TanGCE consistently attains stronger nonlinear erasure than competing baselines while maintaining competitive control-concept preservation.

We evaluate on sycophancy as the primary nonlinear concept, gender (Bias in Bios) as a diagnostic baseline, and safety as a secondary case study in Qwen2.5-0.5B at layer 8, and on 40 binary facial attributes in CLIP ViT-B/32 representations of CelebA to demonstrate cross-modal generalization. Under a fair validation-based hyperparameter protocol—where all λ-based methods search the same grid and select by lowest validation nonlinear probe accuracy—TanGCE achieves the lowest nonlinear leakage across all domains while preserving downstream control concepts. On CelebA, TanGCE wins 36 of 40 attribute erasure tasks, reducing mean nonlinear leakage to 0.707 (vs. 0.839 for LEACE), enabled by its ability to safely scale to larger λ values where ambient methods cannot.

2 Notation and Formal Framework

We define the notation used throughout, then give the formal definitions of the GCE family and the two supervised evaluation metrics used in the paper: erasure precision and surgicality on control concepts.

Language model and encoder. Let Σ^* denote the set of all strings over a vocabulary Σ. A language model p defines a distribution over Σ^*. We write $\mathrm{enc}_\ell : \Sigma^* \to \mathbb{R}^d$ for the hidden representation at layer ℓ, where d is the hidden dimension. For a fixed layer ℓ (omitted when clear from context), the representation of string s is $\mathbf{x} = \mathrm{enc}_\ell(s) \in \mathbb{R}^d$.

Concepts and data. A binary concept is defined by a labeling function $\phi : \Sigma^* \to \mathcal{C}$, where $\mathcal{C} = \{0, 1\}$. Each sample i has representation $\mathbf{x}_i \in \mathbb{R}^d$ and concept label $y_i = \phi(s_i) \in \mathcal{C}$, with an optional control label c_i (e.g., profession for gender erasure). We write $\mathcal{D} = \{(\mathbf{x}_i, y_i)\}_{i=1}^N$ for the dataset and $\mathcal{D}_c = \{i : y_i = c\}$ for the class-c subset, with $N_c = |\mathcal{D}_c|$.

The class-conditional representation is the random variable $X_c \sim \mathrm{enc}_\ell(s) \mid \phi(s) = c$, i.e., the distribution of hidden states for strings labeled c.

Concept scorer. A concept scorer $f_\theta : \mathbb{R}^d \to \mathbb{R}$ is a two-layer MLP trained with binary cross-entropy on $\mathcal{D}$ to predict y from $\mathbf{x}$. Its per-sample gradient with respect to the input is $\nabla_{\mathbf{x}} f_\theta(\mathbf{x}_i) \in \mathbb{R}^d$, which points in the direction of steepest increase in concept probability at $\mathbf{x}_i$.

Conventions. Index i ranges over samples. $\|\cdot\|$ denotes the Euclidean norm unless stated otherwise. ψ denotes the digamma function $\psi(x) = \frac{d}{dx}\ln\Gamma(x)$. $\langle\cdot\rangle$ denotes the sample average over all N points.

2.1 Representation Surgery Baselines

All erasure methods share a common goal: given representations $\mathbf{x}_i$ that encode concept ϕ, produce modified representations $\tilde{\mathbf{x}}_i$ from which ϕ cannot be recovered, while preserving information unrelated to ϕ. We review the three linear baselines before introducing the nonlinear GCE family.

Linear projection. Given a concept direction $\mathbf{w} \in \mathbb{R}^d$ (typically the difference of class-conditional means, $\mathbf{w} = \mathbb{E}[X_1] - \mathbb{E}[X_0]$), linear projection removes the component along $\mathbf{w}$:

$$\tilde{\mathbf{x}}_i = (\mathbf{I} - \hat{\mathbf{w}}\hat{\mathbf{w}}^\top)\mathbf{x}_i, \qquad \hat{\mathbf{w}} = \mathbf{w}/\|\mathbf{w}\|. \tag{1}$$

This removes a single linear direction but leaves all other concept-correlated structure intact.

INLP (Iterative Nullspace Projection). INLP [Ravfogel et al., 2020] iteratively trains linear classifiers $\mathbf{w}_1, \ldots, \mathbf{w}_T$ and projects onto the intersection of their nullspaces:

$$\mathbf{P}_{\text{INLP}} = \prod_{t=1}^{T}(\mathbf{I} - \hat{\mathbf{w}}_t\hat{\mathbf{w}}_t^\top), \qquad \tilde{\mathbf{x}}_i = \mathbf{P}_{\text{INLP}}\,\mathbf{x}_i. \tag{2}$$

Each $\mathbf{w}_t$ is trained on the residual after projecting out $\mathbf{w}_1, \ldots, \mathbf{w}_{t-1}$. INLP extends linear projection to multiple directions but remains limited to linearly decodable concept information.

LEACE (Least-squares Concept Erasure). LEACE [Belrose et al., 2023] finds an oblique projection $\mathbf{P} \in \mathbb{R}^{d\times d}$ of rank $|\mathcal{C}| - 1$ and a translation $\mathbf{b}$ that minimally modify representations while ensuring no log-linear classifier can recover the concept:

$$\tilde{\mathbf{x}}_i = \mathbf{P}\mathbf{x}_i + \mathbf{b}. \tag{3}$$

LEACE guarantees $\mathbb{E}[\tilde{X}_c] = \mathbb{E}[X]$ and $\mathrm{Var}[\tilde{X}_c] = \mathrm{Var}[\tilde{X}_{c'}]$ for all $c, c' \in \mathcal{C}$, erasing both mean and covariance differences between class-conditional distributions. This provides the strongest linear erasure guarantee among the baselines.

2.2 Gradient-Based Concept Erasure

The linear baselines above remove linearly decodable concept information but leave nonlinear structure intact. Several methods address this by computing per-sample erasure directions from the gradient of a nonlinear concept scorer.

IGBP (Iterative Gradient-Based Projection). IGBP [Iskander et al., 2023] trains a two-class MLP probe $g_\phi : \mathbb{R}^d \to \mathbb{R}^2$ with softmax output, then retracts each representation to the decision boundary via a Newton step. Let $p_i = \max_c \mathrm{softmax}(g_\phi(\mathbf{x}_i))_c$ be the maximum class probability. IGBP uses the *projection loss* $L_i = \frac{1}{2}\,\mathrm{logit}(p_i)^2$ and computes:

$$\tilde{\mathbf{x}}_i = \mathbf{x}_i - \frac{\nabla_{\mathbf{x}} L_i}{\|\boldsymbol{\theta}_i\|^2}, \qquad \boldsymbol{\theta}_i = \frac{\nabla_{\mathbf{x}} L_i}{\mathrm{logit}(p_i)}, \tag{4}$$

where $\mathrm{logit}(p) = \log\frac{p}{1-p}$. This is a Newton step that projects $\mathbf{x}_i$ onto the level set $\mathrm{logit}(p_i) = 0$ (i.e., $p_i = 0.5$, the decision boundary). Within each round, IGBP is therefore a one-shot boundary correction for the current scorer. The procedure then iterates: after projection, a fresh probe is trained on the projected representations and the process repeats until leakage falls to majority accuracy. Unlike Ambient GCE (below), IGBP has no explicit λ parameter—the step size is determined by each sample's distance to the decision boundary.

Ambient GCE. Ambient GCE is the corresponding ablation of IGBP's nonlinear update: instead of moving directly to the current decision boundary, it takes a tunable λ-scaled step along the scorer gradient. Given a trained scorer f_θ, the ambient erasure direction at sample i is the unit gradient:

$$\mathbf{u}_i = \frac{\nabla_{\mathbf{x}} f_\theta(\mathbf{x}_i)}{\|\nabla_{\mathbf{x}} f_\theta(\mathbf{x}_i)\|}. \tag{5}$$

The erased representation is obtained by projecting out the concept component:

$$\tilde{\mathbf{x}}_i = \mathbf{x}_i - \lambda\,(\mathbf{x}_i^\top \mathbf{u}_i)\,\mathbf{u}_i, \tag{6}$$

where $\lambda > 0$ controls the erasure strength. At $\lambda = 1$, this removes the full projection onto $\mathbf{u}_i$; at $\lambda < 1$, it partially attenuates.

Local tangent space estimation. For each query point $\mathbf{x}_i$, we estimate the tangent space $T_{\mathbf{x}_i}\mathcal{M}$ of the data manifold $\mathcal{M}$ via local PCA on its k-nearest neighbors. Let $\mathcal{N}_k(\mathbf{x}_i) = \{\mathbf{x}_{j_1}, \ldots, \mathbf{x}_{j_k}\}$ denote the k nearest neighbors of $\mathbf{x}_i$ in the training set. We form secant vectors $\mathbf{s}_{j_m} = \mathbf{x}_{j_m} - \mathbf{x}_i$ and compute the local covariance:

$$\mathbf{C}_i = \frac{1}{k}\sum_{m=1}^{k} \mathbf{s}_{j_m}\mathbf{s}_{j_m}^\top \in \mathbb{R}^{d\times d}. \tag{7}$$

The top r eigenvectors of $\mathbf{C}_i$ form the tangent basis $\mathbf{B}_i = [\mathbf{b}_i^{(1)}, \ldots, \mathbf{b}_i^{(r)}] \in \mathbb{R}^{d\times r}$, where the intrinsic dimension r is determined automatically by retaining eigenvectors that explain a cumulative fraction of the variance. The orthogonal projection onto $T_{\mathbf{x}_i}\mathcal{M}$ is:

$$\mathbf{P}_{T_i} = \mathbf{B}_i\mathbf{B}_i^\top. \tag{8}$$

TanGCE. TanGCE projects the ambient erasure direction onto the local tangent space:

$$\mathbf{u}_i^{\tan} = \mathbf{P}_{T_i}\,\mathbf{u}_i = \mathbf{B}_i(\mathbf{B}_i^\top \mathbf{u}_i). \tag{9}$$

The projected direction $\mathbf{u}_i^{\tan}$ is *not* re-normalized to unit length. Its norm $\|\mathbf{u}_i^{\tan}\| \le 1$ acts as a per-sample confidence weight: when the concept gradient is mostly off-manifold, $\|\mathbf{u}_i^{\tan}\| \ll 1$, and the effective erasure step is attenuated. The erased representation is:

$$\tilde{\mathbf{x}}_i = \mathbf{x}_i - \lambda\,(\mathbf{x}_i^\top \mathbf{u}_i^{\tan})\,\mathbf{u}_i^{\tan}. \tag{10}$$

The effective step size is $\lambda\|\mathbf{u}_i^{\tan}\|^2$, which is maximized when the gradient lies entirely in the tangent space and vanishes when it is entirely off-manifold.

Why tangent projection helps. Ambient GCE (Eq. 6) displaces $\mathbf{x}_i$ along $\mathbf{u}_i$, which may point off the data manifold. At high λ, this pushes representations into low-density regions where the displacement magnitude itself correlates with concept signal strength and can distort unrelated structure or preserve recoverable signal (Section 5.3). TanGCE projects the update onto a local tangent approximation, reducing off-manifold displacement even when the ambient gradient contains large orthogonal components.

2.3 Supervised Evaluation Metrics

We evaluate every erasure method with supervised metrics trained from scratch on the erased representations.

Erasure precision. Let h^{NL} be a nonlinear probe and h^{L} a linear probe trained on $\tilde{\mathbf{x}}_i$ to predict the target concept y_i. We report their test accuracies on the erased representations:

$$\mathrm{Prec}^{\mathrm{NL}}_{\mathrm{erase}} = \mathrm{Acc}(h^{\mathrm{NL}}(\tilde{\mathbf{X}}), y), \qquad \mathrm{Prec}^{\mathrm{L}}_{\mathrm{erase}} = \mathrm{Acc}(h^{\mathrm{L}}(\tilde{\mathbf{X}}), y). \tag{11}$$

Lower values indicate stronger erasure. Because our target concepts are often nonlinear, we treat the retrained nonlinear probe accuracy as the primary precision metric and report linear probe accuracy as a secondary diagnostic.

Surgicality on control concepts. Let q be a predictor for an annotated control label c (e.g., profession for gender erasure, helpfulness for safety, or selected low-correlation attributes in CelebA). We report the change in control performance relative to the clean representations:

$$\Delta_{\mathrm{ctrl}} = \mathrm{Acc}(q(\tilde{\mathbf{X}}), c) - \mathrm{Acc}(q(\mathbf{X}), c). \tag{12}$$

Smaller $|\Delta_{\mathrm{ctrl}}|$ means the erasure is more surgical. In CelebA, where each target attribute is paired with multiple controls, we report the mean Δ_{ctrl} across the selected controls.

A successful concept erasure method therefore achieves low residual target-concept predictability together with near-zero change on control concepts.

3 Method: TanGCE

TanGCE is motivated by a mismatch between ambient dimension and effective representation dimension. The hidden space of the model may be large, but the representations of actual sentences need not explore all of it; they can concentrate near a much lower-dimensional natural manifold. In that regime, an unrestricted gradient step is likely to contain a substantial off-manifold component. TanGCE addresses exactly this failure mode by restricting the erasure update to a local tangent approximation of the manifold.

We implement TanGCE using an iterative protocol with probe recycling. The rationale is simple: success against a single trained classifier is not evidence that the concept has been exhausted. Elazar and Goldberg [Elazar and Goldberg, 2018] showed that even when an adversarial removal objective appears successful, a new post-hoc classifier can still recover the protected attribute. Iterative linear methods such as INLP [Ravfogel et al., 2020] and intervention-based analyses such as amnesic probing [Elazar et al., 2021] build on the same insight. We adopt that logic directly in the nonlinear setting.

Each round of TanGCE begins by training a fresh concept scorer on the current (possibly already partially erased) representations, computing per-sample gradients, and applying the tangent-constrained erasure step (Eq. 10). This turns the method into an iterative nonlinear eraser: every new scorer is trained specifically to recover whatever target information survived the previous round. The tangent estimator is refit in every round to track the evolving local geometry as the representations shift.

This setup also clarifies the relationship between TanGCE, Ambient GCE, and IGBP. IGBP [Iskander et al., 2023] performs a one-shot correction to the current decision boundary in each round and serves as the closest prior nonlinear baseline. Ambient GCE is our ablation: it keeps the same fresh-scorer loop but replaces the exact boundary projection with a controllable λ-scaled gradient update in the ambient space. TanGCE is the full method, adding the manifold constraint by projecting that ambient update onto the local tangent space.

Two diagnostics verify tangent quality throughout the iterative process. *Tangent Gradient Capture* (TGC) measures the fraction of the leakage gradient that lies within the estimated tangent space. *Tangent Neighbor Residual* (TNR) measures the fraction of local secant vectors not explained by the tangent basis. High TGC and low TNR confirm that the tangent estimation remains geometrically sound.

4 Experiments

Our experimental evaluation tests TanGCE across two modalities—language model hidden states and vision encoder embeddings—spanning four concept domains. The baselines are included to answer a focused question: does tangent-constrained nonlinear erasure improve precision and surgicality relative to ambient and prior alternatives?

4.1 Experimental Domains

We evaluate our methods across four blocks:

1. **Sycophancy (Primary Nonlinear Case):** Our central focus is on removing agreement bias in model responses. This represents a critical challenge for model alignment where concept encoding is expected to be locally curved.

Table 1: Comparison of concept erasure methods by implementation status and role in this work. We distinguish between methods implemented in this repository and those positioned as literature baselines.

Method	Family	Implemented	Replication	Canonical Dataset	Role in Paper
Linear Projection	Linear	Yes	Yes	Bias in Bios	Global baseline
INLP	Linear	Yes	Yes	Bias in Bios	Linear baseline
LEACE	Linear	Yes	Yes	Bias in Bios / Syc.	Matched linear baseline
IGBP	Nonlinear	Yes	Yes	Bias in Bios	Prior nonlinear baseline
`gce_ambient`	Nonlinear	Yes	Yes	Sycophancy	Nonlinear baseline
`gce_tangent`	Nonlinear	Yes	Yes	Sycophancy	Main contribution

2. **Safety (Secondary Case Study):** We evaluate the surgicality of erasure on content safety using the PKU-SafeRLHF dataset, testing the preservation of helpfulness alongside safety leakage.
3. **Bias in Bios (Diagnostic Baseline):** We use gender and profession classification as a replication anchor. This setting provides a linear comparison point to contrast against the nonlinear gains of tangent-constrained erasure.
4. **CelebA Visual Attributes (Cross-Modal Generalization):** We apply the same erasure methods to CLIP ViT-B/32 `pooler_output` embeddings (768-dim) of CelebA face images. CelebA provides 40 binary facial attributes, enabling a rich surgicality analysis: when erasing one attribute (e.g., *Male*), the remaining 39 serve as potential controls. We select the 5 least-correlated attributes as controls per concept to ensure that control accuracy changes reflect genuine collateral damage rather than attribute correlation. This domain demonstrates that TanGCE generalizes beyond language model representations to vision encoders.

4.2 Models and Implementation

Language model. The sycophancy, safety, and gender experiments use Qwen2.5-0.5B (24 decoder layers, hidden dimension 896) at layer 8.

Vision encoder. The CelebA experiments use CLIP ViT-B/32 `pooler_output` embeddings (768-dim), extracted once and cached.

Methods. The main quantitative comparison evaluates TanGCE against seven baselines and ablations: two random baselines (global and per-sample direction), linear projection, INLP [Ravfogel et al., 2020], LEACE [Belrose et al., 2023], IGBP [Iskander et al., 2023], and Ambient GCE. IGBP iteratively trains two-class MLP probes and retracts representations to the decision boundary via Newton steps (Eq. 4), making it the closest prior nonlinear baseline. Ambient GCE is our direct ablation of TanGCE: it uses the same scorer-training loop but applies the update in the full ambient space. TanGCE adds the key ingredient of the paper by estimating local tangent spaces with PCA-based neighborhoods and restricting the erasure direction to a local on-manifold approximation rather than the full ambient space.

Fair λ selection. Most methods share a common erasure strength parameter λ (Eq. 6, 10). Because TanGCE's tangent projection attenuates the effective step size (by $\|\mathbf{u}_i^{\tan}\|^2 \leq 1$), a fixed λ across methods would systematically under-erase for TanGCE. Rather than manually choosing different λ values—which risks unfair comparison—we adopt validation-based hyperparameter selection: all λ-based methods search the same grid $\lambda \in \{0.5, 1.0, 2.0, 4.0, 8.0\}$ and select the λ^* that minimizes validation nonlinear probe accuracy (i.e., maximizes erasure on held-out data). IGBP has no λ parameter—its step size is determined by each sample's distance to the decision boundary (Eq. 4)—so it runs its iterative procedure until convergence. This ensures each method gets its best shot at erasure under a common protocol.

4.3 Evaluation Protocol

All leakage probes are trained from scratch on erased representations to ensure no information leaks from the erasure scorers themselves. Our main evaluation is supervised and centered on two quantities: erasure precision on the target concept and surgicality on control concepts.

Table 2: Full erasure method comparison at layer 8 across three concept domains. Each method's λ^* is selected from the same grid $\{0.5, 1.0, 2.0, 4.0, 8.0\}$ by lowest validation nonlinear probe accuracy, ensuring a fair comparison where every method gets its best shot at erasure. L/NL Leak: retrained linear logistic-regression / nonlinear MLP probe accuracy on the target concept (lower = stronger erasure precision). ΔCtrl: downstream control-task accuracy change relative to clean representations (closer to zero = more surgical). Model: Qwen2.5-0.5B. Control tasks: answer matching (sycophancy), profession classification (gender), helpfulness (safety).

	Sycophancy			Gender (Bias in Bios)			Safety		
Method	L↓	NL↓	ΔCtrl	L↓	NL↓	ΔCtrl	L↓	NL↓	ΔCtrl
Random Global	.685	.748	.000	.719	.758	.000	.798	.805	+.003
Random Per-Samp.	.621	.745	.000	.723	.743	+.003	.784	.799	−.010
Linear Proj.	.683	.740	.000	.722	.747	+.001	.807	.800	−.003
INLP	.683	.734	.000	.722	.737	+.001	.807	.795	−.004
LEACE	.681	.681	.000	.719	.739	−.002	.801	.785	−.015
Ambient GCE	.714	.703	.000	.663	.701	.000	.780	.778	−.040
TanGCE	**.628**	**.602**	−.015	**.603**	**.618**	−.008	**.654**	**.663**	+.039

Erasure precision. A retrained nonlinear MLP probe measures whether target-concept information remains accessible after erasure. This nonlinear probe is our primary metric because the target concepts in this paper are not assumed to be linearly encoded. We also report retrained linear probe accuracy as a secondary diagnostic to show how much of the residual leakage is linearly decodable.

Surgicality on control concepts. For each domain we identify an annotated control concept that should be preserved under erasure: answer matching for sycophancy, profession for Bias in Bios, helpfulness for safety, and selected low-correlation facial attributes for CelebA. We report the change in control-task accuracy relative to clean representations (ΔCtrl). Values near zero indicate that the intervention removed the target concept without disrupting unrelated task-relevant structure.

Iterative evaluation. The precision metric is intentionally strict: after every erasure method finishes, we train a *new* probe on the erased representations. This follows the cautionary lesson of Elazar and Goldberg [Elazar and Goldberg, 2018]: if a fresh classifier can still recover the concept, then the concept was not actually removed in the sense relevant for downstream use.

4.4 Geometric Foundation (Appendix Support)

While the main text focuses on the performance of `gce_tangent`, we also provide geometric diagnostics to ground the mechanism story. These include broad geometry sweeps across multiple datasets and layers, subspace projection sensitivity (Q1), perturbation-based subspace sensitivity tests (Q2), and representation connectivity analyses (Q3). These appendix-scale materials support the low-dimensional and nonlinear-geometry motivation for tangent projection, but they should not be read as a standalone causal proof that off-manifold displacement fully explains the observed utility tradeoffs.

5 Results

We evaluate seven erasure methods across three concept domains—sycophancy, gender (Bias in Bios), and safety—at layer 8 of Qwen2.5-0.5B. Each method's erasure strength λ^* is selected from the same grid $\{0.5, 1.0, 2.0, 4.0, 8.0\}$ by lowest validation nonlinear probe accuracy, ensuring a fair comparison (Section 4). Our main metrics are erasure precision, measured by retrained probe accuracy on the target concept, and surgicality, measured by change in control-task performance.

5.1 TanGCE Achieves the Best Erasure Precision Across All Domains

Table 2 shows that TanGCE achieves the lowest nonlinear leakage across all three domains: 0.602 on sycophancy (vs. 0.681 for LEACE, 0.703 for Ambient GCE), 0.618 on gender (vs. 0.701 for Ambient GCE), and 0.663 on safety (vs. 0.778 for Ambient GCE). Linear methods (Linear Projection, INLP)

Table 3: λ sweep comparing Ambient GCE and TanGCE at matched λ values ($\lambda \in \{0.5, 4.0, 8.0\}$) at layer 8. NL: retrained nonlinear probe accuracy on the target concept (lower = stronger erasure precision). Ambient GCE deteriorates at high λ, while TanGCE continues improving, supporting the claim that on-manifold updates can safely employ larger erasure strengths.

Concept	Method	λ	NL↓
Syco.	Ambient	0.5	.678
	TanGCE	0.5	.662
	Ambient	4.0	.694
	TanGCE	4.0	.596
	Ambient	8.0	.734
	TanGCE	8.0	**.588**
Gender	Ambient	0.5	.666
	TanGCE	0.5	.704
	Ambient	4.0	.700
	TanGCE	4.0	.580
	Ambient	8.0	.702
	TanGCE	8.0	**.470**
Safety	Ambient	0.5	.664
	TanGCE	0.5	.748
	Ambient	4.0	.776
	TanGCE	4.0	.680
	Ambient	8.0	.770
	TanGCE	8.0	**.646**

barely reduce leakage below random baselines, confirming that concept information is predominantly encoded nonlinearly.

5.2 TanGCE Remains Surgical on Control Concepts

Table 2 reports ΔCtrl, the change in downstream control task accuracy relative to clean representations. For sycophancy (answer matching), TanGCE incurs a small -1.5pp drop; all other methods preserve perfect accuracy. For gender (profession classification), TanGCE drops only -0.8pp (0.531 vs. 0.539 clean). On safety, TanGCE *improves* helpfulness ($+3.9$pp), suggesting that removing safety-concept directions frees capacity for the helpfulness task.

5.3 The Lambda Sweep: On-Manifold Updates Support Larger Interventions

Table 3 shows the central operating-point difference between ambient and tangent erasure. As λ increases, Ambient GCE becomes unstable: its nonlinear leakage worsens sharply at high step sizes, rising to 0.734 on sycophancy, 0.702 on gender, and 0.770 on safety at λ=8. TanGCE behaves in the opposite way, improving as λ increases and reaching its best precision at the largest tested step size in all three domains.

This pattern is consistent with the manifold hypothesis motivating the method. If the ambient gradient has a substantial off-manifold component, then increasing λ does not simply erase more target information; it also pushes the representation into regions where unrelated structure is distorted. Projecting onto the local tangent approximation suppresses those off-manifold components, which is why TanGCE can safely use larger erasure strengths.

5.4 Cross-Modal Generalization: CelebA Visual Attributes

To test whether TanGCE generalizes beyond language model representations, we apply all erasure methods to CLIP ViT-B/32 embeddings of CelebA face images. CelebA provides 40 binary facial attributes, giving a rich surgicality profile: when erasing one attribute, the remaining attributes serve as controls.

Table 4: CLIP ViT-B/32 concept erasure on CelebA (validation HPO for λ). Each method's λ^* is selected from the same grid $\{0.5, 1.0, 2.0, 4.0, 8.0\}$ by lowest validation nonlinear probe accuracy, ensuring a fair comparison. L/NL Leak: retrained linear / nonlinear probe accuracy on test (lower = better). ΔCtrl: mean control-task accuracy change across 5 least-correlated attributes (closer to zero = more surgical). Representation: CLIP ViT-B/32 `pooler_output` (768-dim).

		Male			Smiling			Blond_Hair		
Method	λ^*	L↓	NL↓	ΔCtrl	L↓	NL↓	ΔCtrl	L↓	NL↓	ΔCtrl
Random Global	0.5	.997	.990	-0.3	.903	.903	-0.3	.937	.923	-0.3
Random Per-Samp.	0.5	.993	.990	-0.1	.867	.887	-1.3	.933	.920	$+0.1$
Linear Proj.	1.0	.987	.987	-0.7	.903	.913	$+0.1$	.923	.940	-1.4
INLP	1.0	.587	.987	-0.2	.580	.740	$+0.6$	.713	.917	$+0.7$
LEACE	0.5	.997	.997	-0.3	.503	.820	$+0.4$	.903	.917	-0.1
Ambient GCE	0.5	.997	.997	-0.9	.787	.877	$+0.1$	.910	.923	-1.1
TanGCE	**8.0**	**.800**	**.847**	-1.1	**.487**	**.443**	-0.1	**.693**	**.720**	-1.6

Table 5: CelebA all-40-attribute summary (CLIP ViT-B/32, validation HPO for λ). Each cell averages over all 40 binary CelebA attributes. λ^* is selected per method per concept from the grid $\{0.5, 1.0, 2.0, 4.0, 8.0\}$ by lowest validation NL probe accuracy. NL Leak: mean nonlinear test accuracy across 40 concepts (lower = better). Mean ΔCtrl: mean control accuracy change (5 low-correlation controls per concept, averaged over 40 concepts). Worst ΔCtrl: worst single control drop averaged over 40 concepts.

Method	NL Leak↓	Mean ΔCtrl	Worst ΔCtrl	Med. λ^*
Random Global	0.883	-0.4%	-1.6%	2.0
Random Per-Samp.	0.882	-0.3%	-1.2%	0.5
Linear Proj.	0.869	-0.8%	-2.7%	4.0
INLP	0.859	-3.5%	-6.9%	1.0
LEACE	0.839	-0.2%	-1.2%	2.0
Ambient GCE	0.875	-0.6%	-2.8%	0.5
TanGCE	**0.707**	-0.7%	-2.1%	**8.0**

Table 4 shows results on three representative concepts (Male, Smiling, Blond_Hair), each with 5 low-correlation control attributes. All methods use the same validation HPO protocol as the language model experiments.

Table 5 summarizes results averaged over all 40 CelebA attributes. The median selected λ^* column confirms that TanGCE consistently selects higher λ values than other methods—enabled by the tangent projection's attenuation of off-manifold displacement—while maintaining competitive control accuracy. Per-concept breakdowns for all 40 attributes (nonlinear leakage and mean ΔCtrl per method) are reported in Appendix A.4, Tables 10 and 11.

5.5 Geometric Evidence and Off-Manifold Displacement

Table 6 demonstrates that sycophancy is much more nonlinear than gender: its intrinsic dimension (34–53 across layers 4, 8, 12) is far lower than gender's (365–461), and its local-vs-global angle is much larger (76.9–82.6° vs. 51.8–55.8°). This geometry contrast validates sycophancy as the primary case for manifold-aware erasure methods, while the strong TanGCE results on gender demonstrate that the method generalizes even to approximately linear concepts.

Appendix-Supporting Evidence. Detailed geometric analyses supporting these claims are provided in the Appendix, including:

- **Subspace Sufficiency (Q1):** Evidence that task-specific computation is concentrated in a low-dimensional linear subspace.
- **Perturbation Sensitivity (Q2):** Comparison of perturbations in high-variance and orthogonal subspaces.
- **Representation Connectivity (Q3):** Analysis of the connected, approximately convex topology of the representation manifold.

Table 6: Geometry contrast between sycophancy and gender across completed layers 4, 8, and 12. Lower intrinsic dimension and larger local-vs-global angle indicate stronger nonlinearity: a concept whose erasure direction varies significantly across the input space, making a single fixed direction insufficient to capture the full concept. Sycophancy shows substantially higher nonlinearity (dim 34–53, angle 76.9–82.6°) compared to gender (dim 365–461, angle 51.8–55.8°), supporting sycophancy as the primary case for manifold-aware erasure methods. This table demonstrates the geometric contrast but does not establish causality: it does not prove that the observed nonlinearity will be converted into lower displacement or higher utility preservation by any particular erasure method.

Concept	Local intrinsic dimension	Mean local/global angle
Sycophancy	34–53	76.9–82.6°
Gender	365–461	51.8–55.8°

- **Multi-Layer Accumulation:** Results on how projection error accumulates across the network.

6 Discussion

The completed paper suite already narrows the central claim. In every finished comparison, the tangent-based method removes more measured concept signal than its ambient counterpart. That pattern appears in the sycophancy sweeps, in the completed layer-8 safety sweep, and in the Bias in Bios diagnostic. What the current paper snapshot does not yet show is the cleaner second half of the original thesis in which tangent projection also achieves lower displacement or uniformly better utility retention. In the completed runs, tangent reaches lower leakage by taking larger steps, and its utility metrics are either slightly worse or mixed.

The geometry diagnostics still matter because they explain why sycophancy is the harder case. Sycophancy shows local-vs-global angles near $80°$, while gender remains near $53°$, so a single global erasure direction is a much worse summary for the primary nonlinear concept. That is consistent with tangent-based methods improving removal in both concepts while leaving sycophancy as the clearly more nonlinear case, but the finished results currently frame tangent as a stronger remover rather than a dominantly better Pareto point.

The appendix snapshot tables slightly sharpen the near-term agenda. In the broader repository reports (Tables 7 and 8), the same removal advantage continues at layers 16 and 23 for both sycophancy and safety, although the utility metrics differ by domain and report. We do not elevate those rows to headline claims because they were not part of the paper-locked evidence set, but they strengthen the case for spending the next round of effort on matched-leakage comparisons and deeper-layer replications rather than on searching for a different primary mechanism.

Two implications follow. First, the paper should presently avoid claiming that off-manifold control is already proven to improve the full leakage-utility frontier; the matched-leakage analysis and broader replications are still needed for that claim. Second, the current evidence suggests that the next important question is not whether tangent projection changes the erasure direction at all, but under which layers and operating points that removal advantage can be converted into a cleaner utility tradeoff.

The matched layer-8 linear-family comparison clarifies one part of that tradeoff. LEACE is more surgical than tangent on this slice because it removes linearly decodable concept signal while taking a much smaller geometric step and preserving more downstream utility, especially on sycophancy where the answer-matching penalty is substantially smaller. That does not make LEACE a substitute for tangent on the main nonlinear claim: LEACE succeeds by solving the linear erasure problem cleanly, whereas tangent remains the stronger method when the target concept is evaluated with a fresh nonlinear probe. The current evidence therefore suggests a division of labor rather than a single winner: LEACE is the cleaner linear baseline, while tangent remains the more aggressive nonlinear remover.

7 Limitations

The current manuscript deliberately limits its main-text quantitative claims to the paper runs that were complete when this draft was assembled. That keeps the claims auditable, but it also means the strongest version of the utility-preservation story is not yet established in the locked evidence set. The deeper iterative sycophancy and safety reports are directionally consistent with the main narrative and are included in Appendix A, yet the paper's central claims still rely on the smaller completed suite.

A second limitation is measurement scope. All experiments use Qwen2.5-0.5B, and utility is measured through task-specific proxies such as answer matching, helpfulness ranking, profession classification, and dataset-source retention. These metrics are appropriate for surgicality, but they do not yet establish broad capability preservation across unrelated tasks.

Finally, the geometry diagnostics support low-dimensional structure, concept nonlinearity, and connectedness, but they do not by themselves prove that curved-manifold effects are the sole causal mechanism behind every leakage–utility tradeoff. The current paper therefore treats geometry as strong supporting evidence for tangent projection rather than as a complete causal proof.

8 Conclusion

We introduced TanGCE, the method presented in this paper: a manifold-aware concept erasure method that constrains erasure gradients to the local tangent space of the representation manifold. The central claim is not just that tangent projection removes more target information, but that it does so for the right geometric reason: when sentence representations occupy a much smaller natural manifold than the ambient hidden space, restricting updates to the tangent space lets the method use larger erasure strengths while keeping control-task changes small.

The comparison to IGBP and Ambient GCE clarifies the role of the manifold constraint. IGBP is the closest prior nonlinear baseline; Ambient GCE is the direct ablation with the same iterative loop but no tangent restriction; and TanGCE is the full method. The resulting λ sweep makes the practical benefit clear: ambient updates become unstable at large step sizes, whereas tangent-constrained updates continue to improve erasure precision.

Cross-modal experiments on 40 CelebA facial attributes in CLIP ViT-B/32 representations confirm that TanGCE generalizes beyond language models. TanGCE wins 36 of 40 attribute erasure tasks under fair HPO, reducing mean nonlinear leakage to 0.707 (vs. 0.839 for LEACE, the strongest baseline), with comparable control-task preservation. The remaining concepts are near-chance or favor another baseline.

More broadly, the iterative nonlinear protocol follows a conservative lesson from prior erasure work: if a freshly trained classifier can still recover the concept, then the concept is still present. By repeatedly retraining the scorer and constraining each erasure step to the tangent space, TanGCE turns that lesson into a practical nonlinear erasure method.

Several directions remain open. First, extending TanGCE to multi-layer erasure—where tangent spaces must be re-estimated after each layer's intervention—is a natural next step. Second, while our experiments use PCA-based tangent estimation, learned manifold representations (e.g., variational autoencoders) could provide more accurate tangent spaces. Finally, the connection between local geometric structure and erasure effectiveness suggests that manifold-aware methods may benefit other representation editing tasks beyond concept removal.

References

Nora Belrose, David Schneider-Joseph, Shauli Ravfogel, Ryan Cotterell, Edward Raff, and Stella Biderman. Leace: Perfect linear concept erasure in closed form. In *Advances in Neural Information Processing Systems 36*, 2023. URL `https://papers.nips.cc/paper_files/paper/2023/hash/d066d21c619d0a78c5b557fa3291a8f4-Abstract-Conference.html`.

Yanai Elazar and Yoav Goldberg. Adversarial removal of demographic attributes from text data. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 11–21, Brussels, Belgium, 2018. Association for Computational Linguistics. doi: 10.18653/v1/D18-1002. URL `https://aclanthology.org/D18-1002/`.

Table 7: Repository snapshot from the iterative sycophancy report at $\lambda = 1.0$ after 7 rounds, across layers 8, 16, and 23. Columns T (tangent-constrained) and A (ambient baseline) compare erasure methods. Utility is answer-matching delta relative to clean representations. Leakage and displacement decrease from left to right (lower is better); utility increases from left to right (higher is better). This snapshot table is not a main-text claim anchor and should be read only as evidence of directional consistency with the layer-8 paper-locked row (Table 2). Deeper-layer iterative tangent runs continue to reduce leakage more than ambient baselines across this exploratory sweep.

Layer	T leak	A leak	T util	A util	T disp	A disp
8	0.063	0.213	-20.7pp	-0.5pp	2.88	0.62
16	0.153	0.400	+0.0pp	+0.0pp	3.79	0.27
23	0.138	0.361	-0.1pp	-0.2pp	44.50	3.11

Table 8: Repository snapshot from the iterative safety report at $\lambda = 1.0$ after 7 rounds, across layers 8, 16, and 23. Columns T (tangent-constrained) and A (ambient baseline) compare erasure methods. Utility is pairwise helpfulness delta. Leakage and displacement decrease from left to right (lower is better); utility increases from left to right (higher is better). This snapshot table is not a main-text claim anchor and should be read only as evidence of directional consistency with the layer-8 paper-locked row (Table 2). Deeper-layer iterative tangent runs continue to reduce leakage more than ambient baselines across this exploratory sweep.

Layer	T leak	A leak	T util	A util	T disp	A disp
8	0.0725	0.2583	-0.052	-0.023	2.70	0.18
16	0.1292	0.3517	-0.092	+0.003	4.37	0.60
23	0.1483	0.3404	-0.062	-0.152	38.32	5.30

Yanai Elazar, Shauli Ravfogel, Alon Jacovi, and Yoav Goldberg. Amnesic probing: Behavioral explanation with amnesic counterfactuals. *Transactions of the Association for Computational Linguistics*, 9:160–175, 2021. doi: 10.1162/tacl_a_00359. URL `https://aclanthology.org/2021.tacl-1.10/`.

Shadi Iskander, Kira Radinsky, and Yonatan Belinkov. Shielded representations: Protecting sensitive attributes through iterative gradient-based projection. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 5961–5977, Toronto, Canada, 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-acl.369. URL `https://aclanthology.org/2023.findings-acl.369/`.

Shauli Ravfogel, Yanai Elazar, Hila Gonen, Michael Twiton, and Yoav Goldberg. Null it out: Guarding protected attributes by iterative nullspace projection. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7237–7256, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.647. URL `https://aclanthology.org/2020.acl-main.647/`.

A Repository Snapshot Tables

This appendix records broader repository snapshot tables that are directionally consistent with the main text but were not part of the locked paper-evidence set when the quantitative claims in Section 5 were written. We include them to document the current state of the project and to guide the next round of matched-leakage and deeper-layer analyses. The central paper claims continue to rely only on the completed paper suite summarized in the main text.

Table 9: Local Table-2-style CelebA visual comparison using CLIP ViT-B/32 embeddings. For each target concept we intervene once per method and evaluate (i) concept leakage via re-trained linear/nonlinear probes (lower is better) and (ii) mean control-task accuracy change across 3 least-correlated control attributes (closer to zero is better). Targets and controls: Male $\rightarrow$ Blurry,Narrow_Eyes,Straight_Hair; Smiling $\rightarrow$ Straight_Hair,Bushy_Eyebrows,Gray_Hair; Blond_Hair $\rightarrow$ Straight_Hair,Narrow_Eyes,Blurry. Lambdas follow Table 2: all methods λ=0.5 except TanGCE λ=8.0.

	Male			Smiling			Blond_Hair		
Method	L↓	NL↓	ΔCtrl	L↓	NL↓	ΔCtrl	L↓	NL↓	ΔCtrl
Random Global	.993	.994	-0.0pp	.891	.911	+0.0pp	.909	.933	-0.1pp
Random Per-Samp.	.993	.994	+0.0pp	.891	.907	+0.2pp	.907	.932	-0.1pp
Linear Proj.	.993	.992	+0.0pp	.900	.906	-0.3pp	.919	.931	-0.2pp
INLP	.994	.993	-0.0pp	.900	.903	+0.3pp	.918	.932	-0.0pp
LEACE	.994	.991	-0.0pp	.894	.894	+0.2pp	.909	.925	-0.1pp
Ambient GCE	.990	.995	-0.2pp	.858	.884	-0.4pp	.893	.920	+0.2pp
TanGCE	.887	.953	-0.8pp	.649	.649	-0.6pp	.699	.747	-2.1pp

A.1 Iterative Sycophancy Snapshot

A.2 Iterative Safety Snapshot

A.3 Local CelebA Visual Table-2-Style Comparison

To ensure a modality-matched benchmark, this appendix now reports a vision-only CelebA run (CLIP ViT-B/32 embeddings) with the Table 2 method family and 3 least-correlated controls per target concept. Artifacts are stored under `outputs/local/celeba_visual_table2_v1/` (including per-method sample folders with 2 saved images each). The consolidated W&B results run is `g52h8kbr`.

A.4 CelebA Per-Concept Detail (All 40 Attributes)

Tables 10 and 11 give the full per-concept breakdown behind the aggregate CelebA result in Table 5. The main-text Table 4 reports three representative concepts (Male, Smiling, Blond_Hair); the appendix tables cover all 40 binary CelebA attributes from the same `celeba_clip_all40_fair_v2` run under the shared validation-HPO protocol. TanGCE achieves the lowest nonlinear leakage on **36 of 40** concepts (LEACE wins on 3, IGBP on 1), with a mean margin of 0.116 absolute NL accuracy over the best competing method per concept. Per-concept mean ΔCtrl remains within roughly a percentage point of zero, consistent with the aggregate mean NL of 0.707 and mean ΔCtrl of -0.7% reported in the main text.

Geometry Note. The broader geometry report continues to support three useful points: early and mid-layer representations are effectively low-dimensional, on-manifold directions carry much of the model's sensitivity in these perturbation tests, and interpolation remains consistent with a connected representation space. At the same time, the Q2 perturbation study is best read as evidence of sensitivity concentration in a high-variance subspace rather than as a standalone proof of curved-manifold causality.

Table 10: Per-concept nonlinear probe leakage on CelebA (CLIP ViT-B/32), all 40 binary attributes. Each cell is retrained nonlinear probe test accuracy after erasure (lower = stronger erasure). λ^* is selected per method per concept from $\{0.5, 1.0, 2.0, 4.0, 8.0\}$ by lowest validation NL accuracy. Bold marks the lowest leakage per row. Abbrev.: RandG = Random Global, RandS = Random Per-Sample, LinProj = Linear Projection, AmbGCE = Ambient GCE, TanGCE = Tangent GCE.

Concept	RandG	RandS	LinProj	INLP	LEACE	IGBP	AmbGCE	TanGCE
5_o_Clock_Shadow	.92	.92	.91	.92	.87	.92	.91	**.77**
Arched_Eyebrows	.79	.79	.76	.76	.69	.77	.77	**.59**
Attractive	.73	.74	.69	.73	.63	**.53**	.73	.60
Bags_Under_Eyes	.76	.75	.74	.75	.70	.77	.75	**.69**
Bald	1.00	.99	.99	.99	.98	1.00	.99	**.97**
Bangs	.91	.91	.89	.89	.87	.92	.91	**.68**
Big_Lips	.80	.79	.74	.80	**.68**	.82	.81	.73
Big_Nose	.76	.76	.73	.74	.72	.73	.76	**.61**
Black_Hair	.85	.84	.82	.81	.79	.83	.82	**.46**
Blond_Hair	.92	.92	.94	.92	.92	.92	.92	**.72**
Blurry	.98	.98	.98	.96	.97	.98	.97	**.88**
Brown_Hair	.80	.80	.76	.75	.75	.80	.80	**.52**
Bushy_Eyebrows	.87	.88	.86	.85	.76	.87	.86	**.66**
Chubby	.94	.94	.95	.95	.92	.95	.94	**.81**
Double_Chin	.94	.94	.94	.93	.92	.94	.95	**.85**
Eyeglasses	.99	1.00	.96	.93	.96	1.00	.96	**.90**
Goatee	.96	.97	.97	.93	.96	.96	.95	**.85**
Gray_Hair	.97	.97	.97	.97	.97	.97	.98	**.89**
Heavy_Makeup	.89	.89	.89	.86	.85	.88	.88	**.70**
High_Cheekbones	.79	.79	.77	.75	.70	.57	.76	**.50**
Male	.99	.99	.99	.99	1.00	.98	1.00	**.85**
Mouth_Slightly_Open	.89	.89	.89	.71	.72	.66	.80	**.43**
Mustache	.94	.95	.95	.94	.92	.95	.93	**.77**
Narrow_Eyes	.88	.88	.80	.87	.80	.88	.88	**.78**
No_Beard	.94	.95	.94	.93	.92	.94	.95	**.77**
Oval_Face	.70	.71	.69	.68	**.67**	.69	.67	.72
Pale_Skin	.93	.93	.94	.95	.93	.92	.93	**.83**
Pointy_Nose	.75	.72	.71	.69	**.63**	.72	.75	.64
Receding_Hairline	.94	.94	.96	.96	.94	.94	.95	**.69**
Rosy_Cheeks	.93	.93	.93	.94	.91	.94	.93	**.79**
Sideburns	.95	.95	.94	.94	.95	.94	.94	**.82**
Smiling	.90	.89	.91	.74	.82	.59	.88	**.44**
Straight_Hair	.78	.78	.79	.77	.78	.78	.78	**.49**
Wavy_Hair	.78	.76	.77	.77	.78	.77	.78	**.52**
Wearing_Earrings	.90	.89	.86	.88	.85	.89	.88	**.61**
Wearing_Hat	1.00	1.00	.97	.97	.97	1.00	.97	**.94**
Wearing_Lipstick	.90	.90	.90	.89	.85	.88	.92	**.75**
Wearing_Necklace	.84	.85	.80	.80	.77	.85	.83	**.68**
Wearing_Necktie	.93	.93	.92	.92	.91	.92	.93	**.78**
Young	.86	.86	.85	.84	.83	.86	.87	**.60**
Mean	.88	.88	.87	.86	.84	.86	.87	**.71**

NeurIPS Paper Checklist

The checklist is designed to encourage best practices for responsible machine learning research, addressing issues of reproducibility, transparency, research ethics, and societal impact. Do not remove the checklist: **The papers not including the checklist will be desk rejected.** The checklist should follow the references and follow the (optional) supplemental material. The checklist does NOT count towards the page limit.

Please read the checklist guidelines carefully for information on how to answer these questions. For each question in the checklist:

- You should answer [Yes], [No], or [N/A].
- [N/A] means either that the question is Not Applicable for that particular paper or the relevant information is Not Available.
- Please provide a short (1–2 sentence) justification right after your answer (even for [N/A]).

The checklist answers are an integral part of your paper submission. They are visible to the reviewers, area chairs, senior area chairs, and ethics reviewers. You will also be asked to include it (after eventual revisions) with the final version of your paper, and its final version will be published with the paper.

The reviewers of your paper will be asked to use the checklist as one of the factors in their evaluation. While [Yes] is generally preferable to [No], it is perfectly acceptable to answer [No] provided a proper justification is given (e.g., error bars are not reported because it would be too computationally expensive" or "we were unable to find the license for the dataset we used"). In general, answering [No] or [N/A] is not grounds for rejection. While the questions are phrased in a binary way, we acknowledge that the true answer is often more nuanced, so please just use your best judgment and write a justification to elaborate. All supporting evidence can appear either in the main paper or the supplemental material, provided in appendix. If you answer [Yes] to a question, in the justification please point to the section(s) where related material for the question can be found.

IMPORTANT, please:

- **Delete this instruction block, but keep the section heading "NeurIPS Paper Checklist"**,
- **Keep the checklist subsection headings, questions/answers and guidelines below.**
- **Do not modify the questions and only use the provided macros for your answers**.

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: **[TODO]**

   Justification: **[TODO]**

   Guidelines:

   - The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: **[TODO]**

   Justification: **[TODO]**

Guidelines:

- The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate "Limitations" section in their paper.
- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer [N/A] means that the paper does not include experiments.

- If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
  (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
  (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
  (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
  (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer [N/A] means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).

- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: **[TODO]**

   Justification: **[TODO]**

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: **[TODO]**

   Justification: **[TODO]**

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
   - The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
   - The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
   - The assumptions made should be given (e.g., Normally distributed errors).
   - It should be clear whether the error bar is the standard deviation or the standard error of the mean.
   - It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
   - For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
   - If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: **[TODO]**

   Justification: **[TODO]**

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.

- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer [N/A] means that there is no societal impact of the work performed.
- If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer [N/A] means that the paper poses no such risks.

- Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: **[TODO]**

    Justification: **[TODO]**

    Guidelines:

    - The answer [N/A] means that the paper does not use existing assets.
    - The authors should cite the original paper that produced the code package or dataset.
    - The authors should state which version of the asset is used and, if possible, include a URL.
    - The name of the license (e.g., CC-BY 4.0) should be included for each asset.
    - For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
    - If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
    - For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
    - If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: **[TODO]**

    Justification: **[TODO]**

    Guidelines:

    - The answer [N/A] means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.
    - At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: **[TODO]**

    Justification: **[TODO]**

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
- Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.

Table 11: Per-concept mean control accuracy change ΔCtrl (%) on CelebA, all 40 binary attributes. For each concept, ΔCtrl is averaged over the 5 least-correlated control attributes (closer to zero = more surgical). λ^* selection matches Table 10.

Concept	RandG	RandS	LinProj	INLP	LEACE	IGBP	AmbGCE	TanGCE
5_o_Clock_Shadow	+0.0	+0.1	-0.7	+0.1	+0.0	+0.1	-2.3	-0.2
Arched_Eyebrows	-1.3	-2.3	-1.2	-0.8	-1.1	-2.5	+0.6	-0.6
Attractive	-0.3	-1.0	-1.7	-0.8	-0.3	-0.9	+0.0	-0.8
Bags_Under_Eyes	-3.7	-1.7	-0.3	-7.7	-0.3	-0.3	-0.3	-0.1
Bald	+0.1	+0.0	-0.1	+0.1	-0.1	+1.1	+2.3	+0.2
Bangs	-3.7	-1.2	-0.5	-7.9	-0.1	-0.7	-0.3	-0.8
Big_Lips	+0.1	-0.0	-0.3	+0.0	-0.1	-0.5	+0.1	-0.1
Big_Nose	-0.1	+0.3	-3.5	-9.7	+0.0	-0.3	-1.8	+0.1
Black_Hair	-0.1	-0.0	+0.1	+0.2	+0.3	-0.3	-0.3	-0.7
Blond_Hair	-0.3	+0.1	-1.4	+0.7	-0.1	-0.4	-1.1	-1.6
Blurry	-1.3	+0.0	-0.1	-5.5	+0.1	-0.7	+0.7	-0.1
Brown_Hair	+0.1	-0.9	-0.3	-6.0	-0.7	+0.4	+0.1	-0.2
Bushy_Eyebrows	+0.0	+0.1	-0.1	-1.5	+0.2	-0.9	-0.3	-0.5
Chubby	-0.1	+0.3	-0.2	-1.4	-0.2	-0.2	+0.4	-2.0
Double_Chin	+0.1	+0.1	-0.4	-12.7	+0.3	+0.7	-0.7	-2.5
Eyeglasses	-0.1	+0.1	-0.0	-0.1	-0.2	-0.4	-0.2	+0.2
Goatee	+0.1	-0.1	+0.0	+0.2	+0.1	+0.5	-0.3	-0.4
Gray_Hair	-0.2	-0.3	-2.1	+0.4	-0.1	-1.1	-1.5	-1.5
Heavy_Makeup	-0.3	-0.1	-1.1	-1.7	-1.3	-1.3	-1.1	-0.9
High_Cheekbones	+0.1	+0.2	+0.1	-0.3	-0.1	-0.4	-0.0	-0.7
Male	-0.3	-0.1	-0.7	-0.2	-0.3	-2.2	-0.9	-1.1
Mouth_Slightly_Open	-0.3	-0.6	+0.1	+0.4	+0.2	+0.3	+0.1	-0.2
Mustache	+0.0	-0.1	+0.1	-10.3	-0.5	+1.0	+0.5	-1.5
Narrow_Eyes	-0.1	-0.2	-0.3	+0.2	-0.1	+0.3	+0.0	+0.0
No_Beard	-1.2	-0.2	-4.0	-6.5	-1.6	-0.1	-0.7	-0.5
Oval_Face	-2.0	+0.1	-0.1	-14.4	-0.6	-0.3	+0.2	-0.3
Pale_Skin	-1.2	-0.1	-0.1	-6.8	-0.9	-0.1	+0.7	-1.0
Pointy_Nose	-0.1	-0.2	+0.3	-1.1	+0.2	-0.7	-0.1	-0.1
Receding_Hairline	-0.1	-0.1	-0.1	-5.9	+0.0	-0.3	+0.1	-1.1
Rosy_Cheeks	-0.5	+0.1	-0.6	-0.1	-0.2	-0.1	-0.1	-1.3
Sideburns	-0.4	+0.0	-0.1	+0.1	+0.1	-0.6	-2.5	-0.1
Smiling	-0.3	-1.3	+0.1	+0.6	+0.4	+0.1	+0.1	-0.1
Straight_Hair	-0.1	-0.2	-0.1	-0.9	-0.1	-0.8	+0.5	-0.7
Wavy_Hair	+0.1	-0.7	-0.9	+0.2	+0.1	-0.4	-0.1	-0.7
Wearing_Earrings	+0.8	-0.3	-1.6	-0.3	-0.1	-1.3	-0.5	-0.3
Wearing_Hat	-0.1	+0.0	-0.1	-0.6	+0.0	+1.0	+0.1	-0.2
Wearing_Lipstick	+0.2	-0.1	-6.1	-21.5	-1.9	-1.2	-1.4	-0.9
Wearing_Necklace	+0.1	-1.7	-1.7	-9.3	+0.3	-1.8	+0.2	-1.2
Wearing_Necktie	+0.0	+0.1	+0.0	+0.2	-0.2	-0.7	-13.4	-1.3
Young	-0.0	-0.7	-1.7	-10.7	+0.1	-0.9	-2.2	-0.8
Mean	-0.4	-0.3	-0.8	-3.5	-0.2	-0.4	-0.6	-0.7

Table 12: Geometry evidence map organizing the appendix diagnostics into four research blocks. Each block addresses a distinct aspect of manifold structure: Q1 examines whether task-relevant computation concentrates in a low-dimensional linear subspace, Q2 tests whether perturbations on the manifold are more consequential than off-manifold perturbations, Q3 validates whether the manifold is connected across domains, and multi-layer accumulation tracks error compounding through the network. These diagnostics support the mechanism discussion and motivate the need for manifold-aware erasure methods but do not by themselves establish causality.

Experiment Block	Research Question	Primary Evidence
Q1: Rank-retention	Subspace concentration	Top-1 agreement under intrinsic projection
Q2: Perturbation sensitivity	High-variance vs. orthogonal directions	KL and top-1 under on/off-subspace noise
Q3: Domain connectivity	Shared vs. domain manifolds	Cross-domain interpolation smoothness
Multi-layer accumulation	Error compounding across the network	Simultaneous intrinsic projection across layers