



## REVISIONS

DOC. NO. SPC-F004 \* Effective: 7/8/02 \* DCP No: 1398

| DCP # | REV | DESCRIPTION  | DRAWN | DATE    | CHECKD | DATE    | APPRVD | DATE    |
|-------|-----|--------------|-------|---------|--------|---------|--------|---------|
| 1453  | A   | RELEASED     | JWM   | 2/26/03 | HO     | 2/28/03 | JC     | 2/28/03 |
| 1741  | B   | 220V Removed | JWM   | 6/22/04 | JC     | 6/22/04 | JC     | 6/22/04 |

**Frequency Counter:**

- Measuring Range:
  - Channel A: 1Hz to 20MHz  
LED display depending on gate time and input signal.  
At least 7 digits are displayed per each second of gate time
  - Channel B: 20MHz to 2.7GHz
- Input Sensitivity
  - Channel A: 20mV RMS Signwave for 100mVp
  - Channel B: 40mV RMS Signwave for 20MHz to 1.3GHz or 70mV RMS Signwave for 1.3MHz to 2.7GHz
- Maximum Input Voltage: 3V
  - Channel A: 35mVp-p
  - Channel B: 3mVp-p
- Input Impedance:
  - Channel A: 1 Megohm
  - Channel B: 50 Ohms
- Selectable Time Base: Channel A, B  
Switch Selectable

**Function Generator**

- Wave Forms: Sign, Square, Triangle, Skewed Sine, Ramp, Pulse, TTL Level
- Frequency: 1Hz to 10MHz
- VCF Voltage Level: 0 to 10VDC
- Output Impedance: Selectable 50 Ohms  $\pm 10\%$   
600 Ohms  $\pm 10\%$
- Output Amplitude: 2vpp to 20vpp open load  
1vpp to 10vpp (50 ohm load)
- Sign Wave: Distortion less than 1% (at 1KHz),  
Flatness + 0.3dB
- Square Wave: Symmetry less than +3% (at 1KHz)  
Rise & Fall time less than 150ns (at 1KHz)
- Triangle Wave: Linierity less than 1% (up to 100KHz),  
5% (100KHz to 20MHz)

**Digital Multimeter (True RMS)**

- Range of Measurement
  - DC Voltage: 4 (400mV to 400V)  $\pm 0.06\%$  + 3dpts  
1 (1000V)  $\pm 0.2\%$  + 3dpts
  - AC Voltage: 4 (400mV to 400V)  $\pm 0.8\%$  + 10dpts  
(40Hz ~ 10 KHz)  $\pm 2.5\%$  + 10dpts  
1 (750V)  $\pm 1.0\%$  + 10dpts  
(40Hz ~ 1KHz)
  - DC Current: 3 (40mA to 400mA)  $\pm 0.3\%$  + 3dpts  
1 (20A)  $\pm 0.8\%$  + 5dpts
  - AC Current: 3 (4mA to 400mA)  
(40Hz ~ 1KHz)  $\pm 1.5\%$  + 10dpts  
(1KHz ~ 10KHz)  $\pm 2.5\%$  + 10dpts  
1 (20A)  $\pm 1.5\%$  + 10dpts  
(40Hz ~ 1KHz)
  - Resistance: 3 (400 Ohms ~ 4 Megohms)  $\pm 0.2\%$  + 10dpts
  - Capacitance: 2 (40nF ~ 400nF)  $\pm 2.0\%$  + 3dpts  
2 (4 $\mu$ F ~ 200 $\mu$ F)  $\pm 3.0\%$  + 5dpts
  - Continuity:  $\leq 40$  Ohms
  - Diode: Test Current max. 1mA at 1K Ohms  
(forward DC voltage max. 3V)
  - Logic: Test current max. 100 $\mu$ A
  - hFE: Yes
  - Signal Output: 10Hz ~ 10.24KHz, C-Mos level between 2.7V & 3.3V

**Power Supply** (3 $\frac{1}{2}$  digit LCD with Back-Light)

|                | Terminal 1 | Terminal 2 | Terminal 3 |
|----------------|------------|------------|------------|
| Output Voltage | 0 ~ 30V    | 5V Fixed   | 15V Fixed  |
| Output Amps    | 0 ~ 3A     | 2A         | 1A         |
| Ripple         | 1mV max.   | 2mV max.   | 2mV max    |
| Output Current | 2A/3A      | 2.2A       | 1.2A       |

**General Features**

Line Voltage: 110V/120VAC AT 50/60Hz  
Dimension: 14 $\frac{1}{2}$ "(W) x 6 $\frac{1}{2}$ "(H) x 12 $\frac{1}{2}$ "(D)  
Includes: AC Power Cord, Test Leads for DMM,  
& Owner's Manual

SPC-F004.DWG

|  |               |         |                                 |          |                     |               |
|--|---------------|---------|---------------------------------|----------|---------------------|---------------|
| TOLERANCES:<br><br>UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY. | DRAWN BY:     | DATE:   | DRAWING TITLE:                  |          |                     |               |
|  | Jeff McVicker | 2/26/03 | Multi-Function Universal System |          |                     |               |
|  | CHECKED BY:   | DATE:   | SIZE                            | DWG. NO. | ELECTRONIC FILE     | REV           |
|  | Hisham Odish  | 2/28/03 | A                               | 72-7290  | 22H6405.dwg         | B             |
|  | APPROVED BY:  | DATE:   | SCALE: NTS                      |          | U.O.M.: INCHES [mm] | SHEET: 1 OF 1 |
|  | John Cole     | 2/28/03 |                                 |          |                     |               |

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.