

Fundamentos de Processamento Imagens

Aula 03 Anatomia de Câmeras Digitais

Instituto de Informática
Universidade Federal de Rio Grande do Sul
Porto Alegre - RS
hefortunato@inf.ufrgs.br

Adaptado de slides do Prof. Manuel Menezes de Oliveira Neto (INF-UFRGS)

27 de agosto de 2009



(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

1 / 32

The Anatomy of Digital Cameras




(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

2 / 32

Formação da imagem - Modelo simples



© 2003 Vincent Bockaert 123di.com



(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

3 / 32

Optical Systems

- In practice, optical systems can be very complex
- The fundamental ideas can be understood studying the simplest optical system: the thin lens
- Thin lens attributes
 - An optical axis passing through the lens center
 - Two focal points, placed on opposite sides of the optical axis and equidistant from the lens center




(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

4 / 32

Geometric Optics of a Thin Lens



- Focal Length
 - distance (in mm) from the lens to its focal point



(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

5 / 32

Thin Lens Properties

- Any ray entering the lens parallel to the optical axis on one side goes through the focus on the other side
- Any ray entering the lens from the focus on one side emerges parallel to the axis on the other side




(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

6 / 32

Geometric Optics of a Thin Lens



(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

7 / 32

Some Definitions

- Aperture
 - adjustable diaphragm of overlapping blades which can be thought of as the iris of the eye
 - The aperture value represents a ratio of the equivalent focal length of a lens to the diameter of its entrance pupil
 - Different notations: f/8, F8, 1:8 (all the same)
 - The larger the f-number the smaller the aperture




(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

8 / 32

Aperture, f-stops



inf


(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

9 / 32

Aperture, f-stops



inf


(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

10 / 32

Aperture, f-stops



inf

(UFRGS)


Fundamentos de Processamento Imagens

27 de agosto de 2009

11 / 32

Shutter Speed

- Length of time the "shutter" allows light onto the CCD
- To "freeze" the action use a shutter speed of 1/250s plus



inf

(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

12 / 32

Some Definitions

- ISO value
 - in traditional film photography the ISO (ASA) value of a film represents the film's sensitivity
 - a film with lower ISO value requires more light to create the same image than a film with a higher ISO value
 - in a digital camera the sensitivity depends on the sensor
 - a CCD is an analogue device which outputs a certain voltage for a certain amount of light that reaches it
 - when you increase the sensitivity you are really just turning up the amplification of this signal (and of the "dark current" noise)

inf

(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

13 / 32

Depth of Field (DOF)

- Region in front (1/3 of the DOF) and behind (2/3 of the DOF) the main focus point which remain sharp
- Affected by aperture, subject distance and focal length
- The bigger the F number, the larger the DOF



inf


(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

14 / 32

Depth of Field (DOF)



inf


(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

15 / 32

CCD Arrays



inf


(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

16 / 32

CCD Arrays



inf

(UFRGS)


Fundamentos de Processamento Imagens

27 de agosto de 2009

17 / 32

CCD Arrays

- Bucket Analogy
- Collect photons and outputs a voltage reading
- Major types of sensor
 - Interline Transfer sensors
 - Full Frame sensors



inf

(UFRGS)


Fundamentos de Processamento Imagens

27 de agosto de 2009

18 / 32

Interline Transfer Sensors

- Used in typical consumer-grade digital cameras
- Transfer values from photodiodes into shift registers
- Can produce video feed output
- Extra electronics required around each pixel
 - Fill factor ~30
 - Use of microlenses to capture and focus more light into the smaller photodiode area
 - Improves fill factor to about 70



inf

(UFRGS)


Fundamentos de Processamento Imagens

27 de agosto de 2009

19 / 32

Interline Transfer Sensors (Cont.)

- CCD Sensor Architecture



inf


(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

20 / 32

CCD Arrays - microlenses



inf

(UFRGS)


Fundamentos de Processamento Imagens

27 de agosto de 2009

21 / 32

Full Frame Sensors

- Used in professional cameras (high image quality)
- Do not use shift registers, requires mechanical shutter
- Fill factor: 70
- High sensitivity
- High dynamic range
- No need for microlenses
- Disadvantages
 - Cannot get video feed out
 - Top shutter speed constrained by mechanical shutter



inf


(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

22 / 32

Sensor sizes



inf

(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

23 / 32

Sensor sizes

Common Image Sensor Sizes

In the table below "Type" refers to the commonly used type designation for sensors, "Aspect Ratio" refers to the ratio of width to height, "Dia." refers to the diameter of the tube size (this is simply the Type converted to millimeters), "Diagonal / Width / Height" are the dimensions of the sensor's image producing area.

| Type | Aspect Ratio | Dia. (mm) | Sensor (mm) | | |
|------------|--------------|-----------|-------------|--------|--------|
| | | | Diagonal | Width | Height |
| 1/3.6" | 4:3 | 7.056 | 5.000 | 4.000 | 3.000 |
| 1/3.2" | 4:3 | 7.938 | 5.680 | 4.536 | 3.416 |
| 1/3" | 4:3 | 8.467 | 6.000 | 4.800 | 3.600 |
| 1/2.7" | 4:3 | 9.407 | 6.721 | 5.371 | 4.035 |
| 1/2.5" | 4:3 | 10.160 | 7.182 | 5.760 | 4.290 |
| 1/2.3" | 4:3 | 11.044 | 7.700 | 6.160 | 4.620 |
| 1/2" | 4:3 | 12.700 | 8.000 | 6.400 | 4.800 |
| 1/1.8" | 4:3 | 14.111 | 8.933 | 7.176 | 5.319 |
| 1/1.7" | 4:3 | 14.941 | 9.500 | 7.600 | 5.700 |
| 2/3" | 4:3 | 16.933 | 11.000 | 8.800 | 6.600 |
| 1" | 4:3 | 25.400 | 16.000 | 12.800 | 9.600 |
| 4/3" | 4:3 | 33.867 | 22.500 | 18.000 | 13.500 |
| 1.8" (H) | 3:2 | 45.720 | 28.400 | 23.700 | 15.700 |
| 35 mm film | 3:2 | n/a | 43.300 | 36.000 | 24.000 |

inf

(UFRGS)

Fundamentos de Processamento Imagens

27 de agosto de 2009

24 / 32

Sensor sizes

Implementation Examples

Below is a list of a few digital cameras (as examples) and their sensor size.


| Camera | Sensor Type | Pixel count | Sensor size |
|--------------------------|-------------|--------------|----------------|
| Konika Minolta DiMAGE Xg | 1/2.7" CCD | 3.3 million | 5.3 x 4.0 mm |
| Powershot 5500 | 1/1.8" CCD | 5.0 million | 7.2 x 5.3 mm |
| Nikon Coolpix 8800 | 2/3" CCD | 8.0 million | 8.8 x 6.6 mm |
| Olympus C-8080 Wide Zoom | 2/3" CCD | 8.0 million | 8.8 x 6.6 mm |
| Sony DSC-828 | 2/3" CCD | 8.0 million | 8.8 x 6.6 mm |
| Konika Minolta DiMAGE A2 | 2/3" CCD | 8.0 million | 8.8 x 6.6 mm |
| Nikon D70s | CCD | 6.1 million | 23.7 x 15.7 mm |
| Nikon D2X | CMOS | 12.2 million | 23.7 x 15.7 mm |
| Kodak DSC-14n | CMOS | 13.8 million | 36 x 24 mm |
| Canon EOS-1Ds Mark II | CMOS | 16.6 million | 36 x 24 mm |

Color CCD Cameras

- Photodiodes are monochrome devices
- In order to capture color, we need to use color filters
- Approaches
 - Use three CCDs (one for each of the RGB channels)
 - Use one CCD with a color filter array (CFA)


Three-CCD Camera

- A beam splitter is used to project the incident light onto three CCD arrays (RGB)
- Higher quality, but more expensive and bigger cameras



Color Filter Array (CFA)


- Bayer filter Pattern
- Human visual system more sensitive to green
 - Luminance: $Y = 0.299 \cdot R + 0.587 \cdot G + 0.114 \cdot B$




Bayer filter

Color Filter Array (CFA)

- Bayer filter Pattern
- Human visual system more sensitive to green
 - Luminance: $Y = 0.299 \cdot R + 0.587 \cdot G + 0.114 \cdot B$



Producing the Final Image



Digital Image Noise

| Blue Sky Crop | A | B | C | D | E |
|------------------|--------------|----------|----------|----------|-----------------------------------|
| RGB | | | | | |
| Red Channel | | | | | |
| Camera Grade | Professional | Prosumer | Prosumer | Prosumer | Prosumer |
| Camera Type | SLR | SLR | Compact | Compact | Crop C after 123d noise reduction |
| Pixel Size | Large | Large | Small | Small | |
| ISO | 100 | 200 | 100 | 800 | |
| Red Ch. St. Dev. | 1.8 | 2.5 | 5.6 | 22.6 | 1.4 |

References

- Phil Askey. Glossary: Digital Photography Review. (<http://www.dpreview.com/learn/Glossary/>)
- Sally W. Grotta. Anatomy of a Digital Camera: Image Sensors. (<http://www.extremetech.com/article2/0,3973,474237,00.asp>)
- E. Trucco and A. Verri. Introductory Techniques for 3-D Computer Vision. Prentice Hall, 1998.
- UVP Inc. Understanding CCD Cameras. Focal Points Application Note FP-114.