

Sysdba commands:

Login pod sysdba

sqlplus / as sysdba

```
[oracle@localhost ~]$ sqlplus / as sysdba
```

USER MANIPULACIA:

Vytvorenie usera

create user Testuser identified by Heslo123;

```
SQL> create user Testuser identified by Heslo123;  
User created.
```

vynútenie resetu hesla bez jeho manuálnej zmeny

alter user Testuser password expire;

```
SQL> alter user Testuser password expire;  
User altered.
```

Unlock zablokovaného účtu (ako sysdba)

alter user Testuser account unlock;

```
SQL> alter user Testuser account unlock;  
User altered.
```

dropnutie usera:

drop user Testuser;

```
SQL> drop user Testuser;  
User dropped.  
SQL> drop user Testuser2;  
User dropped.
```

PRIDAVANIE ROLY A PRAV USEROVY:

grantnutie Testrole userovi profil aby mal prava

grant Testrole to Testuser;

```
SQL> grant Testrole to Testuser;  
Grant succeeded.
```

Odobranie Testrole Testuserovi

revoke Testrole from Testuser;

```
SQL> revoke Testrole from Testuser;  
Revoke succeeded.
```

Priradiť userovi profil Testprofile

alter user Testuser profile Testprofile;

```
SQL> alter user Testuser profile Testprofile;  
User altered.
```

Pridanie práv na vytvorenie relácie danému userovi

grant create session to Testuser;

```
SQL> grant create session to Testuser;  
  
Grant succeeded.
```

ROLE a PROFILI:

Vytvoríme Testrole:

create role Testrole;

```
SQL> create role Testrole;  
  
Role created.
```

Udelenie roli Testrole oprávnenie prihlasovať sa do databázy a vytvárať tabuľky.

grant create table, create session to Testrole;

```
SQL> grant create table, create session to Testrole;  
  
Grant succeeded.
```

Vytvorenie profilu ze po neuspes login zamkne ucet

create profile Testprofile limit failed_login_attempts 1;

```
SQL> create profile Testprofile limit failed_login_attempts 1;  
  
Profile created.
```

user commands:

prihlásenie pod userom

sqlplus Testuser/Heslo123

```
[oracle@localhost ~]$ sqlplus Testuser/Heslo123  
  
SQL*Plus: Release 19.0.0.0.0 - Production on Wed Mar 25 11:53:11 2026  
Version 19.3.0.0.0  
  
Copyright (c) 1982, 2019, Oracle. All rights reserved.  
  
Last Successful login time: Wed Mar 25 2026 11:52:30 +01:00  
  
Connected to:  
Oracle Database 19c Enterprise Edition Release 19.0.0.0.0 - Production  
Version 19.3.0.0.0
```

Nastavenie linesize a check session relacie

(linesize pojde, status n)

```
SQL> set linesize 150;  
SQL> select status from v$instance;  
select status from v$instance  
*  
  
ERROR at line 1:  
ORA-00942: table or view does not exist
```

Vytvorenie tabulky

```
CREATE TABLE Studenti (Meno VARCHAR(20));
```

NEMAM PRAVA

```
SQL> CREATE TABLE Studenti (Meno VARCHAR(20));
CREATE TABLE Studenti (Meno VARCHAR(20))
*
ERROR at line 1:
ORA-01031: insufficient privileges
```

Pozrieme desc a select z tabulky

```
SQL> desc Studenti;
Name                                         Null?    Type
-----
MENO                                         VARCHAR2(20)

SQL> select * from Studenti;
no rows selected
```

Dropneme tabulku

```
SQL> drop table Studenti;

Table dropped.
```

PFILE SPFILE:

```
cd /u01/appl/oracle/product/19.0.0/dbhome_1/dbs
```

```
. oraenv
```

```
dual1
```

```
sqlplus / as sysdba
```

```
startup;
```

Overenie ci je system startnuty SPfilom

show parameter spfile;

```
SQL> show parameter spfile;

NAME                                     TYPE        VALUE
-----
spfile                                 string      /u01/appl/oracle/product/19.0.0/dbhome_1/dbs/spfileedual1.ora
```

show parameter processes; -> napíše všetko čo obsahuje processes, ale to nevadí

```
SQL> show parameter processes;

NAME                                     TYPE        VALUE
-----
aq_tm_processes                        integer      1
db_writer_processes                    integer      1
gcs_server_processes                   integer      0
global_txn_processes                  integer      1
job_queue_processes                    integer      80
log_archive_max_processes              integer      4
processes                              integer      320
```

Zmena value procesu na 333 (scope nastavíme či meníme v operačnej pamäti alebo spfile alebo both)

alter system set processes = 333 scope = spfile;

(treba aj restart)

```
SQL> alter system set processes = 333 scope = spfile;
System altered.
SQL> show parameter processes;
NAME                                TYPE          VALUE
-----
aq_tm_processes                     integer       1
db_writer_processes                 integer       1
gcs_server_processes                integer       0
global_txn_processes                integer       1
job_queue_processes                 integer       80
log_archive_max_processes            integer       4
processes                           integer       320
SQL> shutdown immediate;
Database closed.
Database dismounted.
ORACLE instance shut down.
SQL> startup;
ORACLE instance started.

Total System Global Area 2415917880 bytes
Fixed Size                  8899384 bytes
Variable Size               520093696 bytes
Database Buffers            1879048192 bytes
Redo Buffers                  7876608 bytes
Database mounted.
Database opened.
SQL> show parameter processes;
NAME                                TYPE          VALUE
-----
aq_tm_processes                     integer       1
db_writer_processes                 integer       1
gcs_server_processes                integer       0
global_txn_processes                integer       1
job_queue_processes                 integer       80
log_archive_max_processes            integer       4
processes                           integer       333
```

Vytvorenie PFilu

create pfile from spfile;

```
SQL> create pfile from spfile;
File created.
```

ideme sa pozriet ci sa nam vytvoril pfile

(vytvoril sa, initdual1.ora)

/u01/appl/oracle/product/19.0.0/dbhome_1/dbs

```
[oracle@localhost dbs]$ ll
total 24
-rw-rw----. 1 oracle oinstall 1544 Mar 17 12:07 hc_dual1.dat
-rw-r--r--. 1 oracle oinstall 1037 Mar 18 10:11 initdual1.ora
-rw-r--r--. 1 oracle oinstall 3079 May 14 2015 init.ora
-rw-r-----. 1 oracle oinstall 24 Dec 4 10:21 lkDUAL1
-rw-r-----. 1 oracle oinstall 2048 Dec 4 10:23 orapwdual1
-rw-r-----. 1 oracle oinstall 3584 Mar 17 12:07 spfiledual1.ora
```

Cez nano si zmenime pfile processes na 300

```
GNU nano 2.9.8                               initdual1.ora

.dispatchers=(PROTOCOL=TCP) (SERVICE=dual1XDB)
.local_listener='LISTENER_DUAL1'
.nls_language='AMERICAN'
.nls_territory='AMERICA'
.open_cursors=300
.pga_aggregate_target=767m
.processes=300
.remote_login_passwordfile='EXCLUSIVE'
.sga_target=2299m
.undo_tablespace='UNDOTBS1'
```

vytvorit spfile z pfile

shutdown immediate;
create spfile from pfile;

```
SQL> shutdown immediate;
Database closed.
Database dismounted.
ORACLE instance shut down.
SQL>
SQL> create spfile from pfile;

File created.
```

Kontrola ci bezime z spfilu a kontrola ci je processes 300

show parameter spfile;

```
SQL> show parameter spfile;

NAME                                TYPE                                VALUE
-----                                -
spfile                              string                              /u01/appl/oracle/product/19.0.
0/dbhome_1/dbs/spfileduall.ora
SQL> show parameter processes;

NAME                                TYPE                                VALUE
-----                                -
aq_tm_processes                     integer                             1
db_writer_processes                 integer                             1
gcs_server_processes                integer                             0
global_txn_processes                integer                             1
job_queue_processes                 integer                             80
log_archive_max_processes            integer                             4
processes                           integer                             300
```

Nastavenie pfile processes na 320 a startovanie z neho

alter system set processes – 320 scope – spfile;

```
SQL> alter system set processes = 320 scope = spfile;
```

System altered.

```
SQL> show parameter processes;
```

SP2-0158: unknown SHOW option "parameter"

SP2-0158: unknown SHOW option "processes"

```
SQL> show parameter processes;
```

NAME	TYPE	VALUE
aq_tm_processes	integer	1
db_writer_processes	integer	1
gcs_server_processes	integer	0
global_txn_processes	integer	1
job_queue_processes	integer	80
log_archive_max_processes	integer	4
processes	integer	300

```
SQL> shutdown immediate;
```

Database closed.

Database dismounted.

ORACLE instance shut down.

```
cSQL>create pfile from spfile;
```

File created.

```
SQL> startup pfile=initduall.ora;
```

ORACLE instance started.

Total System Global Area 2415917880 bytes

Fixed Size 8899384 bytes

Variable Size 520093696 bytes

Database Buffers 1879048192 bytes

Redo Buffers 7876608 bytes

Database mounted.

Database opened.

```
SQL> show parameter spfile;
```

NAME	TYPE	VALUE
spfile	string	

```
SQL> show parameter processes;
```

NAME	TYPE	VALUE
aq_tm_processes	integer	1
db_writer_processes	integer	1
gcs_server_processes	integer	0
global_txn_processes	integer	1
job_queue_processes	integer	80
log_archive_max_processes	integer	4
processes	integer	320