

NumPy

Efficient Arrays and Numerical Computing for Python

Numerical Python

Provides efficient storage and operations on dense data buffers, i.e., arrays.

- ▶ `ndarray` is the fundamental object
- ▶ Vectorized (no loop) operations on arrays
- ▶ Broadcasting
- ▶ File IO and memory-mapped files

```
In [1]: import numpy as np
```

NumPy Array Element Types

Arrays have elements of homogeneous data type

```
In [2]: nums = [1, 2, 3.14]

In [3]: nums
Out[3]: [1, 2, 3.14]

In [4]: np.array(nums)
Out[4]: array([ 1. , 2. , 3.14])

In [5]: type(Out[4][0])
Out[5]: numpy.float64
```

- ▶ Notice that the values were converted to floats.

You can specify an explicit element type with the `dtype` keyword argument:

```
In [6]: np.array(nums, dtype='int')
Out[6]: array([1, 2, 3])
```

Basic Array Creation

Pass Python lists to `np.array()` (nested lists create multi-dimensional arrays)

```
In [9]: np.array([[1,2,3],[4,5,6]])  
Out[9]:  
array([[1, 2, 3],  
       [4, 5, 6]])
```

Create a one-dimensional array of zeros, `dtype` defaults to `float`:

```
In [10]: np.zeros(4)  
Out[10]: array([ 0., 0., 0., 0.])
```

Create a multi-dimensional array of 1s with element type `int`. Note that first argument is a tuple of array dimensions.

```
In [11]: np.ones((2, 3), dtype=int)  
Out[11]:  
array([[1, 1, 1],  
       [1, 1, 1]])
```

Create a 2-d array of the same element values:

```
In [12]: np.full((2, 3), 2.72)  
Out[12]:  
array([[ 2.72,  2.72,  2.72],  
       [ 2.72,  2.72,  2.72]])
```

Creating a range is similar to Python's built-in `range(start, end, stride)`:

```
In [13]: np.arange(0, 10, 2)
```

Creating Arrays of Random Numbers

Create a 2×3 array of values uniformly distributed between 0 and 1:

```
In [28]: np.random.random((2, 3))
Out[28]:
array([[ 0.93923457,  0.41299137,  0.07451052],
       [ 0.32800936,  0.44435825,  0.4520937 ]])
```

Create an 2×3 array of numbers normally distributed with mean 71.36 and standard deviation of 14.79:

```
In [26]: np.random.normal(71.36, 14.79, (2, 3))
Out[26]:
array([[ 71.24362489,  61.05019638,  72.25408014],
       [ 63.03759916,  70.64992342,  75.94207076]])
```

Create a 2×3 array of int values in the interval [1, 11):

```
In [29]: np.random.randint(1, 11, (2, 3))
Out[29]:
array([[9, 8, 6],
       [9, 5, 9]])
```

3-d identity matrix:

```
In [31]: np.identity(3)
Out[31]:
array([[ 1.,  0.,  0.],
       [ 0.,  1.,  0.],
       [ 0.,  0.,  1.]])
```

NumPy Array Attributes

Given:

```
In [33]: a = np.array([[1,2,3], [4,5,6]])
```

```
In [34]: a
```

```
Out[34]:  
array([[1, 2, 3],  
       [4, 5, 6]])
```

`ndim` is the number of dimensions:

```
In [37]: a.ndim
```

```
Out[37]: 2
```

`shape` is a tuple giving the number of elements in each dimension:

```
In [35]: a.shape
```

```
Out[35]: (2, 3)
```

`dtype` is the type of the elements

```
In [36]: a.dtype
```

```
Out[36]: dtype('int64')
```

1-D Array Indexing and Slicing

1-d arrays similar to Python lists:

```
In [41]: a1 = np.arange(10)
```

```
In [44]: a1[1]
```

```
Out[44]: 1
```

```
In [45]: a1[-1]
```

```
Out[45]: 9
```

```
In [46]: a1[2:5]
```

```
Out[46]: array([2, 3, 4])
```

Assignment of single value to a (sub)range *broadcasts* the value to the (sub)range:

```
In [47]: a1[2:5] = 11
```

```
In [48]: a1
```

```
Out[48]: array([ 0, 1, 11, 11, 11, 5, 6, 7, 8, 9])
```

Notice that the original array is modified.

2-D Array Indexing and Slicing

Given:

```
In [49]: a3 = np.array([[1,2,3],[4,5,6],[7,8,9]])
```

```
In [50]: a3
```

```
Out[50]:
```

```
array([[1, 2, 3],  
       [4, 5, 6],  
       [7, 8, 9]])
```

Single scalar value:

```
In [51]: a3[1,1]
```

```
Out[51]: 5
```

Subarray:

```
In [52]: a3[1:, 1:]
```

```
Out[52]:
```

```
array([[5, 6],  
       [8, 9]])
```

Single column:

```
In [53]: a3[:, 2]
```

```
Out[53]: array([3, 6, 9])
```

Single row:

```
In [54]: a3[2, :]
```

```
Out[54]: array([7, 8, 9])
```


Array Reshaping

2-d arrays

```
In [62]: a3 = np.arange(1, 13)
```

```
In [63]: a3
```

```
Out[63]: array([ 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12])
```

```
In [64]: a3.reshape(3, 4)
```

```
Out[64]:
```

```
array([[ 1, 2, 3, 4],  
       [ 5, 6, 7, 8],  
       [ 9, 10, 11, 12]])
```

```
In [65]: a3.reshape(4, 3)
```

```
Out[65]:
```

```
array([[ 1, 2, 3],  
       [ 4, 5, 6],  
       [ 7, 8, 9],  
       [10, 11, 12]])
```

Universal Functions on NumPy Arrays

Operations between scalars and arrays are *vectorized*.

```
In [108]: a = np.arange(9)

In [109]: a
Out[109]: array([0, 1, 2, 3, 4, 5, 6, 7, 8])

In [110]: 2 ** a
Out[110]: array([ 1,  2,  4,  8, 16, 32, 64, 128, 256])

In [111]: 2 ** a.reshape((3, 3))
Out[111]:
array([[ 1,  2,  4],
       [ 8, 16, 32],
       [64, 128, 256]])
```

Operations between like-shaped arrays are also vectorized:

```
In [114]: np.arange(2, 20, 2) / np.arange(1, 10)
Out[114]: array([ 2.,  2.,  2.,  2.,  2.,  2.,  2.,  2.,  2.])
```

Array Aggregations

```
In [117]: np.arange(10).sum()
```

```
Out[117]: 45
```

```
In [119]: np.array([8,6,7,5,3,0,9]).min()
```

```
Out[119]: 0
```

```
In [120]: np.array([8,6,7,5,3,0,9]).max()
```

```
Out[120]: 9
```

2-D Aggregations

```
In [131]: np.arange(9).reshape(3,3)
```

```
Out[131]:
```

```
array([[0, 1, 2],  
       [3, 4, 5],  
       [6, 7, 8]])
```

```
In [132]: np.arange(9).reshape(3,3).min(axis=0)
```

```
Out[132]: array([0, 1, 2])
```

```
In [133]: np.arange(9).reshape(3,3).max(axis=0)
```

```
Out[133]: array([6, 7, 8])
```

```
In [134]: np.arange(9).reshape(3,3).min(axis=1)
```

```
Out[134]: array([0, 3, 6])
```

```
In [135]: np.arange(9).reshape(3,3).max(axis=1)
```

```
Out[135]: array([2, 5, 8])
```

Loading Data From Files

Load CSV into 2-d array:

```
In [89]: studs = np.loadtxt('grades.csv', delimiter=',', dtype=np.string_)
Out[89]:
array([[b'Student', b'Exam 1', b'Exam 2', b'Exam 3'],
       [b'Thorny', b'100', b'90', b'80'],
       [b'Mac', b'88', b'99', b'111'],
       [b'Farva', b'45', b'56', b'67'],
       [b'Rabbit', b'59', b'61', b'67'],
       [b'Ursula', b'73', b'79', b'83'],
       [b'Foster', b'89', b'97', b'101']],
      dtype='<S7')
```

Mean of a slice of a row:

```
In [98]: np.array(studs[1, 1:], dtype=float)
Out[98]: array([ 100.,  90.,  80.])

In [99]: thorny_avg = np.array(studs[1,1:], dtype=float).mean()

In [100]: thorny_avg
Out[100]: 90.0
```

Mean of a slice of a column:

```
In [103]: np.array(studs[1:, 1], dtype=float)
Out[103]: array([ 100.,  88.,  45.,  59.,  73.,  89.])

In [101]: exam1_avg = np.array(studs[1:, 1], dtype=float).mean()

In [102]: exam1_avg
Out[102]: 75.666666666666671
```