

Software Engineering (303105254)







UNIT-5

Coding and Unit Testing







Programming Principles and Guidelines

- 1. Select data structures that will meet the need of the design.
- 2. Keep conditional logic as simple as possible.
- 3. Understand the software architecture and make interfaces that are according to it.
- 4. Select meaningful variable names and follow other local coding standards.
- 5. Write code that's self-documenting.
- 6. Create a visual layout.
- 7. Constrain your algorithm by structured programming practice.







Programming Practices

Control construct

The single entry and exit constructs need to be used.

Use of goto

The goto statements make the program unstructured. So avoid use of goto statements as possible.

Information hiding

Nesting

Structure inside another structure is called as nesting. If there is too deep nesting then it becomes hard to understand the code as well as complex.

User defined data types

User can define data type to enhance the readability of the code.





Programming Practices (Contd.)

Modular size

The size of program may be large or small. There is no rule for size of the program. So as possible generate different module but not of large size.

Side effects

Sometimes if some part of code may change then it may generate some kind of problems called as side effects.

Robustness

If any kind of exception is generated, the program should generate some kind of output. Then it is called as robustness. In this situation the programs do not crash.

Switch case with defaults

Inside the switch case statement if any value which is unpredictable is given as argument then there should be default case to execute it





Coding Standards

Good software development organizations normally require their programmers to adhere to some well-defined and standard style of coding called coding standards.







- Most software development organizations formulate their own coding standards that suit them most, and need their engineers to follow these standards strictly.
- The purpose of requiring all engineers of an organization to adhere to a standard style of coding is the following:

A coding standard gives a uniform appearance to the codes written by different engineers.

It enhances code understanding.

It encourages good programming practices.







- A coding standard lists several rules to be followed such as, the way variables are to be named, the way the code is to be laid out, error return conventions, etc.
- The following are some representative coding standards:

Rules for limiting the use of global

These rules list what types of data can be declared global and what cannot.

Naming conventions for global & local variables & constant identifiers

A possible naming convention can be that global variable names always start with a capital letter, local variable names are made of small letters, and constant names are always capital letters.





Contents of the headers preceding codes for different modules

- The information contained in the headers of different modules should be standard for an organization.
- The exact format in which the header information is organized in the header can also be specified.

The following are some standard header data

Module Name Creation Date Author's Name Modification

history Synopsis of the module

Global variables accessed/modifiedby the module Different functions supported, along with their input/output parameters





Error return conventions and exception handling mechanisms

- The way error conditions are reported by different functions in a program are handled should be standard within an organization.
- For example, different functions while encountering an error condition should either return a 0 or 1 consistently.








Incremental Development of Code

- Then test that code based on some cases then execute the test script.
- It should be checked that any kind of errors are generated then fix the errors.
- If any kind of errors are not generated then covered all the functionalities mentioned in the specification, the process is terminated.
- Each and every functionality is written and immediately tested is one of its advantages







Coding Guidelines

- The following are some representative coding guidelines
- Do not use a coding style that is too clever or too difficult to understand
- The code should be well-documented
- The length of any function should not exceed 10 source lines
- Do not use goto statements







The Types of Faults

Algorithmic	Logic is wrong Code reviews			
Syntax	Wrong syntax; typos Compiler			
Computation/ Precision	Not enough accuracy			
Documentation	Misleading documentation			
Stress/Overload	Maximum load violated			
Capacity/Boundary	Boundary cases are usually special cases			
Timing/Coordination	Synchronization issues Very hard to replicate			
Throughput/Performance	System performs below expectations			
Recovery	System restarted from abnormal state			
Hardware & related software	Compatibility issues			
Standards	Makes for difficult maintenance			







Code Review

- CodeReview is carried out after the module is successfully compiled and all the syntax errors have been eliminated.
- Code Reviews are extremely cost-effective strategies for reduction in coding errors and to produce high quality code.

Types of Reviews

Code Walk Through Code Inspection







Code Walk Through

- Code walk through is an informal code analysis technique.
- The main objectives of the walk through are to discover the algorithmic and logical errors in the code.
- A few members of the development team are given the code few days before the walk through meeting to read and understand code.
- Each member selects some test cases and simulates execution of the code by hand
- The members note down their findings to discuss these in a walk through meeting where the coder of the module is present.







Code Inspection

- The aim of Code Inspection is to discover some common types of errors caused due to improper programming.
- In other words, during Code Inspection the code is examined for the presence of certain kinds of errors.
 - For instance, consider the classical error of writing a procedure that modifies a parameter while the calling routine calls that procedure with a constant actual parameter.
 - It is more likely that such an error will be discovered by looking for these kinds of mistakes in the code.
 - In addition, commitment to coding standards is also checked.





Few Classical Programming Errors

- Use of uninitialized variables
- Jumps into loops
- Non terminating loops
- Array indices out of bounds
- Improper storage allocation and de-allocation
- Mismatches between actual and formal parameter in procedure calls
- Use of incorrect logical operators or incorrect precedence among operators
- Improper modification of loop variables







Software Documentation

- When various kinds of software products are developed, various kinds of documents are also developed as part of any software engineering process e.g.
 - Users' manual,
 - Software requirements specification (SRS) documents,
 - Design documents,
 - Test documents,
 - Installation manual, etc







Software Testing

Testing is the process of exercising a program with the specific intent of finding errors prior to delivery to the end user.

Don't view testing as a "safety net" that will catch all errors that occurred because of weak software engineering practice.







Who tests the Software?

Developer

Understands the system but, will test "gently" and, is driven by "delivery"

Testing without plan is of no point It wastes time and effort

Must learn about the system, but, will attempt to break it and, is driven by quality


Testing need a strategy Dev team needs to work with Test team, "Egoless Programming"

Teste





When to test Software?







Verification vs Validation

Verification Are we building the product right?

The objective of Verification is to make sure that the product being develop is as per the requirements and design specifications.

Validation Are we building the right product?

The objective of Validation is to make sure that the product actually meet up the user's requirements, and check whether the specifications were correct in the first place.





Verification

VS

Validation (Contd.)

- ☐ Process of evaluating products of a development phase to find out whether they meet the specified requirements.
- ☐ Activities involved: Reviews,
- **Meetings and Inspections**
- ☐ Carried out by QA team
- ☐ Execution of code is not comes under
- Verification
- ☐ Explains whether the outputs are according to inputs or not

- ☐ Process of evaluating software at the end of the development to determine whether software meets the customer expectations and requirements.
- ☐ Activities involved: Testing like black box testing, white box testing, gray box testing
- ☐ Carried out by testing team
- ☐ Execution of code is comes under Validation
- ☐ Describes whether the software is accepted by the user or not







Software Testing Strategy

Unit Testing	
	 It concentrate on each unit of the software as implemented in source code. It focuses on each component individual, ensuring that it functions properly as a unit.

Integration Testing									
	•	sof Int	ftware arc egration t	hite esti	cture ng is	e the proc	ess of te	nstruction of sting the or modules	
									1





Software Testing Strategy (Contd.)

Validation Testing	
	Software is validated against requirements established as a part of requirement modeling
	• It give assurance that software meets all
	informational, functional, behavioral and performance requirements.
System Testing	
	 The software and other software elements are tested as a whole
	 Software once validated, must be combined with
	other system elements e.g. hardware, people, database etc





Unit Testing

- Unit is the smallest part of a software system that is testable.
- It may include code files, classes and methods which can be tested individually for correctness.
- Unit Testing validates small building block of a complex system before testing an integrated large module or whole system
- The unit test focuses on the internal processing logic and data structures within the boundaries of a component.







- The module is tested to ensure that information properly flows into and out of the program unit
- Local data structures are examined to ensure that data stored temporarily maintains its integrity during execution
- All independent paths through the control structures are exercised to ensure that all statements in module have been executed at least once
- Boundary conditions are tested to ensure that the module operates properly at boundaries established to limit or restricted processing
- All error handling paths are tested.







- Component-testing (Unit Testing) may be done in isolation from rest of the system
- In such case the missing software is replaced by Stubs and Drivers and simulate the interface between the software components in a simple manner







- Let's take an example to understand it in a better way.
- Suppose there is an application consisting of three modules say, module A, module B & module C.
- Developer has design in such a way that module B depends on module A & module C depends on module B
- The developer has developed the module B and now wanted to test it.
- But the module A and module C has not been developed yet.
- In that case to test the module B completely we can replace







- Driver and/or Stub software must be developed for each unit test
- A driver is nothing more than a "main program"
 - It accepts test case data
 - Passes such data to the component and
 - Prints relevant results.
- Driver
 - Used in Bottom up approach
 - Lowest modules are tested first.
 - Stimulates the higher level of components
 - Dummy program for Higher level component







- Stubs serve to replace modules that are subordinate (called by) the component to be tested.
- A stub or "dummy subprogram"
 - Uses the subordinate module's interface
 - May do minimal data manipulation
 - Prints verification of entry and
 - Returns control to the module undergoing testing
- Stubs
 - Used in Top down approach
 - Top most module is tested first
 - Stimulates the lower level of components
 - Dummy program of lower level components







Metrics

 Metrics are quantitative measure that the software engineer to gain the efficiency of the process

Types of Measures

Size Measure **Complexity Measure**







Size Measure

Size oriented measure is derived by considering the size of software that has been produced.

Any organization builds a simple record of size measure for the software projects. It is built based on past experiences.

Set of size measure is given below:

- Size = Kilo Line of Code
- Effort = Person month
- Productivity = KLOC/Person-month
- Cost = \$/KLOC
- Quality = Number of faults / KLOC
- Documentation = Pages/KLOC

Size measure is based on line of code computation.





Complexity Measure

- If the complexity is measured in terms of line of code then it may vary from system to system.
- Complexity can be done by various methods such as cyclomatic complexity, Halstead measure and Knot count measure.
- Cyclomatic complexity
 - Independent path is any path through use of the program that introduces at least one new set of processing statements or a new condition.
 - Cyclomatic complexity is software metric that provides a quantitative measure of the logical complexity of a program.
 - It defines number of independent paths in the basis of set of program and provides us with an **upper bound for the number of tests that must be conducted to ensure all statements have been executed at least once.**





Cyclomatic Complexity

It can be computed 3 ways:

- The number of regions corresponds to cyclomatic complexity.
- Cyclomatic complexity V (G) can be defined as

$$V(G) = E-N+2$$

Where E is number of flow graph edges and N is the number of flow graph nodes.

Cyclomatic complexity V (G) can also be defined as

$$V(G) = P + 1$$

Where P is the number of predicate nodes contained in the graph.








Cyclomatic Complexity

```
V(G) = e - n + 2

Where
e is total number of edges
n is total number of nodes
```



The Cyclomatic complexity of the above module is

```
e = 10
n = 8
Cyclomatic Complexity = 10 - 8 + 2
= 4
```





Halstead Measure

- Halstead's theory of software science is one of "the best known and most thoroughly studied composite measures of (software) complexity".
- Software science assigns quantitative laws to the development of computer software, using a set of primitive measures that may be derived after code is generated or estimated once design is complete.







Halstead Measure (Contd.)

- These follow:
- n1= the number of distinct operators that appear in a program. n2= the number of distinct operands that appear in a program. N1= the total number of operator occurrences. N2= the total number of operand occurrences.

	Symbol	Formula
Program Length	N	N = N1 + N2
Program Vocabulary	n	n = n1 + n2
Volume	V	V = N * (log2n)
Difficulty	D	D = (n1/2) * (n2/2)
Effort	Е	E = D * V





Halstead Measure (Contd.)

Program Length

The length of a program is total usage of operators and operands in the program.

Length =
$$N1 + N2$$

Program vocabulary

The program vocabulary is the number of unique operators and operands used in the program.

Vocabulary
$$n = n1 + n2$$

Program Volume

The program volume can be defined as the maximum number of bits to encode the program.

Halstead shows that length N can be estimated





Knot Count

- Knot is a crossing of control flows. These crossings occur due to non-structural
- jumps in the program.
- Typically the goto statements cause this kind of non-structural jump. This metric is designed for FORTRAN language.
- If the knot is more intertwined then that means the program is more complex.
- The code with large knots is generally extremely difficult to read and understand.







Comparison of Different Metrics

Size measure	Cyclomatic Complexity	Halstead's measure	Knot count
 This is simple method of obtaining the metrics. It is based on lines of code. 	 This measure is based on the control flow of the programming constructs such as if then else, do-while, repeat-until and so on. 	 The measurable quantities of the program are operators and operands. 	 It is basically designed for the FORTRAN programs.
 Modules of the same size can have different complexities. 	 For larger number of decisions larger is the complexity. 	 It is based on length and volume of the program. 	 More number of knots indicates more complex in the program.

DIGITAL LEARNING CONTENT



Parul[®] University













