

Chapter-3

Network Defense tools


1. Firewalls and Packet Filters: Firewall Basics
2. Packet Filter Vs Firewall.
3. Firewall Protects a Network.
4. Packet Characteristic to Filter
5. Stateless Vs Stateful Firewalls
6. Network Address Translation(NAT) and Port Forwarding
7. The basic of Virtual Private Networks
8. Linux Firewall
9. Windows Firewall
10. Snort: Introduction Detection System

1. Firewalls and Packet Filters

1.1 Firewall Basics

A **firewall** is a security system that monitors and controls incoming and outgoing network traffic based on predefined security rules.

Firewalls and packet filters are essential network security tools that control incoming and outgoing traffic based on pre-defined rules. Packet filters (acting as the first line of defense) inspect individual packet headers—source/destination IP addresses, ports, and protocols—to allow or block traffic. While fast, they are basic, whereas modern firewalls (like stateful inspection) track connection states for better security.



1.2 Key Components and Concepts

- **[Packet Filtering Firewall] (First Generation):** Operates at the Network Layer (Layer 3) of the OSI model, acting as a gateway between internal and external networks.
- **Filtering Rules:** Decisions are made based on Access Control Lists (ACLs), which define permitted or denied traffic based on IP addresses, port numbers, and protocols.
- **Stateless vs. Stateful:**
 - **Stateless:** Examines each packet in isolation, making them fast but less aware of ongoing traffic context.
 - **Stateful:** Tracks the state of active connections, ensuring incoming packets are legitimate responses to internal requests.

1.3 Types of Firewall Technologies

- **Packet Filtering Firewall:** Basic, fast, low-cost; blocks/allows based on headers (IP/Port).
- **Application Gateways (Proxy Firewalls):** Operates at the application layer to inspect traffic for specific applications (e.g., HTTP, FTP).

- **Next-Generation Firewalls (NGFW):** Combines traditional firewall capabilities with additional functions like deep packet inspection, intrusion prevention systems (IPS), and application control.
- **Web Application Firewalls (WAF):** Specifically designed to protect web applications by filtering HTTP traffic and preventing attacks like SQL injection and cross-site scripting.

1.4 Limitations of Packet Filtering

- **No Payload Inspection:** Generally, they cannot analyze the actual content (payload) of the packet, only the header information.
- **Vulnerability:** Simple rules can sometimes be bypassed by malicious traffic that mimics legitimate protocol packets.
- **Internal Threats:** Firewalls, specifically packet filters, are usually positioned at the perimeter and may not protect against attacks originating from inside the network.

1.5 Common Use Cases

- Blocking all UDP traffic or restricting traffic to specific, secure ports (e.g., allowing port 443 for HTTPS).
- Protecting internal resources from external unauthorized access by filtering incoming traffic at the router level.
- Creating a DMZ (Demilitarized Zone) for public-facing servers.

1.6 Purpose of Firewall:

- Prevent unauthorized access to networks
- Block malicious traffic
- Allow legitimate communication
- Protect internal systems from external threats

1.7 Types of Firewalls:

- Hardware Firewall
- Software Firewall
- Cloud Firewall

2. Packet Filter Vs Firewall

A packet filter is a specific, foundational *type* of firewall. While a **firewall** is a broad security barrier that monitors and controls all network traffic, a **packet filter** is a basic mechanism within some firewalls that simply allows or blocks data based on superficial packet headers.

2.1. Packet Filter (The "Inspector")

Packet filters operate at the network layer (Layer 3) of the OSI model.

- **How it works:** It examines individual data packets in isolation and checks them against a static list of rules.
- **Criteria used:** Source and destination IP addresses, port numbers, and protocols.
- **Pros:** Extremely fast and cost-effective.
- **Cons:** Stateless (doesn't remember connection history) and blind to the actual payload, making it vulnerable to IP spoofing and malicious files hidden in safe traffic types.

2.2. Firewall (The "Security System")

A firewall is a broader umbrella term for a hardware or software system designed to block unauthorized access while permitting authorized communications.

- **Capabilities:** Firewalls can incorporate packet filtering but also utilize advanced features like stateful inspection (remembering connection states), proxy services, deep packet inspection, and user authentication.
- **Layer of Operation:** Can span from Layer 3 up to the Application Layer (Layer 7).
- **Pros:** Highly secure, capable of inspecting the contents/payload of traffic, and can thwart sophisticated application-layer attacks.
- **Cons:** More complex to configure and can introduce latency due to heavy processing

Feature	Packet Filter	Modern Firewall
Scope	A single filtering technique used <i>within</i> a firewall.	The entire network security system.
Data Inspected	Only headers (IP, Port, Protocol).	Headers + Payload (contents of the data).
Context Awareness	Generally examines each packet in isolation (stateless).	Tracks the context and state of an entire connection.
Security Level	Low to moderate.	High (stops malware, intrusions, and app-level threats).
Speed	Very fast.	Slower (due to deep inspection and processing).

Packet Filter vs Firewall

Feature	Packet Filter	Firewall
Definition	Filters packets based on header info	Complete security system controlling traffic
Decision Based On	IP address, port, protocol	Rules, sessions, application data
Complexity	Simple	Advanced
Security Level	Basic	Higher security

Packet filtering checks:

- Source IP address
- Destination IP address
- Source port
- Destination port
- Protocol type (TCP/UDP/ICMP)

A packet filter is usually a component of a firewall.

3.Firewall Protects a Network

A firewall is a network security system that establishes a barrier between a trusted internal network and untrusted external sources like the internet. It actively monitors, filters, and controls all incoming and outgoing data packets based on a strict set of predefined security rules.

3.1 How Firewalls Protect Networks

- **Unauthorized Access Block:** Acts as a gatekeeper, preventing hackers and unauthorized devices from infiltrating private networks.
- **Malware Prevention:** Blocks malicious code and viruses from entering the network and prevents compromised machines from spreading infections.
- **Traffic Monitoring:** Filters traffic by examining packet headers, analyzing data states, or utilizing proxy servers to ensure only safe connections pass through.
- **Data Exfiltration:** Monitors outbound traffic to prevent bad actors from moving sensitive internal data out of the network.

3.2 Types of Firewalls

- **Hardware Firewalls:** Physical devices positioned between the network and the internet, typically integrated into routers.
- **Software Firewalls:** Programs installed on individual computers or servers, such as native OS security like [Microsoft Windows Firewall](#).
- **Cloud Firewalls:** Virtual firewalls used for protecting cloud-based infrastructures and remote or distributed work environments.

3.3 How Firewall Protects a Network

Firewall protection works by:

1. Monitoring network traffic
2. Allowing trusted traffic
3. Blocking suspicious packets
4. Logging security events
5. Enforcing security policies

Example:

- Allow web traffic on port 80 and 443
- Block Telnet on port 23

This reduces exposure to attacks.

4. Packet Characteristic to Filter

4.1. Packet filtering evaluates network traffic against predefined rules, analyzing the header information of incoming and outgoing data packets to determine if they should be allowed or dropped. This rapid, layer-by-layer inspection relies primarily on the following core packet characteristics:

4.2. Key Packet Characteristics to Filter

- **Source and Destination IP Addresses:** Identifies the packet's origin and intended endpoint. You can filter to block traffic from untrusted IP addresses or restrict access to specific internal servers.
- **Port Numbers:** Acts as the logical "door" for network services. Filtering ports allows you to block insecure services (e.g., Telnet on port 23) while allowing authorized traffic (e.g., HTTP on port 80, HTTPS on 443).
- **Protocol Type:** Determines the transport method, such as TCP, UDP, or ICMP. Filtering protocols helps prevent network mapping (blocking ICMP) or block specific traffic types entirely.
- **Interface / Zone:** Applies rules based on which physical or virtual firewall interface the packet traverses (e.g., untrusted external internet vs. a secured internal LAN).
- **IP Flags & Options:** Inspects specialized flags in the packet header (like the SYN flag) to detect and block connection initiation requests or malformed packets.

Packet Characteristics to Filter

Packet filtering rules examine:

Network Layer Information

- Source IP
- Destination IP
- Protocol

Transport Layer Information

- Source port
- Destination port
- TCP flags

Other Characteristics

- Packet size
- Fragmentation
- Direction (inbound/outbound)

Example rule:

- Block all traffic from suspicious IP addresses

5. Stateless Vs Stateful Firewalls

Stateless and stateful firewalls differ primarily in how they process traffic: **stateless firewalls evaluate each packet in isolation** based on static rules, while **stateful firewalls track the entire context of a connection**. Stateless is faster and simpler, whereas stateful is highly secure and context-aware.



5.1 Stateless Firewalls

- **How it works:** Inspects packet headers (source/destination IP, ports, and protocols) against predefined Access Control Lists (ACLs) without remembering past traffic.
- **The "Two-Way Rule":** Because it has no memory, if a client inside your network requests a web page, you must manually write an ACL rule allowing the outbound request **and** a separate rule allowing the inbound response (which often hits random, high-numbered ephemeral ports).
- **Pros:** Extremely fast and highly lightweight. Ideal for high-speed core routing where simple 1:1 packet filtering is needed.
- **Cons:** Less secure. Attackers can craft malicious packets that look legitimate on their own to bypass rules.

5.2 Stateful Firewalls

- **How it works:** Maintains an internal "state table" of active connections. When a connection is initiated from the inside, it remembers the session and **automatically allows the return traffic**.
- **The "Smart" Bouncer:** It understands the lifecycle of a connection, from initial handshake to tear-down, enabling it to drop out-of-sequence packets and prevent complex attacks like TCP session hijacking.
- **Pros:** Highly secure and context-aware. It minimizes manual rule-writing because you generally only need to permit outbound traffic.
- **Cons:** Slower than stateless firewalls because tracking connections requires more CPU and memory.

Feature	Stateless Firewall	Stateful Firewall
Connection Tracking	No	Yes
Inspection Context	Packet-by-packet	Full session/context
Speed/Performance	Faster	Slightly slower
Security Level	Basic	Advanced
Configuration	Complex for dynamic traffic (requires explicit return rules)	Easier for standard traffic (automatically permits return flows)

Stateless vs Stateful Firewalls

Stateless Firewall

A stateless firewall checks each packet independently.

Characteristics:

- No memory of previous packets
- Fast processing
- Simple rules

Example:

- Allow packets to port 80

Advantages:

- Faster
- Lower resource usage

Disadvantages:

- Less secure

Stateful Firewall

A stateful firewall tracks active connections.

Characteristics:

- Maintains session table

- Monitors connection states

Example:

- Allows return traffic only for established sessions

Advantages:

- Better security
- Smarter filtering

Disadvantages:

- More memory and CPU required

6. Network Address Translation(NAT) and Port Forwarding

Network Address Translation (NAT) and port forwarding allow multiple devices on a private network to share a single public IP address to access the internet. NAT masks internal IP addresses (e.g., 192.168.x.x) for outbound traffic, while port forwarding opens specific paths for incoming traffic to reach services, like web servers or gaming hosts, inside the network

6.1 Network Address Translation (NAT)

- **Purpose:** Conserves IPv4 addresses by enabling a private network (LAN) to use one public IP address.
- **Mechanism:** When a device sends a request, the router replaces the private IP with its own public IP and assigns a unique port, storing this in a NAT table.
- **Return Traffic:** When the server responds, the NAT router uses the table to direct the packet back to the correct internal device

6.2 Port Forwarding

- **Purpose:** Allows external users on the internet to access a specific device or service inside a private network.
- **Mechanism:** A rule created on the router redirects incoming traffic on a specific public port to a specific internal IP address and port.
- **Examples:** Port 80 for web servers, 21 for FTP, or 25565 for Minecraft servers.

6.3 Key Differences and Interaction

- **NAT** is usually automatic for outgoing traffic (connections initiated from inside).
- **Port Forwarding** is a manual configuration required to allow incoming traffic (connections initiated from outside).
- **Limitations:** Port forwarding requires a dedicated public IP. If your ISP uses [CGNAT](#) (Carrier-Grade NAT), where many customers share one public IP, you cannot set up port forwarding.

NAT translates private IP addresses into public IP addresses.

Purpose

- Conserves public IP addresses
- Hides internal network structure
- Adds security layer

Types of NAT

1. Static NAT
2. Dynamic NAT
3. PAT (Port Address Translation)

Example: Private IP: 192.168.1.10 , Public IP: 203.45.10.5

Port forwarding redirects communication requests from one address/port to another.

Uses

- Hosting web servers
- Gaming servers
- Remote desktop access

Example:

- External Port 8080 → Internal Port 80

This allows outside users to access internal services.

7.The basic of Virtual Private Networks

A Virtual Private Network (VPN) creates an encrypted "tunnel" between your device and the internet, masking your IP address and securing data traffic from ISPs, hackers, and advertisers. It protects privacy on public Wi-Fi, bypasses geographical restrictions, and prevents ISP throttling.

7.1 Key Components of a VPN

- **Encryption:** Converts your data into unreadable code ("gibberish") in real time, making it useless to intercepted third parties.
- **Tunneling:** Routes your traffic through a secure pathway between your device and the VPN server.
- **IP Masking:** Hides your real location and IP address, substituting it with the IP address of the VPN server.

7.2 Main Benefits

- **Security on Public Wi-Fi:** Encrypts personal data (logins, banking) on unsecured networks in cafes or airports.
- **Privacy Protection:** Prevents ISPs and advertisers from monitoring browsing history.
- **Bypassing Geo-Restrictions:** Allows access to region-locked content by connecting to servers in different countries.
- **Remote Work:** Enables secure access to corporate internal networks from remote locations.

7.3 Common Use Cases

- **Remote Employees:** Accessing company resources securely.
- **Streaming Content:** Accessing streaming libraries not available in your home country.
- **Preventing Throttling:** Stopping ISPs from slowing down internet speeds based on activity (e.g., streaming).

7.4 Limitations

- **Speed:** Due to encryption overhead, connection speeds can sometimes be slower.
- **Not Total Anonymity:** While a VPN increases privacy, it does not make you entirely invisible to websites, especially if you log in to accounts.

A VPN creates a secure encrypted tunnel over public networks.

Functions

- Encrypts internet traffic
- Hides IP address
- Secures remote access

Benefits

- Privacy
- Secure remote work
- Bypass geo-restrictions

VPN Protocols

- PPTP
- L2TP
- IPSec
- OpenVPN
- WireGuard

8. Linux Firewall

A Linux firewall is a robust gatekeeper that monitors and filters network traffic based on predefined security rules. It is essential for protecting your system against unauthorized access, hacking bots, and data breaches.

The Linux kernel relies on the `Netfilter` framework to filter packets, but users interact with it through higher-level management tools. The three primary tools used across different distributions are:

1. UFW (Uncomplicated Firewall)

- **Best for:** Beginners, Ubuntu, Debian, and Linux Mint.
- **How it works:** Provides an incredibly easy-to-read command-line syntax for laymen.
- **Common commands:**
 - Check status: `sudo ufw status`
 - Enable firewall: `sudo ufw enable`
 - Allow incoming SSH: `sudo ufw allow ssh`

2. firewalld

- **Best for:** Red Hat-based systems (RHEL, Fedora, CentOS).
- **How it works:** Uses "zones" to establish trust levels for network connections (e.g., public, home, or work).
- **Common commands:**
 - Check active zones: `sudo firewall-cmd --get-active-zones`
 - Open a port permanently: `sudo firewall-cmd --zone=public --add-port=80/tcp --permanent`
 - Apply changes: `sudo firewall-cmd --reload`

3. iptables / nftables

- **Best for:** Advanced administrators and deep, granular network packet manipulation.
 - **How it works:** nftables is the modern standard superseding the legacy iptables. It interacts directly with the kernel to build complex rule sets.
-

. Linux Firewall

Linux systems commonly use:

iptables

Traditional Linux firewall tool.

Functions:

- Filter packets
- NAT
- Port forwarding

Example:


```
iptables -A INPUT -p tcp --dport 22 -j ACCEPT
```

Allows SSH traffic.

ufw (Uncomplicated Firewall)

Simplified firewall management.

Commands:

```
ufw enable  
ufw allow 80  
ufw status
```

Used mainly in Ubuntu.

firewalld

Dynamic firewall manager in Red Hat/CentOS.

Features:

- Zones
 - Runtime configuration
-

9. Windows Firewall

Windows Firewall is a built-in security application that protects your device by filtering network traffic. It evaluates incoming and outgoing data, blocking or allowing communication based on defined safety rules. It operates across three distinct profiles: **Domain** (work), **Private** (home), and **Public** (unsafe Wi-Fi).

9.1 Managing Your Settings

By default, the firewall is active and requires no manual tweaking. If you need to check or modify your settings:

1. Press Windows Key + I to open **Settings**.
2. Go to **Privacy & security** (Windows 11) or **Update & Security** (Windows 10).
3. Click **Windows Security** and select **Firewall & network protection**

9.2 Allowing Apps Through the Firewall

If a trusted app or game is blocked from accessing the internet, you can create an exception rather than disabling the firewall entirely:

1. In the **Firewall & network protection** menu, click **Allow an app through firewall**.
2. Click **Change settings** (you may need administrator credentials).
3. Check the box next to the app, or click **Allow another app** to browse for the file path.
4. Choose which networks (Private vs. Public) you want this rule to apply

9.3 Advanced Settings

For granular control (e.g., restricting specific ports, blocking outbound traffic to certain websites, or creating custom rules):

1. Search for wf.msc in the Windows Search bar and hit **Enter**.
 2. Use the left pane to navigate between **Inbound Rules**, **Outbound Rules**, and **Connection Security Rules**.
 3. Right-click the rule type to create a **New Rule** and follow the configuration wizard.
-

Built-in firewall in Microsoft Windows.

Features

- Inbound/outbound filtering
- Application blocking
- Domain/private/public profiles

Benefits

- Easy configuration
- Integrated with Windows Security

Configuration path:

- Control Panel → Windows Defender Firewall

Common rules:

- Allow HTTP/HTTPS

Block unwanted applications

10.Snort: Introduction Detection System

Snort is a powerful, free, and open-source Network Intrusion Detection and Prevention System (IDS/IPS) developed by Cisco. It monitors network traffic in real-time, analyzes data packets against a predefined set of rules, and alerts security teams or drops traffic when it identifies malicious patterns or suspicious activity

10.1 Core Features & Architecture

Snort performs three primary functions:

- **Packet Sniffer:** Captures and displays network traffic in real-time (similar to tools like tcpdump).
- **Packet Logger:** Saves network traffic to disk for offline analysis and debugging.
- **Intrusion Detection/Prevention (IDS/IPS):** Inspects traffic for threats like port scans, DoS attacks, malware, and buffer overflows, taking action based on the ruleset.

Internally, Snort operates in modular stages:

1. **Packet Decoder:** Prepares raw packets for processing.
2. **Preprocessors:** Normalizes traffic (e.g., reassembling fragmented packets) before evaluation.
3. **Detection Engine:** Matches the packets against the rules.
4. **Logging and Alerting:** Generates logs or sends alerts if a match occurs.

10.2 How the Rules Engine Works

Snort relies entirely on its rule-based language to detect threats. Rules are similar to firewall rules but focus on deep packet inspection. Every rule has two main components:

- **Rule Header:** Specifies the action (e.g., alert, log, pass), the protocol (TCP, UDP, ICMP), and the source/destination IPs and ports.
- **Rule Options:** Define specific criteria such as message strings, payload content, and the unique signature ID (SID).

Example Snort Rule:

```
alert tcp any any -> $HOME_NET 21 (msg:"FTP Authentication Attempt"; sid:10003; rev:1;)
```

10.3 Deployment Modes

- **IDS Mode:** Sits passively on a network switch (usually spanning ports) to monitor traffic. If a malicious packet is detected, it logs the event but does not block the traffic.
- **IPS Mode:** Deployed "inline" (typically as a choke point between the router and the firewall), where it can actively drop or reject malicious packets before they enter the network

Snort: Intrusion Detection System (IDS)

Snort is an open-source Network Intrusion Detection and Prevention System.

Snort

Functions

- Packet sniffing
- Packet logging
- Intrusion detection
- Intrusion prevention

Snort Modes

1. Sniffer Mode

Reads packets and displays them.

2. Packet Logger Mode

Logs packets to disk.

3. IDS Mode

Analyzes traffic using rules.

Snort Rule Structure

Example:

```
alert tcp any any -> 192.168.1.0/24 80
```

Meaning:

- Alert on TCP traffic to internal web server

Advantages of Snort

- Open source
- Real-time detection
- Custom rules
- Protocol analysis

Limitations

- Requires tuning
- Can generate false positives

11.Importance of Network Defense Tools

Network defense tools are critical for safeguarding digital assets against unauthorized access, data breaches, and cyber attacks. They ensure business continuity, maintain customer trust, and protect sensitive information. Without these tools, organizations risk severe financial losses, operational downtime, and regulatory penalties.

11.1 Core Benefits of Network Defense

- **Data Protection:** Secures confidential customer information, financial records, and intellectual property from leaks or theft.
- **Downtime Prevention:** Mitigates the impact of attacks like ransomware and DDoS, preventing costly network shutdowns and operational interruptions.
- **Regulatory Compliance:** Assists organizations in meeting strict industry mandates such as GDPR, HIPAA, and PCI-DSS.
- **Secure Remote Access:** Facilitates safe, encrypted connections (e.g., via VPNs and Firewalls) for hybrid and remote workforces.

11.2 Essential Types of Defense Tools

Implementing a *defense in depth* strategy—where multiple, overlapping security layers are utilized—is the gold standard for network security. This relies on several key technologies:

- **Firewalls:** Act as the primary gatekeepers, establishing a strict barrier between trusted internal networks and untrusted external environments (like the internet).
- **Intrusion Detection and Prevention Systems (IDPS):** Continuously monitor network traffic to identify suspicious activities or policy violations, proactively blocking threats before they escalate.
- **Virtual Private Networks (VPNs):** Encrypt data transmitted over the internet, allowing remote users to connect securely to corporate networks.
- **Endpoint Detection and Response (EDR):** Monitors devices (laptops, smartphones, servers) connected to the network to detect and mitigate malicious activities on the endpoints themselves.

Importance of Network Defense Tools

These tools help:

- Prevent cyberattacks
- Detect malicious traffic
- Protect confidentiality
- Ensure availability
- Maintain network security policies

Summary

Network defense tools include:

- Firewalls
- Packet filters
- NAT
- Port forwarding

- VPNs
- Linux/Windows firewalls
- IDS tools like Snort

Together, they provide layered security for networks.

Parul[®] University | **NAAC** **A++**
Vadodara, Gujarat | **GRADE**



<https://paruluniversity.ac.in/>