

Novosibirsk State University
*THE REAL SCIENCE

MATHEMATICAL CENTER IN AKADEMGORODOK

Uncertainty and Hallucinations in Large Language Models

Ivan Bondarenko

Novosibirsk State University

* A few words about me

- 2006 - 2013 **DonNTU**: taught students neural networks
- 2013 - 2014 **GlobalLogic**: developed with C/C++
- 2014 - 2018 **2GIS**: was analyzing data with Python
- 2018 - 2020 **MIPT / Data Monsters**: researched chat-bots
- 2020 - 2022 **Huawei**: developed Apache Spark based AutoML framework
- 2015 - … **NSU**: teach, research and inspire the ML team
- 2023 - … **Siberian Neuronets**: build a startup for conversational AI

* Real-World Distributional Shift

- ★ computer vision
- ★ natural language processing
- ★ tabular data processing

…

* What difference between caw and camel?

* Cow on sandy beach?



?

* Brief note about uncertainty

Total uncertainty

=

Aleatoric uncertainty

+

Epistemic uncertainty

* Epistemic uncertainty

The model **simplistically** reflects reality.

The training data **is not enough to correctly estimate** the model parameters.

* Ensembles of algorithms. Why they work?

$$H\left(A \middle| X_1, \ldots, X_N\right) \leq H\left(A \middle| X_1, \ldots, X_{N-1}\right)$$

* Ensembles of algorithms. Why they model the epistemic uncertainty?



* Ensembles of algorithms. Why they model the epistemic uncertainty?



* Ensembles of algorithms. Why they model the epistemic uncertainty?



* Bayesian NN as approximation of deep ensemble



The illustrations are based on the paper "**A Comprehensive guide to Bayesian Convolutional Neural Network with Variational Inference**", published at arXiv in 2019: https://arxiv.org/pdf/1901.02731.pdf

* Bayesian Inference in NN using *P*(*w*|*D*)

$$P(\hat{y} \mid \hat{x}) = M_{P(w|D)}[P(\hat{y} \mid \hat{x}, w)]$$

This is equivalent to an infinite ensemble of neural networks with each possible configuration of the weights

* Language Models with Autoregressive Decoder



The illustration is based on the paper "**Sequence to Sequence Learning with Neural Networks**", published at proceedings of NIPS in 2014: https://research.google/pubs/sequence-to-sequence-learning-with-neural-networks

* Attack Example on Autoregressive Language Model

Milad Nasr, *Nicholas Carlini* et al. (2023)

Scalable Extraction of Training Data from (Production) Language Models

arXiv:2311.17035



* What difference between error and hallucination?

An error is a grammatical mistake:

1. Undergeneration

   A neural network is an effe **What's next?**

2. Morphological inaccuracies

   *Neur**on** networks **is** an effective approach to artificial intelligence*

* What difference between error and hallucination?

A hallucination is a semantic or pragmatic mistake:

1. Repetition

   A neural network is ***is is is is is is is***

2. Answer with the correct syntax and morphology, but **meaningless**

   Question: *What is a neural network?*

   Answer: *Support vector machine are a type of binary classification algorithm based on supervised learning.*

* Connection between hallucinations and LLM training

There are two states of LLM training:

1. Self-supervised pre-training
2. Supervised fine-tuning

* Self-supervised pre-training



The illustration is based on the paper "**BART: Denoising Sequence-to-Sequence Pre-training for Natural Language Generation, Translation, and Comprehension**", published at Annual Meeting of the Association for Computational Linguistics in 2019: https://aclanthology.org/2020.acl-main.703.pdf

* Supervised fine-tuning

For example, fine-tuning for a **machine translation** task:

Подожди, ты это серьёзно?

Excuse me, you're serious?

* Self-supervised pre-training: grammatical or semantic?



Examples of meaningless synthetic texts (in Russian):

1. либерализуем мы хоронив между согреваньем
2. не предо календариком обкидавши и я измыслить укрощать поглубже б желал
3. и вы исключительно устыдив собираетесь фырчать милитаризировавши
4. почти затупив не виноватого сто первого преуспевания почти гриппуя шестиклассник с краснознаменском дидактиков

* Evaluation of “synthetically” pre-trained LLM

Russian SuperGLUE

Testing methodology is based on tasks, typically proposed for “strong AI”:

- logic,
- commonsense,
- reasoning.



Tatiana Shavrina, Alena Fenogenova, Anton Emelyanov, Denis Shevelev, Ekaterina Artemova, Valentin Malykh, Vladislav Mikhailov, Maria Tikhonova, Andrey Chertok, Andrey Evlampiev
RussianSuperGLUE: A Russian Language Understanding Evaluation Benchmark
Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)

* Russian SuperGLUE results

Task	Natural RoBERTa	**Synthetic RoBERTa**	Metric
LiDiRus	0.0	0.0	Matthews Coefficient
RCB	0.217 / 0.484	0.091 / 0.158	F1 / Accuracy
PARus	0.498	0.502	Accuracy
TERRa	0.487	0.487	Accuracy
RUSSE	0.587	0.587	Accuracy
RWSD	0.669	0.331	Accuracy

* Connection between hallucinations and LLM training

There are two states of LLM training:

1. Self-supervised pre-training
    - **grammar is learned** to a greater extent
2. Supervised fine-tuning
    - **semantics is learned** to a greater extent

* Connection between hallucinations and LLM training

There are two states of LLM training:

1. Self-supervised pre-training
    - **grammar is learned** to a greater extent
    - tens of **millions** of texts
2. Supervised fine-tuning
    - **semantics is learned** to a greater extent
    - tens of **thousands** of texts

* What is hallucination?

This is a distributional shift applied to LLM, i.e. a semantic shift!

Опять я проспал! (I overslept again!)

I woke up again! (Я снова проснулся!)

* How to detect hallucinations?

SemEval-2024 Task-6 - **SHROOM**, a **S**hared-task on **H**allucinations and **R**elated **O**bservable **O**vergeneration **M**istakes

https://helsinki-nlp.github.io/shroom/2024

* How to detect hallucinations?

Three tasks:

1. Machine translation
2. Paraphrase generation
3. Definition modeling

* How to detect hallucinations?

When a model hallucinates, it doubts! Epistemic uncertainty can help us:

Hallucination	$\log(P_{seq})$
Yes	-0.63245
No	-0.54833

* How to detect hallucinations?

When a model hallucinates, its response doesn't match the context!

Hallucination	**BERT score (F1)**
Yes	0.88413
No	0.90118



* How to detect hallucinations?

Train a classifier that detects semantic mismatches *



The verified system's task is a paraphrase generation. The sentence generated by the verified system: ***Where'd all the kids go to?*** *The generation context:* ***Where did everybody go?***

* https://huggingface.co/bond005/xlm-roberta-xl-hallucination-detector

* How to detect hallucinations?

Feature importances

Semantic mismatching features

Epistemic uncertainty features



* How to detect hallucinations?

SHROOM results (model-aware track)

Rank	Team name	Accuracy
1	HaRMoNEE	0.813
10	DeepPavlov	0.799
29	**SibNN**	**0.768**
-	baseline	0.745
44	Skoltech	0.557
46	octavianB	0.483

* How to detect hallucinations?

SHROOM results (model-agnostic track)

Rank	Team name	Accuracy
1	GroupCheckGPT	0.847
6	DeepPavlov	0.821
28	**SibNN**	**0.770**
-	baseline	0.697
39	Skoltech	0.684
49	OxYuan	0.461

* How to detect hallucinations?

SemEval-2024 Task-5 - **Mu-SHROOM**, a **Mu**ltilingual **S**hared-task on **H**allucinations and **R**elated **O**bservable **O**vergeneration **M**istakes

https://helsinki-nlp.github.io/shroom

* How to detect hallucinations?

Mu-SHROOM results (for Chinese)

Rank	Team name	IoU
1	YNU-HPCC	0.553971
2	LCTeam	0.523231
3	**nsu-ai**	**0.493722**
4	DeepPavlov	0.490002
-	Baseline (mark all)	0.477155
26	FENJI	0.037113

N*

* Conclusions

1) **hallucinations** are related with **"semantics" shifts** in LLMs
2) epistemic **uncertainty** modeling for LLM is **theoretically sound**, but it is **less effective in practice** than expected
3) **semantic mismatch** detection using an external model **is effective**

* A little bonus :)

LLM-based dialogue system about Novosibirsk State University:

https://t.me/meno_nsu_bot

*

Thank you for attention!

N*