Modeling Angiogenesis in Hypoxic Breast Cancer Tumors

Kali Konstantinopoulos¹, Timothy Mahajan¹, Furkan Kurtoglu¹, John Metzcar¹, Daniele Gilkes², Paul Macklin¹

- 1) School of Informatics, Computing, and Engineering, Indiana University
- 2) School of Medicine, John Hopkins University

Introduction

- Hypoxic conditions occur in the center of tumor after tumor cells use and deplete oxygen.
- Hypoxic cells secrete signaling chemicals to induce vascularization, such as vascular epithelial growth factor (VEGF).


Methods


- This model is developed with using agentbased multicellular system simulator which is called PhysiCell¹.
- Cells are changing behavior according to oxygen level. After they become hypoxic, their genes are regulated.
- Our model accounts for this vascularization by increasing VEGF secretion by hypoxic cells.
- Vasculature is controlled by three mechanisms, which are grow, death, and advective flux.
- Blood supplies or uptakes metabolites from microenvironment according to blood target values.


Advective Flux:
$$\mathbf{J} = \mu_{\mathbf{v}} \mathbf{v}_{\mathbf{m}} \rho_{\mathbf{v}} \frac{\nabla \mathbf{a}}{\parallel \nabla \mathbf{a} \parallel}$$

$$\mathbf{S} = \beta \mathbf{b}_{\mathbf{v}} (1 - \frac{\rho_{\mathbf{v}}}{\overline{\rho}_{\mathbf{v}}}) \rho_{\mathbf{v}} - \mathbf{d}_{\mathbf{v}} \frac{\nabla \mathbf{a}}{\overline{\rho}_{\mathbf{t}}}$$

Results









was an expected behavior in order


Cellular layering is formed as:


Tumor has a necrotic core that has

nearly no oxygen.









Future Work

- This model will be uploaded to NanoHUB to be able to run in cloud with user interface².
- Also, angiogenesis will be an external module that can be added to simulation which will be build in NanoHUB.

Acknowledgements

- National Science Foundation (Award 1720625),
- National Institutes of Health (U01-CA232137-01),
- **Breast Cancer Research Foundation**
- Jayne Koskinas Ted Giovanis Foundation for Health and Policy.

References

[1] PhysiCell: An open source physics-based cell simulator for 3-D multicellular systems. Ghaffarizadeh A, Heiland R, Friedman SH, Mumenthaler SM, Macklin P. PLOS Computational Biology 14(2): e1005991. doi: 10.1371/journal.pcbi.1005991 (2018)

[2] xml2jupyter: Mapping parameters between XML and Jupyter widges. Heiland R, Mishler D, Zhang T, Bower E, Macklin P. bioRxiv 601211; doi: 10.1101/601211 (2019)

[3] Experimental and computational analyses reveal dynamics of tumor vessel cooption and optimal treatment strategies C Voutouri, N D. Kirkpatrick, E Chung, F Mpekris, J W. Baish, L L. Munn, D Fukumura, T Stylianopoulos, R K. Jain: PNAS: https://doi.org/10.1073/pnas.1818322116



