


Compressive MR Fingerprinting Reconstruction with Neural Proximal Gradient Iterations (*accepted to MICCAI'20*)



Dongdong Chen¹ (d.chen@ed.ac.uk), Mike E. Davies^{1,2}, Mohammad Golbabaei²

¹ School of Engineering, the University of Edinburgh, ²Department of Computer Science, University of Bath



Bloch responses
Signal
Repetition time
Subsampled Fourier transformation
MRF image x

$$y = H(x) + \xi \quad \text{where, for each voxel } x_v \approx \rho_v \mathcal{B}(T1_v, T2_v)$$

$$\arg \min_{x, m} \|y - Hx\|_2^2 + \phi(x, m)$$

$$\text{PGD} : \begin{cases} g^{(t+1)} = x^{(t)} + \alpha^{(t)} H^H (y - Hx^{(t)}) \rightarrow \text{Gradient with step size } \alpha \\ \{x^{(t+1)}, m^{(t+1)}\} = \text{Prox}_\phi(g^{(t+1)}) \rightarrow \text{Proximal update} \end{cases}$$

Deep Neural Network

$$\text{Prox} := \text{BLOCH} \circ \mathcal{G}$$




Table 1: Average errors (NRMSE, SSIM, MAE), memory (for storing a dictionary or a network) and runtimes (per image slice) required for computing T1, T2 and PD maps using the MRF baselines and our PGD-Net algorithm.

	NRMSE			SSIM			MAE (msec)			time (sec)		memory (MB)
	T1	T2	PD	T1	T2	PD	T1	T2	PD	T1	T2	
FGM	0.475	0.354	1.12	0.614	0.652	0.687	350.0	14.6	1.29			8.81
BLIP+FGM	0.230	0.545	0.073	0.886	0.880	0.984	91.7	8.0	79.28			8.81
MRFCNN	0.155	0.158	0.063	0.943	0.972	0.987	80.3	5.4	0.083			4.72
SCQ	0.172	0.177	0.064	0.929	0.967	0.984	91.7	6.1	0.132			464.51
\mathcal{G} (encoder alone)	0.142	0.155	0.065	0.948	0.973	0.987	77.1	5.6	0.067			0.55
PGD-Net ($T=2$)	0.104	0.138	0.050	0.973	0.979	0.991	59.9	5.0	0.078			0.57
PGD-Net ($T=5$)	0.100	0.132	0.045	0.975	0.981	0.992	50.8	4.6	0.103			0.57

The proposed PGD-Net:

- ❑ **State-of-the-art MRF reconstruction**
- ❑ **Interpretable and Physics-engaged**
- ❑ **Cheaper computation**
- ❑ **Cheaper memory**




Figure 1: T1 (sec), T2 (sec), T1 error, T2 error, PD (a.u.), PD error. Color bars indicate the scale for each map.