

Tenure sandbox — HERO + F-HERO (exploratory)

Purpose: Tenure-domain hero readouts on Mac, parallel to MBB `../sports_sandbox/`.

Campaign plan (print this): `TENURE_HERO_Campaign_Plan.md`

Pipeline map (MBB mirror): `TENURE_hero_pipeline.md`

Living thread: `_DISPOSABLE_tenure_hero_thread.md` — say `anchor` in chat for YOU ARE HERE.

Perf / pool spec fork: `tenure_perf_metrics_discussion.md`

Data handoff: `../20260901_PEER_to_COMPASS_tenure_hero_mac_handoff.md`

Layout

```
tenure_sandbox/  
  README.md           ← this file  
  TENURE_HERO_Campaign_Plan.md ← print stack #1  
  TENURE_hero_pipeline.md  
  _DISPOSABLE_tenure_hero_thread.md  
  hero/               ← Pass A HERO outputs  
  fhero/              ← F-HERO (later)  
  basic_data_plots/   ← porch BDPs + TENURE_BDP_slides_AUTO.pptx
```

Input (not in this folder): `tenure/tenure_pipeline/faculty_panel_with_pools.jsonl`

Script: `tenure/scripts/tenure_pass_a_hero.py`

v0 lock (summary)

Item	Value
Filter	HIGH/MEDIUM OpenAlex; non-null LOO on assistant rows
Grain	Person-level mean <code>poolq_loo_mean</code>
Bins	16 quantile
Y	Tenure rate among resolved (tenure + attrition); censored excluded
ρ	Diagnostic in Act III — not parked unless data say so

Filename tokens (v0)

Example: `HERO_tenure_q16_infHM_resolved_v0.png`

Token	Meaning
<code>tenure</code>	Domain
<code>q16</code>	16 quantile LOO bins
<code>infHM</code>	Inference filter HIGH + MEDIUM
<code>resolved</code>	Rates use resolved denominator (Option A)

Each PNG should have matching `*_binned.csv` and `*_provenance.json`.

Run (after script lands)

```
# repo root – HERO  
python tenure/scripts/tenure_pass_a_hero.py  
python tenure/scripts/tenure_pass_a_hero.py --n-bins 20 --output-tag q20_loo_infHM # dip robustness  
  
# porch basic data plots + slides  
python tenure/scripts/tenure_basic_plots.py  
python tenure/scripts/build_tenure_basic_plots_slides.py
```

Outputs → `hero/` and `basic_data_plots/` under this folder.