

Comment	Description	Designator	Footprint	LibRef	Quantity
Constant Voltage Source	Constant Voltage Source	BH1	HDR1X2	Battery	1
ESP32DEVKITV1	Dual core, Wi-Fi: 2.4 GHz up to 150 Mbits/s, BLE (Bluetooth Low Energy) and legacy Bluetooth, 32 bits, Up to 240 MHz	BOARD1	ESP32-DEVKITV1	ESP32DEVKITV1	1
Step Down Buck DC DC 3A		BOARD3	Step Down Buck DC DC 3A	Step Down Buck DC DC 3A	1
Resistor_1	Resistor	BSR1	Smd Resistor	Resistor_1	1
	Resistor	BSR2	Smd Resistor	Resistor_2	1
	Diode	DFB1	Smd Thermistor Terminal	Diode	1
LoraWAN Radioenge		Lora1	LORAMESH	LoraWAN Radioenge	1
Panel+Servo	Header, 5-Pin	PH1	HDR1X5	Header 5	1
	Resistor	PR1, PR2, PR3	1/4W SMD Resistor	Resistor	3
Push Button Normally Opened	Push Button Normally Opened	S1, S2	Smd Push Button (Extended Legs)	Push Button NO	2
Thermistor		TH1	Smd Thermistor Terminal	Thermistor	1
Resistor_3	Resistor	TR1	Smd Resistor	Resistor_3	1