

Model

IES-BATT-157R



[Overview]

Indoor battery rack with IP20 protection level,
inbuild lithium-ion battery and BMS

[Easy Installation And Maintenance]

Local and remote management, standard
rack&module design, front maintenance

[Safety & Reliable]

Self-developed 2-level / 3-level BMS,
complex protection, safe and reliable

[High Density]

LP high-capacity Li-ion battery with aluminum
shell, over 130wh/kg

[Long Lifespan]

Long cycle life, 8000 cycles *

[Cell Balancing Technology]

Active cell balancing and passive cell
balancing

CE UN38.8



IES

INFINITE | ENERGY | STORAGE

DATASHEET

Model	IES-BATT-157R
-------	---------------

Performance

Battery module (Wh/V)	14.336 kWh, 51.2 V, 110 kg (242.5 lbs)
Number of modules	11
Cell technology	LFP (LiFePO4)
Battery usable energy [1]	157.696 kWh
Nominal voltage	563.2 V
Operating voltage	501.6–617.76 V
Nominal output current	140 A / 280 A

Communication

Display	SOC status indicator, LED indicator, LCD display
Communication	Ethernet / CAN / RS485

General Specification

Dimension (W*D*H)	1721x840x1776 mm
	66.8x33.1x69.9 inch
Weight	1540kg (3395lbs)
Operating temperature [2]	–20 to 60 °C (–4 to 140 °F)
Environmental humidity	≤ 95%RH (No condensation)
Protection rating	IP 20
Cycle life [3]	8000 Cycles @ 80% DOD / 25°C / 0.5C, 70% EOL
Scalability	Yes
Application	ON Grid / ON Grid + Backup / OFF grid
Compatible PCS	Refer to compatible PCS list

Standard Compliance

Certificates	Cell: UN38.3 / IEC62619 / UL 1642 / JET
	Pack: UN38.3 / IEC62619 / IEC61000
	System: UL 9540 (More available upon request)

Ordering and Deliverable Part

Part	IES-BATT-14.3P-F-OT
	IES-BATT-BCU-157H1-OT
	IES-BATT-R18

[1] Test conditions: 100% depth of discharge (DoD), 0.2C rate charge & discharge at 25°C

[2] Charge/discharge derating occurs when the operating temperature from –10°C to 5 °C & 45 °C to 55 °C

[3] Condition apply. Refer to Warranty Letter

CE UN38.8

