



Tel: 021 555 2181
Website: solar.md.com

Solar MD HV Range Overview

Model / Technical Data	SS7011	SS7013	SS7014	SS7016	SS7017	SS7019	SS7020	SS7021	SS7023	SS7024
Cell Chemistry	Lithium Iron Phosphate (LiFePO4)									
Cell Manufacturer	Contemporary Amperex Technology Co. Limited (CATL)									
Nominal Voltage	409.6V	460.8V	512V	563.2V	614.4V	665.6V	716.8VDC	768V	819.2V	870.4V
Operational Voltage	358.4 - 444.8VDC	403.2 - 500.4VDC	448 - 556VDC	492.8 - 611.6VDC	537.6 - 667.2VDC	582.4 - 722.8VDC	627.2 - 778.4VDC	672 - 834VDC	716.8 - 889.6VDC	761.6 - 954.2VDC
Rated Capacity	114.4 kWh	128.7 kWh	143 kWh	157.3 kWh	171.6 kWh	185.9 kWh	202.2 kWh	214.5 kWh	228.8 kWh	243.1 kWh
Useable @0.3C	104 kWh	117 kWh	130 kWh	143 kWh	156 kWh	169 kWh	182 kWh	195 kWh	208 kWh	221 kWh
Nominal Power	80 kW	90 kW	100 kW	110 kW	120 kW	130 kW	140 kW	150 kW	160 kW	170 kW
Cycle Life @25°C	>6000									
Modules	8	9	10	11	12	13	14	15	16	17
Opertational Temp.	-5°C to +50°C									
Storage Duration	6 months @ 25°C									
Efficiency	99%									
Transport	UN3480 & UN38.3									
Weight	985 kg	1100 kg	1220 kg	1335 kg	1452 kg	1573 kg	1700 kg	1815 kg	1940 kg	2055 kg
Dimensions	848 x 704 x 1245 mm		848 x 704 x 1490 mm		848 x 704 x 1976 mm				848 x 704 x 2221 mm	
Module Enclosure	Black powder coated steel encl.									
Comms Type	CAN/RS485/Ethernet									
Interface	Multicolor LED and BMS indicator									
Safety Standard	Battery -IEC62619 / UN38.3 / UL1642									
Cell Certificate	Cell -TUV / CE / RCM / UL1642									
Warranty	Cells: 12 years Workmanship: 5 years									