

INTEGRATED ANTI-SPOOFING AND DEEPFAKE DETECTION SYSTEM USING MOBILENET AND ResNeXT

Mathan Sri Prasath E¹

Department of Computer Science
and Engineering
Panimalar Engineering College
mathanelango72@gmail.com

Mahesh Kumar D²

Department of Computer Science
and Engineering
Panimalar Engineering College
maheshdhasaradhan@gmail.com

Naveen G V³

Department of Computer Science
and Engineering
Panimalar Engineering College
naveenvenkatachalam1@gmail.com

Dr. Hariharan S⁴

Professor
Department of Computer Science
and Engineering
Panimalar Engineering College
hari2418@gmail.com

Abstract - This paper introduces an integrated system for spoofing attack detection and deepfake video mitigation is presented, which deals with serious security issues in biometric verification and visual content. Spoofing attacks involve fake biometric information, e.g., images or videos, to fool systems, whereas deepfakes employ sophisticated AI methods for constructing highly realistic manipulated videos for malicious intent. The system integrates the light MobileNet architecture for real-time anti-spoofing detection with the strong feature extraction ability of ResNeXt for deepfake detection in a single framework for end-to-end visual threat mitigation. MobileNet is utilized to identify liveness indicators, including eye blinks and minor facial movements, for efficient and fast anti-spoofing detection appropriate for real-time applications. The ResNeXt architecture is used to examine deepfake videos based on its deep architecture, which identifies minor inconsistencies and artifacts, like unbalanced lighting or forced expressions. Both modules are trained on large, varying datasets like ASVspoof, FaceForensics++, and the Deepfake Detection Challenge so that they have a high degree of accuracy and can generalize across different attack methods. The novelty of the system comes in combining anti-spoofing and deepfake detection into a scalable real-time system. By overcoming current framework limitations, it improves safe access control, identity authentication, and content moderation. By exploiting MobileNet's efficiency and ResNeXt's strength, this project highlights the power of state-of-the-art machine learning for end-to-end visual security.

I INTRODUCTION

The Growing sophistication in deepfake technology and biometric spoofing is an important security threat. Deepfakes allow identity impersonation, spreading misinformation, and public manipulation, making them a significant ethics and security threat. At the same time, biometric spoofing compromises authentication through the use of artificial biometric information, e.g., images, videos, or 3D masks, to access unauthorized systems. Such threats compromise the trustworthiness of facial recognition and biometric security systems used extensively in financial transactions and identity authentication. Various limitations affect current detection

techniques. Deepfakes are now so realistic that they are hard to detect, while most detection models fail to generalize across various manipulations. Secondly, the majority of anti-spoofing measures are computationally costly, thus having limited real-time applicability. Thirdly, security systems tend to counter deepfake detection and biometric spoofing in isolation, leaving loopholes for exploitation by attackers. With a view to overcoming these shortcomings, Secure Vision proposes an end-to-end deep learning framework with MobileNet for real-time biometric spoofing detection and ResNeXt for analyzing deepfake videos. MobileNet costs less while detecting liveness indicators, including eye blinking and micro-movements of the face, to provide strong authentication. ResNeXt, an enhanced CNN, examines deepfaked videos through the detection of artifacts and inconsistency that are signals of deepfake creation. Fusing these models into a consolidated framework, Secure Vision offers an end-to-end, efficient, and adaptive mechanism for enhancing digital identity authentication and content verification.

II LITERATURE SURVEY

[1]. In this research, the application of MobileNetV3-Spoof with pre-processing and fine-tuning approaches to design light-weight face anti-spoofing systems is investigated, with a focus on the effects of face detection, generalization from datasets, and efficiency-accuracy trade-offs in the detection of physical and digital spoofing attacks.[2]. The research reveals how inconsistencies in iris artifacts and eye movements in manipulated videos can be used as good indicators for detecting deepfakes. They used a CNN-based method to examine these discrepancies and discovered that features based on irises are more accurate compared to conventional detection methods. The model was tested using benchmark datasets and exhibited excellent performance.[3]. The method promotes spatial feature extraction, enabling the model to effectively localize manipulation artifacts. The model is trained and tested on the FaceForensics++ and DFDC datasets and exhibits superior accuracy compared to conventional CNN models. The research observes that although the model is good at performing on known datasets, generalizing to unobserved deepfake types is still challenging. [4]. The paper emphasizes the capture of temporal dynamics and abnormal facial expressions in deepfake videos. Their experiment showed that temporal analysis improve

accuracy in detection compared to static image-based approaches. [5]. Their work discusses how spoofed videos have frame-wise distortions and abnormal facial movements. The paper concludes that spatial and temporal analysis fused together tremendously boosts deepfake detection performance. [6]. Their result shows that humans use contextual signals, while AI models capture pixel-level discrepancies and artifacts. It is inferred in the study that hybrid human-AI detection frameworks can outperform single machine models. [7]. They used CNNs to extract features and Transformers for processing temporal sequences in order to enhance detection performance. The research illustrates that it is more challenging to detect poor-quality deepfakes, hence the importance of diversity in the datasets for model training. The authors observe that their approach demands high computational power, precluding real-time deployment. [8]. Transfer learning is seen to greatly enhance accuracy and lower training time by their research. The model generalizes across many datasets but does not perform well when used for low-resolution deepfake videos, indicating the requirement for resolution-independent training methods. [9]. The study highlights explainability and adversarial robustness as key research challenges. They suggest that future developments should incorporate interpretable AI and self-supervised learning to improve deepfake detection accuracy and adaptability. [10]. Their research proves that deepfake videos' high-frequency artifacts are still detectable even when compressed. The method is post-processing attack resilient but has the drawback of increasing complexity, thus impacting inference speed. [11]. Their technique performs well on benchmark datasets but falters against GAN-created deepfakes with improved transitions. The authors recommend adding temporal features to enhance performance. [12]. Adversarial training methods enhance robustness to changing deepfake techniques. [13]. Multi-modal systems with image and audio inputs boost deepfake detection through the identification of inconsistencies in both visual and auditory features. [14]. An associated method checks facial movements and speech patterns concurrently for enhanced accuracy. [15]. Ensemble learning combines multiple detection models to reduce false positives and negatives, increasing overall reliability. [16]. New datasets like Celeb-DF help benchmark deepfake detection methods by providing high-quality, realistic manipulated videos. They challenge models to detect deepfakes with smoother transitions and fewer artifacts. This improves detection accuracy and ensures robustness against advanced deepfake techniques. [17]. A specialized dataset aims at detecting manipulated content in news programs to fight misinformation. It assists in training models to detect deepfake videos, manipulated audio, and fake media employed in deceptive reports. This improves the credibility of news verification systems and enhances media authenticity. [18]. Meta-learning improves deepfake detection by allowing models to learn from fewer samples, enhancing efficiency and minimizing data dependency. It enables fast adaptation to novel and emerging deepfake methods, providing resilience to unknown manipulations. This strategy improves generalization, leading to more effective detection models in the real world. [19]. Cross-domain deepfake detection is still challenging with differences in manipulation methods and data distributions. Domain adaptation methods facilitate model generalization by allowing detection systems to adjust to various deepfake styles and datasets. This boosts resilience to hidden and adapting deepfake approaches. [20]. Explainable AI (XAI) enhances deepfake detection by making models more transparent and interpretable. Techniques like saliency maps and attention mechanisms highlight key features used for classification. This improves trust, debugging, and bias mitigation in AI-driven detection. XAI ensures reliable and explainable decisions in

media forensics and security.

III METHODOLOGY

MobileNet is optimized for real-time efficiency and lightness of processing, which is ideally suited for biometric spoofing detection. One of the innovations that make it so efficient is in using Depthwise Separable Convolutions, which considerably curtails computational complexity from the point of view of regular convolutional layers. Instead of performing a single convolution operation on all input channels simultaneously, MobileNet splits the process into two distinct steps. The initial operation, Depthwise Convolution, applies a single convolutional filter to each input channel separately, thus spatial features are extracted independently. The second operation, Pointwise Convolution, uses a 1×1 convolution to fuse information from various channels, enabling the network to learn sophisticated feature representations while being efficient. This decoupling of spatial and cross-channel feature extraction minimizes the number of parameters and computations involved, making MobileNet extremely optimized for real-time use cases like biometric anti-spoofing, where speed and precision are paramount.

Mathematically, the output Y of a Depthwise Separable Convolution is given by:

$$Y = X * K_d * K_p$$

Where,

- X is the input feature map (e.g., a facial image frame).
- K_d is the depthwise convolution kernel, which applies a separate filter to each input channel.
- K_p is the pointwise convolution kernel, which fuses features across channels using a 1×1 convolution.

By replacing standard convolutions with this two-step process, MobileNet reduces computational cost by a factor of:

$$\frac{1}{D_k^2} + \frac{1}{N_c}$$

Where,

- D_k is the kernel size.
- N_c is the number of output channels.

After feature extraction, MobileNet uses a fully connected layer with a Softmax activation function to classify the input as real or fake:

$$e^{z_{real}}$$

$$P(y = \{real\} | x) = \frac{e^{z_{real}}}{e^{z_{real}} + e^{z_{fake}}}$$

Where,

- Z_{real} and Z_{fake} are the model's logits for real and fake classes.
- The Softmax function normalizes these scores into probabilities.
- If $P(y = \{real\})$ is greater than 0.5, the system classifies the input as real; otherwise, it is fake.

ResNeXt is a deep convolutional neural network (CNN) based on aggregated transformations to enhance feature extraction, and is particularly well-positioned for detecting deepfake artefacts. ResNeXt architecture is crafted specifically to identify sophisticated facial deformations and minor inconsistencies in tampered media, which are generally challenging to identify

using traditional methods. In contrast to ResNeXt, wherein performance is upgraded with depth increase or width growth, ResNeXt propagates feature learning with multiple paths of transformation and hence performs more parallel convolution operations. By means of this, termed as aggregated transformations, the network learns rich sets of features simultaneously, giving improved generalization. The result of the final ResNeXt is then computed as addition of all the paths of transformation,

$$y = \sum_{i=1}^c T_{i(x)}$$

where,

- x is the input feature map.
- C is the number of transformation paths (cardinality).
- $T_{i(x)}$ represents the transformation function applied to each path.

Similar to MobileNet, ResNeXt uses Softmax to classify inputs:

$$Prediction = \operatorname{argmax}(P(y))$$

where the final classification is performed based on the most likely class (real or forged).

The Secure Vision integrates MobileNet for real-time biometric anti-spoofing and ResNeXt for deepfake detection. Lightweight MobileNet enables real-time, while ResNeXt's aggregation transformations enable detection of fine-grained deepfake anomalies. Using Softmax probability prediction, threshold-based classification, and confidence scoring, the system conducts strong and precise spoofing and deepfake media detection, where the end classification is arrived at from the highest-probability class (real or fake).




Fig 1 System Workflow

The diagram shows the workflow of the safe vision system, which contains the description of the sequential stages involved in the deepfake detection and biometric anti-spoofing. The process starts with the user input, where images or videos are uploaded for analysis. These inputs undergo preprocessing to increase stability, including the preceding, noise removal, shape and generalization. The feature extraction module then

identifies major features such as facial landmarks, texture patterns and frequencies artifacts, analyzed by detection modules to detect deepfake disclosures. The extracted features are then passed into the classification module, where deep learning models, including ResNeXt, classify the input as real or fake, which are based on the probability score. Finally, the result performs the result (user interface) classification results, in which the level of confidence and detected discrepancies are detected, ensuring a transparent and effective deputy detection process.

IV DATA COLLECTION & PREPROCESSING

The initial stage is the acquisition and preprocessing of datasets required to train biometric spoofing as well as deepfake detection models. To implement a strong biometric spoofing detection system, datasets like ASVspoof and Replay-Attack are employed, which carry varied spoofing attempts like printed images, videos, and 3D mask attacks. Datasets like FaceForensics++ and the Deepfake Detection Challenge (DFDC) dataset are employed in deepfake detection, offering diverse AI-generated manipulated videos. After being gathered, the data is subjected to preprocessing methods to improve model performance. Images and videos are resized to ensure consistency in input sizes, and normalization is used to ensure uniform pixel distributions for better computational efficiency. Data augmentation through flipping, rotation, and contrast changes improves generalization and avoids overfitting. Moreover, face alignment and detection methods aim to extract facial areas, remove background noise, and make sure the model identifies relevant features essential in differentiating between real and fake facial presentations.

V MODEL TRAINING

The Secure Vision system is trained on its deepfake detection model with a blend of large-scale datasets, sophisticated deep learning methods, and temporal analysis to be resilient against changing manipulation techniques. The training process starts with dataset preparation, where the model is trained on various deepfake datasets like FaceForensics++ and Deepfake Detection Challenge (DFDC). These data include hundreds of real and synthetic videos produced with various deepfake methods to enable the model to learn various patterns of manipulations. A preprocessing list including frame extraction, noise removal, normalization, and resizing standardizes each frame of a video prior to processing by the model.

ResNeXt as the Secure Vision backbone applies group convolutions that effectively extract deep hierarchical features in input images. The model is trained with supervised learning, where every training sample is marked as real or fake, and the system tries to minimize a cross-entropy loss function to enhance classification accuracy. The model is also trained with data augmentation techniques such as random cropping, brightness modifications, and rotation to enhance generalization and avoid overfitting. To handle temporal discrepancies, the system conducts frame-by-frame analysis so that it can learn illumination changes and facial expressions in the temporal domain in actual videos compared to deepfake videos.

Secure Vision also employs transfer learning, seeding ResNeXt with pre-trained weights on large-scale image datasets like ImageNet, which enables faster convergence and improved feature extraction. Backpropagation with Adam optimization is used during training, fine-tuning model parameters according to feedback from the loss function. For even greater accuracy, Explainable AI (XAI) methods,

including Grad-CAM visualization, are incorporated to emphasize significant areas in the video that assist in classifying deepfakes. Regular updating of the model with new deepfake data and hyperparameter tuning ensures adaptability to new manipulation methods without compromising high detection accuracy and reliability for real-world usage.

VI SYSTEM IMPLEMENTATION

Preprocessing Module is an essential part of the Deepfake Detection System, as it normalizes and optimizes input media for effective analysis. Raw images and videos typically consist of noise, resolution anomalies, and format differences, which adversely affect deep learning models. To address these issues, the system first converts media into a common format with JPEG, PNG, MP4, and AVI support and images in RGB and videos divided into frames at a known frame rate (e.g., 30 FPS). Noise removal techniques such as Gaussian Blur and Bilateral Filtering eliminate distortions, and histogram equalization enhances contrast to make deepfakes more detectable. For consistency, all the extracted images and frames are resized to 224×224 pixels, and pixel values are normalized (scaled to 0 to 1 range) for normalized inputs. Since processing every video frame is computationally expensive, keyframe selection is employed with algorithms for detecting changes in the scene in such a way that only the most important frames are processed. The process optimized enhances system efficiency by removing redundancy at the cost of necessary visual information. Smoothed media is then passed to the Feature Extraction Module following post-preprocessing whose analysis searches for deepfake-typical manipulation patterns and artifacts. The module significantly enhances efficiency, reliability, and accuracy in the detection of high-quality and standardized deepfakes.

The Feature Extraction Module identifies distortions and normal features of deepfakes through the analysis of texture abnormalities, facial landmark inconsistencies, and frequency irregularities with the deployment of advanced image processing and deep learning technologies. Dlib Facial Landmark Predictor, facial landmark detection detects primary features like eyes, nose, mouth, and jawline and searches for asymmetry and synthetic curving resulting from deepfake production. Texture analysis based on Local Binary Patterns (LBP) also identifies forged textures as deepfake images tend to appear unrealistically smooth against authentic photos. Frequency domain analysis employs Fourier Transform to expose high-frequency artifacts created by deepfake models and Wavelet Transform to detect fine-grained inconsistencies not noticeable in the spatial domain. In addition to that, blink detection for liveness analysis is done using OpenCV and Dlib in order to track frequency of eye closings and spotting abnormal blinking patterns, a common weakness in deepfakes. Such attributes are then passed on to the Classification Module where deep learning models analyze the input to validate whether it is genuine or not, providing reliable and accurate deepfake detection.

The Classification Module is the brain of the Deepfake Detection System, in which features extracted are analyzed and labeled as real or a deepfake. The module employs deep learning models like ResNeXt and MobileNet to provide accurate classification. ResNeXt, with its residual network design involving aggregated transformations, is trained for identifying deepfake face fakes by grasping intricate patterns

and minute anomalies across various regions of the face via multi-path learning. Concurrently, light-weight MobileNet is utilized for biometric spoofing detection with identification of static image attacks and replay attacks as well as efficient inference speed to allow real-time detection. The classification process starts with the feeding of extracted features into a Convolutional Neural Network (CNN), where decision-making is performed through hierarchical patterns learned. The final layer uses a Softmax activation function that produces a probability score which determines if the input is authentic (score > 0.5) or a deepfake (score < 0.5). To enhance dependability, the system produces a confidence score, classifying media as "Suspected Manipulation" if confidence levels are below a predetermined threshold. Results are then stored in a database after classification, triggering an alert if a deepfake is detected. An extensive report is also generated, indicating identified artifacts, confidence, and significant feature importance, to be transparent to the decision-making process.

VII DATABASE DESIGN


Secure Vision employs relational and NoSQL databases to store user interactions, logs, and system outputs in an efficient manner. The schema of the database includes several tables, including Users, where user information like User_ID, Name, Email, and Role (Admin/User) is stored; Biometric Logs, which stores Log_ID, User_ID, uploaded Image/Video, Timestamp, and Detection Result (Real/Fake); and Deepfake Logs, which stores Log_ID, User_ID, Video_ID, Detection Score, and Timestamp. These organized records support safe data handling, auditing, and recovery of detection outcomes. For high precision in biometric spoofing and deepfake detection, the system is trained using real-world datasets that offer diverse variations of tampered and genuine media. In the case of biometric spoofing detection, the ASVspoof Dataset is employed, with both genuine and spoofed facial images, enabling the model to distinguish between live faces and presentation attacks. In order to identify deepfakes, the framework leverages FaceForensics++, a preprocessed collection of authentic and deepfake videos, and the DFDC dataset, an industry standard collection of deepfakes generated by AI. The datasets include variability that is required for robustness and generalization of models in real-world environments.

VIII RESULT AND DISCUSSION


Deepfake Detection System can distinguish between real and fake media, vindicating its effectiveness in identifying deepfake videos and spoofed biometric data. The system is effective enough to scan images and videos and obtain major features such as facial features, texture outliers, and behavior patterns to identify possible forgeries. The classification part correctly classifies genuineness, and the feature of reporting enables users to get detailed information regarding detection results. The system provides the user with a perfect experience with smooth processing of input validation, error detection, and real-time inspection. During testing, the system was stable, responding effectively to different types of deepfakes and adversarial attacks. The findings validate that the implementation is appropriate for real-world applications in security, digital forensics, and content verification. Future developments will target better model generalization, increased processing speed, and greater coverage of datasets to address emerging deepfake methods.

The below figure illustrates the significant performance measures of the Secure Vision system, including Accuracy, Precision, Recall, and F1-score for both biometric anti-spoofing


(MobileNet) and deepfake detection (ResNeXt). These metrics are significantly used to measure the effectiveness of the system in identifying real and fake media. Accuracy is the total accuracy of the model, Precision is the number of fakes detected that are indeed fake, Recall is how well the model identifies all fakes, and the F1-score balances Precision and Recall to have a better overall assessment.



The AUC-ROC (Area Under the Curve - Receiver Operating Characteristic) plot measures MobileNet (anti-spoofing biometric) and ResNeXt (deepfake detection) performance for separating real and fake inputs. The True Positive Rate (TPR) is modeled against the False Positive Rate (FPR) at varying classification thresholds. The larger the AUC value, the larger the discriminatory power. It can be observed from the graph that ResNeXt has a larger AUC, which means stronger deepfake detection capability, and MobileNet performs well in real-time biometric spoofing detection.



The accuracy comparison table compares the performance of the Secure Vision system with benchmark deep learning models widely employed for biometric anti-spoofing and deepfake detection. Our MobileNet (97%) and ResNeXt (98%) models perform better than conventional models such as XceptionNet (93%), EfficientNet (94%), and VGG-16 (91%) in spoofing attack detection and deepfake media detection. ResNeXt, with its aggregated transformations, has the best accuracy, while MobileNet provides lightweight, real-time processing. The findings indicate that Secure Vision has a better balanced performance between precision and computational efficiency, thus it is suitable for real-time security purposes.



IX CHALLENGES ENCOUNTERED

One of the most important challenges of developing the Secure Vision system was to provide it with robustness against new deepfake and spoofing methods that are emerging constantly. Deepfake generation techniques improve with time, and it gets harder to find subtle manipulations. Although the system was developed using popular datasets such as FaceForensics++ and DFDC, the new deepfake models bring along very advanced features that can fool conventional detection strategies. Likewise, sophisticated biometric spoofing methods like 3D mask attacks and adversarial attacks are a major challenge, necessitating regular updates and retraining of the model to remain effective against new threats.

Another key challenge was real-time processing with high accuracy. MobileNet integration for biometric anti-spoofing guarantees light computation, but ResNeXt, employed for deepfake detection, is a deeper network that demands more computational power. Real-time processing of high-resolution video frames was computationally demanding, particularly when examining several frames per second for liveness detection and feature extraction. This issue called for optimization techniques such as frame selection algorithms, model quantization, and parallel processing in an effort to improve efficiency without degrading detection performance.

The project also involved data-related challenges, namely, collecting varied and good-quality datasets to train. Deep learning model performance is greatly influenced by the quality and variety of training data, but the datasets available from public sources will usually suffer from bias, unbalanced data, or bad representation of actual cases. Making sure that the system could operate under varying input conditions, such as changing lighting, resolutions of cameras, and varying demographic features, meant a lot of data preprocessing and augmentation. However, dataset balancing to avoid overfitting to certain categories of deepfakes or spoofing attacks was a persistent problem.

Interpretability and explainability of the model's decision was a challenge, especially for high-stakes uses like biometric verification and fraud detection. Deep learning models, particularly CNNs such as MobileNet and ResNeXt, are black

box models, where it is challenging to give concise explanations for the reason why a given input has been labeled real or fake. This invisibility can lead to issues of trust in situations where false negatives or false positives have severe implications, like denying authentic users or granting unauthorized entry. Resolving this involved the integration of visualization methodologies, feature importance evaluation, and confidence scoring mechanisms to improve model reliability and interpretability.

X LIMITATION

Though possessing upper-tier abilities, the Secure Vision system is limited by a series of factors on its general performance and versatility. A major challenge lies in generalizing detection of deepfakes against emerging manipulation techniques. Deepfake technology is continually evolving, and AI models continue generating increasingly realistic-sounding synthetic material. Although the system is trained on databases such as FaceForensics++ and DFDC, it can fail to identify deepfakes created by unknown or advanced techniques, which results in false negatives. Changes in lighting levels, facial expressions, and ambient noise can create inconsistencies in biometric spoofing detection, with the potential impact on the precision of MobileNet in real applications.

Another significant limitation is computational cost and resource requirement, especially for real-time processing of high-definition video. While MobileNet is light inference-optimized, the use of ResNeXt for deepfake detection significantly adds to the computational expense of the model. Deep learning models require a lot of GPU power and memory to process high-definition video frames, and therefore it's difficult to implement the system in low-resource devices like mobile phones or edge-based security systems. It keeps away from access by organizations or bodies that are not equipped with the appropriate hardware, which would discourage widespread adoption.

Finally, the confidence scoring and thresholding mechanism of the classification module can at times produce false positives, where actual biometric inputs or real videos are incorrectly tagged as fake. Low-quality compression of videos, motion blur, and adversarial attacks can compromise feature extraction and make the model misclassify authentic content. In addition, the use of pre-defined confidence thresholds also implies that borderline cases might not always be treated optimally, requiring manual intervention and incurring operational overhead. To overcome these constraints involves ongoing model tuning, incorporating adaptive learning methods, and the creation of more robust algorithms to resist upcoming deepfake attacks.

XI CONCLUSION

Deepfake Detection System is capable of detecting the manipulated media successfully with state-of-the-art preprocessing, feature extraction, and deep learning-based classification. It provides effective and reliable detection of deepfakes and biometric spoofing attempts with state-of-the-art AI models like ResNeXt and MobileNet. By a disciplined and systematic pipeline, the system handles media inputs by preprocessing images and videos first, extracting key facial, texture, and frequency-based features subsequently, and classifying the content as real or fake lastly. This helps the model improve detection of minor artifacts, discrepancies, and unnatural distortions created in deepfake generation. The

performance of the system's evaluation indicates its capability of detecting different deepfake manipulation approaches, providing better security in critical applications like biometric authentication, media content validation, and digital forensics. In addition, the module for generating reports offers in-depth information about the analysis, making it easier for users to achieve a clear and understandable evaluation of the authenticity of the analyzed media.

Although it has its robust performance, the system still faces difficulty dealing with adversarial deepfake attacks and edge situations with low-resolution or heavily compressed media. Highly advanced AI-manufactured fakes are difficult to detect since they utilize blending techniques subtly applied and highly developed neural rendering which reduces detectable artifacts. The low-quality input will also lead to the degradation of critical information, thus making it difficult to recognize deepfakes. Since the system will successfully distinguish between real and fake material in normal situations, it needs additional sophistications in detection techniques in an effort to identify very advanced deepfakes.

The system has been developed with scalability and flexibility in mind so that it can adapt to protect against emerging threats and new deepfake techniques. Enhancements down the line will target the augmentation of AI model training, utilization of more robust and challenging data sets, and optimizing real-time processing for enhanced speed and accuracy. Adversarial training, where models are presented with more evasive and adversarially designed deepfakes, will continue to make detection more robust. Moreover, hybrid models that couple deep learning and heuristic-based methodologies could enhance total detection rates.

The results of this study corroborate that deepfake detection technology is an imperative instrument to counter digital deception, disinformation, and impersonation. As technologies for creating deepfakes become more sophisticated, dynamic and active detection tools such as this will be instrumental in maintaining digital security and trust. This system is an important addition to digital interactions protection, biometric authentication system protection, and media integrity preservation amidst the advent of extremely realistic AI-generated content.

XII REFERENCE

- [1]. L. S. Luevano, Y. Martínez-Díaz, H. Méndez-Vázquez, M. González-Mendoza and D. Frey, (2024). Assessing the Performance of Efficient Face Anti-Spoofing Detection Against Physical and Digital Presentation Attacks. pp. 1021-1028, doi: 10.1109/CVPRW63382.2024.00108.
- [2]. C. P. M. Chan, S. W. Lee, and J. See, "DeepFake Video Detection Using Deep Learning and Iris Detection," in 2021 IEEE International Conference on Image Processing (ICIP), Anchorage, AK, USA, 2021, pp. 1239–1243, doi: 10.1109/ICIP42928.2021.9506664.
- [3]. J. Dong, W. Wang, Y. Tang, Y. Zhang, and H. Liu, "Deepfake Video Detection Using Inception-ResNet and Attention Mechanism," in 2021 IEEE International Conference on Multimedia and Expo (ICME), Shenzhen, China, 2021, pp. 1–6, doi: 10.1109/ICME51207.2021.9428434.

- [4]. M. N. Husen, A. Kurniawan, and M. Pamungkas, "Deepfake Detection on Video Sequences Using Inception-ResNet-v2 and LSTM," in 2020 3rd International Conference on Intelligent Autonomous Systems (ICoIAS), Singapore, 2020, pp.138, doi: 10.1109/ICoIAS49312.2020.9081914.
- [5]. M. Sabir, J. Cheng, A. Jaiswal, Y. Wu, L. Nataraj, and S. Chandrasekaran, "Recurrent Convolutional Strategies for Face Manipulation Detection in Videos," in 2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW), Seattle, WA, 10.1109/CVPRW50498.2020.00203.
- [6]. P. Korshunov and S. Marcel, "Human vs. Machine: Benchmarking Humans Against Deepfake Detection Systems," in 2020 8th International Conference on Biometrics Theory, Applications and Systems (BTAS), Washington, DC, USA, 2020, pp. 1–6, doi: 10.1109/BTAS48898.2020.9528289.
- [7]. R. Chugh, V. Agarwal, S. Subramanian, and K. R. Ramakrishnan, "Not Made For Each Other—Combining CNN and Transformers for Deepfake Detection," in 2021 IEEE/CVF International Conference on Computer Vision (ICCV), Montreal, QC, Canada, 2021, pp. 15024–15033, doi: 10.1109/ICCV48922.2021.01514.
- [8]. S. Mittal, A. Verma, and R. Jain, "Transfer Learning for Deepfake Detection," in 2020 6th International Conference on Signal Processing and Communication (ICSC), Noida, India, 2020, pp. 69–74, doi: 10.1109/ICSC48311.2020.9182767.
- [9]. W. Wang, Y. Zhang, and H. Liu, "Deep Neural Networks for Deepfake Detection: A Survey," in 2020 IEEE International Conference on Artificial Intelligence and Knowledge Engineering (AIKE), Phuket, Thailand, 2020, pp. 290–296, doi: 10.1109/AIKE48582.2020.00048.
- [10]. X. Luo, J. Lv, H. Song, Z. Yu, and G. Yang, "Dual-Stream CNNs for Forgery Detection in DeepFake Videos," in 2020 IEEE International Conference on Image Processing (ICIP), Abu Dhabi, UAE, 2020, pp. 2556–2560, doi: 10.1109/ICIP40778.2020.9191035.
- [11]. X. Wang, Y. Li, and H. Jiang, "Fake Video Detection with Convolutional Neural Networks," in 2019 10th International Conference on Advanced Computational Intelligence (ICACI), Guilin, 10.1109/ICACI.2019.8778503.
- [12]. Z. Chen, S. Wang, D. Yan, and Y. Li, "A Spatio-Temporal DeepFake Video Detection Method Based on TimeSformer-CNN," Proc. 3rd Int. Conf. Distributed Computing and Electrical Circuits and Electronics (ICDCECE), 2024, pp. xx-xx, doi: 10.1109/ICDCECE60827.2024.10549278.
- [13]. A. Berjawi, K. Samrouth, and O. Deforges, "Optimization of DeepFake Video Detection Using Image Preprocessing," 2023 Fifth International Conference on Advances in Computational Tools for Engineering Applications (ACTEA), 2023. doi: 10.1109/ACTEA58025.2023.10193954.
- [14]. J. Dong, W. Wang, Y. Tang, Y. Zhang, and H. Liu, "Deepfake Video Detection Using Inception-ResNet and Attention Mechanism," in 2021 IEEE International Conference on Multimedia and Expo (ICME), Shenzhen, China, 2021, pp.6, doi: 10.1109/ICME51207.2021.9428434.
- [15]. H. Liu, P. Bestagini, L. Huang, W. Zhou, S. Tubaro, W. Zhang, and N. Yu, "IT WASN'T ME: IRREGULAR IDENTITY IN DEEPFAKE VIDEOS," 2023 IEEE International Conference on Image Processing (ICIP), 2023. doi: 10.1109/ICIP49359.2023.10222654.
- [16]. R. Sun, Z. Zhao, L. Shen, Z. Zeng, Y. Li, B. Veeravalli, and Y. Xulei, "An Efficient Deep Video Model for Deepfake Detection," 2023 IEEE International Conference on Image Processing(ICIP),2023.doi:10.1109/ICIP49359.2023.10222682.
- [17]. D. S. Vahdati, T. D. Nguyen, A. Azizpour, and M. C. Stamm, "Beyond Deepfake Images: Detecting AI-Generated Videos," 2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW), 2024. doi: 10.1109/CVPRW63382.2024.00443.
- [18]. A. Jakka, V. R. J, M. Challa, V. K. M, and G. Kookkal, "Deepfake Video Detection using Deep Learning Approach," 2024 15th International Conference on Computing Communication and Networking Technologies (ICCCNT), 2024. doi: 10.1109/ICCCNT61001.2024.10726218.
- [19]. J. Vijaya, A. A. Kazi, K. G. Mishra, and A. Praveen, "Generation and Detection of Deepfakes using Generative Adversarial Networks (GANs) and Affine Transformation," 2023 14th International Conference on Computing Communication and Networking Technologies (ICCCNT), 2023. doi: 10.1109/ICCCNT56998.2023.1030781.
- [20]. N. M. Alnaim, Z. M. Almutairi, M. S. Alsuwat, H. H. Alalawi, A. Alshobaili, and F. S. Alenezi, "DFFMD: A Deepfake Face Mask Dataset for Infectious Disease Era With Deepfake Detection Algorithms," IEEE Access, vol. 11, pp. 3246661, 2023. doi: 10.1109/ACCESS.2023.3246661.