VizPI Labeling Guide v3

PRIME Lab, Virginia Tech. Version 3, 2025-11-17 (v2: 2025-11-10). For labeling 30-second windows of VizPI replays from CS 3114 deployment #2 (2025-11-12).

What a window is

Each window is 30 seconds of one student's session. Windows start at a run event when one falls within 5 seconds of the nominal boundary, otherwise on the 30-second grid. Watch the replay at 1x for the window plus 30 seconds of context before it.

States (pick exactly one)

	Definition	Typical evidence
	Making progress toward the spec	edits that change test resu
	Active but unproductive	edits/runs that do not char
w in v3)	Error or failed test in the last 60 s AND no edit or run for >= 45 s of the window AND no help request	scrolling, idle cursor, re-re
	Asking the TA queue or the assistant	help button, assistant pron
	Not working on the assignment	other tabs, no IDE focus fo

Decision rules

• If a help request happens anywhere in the window, label help_seeking, even if the student was stalled before it.

• stalled-after-error needs all three conditions. If the student edits once in the last 10 s, it is stuck, not stalled.

• Windows flagged partial_telemetry (section B, 3:30-4:10 pm) are labeled normally; add the comment #partial if a gap is visible.

• Unsure between two states: pick the earlier one in the table and add #unsure.

Calibration (2025-11-14)

Before batch A the three raters labeled 40 windows together (8 per state, both sections), discussed every disagreement and wrote down the edge cases above. Batches of 780 windows follow, with 15% pairwise overlap for agreement.

Changes from v2

• Added stalled-after-error. v2 put these windows under stuck or, sometimes, off_task.

• Clarified the window start rule (align to run events).

• Keyboard shortcuts: 1 productive, 2 stuck, 3 help_seeking, 4 stalled-after-error, 5 off_task (labeler v0.3.1).