
This battery holder is designed for use with protected 18650 batteries (PCB)

Date	SYM	REVISION RECORD	AUTH	DR.	CK.
07/22/17	D	ADDED MOUNTING INSTRUCTION	T.B.	B.S.	
05/17/19	E	UPDATED NOTES	T.B.	B.S.	
10/19/23	F	ADDED UL FILE NO.	T.B.	B.S.	
08/21/24	G	UPDATED UL FILE NO.	D.L.	B.S.	



NOTES:

Material: Self-extinguishing Thermoplastic Polyester, color black
Temperature Range: -40°c to +180°c
Contacts: 302 Stainless Steel Spring Temper, Nickel Plated
Flammability Rating: UL 94V-0, UL File # E45587
Wires: 24AWG, TR64, 300V, 80°C
Dielectric Strength: 560 Volts/Mil. at 25°C for 5 Sec.
Resistance to Solvents: Xylene, ethyl, butyl, methyl & toluene
Weight: 12.67g.
ROHS COMPLIANT

Mounting Instruction:

Use 2-56 machine screws or eyelets 0.089" OD by 0.15" flange stimpson GS-3 series or equivalent. also adhesives and double sided tapes work well.

Estimated Weight: 12.0 g

Tolerance (Inches)	MPD Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
Decimal ±.5 (.020)		Scale	Drawn By B.S. Approved By T.B.
Fractional ± .8 (.030)	Title: ONE 18650 LI-ION CELL HOLDER		
Angular ± 3°	Date: 08/21/24	Drawing Number: BH-18650-W	