

Terse register (flags)

Named register (arguments)

DESCRIBE	<code>tb(d, smoking, disease, col, p)</code>
TABLE 1	<code>table1(d, c(age, sex), by = grp, miss)</code>
EFFECT (PR)	<code>tb(d, x, y, pr, ref = "Never")</code>
EFFECT (OR)	<code>tb(d, x, y, or, ref = "Never")</code>
REGRESSION	<code>regtab(d, "y", ~ x + z)</code>

<code>tb(d, smoking, disease, test = TRUE)</code>
<code>table1(d, vars = c(age, sex), by = grp, missing = TRUE)</code>
<code>tb(d, x, y, measure = "pr", ref = "Never")</code>
<code>measure(result, "or")</code>
<code>regtab(d, outcomes = "y", predictors = ~ x + z, family = "binomial")</code>

FLAGS (shared by tb() and table1())

row	row %	col	column %	cell	total %	or	odds ratio
pr	prevalence ratio	rr	risk ratio	p	add p-value	miss	show missing

Deprecated (warn once): `rp` → `pr`, `m` → `miss`

REVISE & REPORT A RESULT (results are immutable evidence)

`adjust(res, age)`

add a covariate

`sensitivity(res, measure = 'or')`

re-estimate under a variation

`as_methods(res)`

write the methods sentence

`flow(res)`

participant-flow object

`subgroups(res, sex)`

effect within subgroups

`e_value(res)`

unmeasured-confounding bound

`strobe(res)`

reporting checklist

`style(res, 'jama') |> export_docx(f)`

restyle + Word file

LIFECYCLE

Prepare → Describe → Compare & Estimate → Diagnose & Validate → Compose & Export → Guidance & Repro → Extend

`is_simtab(x, 'tb')` tests the preset. Named args always beat flags. Every result exports to Word / PowerPoint / Excel / gt.

`vignette('migration-3-0')` | `vignette('simtablr-for-spss-users')` | `vignette('reviewer-asked-for')` | `vignette('growing-simtablr')`