

BUMPER: A Tool for Coping with Natural Language Searches of Millions of Bugs and Fixes

<https://bumper-app.com>

Mathieu Nayrolles, Wahab Hamou-Lhadj


Software Behaviour Analysis (SBA) Research Lab, ECE, Concordia, Montréal, Canada
mathieu.nayrolles@gmail.com, wahab.hamou-lhadj@concordia.ca

March 16, 2016


What developers do when facing an unknow bug ?

- In 2015, we surveyed:
 - ① École de Technologie Supérieure, Montréal, Québec, Canada
 - ② Université du Québec À Montréal, Montréal, Québec, Canada
 - ③ Concordia University, Montréal, Québec, Canada
 - ④ Participants of 2015 the Consortium for Software Engineering Research, Toronto, Ontario, Canada.
- When facing an unknown bug, crash or exception, where do you look for informations ?
- When facing an unknown bug, crash or exception, what are you searching for ?
- Surveyed 150 people and received 89 responses (59%)

When facing an unknown bug, crash or exception, where do you look for informations ?



When facing an unknown bug, crash or exception, what are you searching for?



- Results are not surprising.
 - 1 Online searches
 - 2 How to do X
 - 3 Copy/past the exception at hand
- Usually, a solution is quickly found, but ...
- Pain in navigating between bug report systems and code versionning systems.

- BUMPER: BUg Metarepository search engine for develoPErs and Researchers
 - Aggregates information from bug report and code versionning systems
 - Online Search Engine with million bug reports AND fixes from major open-source repositories
 - Apache Software Foundation, Netbeans, Eclipse, Gnome, FireFox, Chrome, Kde, ...
 - Imports bugs reports from Bugzilla, JIRA and Github, ... and fixes from SVN, Mercurial, Git, ...
 - Natural language for developers
 - Advanced API for researchers

BUMPER Data (as of now)

| Dataset | R/F BR | CS | Files | Projects |
|----------|---------|-----------|---------|----------|
| Gnome | 550,869 | 1,231,354 | 367,245 | 512 |
| Netbeans | 53,258 | 122,632 | 30,595 | 39 |
| Apache | 49,449 | 106,366 | 38,111 | 349 |
| Eclipse | 78,830 | 184,900 | 21,712 | 190 |
| Total | 732,406 | 1,645,252 | 457,663 | 1,930 |

Google-like usage for developers

bumper

Find Out How Others Fixed It

Type your search



SHOWCASE

ADVANCED QUERY MODE

API

DATASETS

PUBLICATIONS

ABOUT

Bug reports and bug fixes, side by side

Null Pointer Exception

About 27626 results (0.01 seconds)

LANGUAGES  DATASETS 

DOWNLOAD 

▲ **NullPointerException at org.netbeans.api.java.source.JavaSource\$JavaSourceAccessorImpl.
38**
https://netbeans.org/bugzilla/show_bug.cgi?id=189412 **java, netbeans, java**

▼ Build: NetBeans IDE 6.9 (Build 201006101454) VM: Java HotSpot(TM) Client VM, 16.2-b04, Java(TM) SE Runtime Environment, 1.6.0_19-b04 OS: Windows 7 Stacktrace: java.lang.NullPointerException...

▲ **NullPointerException at org.netbeans.modules.java.source.usages.LuceneIndex\$DirCache.clc
10**
https://netbeans.org/bugzilla/show_bug.cgi?id=189499 **java, netbeans, java**

▼ Build: NetBeans IDE Dev (Build 201008130001) VM: Oracle JRockit(R), R28.0.1-21-1333993-1.6.0_20-20100512-2131-windowsx86_64, Java(TM) SE Runtime Environment, 1.6.0_20-b02 OS: Windows 7...

▲ **Enable collecting thread cpu timestamps by default
4**
https://netbeans.org/bugzilla/show_bug.cgi?id=189621 **java, netbeans, profiler**

▼ Given the fact that thread cpu timestamps are available to JVM (1.6+) on all major operating systems and obtaining them is reasonably quick [1] we can enable collecting them by default.

▲ **NullPointerException at java.util.Arrays\$ArrayList.<init>
2**
https://netbeans.org/bugzilla/show_bug.cgi?id=177814 **java, netbeans, platform**

▼ Build: NetBeans IDE Dev (Build 2009111981.600) VM: Java HotSpot(TM) Client VM, 1.4.2...

176129.80dc07f52485 #189412 NullPointerException at
org.netbeans.api.java.source.JavaSource\$JavaSourceAccessorImpl.setJavaSource
• java.source/src/org/netbeans/modules/java/source/JavaSourceAccessor.java
• java.source/src/org/netbeans/modules/java/source/parsing/JavadocParserResult.java

(2) files, (10) insertions, (4) deletions

Index: java.source/src/org/netbeans/modules/java/source/JavaSource
Accessor.java

```
@@ -84,6 +84,7 @@  
import org.openide.text.PositionRef;  
import org.openide.util.Exceptions;  
import org.openide.util.Mutex;  
+import org.openide.util.Parameters;  
  
/**  
 *
```

Index: java.source/src/org/netbeans/modules/java/source/JavaSource
Accessor.java

```
@@ -316,9 +317,14 @@  
}  
  
@Override  
- public void run(Result result, SchedulerEvent event) {  
+ public void run(@NonNull Result result, SchedulerEvent ev
```

SHOWCASE

ADVANCED QUERY MODE

API

DATASETS

PUBLICATIONS

ABOUT

Using BUMPER for bug-fixing tasks

When I run the CSVReader with a simple main like this:

Listing 1: Java Bug


```
CsvFileUtils csvFileUtils = 1
    new CsvFileUtils(" quebec.txt" ); 2
3
for (int i = 0; i < 2000; i++) { 4
    printArray(csvFileUtils 5
        .readOneLine()); 6
} 7
```

*I got the following Exception: Exception in thread "main"
java.lang.NullPointerException at
CsvFileUtils.readLine(CsvFileUtils.java:22) at
Main.main(Main.java:11). Can you please fix CsvFileUtils ?*

Using BUMPER for bug-fixing tasks (cont'd)

- New survey (20 developers, 40% response rate)
- Find a suitable code snippet to fix the bug using:
 - Google search engine
 - Bumper search engine
- Google 6.94 minutes and 7.57 web pages
- BUMPER 4.5 minutes and 1 web page (<https://bumper-app.com>)

BUMPER Metamodel



API Usage for researchers

- All fields are indexed for fast search
- Two special indexes:
 - `report_t`: Contains a concatenation of all the bug-related fields
 - `fix_t`: Contains a concatenation of all the fix-related fields
- Search for "*YOUR TERMS*" in bug reports and bug fixes:

(type : "BUG" AND report_t : "YOUR TERMS"
AND - churns : 0)

OR

({!parent which = "type : BUG"}type : "CHANGESET"
AND fix_t : "YOUR TERMS")

- Bug reports with at least one fix having:
 - The word “Exception” in the bug report
 - Belonging to “Axis2” or “ide” projects
 - Reported by “Rich” or is “fixed”
 - With a “major” severity or a fixing time greater than 10 days

*(type : “BUG” AND report_t : “Exception”
AND (project : “Axis2” OR project : “ide”)
AND (reporter : “Rich” OR resolution : “fixed”)
AND (severity : “Major” OR fixing_time : [10 TO *])
AND — churns : 0)*

Conclusion

- <https://bumper-app.com>
- Million bugs and associated fixes
- Apache Software Foundation, Netbeans, Eclipse, Gnome, FireFox, Chrome, Kde, ...
- Imports bugs from Bugzilla, JIRA ... and fixes from SVN, Mercurial, Git, ...
- Natural Language Search for developers
- Advanced API for researchers

QUESTIONS?