

Mathis Bouverot-Dupuis

CNAM – ??

12 juillet 2022

Model


Weber Point

Alignment

Suzuki & Yamashita's Model

Very simple (dumb) robots :


- ▶ Points in R^2 (can overlap)



Suzuki & Yamashita's Model

Very simple (dumb) robots :


- ▶ Points in R^2 (can overlap)
- ▶ Anonymous



Suzuki & Yamashita's Model

Very simple (dumb) robots :


- ▶ Points in R^2 (can overlap)
- ▶ Anonymous
- ▶ No direct communication



Suzuki & Yamashita's Model

Very simple (dumb) robots :


- ▶ Points in R^2 (can overlap)
- ▶ Anonymous
- ▶ No direct communication
- ▶ No common direction/scale



Suzuki & Yamashita's Model

Very simple (dumb) robots :


- ▶ Points in R^2 (can overlap)
- ▶ Anonymous
- ▶ No direct communication
- ▶ No common direction/scale
- ▶ Strong multiplicity detection



Suzuki & Yamashita's Model

Very simple (dumb) robots :

- ▶ Points in R^2 (can overlap)
- ▶ Anonymous
- ▶ No direct communication
- ▶ No common direction/scale
- ▶ Strong multiplicity detection
- ▶ Same robotgram



Weber point : Definition

- ▶ Let X : multiset of points in R^2

Weber point : Definition

- ▶ Let X : multiset of points in R^2
- ▶ Sum of distances to X :

$$D_X(p) := \sum_{x \in X} \|x - p\|$$

Weber point : Definition

- ▶ Let X : multiset of points in R^2
- ▶ Sum of distances to X :

$$D_X(p) := \sum_{x \in X} \|x - p\|$$

- ▶ Set of weber points of X :

$$\{p \mid p \text{ minimizes } D_X\}$$

Weber point : Definition

- ▶ Let X : multiset of points in R^2
- ▶ Sum of distances to X :

$$D_X(p) := \sum_{x \in X} \|x - p\|$$

- ▶ Set of weber points of X :

$$\{p \mid p \text{ minimizes } D_X\}$$

- ▶ Similar to barycenter (sum of distances v.s. sum of distances squared).

Weber point v.s Barycenter

	barycenter	weber point
exists		
unique		
computable		

Weber point v.s Barycenter

	barycenter	weber point
exists	Yes	Yes
unique		
computable		

Weber point v.s Barycenter

	barycenter	weber point
exists	Yes	Yes
unique	Yes	No
computable		

Weber point v.s Barycenter

	barycenter	weber point
exists	Yes	Yes
unique	Yes	No
computable	Yes	No

Weber point v.s Barycenter

	barycenter	weber point
exists	Yes	Yes
unique	Yes	No
computable	Yes	No

When is the weber point unique ?

Weber point v.s Barycenter

	barycenter	weber point
exists	Yes	Yes
unique	Yes	No
computable	Yes	No

When is the weber point unique ?

- Points not aligned.

Weber point v.s Barycenter

	barycenter	weber point
exists	Yes	Yes
unique	Yes	No
computable	Yes	No

When is the weber point unique ?

- ▶ Points not aligned.
- ▶ Odd number of points.

Weber point v.s Barycenter

	barycenter	weber point
exists	Yes	Yes
unique	Yes	No
computable	Yes	No

When is the weber point unique ?

- ▶ Points not aligned.
- ▶ Odd number of points.
- ▶ Otherwise : sometimes.

Weber point v.s Barycenter

	barycenter	weber point
exists	Yes	Yes
unique	Yes	No
computable	Yes	No

When is the weber point unique ?

- ▶ Points not aligned.
- ▶ Odd number of points.
- ▶ Otherwise : sometimes.

How about computability ?

Weber point v.s Barycenter

	barycenter	weber point
exists	Yes	Yes
unique	Yes	No
computable	Yes	No

When is the weber point unique ?

- ▶ Points not aligned.
- ▶ Odd number of points.
- ▶ Otherwise : sometimes.

How about computability ?

- ▶ We don't care (toy example).

Weber point v.s Barycenter

	barycenter	weber point
exists	Yes	Yes
unique	Yes	No
computable	Yes	No

When is the weber point unique ?

- ▶ Points not aligned.
- ▶ Odd number of points.
- ▶ Otherwise : sometimes.


How about computability ?

- ▶ We don't care (toy example).

Why use the weber point ?


Contraction Lemma

- Let X , Y : multiset of points (cf. figure).




Contraction Lemma

- ▶ Let X , Y : multiset of points (cf. figure).
- ▶ Suppose $w \in WP(X)$.




Contraction Lemma

- ▶ Let X , Y : multiset of points (cf. figure).
- ▶ Suppose $w \in WP(X)$.
- ▶ Then $w \in WP(Y)$.



Contraction Lemma (proof idea)


Alternate characterization of weber points :



Contraction Lemma (proof idea)

Alternate characterization of weber points :


- Recall $D_X(p) := \sum_{x \in X} \|x - p\|$.



Contraction Lemma (proof idea)

Alternate characterization of weber points :


- ▶ Recall $D_X(p) := \sum_{x \in X} \|x - p\|$.
- ▶ D_X is convex & differentiable (almost) everywhere.



Contraction Lemma (proof idea)

Alternate characterization of weber points :


- ▶ Recall $D_X(p) := \sum_{x \in X} \|x - p\|$.
- ▶ D_X is convex & differentiable (almost) everywhere.
- ▶ Minimizing $D_X \iff$ gradient of D_X is 0.



Contraction Lemma (proof idea)


Alternate characterization of weber points :

- ▶ Recall $D_X(p) := \sum_{x \in X} \|x - p\|$.
- ▶ D_X is convex & differentiable (almost) everywhere.
- ▶ Minimizing $D_X \iff$ gradient of D_X is 0.
- ▶ Gradient : $\nabla D_X(p) = \sum_{x \in X} \frac{p-x}{\|p-x\|}$



Alignment

Goal : move robots to a common line, and make them stay on the line.



Alignment

Goal : move robots to a common line, and make them stay on the line.

Coq

Definition aligned : configuration → **Prop**.

Alignment

Goal : move robots to a common line, and make them stay on the line.

Coq

Definition aligned : configuration → Prop.

Coq

Definition eventually_aligned (c:configuration)
(d:demon) (r:robogram) :=
 Stream.eventually
 (Stream.forever (Stream.instant aligned))
 (execute r d c).

Alignment

Goal : move robots to a common line, and make them stay on the line.

Coq

Definition aligned : configuration → Prop.

Coq

Definition eventually_aligned (c:configuration)
(d:demon) (r:robogram) :=
 Stream.eventually
 (Stream.forever (Stream.instant aligned))
 (execute r d c).

Coq

Theorem alignment_correct :=
 ∀ (c:configuration) (d:demon),
 (* Hypotheses *) →
 eventually_aligned c d align_robogram.

Robogram

Very simple robogram : move towards the weber point (in a straight line) until aligned.

Robogram

Very simple robogram : move towards the weber point (in a straight line) until aligned.

Coq

```
Definition align_robogram (obs:observation) : R2 :=  
  if aligned_dec obs  
  then origin  
  else weber_calc obs.
```

Robogram

Very simple robogram : move towards the weber point (in a straight line) until aligned.

Coq

```
Definition align_robogram (obs:observation) : R2 :=  
  if aligned_dec obs  
  then origin  
  else weber_calc obs.
```

Coq

```
Definition observation := multiset R2.
```

Setting

Suzuki & Yamashita's Model : several versions.

- ▶ Fully-synchronous (FSYNC), semi-synchronous (SSYNC) or asynchronous (ASYNC) ?

Setting

Suzuki & Yamashita's Model : several versions.

- ▶ Fully-synchronous (FSYNC), semi-synchronous (SSYNC) or asynchronous (ASYNC) ?
- ▶ Rigid or flexible ?

Setting

Suzuki & Yamashita's Model : several versions.

- ▶ Fully-synchronous (FSYNC), semi-synchronous (SSYNC) or asynchronous (ASYNC) ?
- ▶ Rigid or flexible ?

My proofs (alignment) :

Setting

Suzuki & Yamashita's Model : several versions.

- ▶ Fully-synchronous (FSYNC), semi-synchronous (SSYNC) or asynchronous (ASYNC) ?
- ▶ Rigid or flexible ?

My proofs (alignment) :

- ▶ SSYNC & rigid.

Setting

Suzuki & Yamashita's Model : several versions.

- ▶ Fully-synchronous (FSYNC), semi-synchronous (SSYNC) or asynchronous (ASYNC) ?
- ▶ Rigid or flexible ?

My proofs (alignment) :

- ▶ SSYNC & rigid.
- ▶ SSYNC & flexible.

Setting

Suzuki & Yamashita's Model : several versions.

- ▶ Fully-synchronous (FSYNC), semi-synchronous (SSYNC) or asynchronous (ASYNC) ?
- ▶ Rigid or flexible ?

My proofs (alignment) :

- ▶ SSYNC & rigid.
- ▶ SSYNC & flexible.
- ▶ ASYNC (first time in Pactole) & flexible.

ASync model

How do we represent robots ?

ASYNC model

How do we represent robots ?

- ▶ SSYNC : current position only.

ASync model

How do we represent robots ?

- ▶ SSync : current position only.
- ▶ ASync : start, destination & current positions.

ASync model

How do we represent robots ?

- ▶ SSync : current position only.
- ▶ ASync : start, destination & current positions.

Coq

```
(* start, dest and ratio *)
```

```
Definition info := (location * location * ratio)%type.
```


ASync model

How do we represent robots ?

- ▶ SSYNC : current position only.
- ▶ ASYNC : start, destination & current positions.

Coq

```
(* start, dest and ratio *)
```

```
Definition info := (location * location * ratio)%type.
```

Coq

```
Instance St : State info :=
```

```
{ get_location := fun '(start, dest, r) =>  
  straight_path start dest r }.
```

ASync model

How do we represent robots ?

- ▶ SSync : current position only.
- ▶ ASync : start, destination & current positions.

Coq

```
(* start, dest and ratio *)
```

```
Definition info := (location * location * ratio)%type.
```

Coq

```
Instance St : State info :=
```

```
{ get_location := fun '(start, dest, r) =>  
  straight_path start dest r }.
```

How to update robots each round ?

ASync model

How do we represent robots ?

- ▶ SSync : current position only.
- ▶ ASync : start, destination & current positions.

Coq

```
(* start, dest and ratio *)  
Definition info := (location * location * ratio)%type.
```

Coq

```
Instance St : State info :=  
{ get_location := fun '(start, dest, r) =>  
  straight_path start dest r }.
```

How to update robots each round ?

- ▶ Activated robots :

```
new_start <- straight_path start dest ratio  
new_dest  <- robogram (obs_from_config config)  
new_ratio <- 0
```

ASync model

How do we represent robots ?

- ▶ SSync : current position only.
- ▶ ASync : start, destination & current positions.

Coq

```
(* start, dest and ratio *)  
Definition info := (location * location * ratio)%type.
```

Coq

```
Instance St : State info :=  
{ get_location := fun '(start, dest, r) =>  
  straight_path start dest r }.
```

How to update robots each round ?

- ▶ Activated robots :

```
new_start <- straight_path start dest ratio  
new_dest  <- robogram (obs_from_config config)  
new_ratio <- 0
```

- ▶ Other robots :

```
new_ratio <- ratio + demon_ratio
```

ASYNC model : rigid & flexible

How to define rigid & flexible demons in ASYNC ?

ASYNC model : rigid & flexible

How to define rigid & flexible demons in ASYNC ?

Rigid : no longer the default setting.

Coq

```
Definition rigid_da_prop (da:demonic_action) :=  
  ∀ (c:configuration) (id:identifier),  
    da.(activate) id = true →  
    get_location (c id) ≡ get_destination (c id).
```

ASync model : rigid & flexible

How to define rigid & flexible demons in ASync ?

Rigid : no longer the default setting.

Coq

```
Definition rigid_da_prop (da:demonic_action) :=  
  ∀ (c:configuration) (id:identifier),  
    da.(activate) id = true →  
    get_location (c id) ≡ get_destination (c id).
```

Flexible :

Coq

```
Definition flex_da_prop (da:demonic_action) ( $\delta$ :R) :=  
  ∀ (c:configuration) (id:identifier),  
    da.(activate) id = true →  
    get_location (c id) ≡ get_destination (c id) ∨  
     $\delta \leq \text{dist} (\text{get\_start} (c id)) (\text{get\_location} (c id)).$ 
```

Decreasing measure

We define a measure that decreases each time a robot is activated.