

# Game Notes

Aresh Pourkavoos

April 26, 2022

Position within square stored as an odd signed integer in half-pixels, e.g.

101	011	001	011
-3	-1	1	3

Requires entities to have odd pixel dims to be centered

Edge/vertex states are not possible

Updating position requires doubling velocity first

Store position as  $x$  and  $y$  seen on screen or relative to a square's axes?

Screen position:

- Graphics and movement are easier
- Collision would be most convenient by loading the current square rotated

Relative position:

- Collision is easier, just check against stored square
- Need to ensure that rendering is done correctly

View splitting is decided by determinant sign: will always give edge to cell further (counter?)clockwise

Vertices/edges are on the border between pixels (even position): do not require a special case



Shaded pixel: camera

Lines: region boundaries

Inlined pixels: edge cases (given to clockwise region in this case)

Going through a singularity and back is a holonomy loop

Entity gravity is ambiguous when not in the same square as the player:

- Freeze when player leaves the square: unintuitive, esp for flat regions
- Based on last player interaction: better, but initial direction must be set: could be none

Have “naked” singularities or cover them up?

Naked is easier to implement if accounted for at the cost of real physics:

an object of finite size can’t actually pass through one

Not checking self-collisions would obviate this but may result in graphical glitches

Covering singularities would prevent glitches and restore accuracy but might hurt level design

Larger squares → fewer singularities → less harm in covering them

However, smaller squares → more convenient to travel/execute holonomy

Rendering function is recursive:

- Accept left+right boundary points, square to render, position/orientation of square, quadrant
- Render given square in full
- Check if furthest vertex given by quadrant (“splitting vertex”) falls strictly within bounds
- If not, call with same bounds/quadrant, single adjacent square with new position/orientation
- If so, make 2 recursive calls changing appropriate bounds to splitting vertex
- Store the result of the 2nd call in a separate buffer
- Could maintain a stack of buffers and add depth as an argument: depth necessary anyway
- Mask buffer with line between camera and splitting vertex (anti-aliasing here!)
- Overlay with original buffer

4 base cases starting from current square with left/right bounds along x/y axes

Renders current square 4x and squares in same row/col 2x

Art style between pixel and vector: each “pixel” is not a solid color but one of a few predefined shapes, e.g. solid color, 2 colors split diagonally, split by circular arc