

DD2448 Foundations of Cryptography

Lecture 2

Douglas Wikström
KTH Royal Institute of Technology
dog@kth.se

January 25, 2020

Last Lecture: Summary of Simple Ciphers

- ▶ Caesar cipher and affine cipher: $m_i \mapsto am_i + b$.

- ▶ Substitution cipher (generalize Caesar/affine):

$$m_i \mapsto \sigma(m_i)$$

- ▶ Vigenère cipher (more uniform frequency table):

$$m_i \mapsto m_i + k_i \bmod I$$

- ▶ Hill cipher (invertible linear map):

$$(m_1, \dots, m_l) \mapsto (m_1, \dots, m_l)A$$

- ▶ Transposition cipher (permutation):

$$(m_1, \dots, m_l) \mapsto (m_{\pi(1)}, \dots, m_{\pi(l)})$$

$$(m_1, \dots, m_l) \mapsto (m_1, \dots, m_l)M_\pi \quad (\text{equivalently})$$

Simple Ciphers are Bad, What is a Good Block Cipher?

- ▶ For every key a block-cipher with plaintext/ciphertext space $\{0,1\}^n$ gives a permutation of $\{0,1\}^n$.

What would be an good cipher?

Simple Ciphers are Bad, What is a Good Block Cipher?

- ▶ For every key a block-cipher with plaintext/ciphertext space $\{0,1\}^n$ gives a permutation of $\{0,1\}^n$.

What would be an good cipher?

- ▶ A good cipher is one where each key gives a **randomly chosen permutation** of $\{0,1\}^n$.

Why is this not possible?

Simple Ciphers are Bad, What is a Good Block Cipher?

- ▶ For every key a block-cipher with plaintext/ciphertext space $\{0, 1\}^n$ gives a permutation of $\{0, 1\}^n$.

What would be an good cipher?

- ▶ A good cipher is one where each key gives a **randomly chosen permutation** of $\{0, 1\}^n$.

Why is this not possible?

- ▶ The representation of a single typical function $\{0, 1\}^n \rightarrow \{0, 1\}^n$ requires roughly $n2^n$ bits ($147 \times 10^{6.3}$ for $n = 64$)

Simple Ciphers are Bad, What is a Good Block Cipher?

- ▶ For every key a block-cipher with plaintext/ciphertext space $\{0,1\}^n$ gives a permutation of $\{0,1\}^n$.

What would be an good cipher?

- ▶ A good cipher is one where each key gives a **randomly chosen permutation** of $\{0,1\}^n$.

Why is this not possible?

- ▶ The representation of a single typical function $\{0,1\}^n \rightarrow \{0,1\}^n$ requires roughly $n2^n$ bits ($147 \times 10^{6.3}$ for $n = 64$)
- ▶ What should we look for instead?

Something Smaller

Idea. Compose smaller weak ciphers into a large one. Mix the components “thoroughly”.

Something Smaller

Idea. Compose smaller weak ciphers into a large one. Mix the components “thoroughly”.

Shannon (1948) calls this:

- ▶ **Diffusion.** “In the method of diffusion the statistical structure of M which leads to its redundancy is dissipated into long range statistics...”
- ▶ **Confusion.** “The method of confusion is to make the relation between the simple statistics of E and the simple description of K a very complex and involved one.”

Substitution-Permutation Networks

Substitution-Permutation Networks (1/2)


- ▶ **Block-size.** We use a block-size of $n = \ell \times m$ bits.
- ▶ **Key Schedule.** Round r uses its own round key K_r derived from the key K using a key schedule.
- ▶ **Each Round.** In each round we invoke:
 1. **Round Key.** xor with the round key.
 2. **Substitution.** ℓ substitution boxes each acting on one m -bit word (m -bit S-Boxes).
 3. **Permutation.** A permutation π_i acting on $\{1, \dots, n\}$ to reorder the n bits.

Substitution-Permutation Networks (2/2)


U_{i-1}

K_i


Substitution-Permutation Networks (2/2)




Substitution-Permutation Networks (2/2)




Substitution-Permutation Networks (2/2)




Substitution-Permutation Networks (2/2)



Substitution-Permutation Networks (2/2)



A Simple Block Cipher (1/2)



► $|P| = |C| = 16$

► 4 rounds


► $|K| = 32$

► r th round key K_r consists of the $4r$ th to the $(4r + 16)$ th bits of key K .

► 4-bit S-Boxes

A Simple Block Cipher (2/2)

S-Boxes the same ($S \neq S^{-1}$)




► $Y = S(X)$

► Can be described using 4 boolean functions

Input	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
Output	E	4	D	1	2	F	B	8	3	A	6	C	5	9	0	7

A Simple Block Cipher (2/2)

S-Boxes the same ($S \neq S^{-1}$)



► $Y = S(X)$

► Can be described using 4 boolean functions

Input	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
Output	E	4	D	1	2	F	B	8	3	A	6	C	5	9	0	7

16-bit permutation ($\pi = \pi^{-1}$)

Input	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Output	1	5	9	13	2	6	10	14	3	7	11	15	4	8	12	16


AES

Advanced Encryption Standard (AES)

- ▶ Chosen in worldwide **public competition** 1997-2000.
Probably no backdoors. Increased confidence!
- ▶ Winning proposal named “Rijndael”, by Rijmen and Daemen
- ▶ Family of 128-bit block ciphers:


Key bits	128	192	256
Rounds	10	12	14
- ▶ The first key-recovery attacks on full AES due to Bogdanov, Khovratovich, and Rechberger, published **2011**, is faster than brute force by a factor of about **4**.
- ▶ ... algebraics of AES make some people uneasy, but they have been uneasy for years now.

- ▶ **AddRoundKey**: xor with round key.
- ▶ **SubBytes**: substitution of bytes.
- ▶ **ShiftRows**: permutation of bytes.
- ▶ **MixColumns**: linear map.



Similar to SPN


The 128 bit state is interpreted as a 4×4 matrix of bytes.



Something like a mix between substitution, permutation, affine version of Hill cipher. In each round!


SubBytes

SubBytes is field inversion in \mathbb{F}_{2^8} plus affine map in \mathbb{F}_2^8 .




ShiftRows

ShiftRows is a cyclic shift of bytes with offsets: 0, 1, 2, and 3.



MixColumns

MixColumns is an invertible linear map over \mathbb{F}_{2^8} (with irreducible polynomial $x^8 + x^4 + x^3 + x + 1$) with good diffusion.



Decryption

Uses the following transforms:

- ▶ **AddRoundKey**
- ▶ **InvSubBytes**
- ▶ **InvShiftRows**
- ▶ **InvMixColumns**


Feistel Networks

- ▶ Identical rounds are iterated, but with different round keys.
- ▶ The input to the i th round is divided in a left and right part, denoted L^{i-1} and R^{i-1} .
- ▶ f is a function for which it is somewhat hard to find pre-images, but f is **not invertible**!
- ▶ One round is defined by:


$$\begin{aligned}L^i &= R^{i-1} \\ R^i &= L^{i-1} \oplus f(R^{i-1}, K^i)\end{aligned}$$

where K^i is the i th round key.


Feistel Round




Feistel Round




Feistel Round



Feistel Round



Feistel Cipher



Feistel Round.

$$L^i = R^{i-1}$$

$$R^i = L^{i-1} \oplus f(R^{i-1}, K^i)$$

Feistel Round.

$$L^i = R^{i-1}$$

$$R^i = L^{i-1} \oplus f(R^{i-1}, K^i)$$

Inverse Feistel Round.

$$L^{i-1} = R^i \oplus f(L^i, K^i)$$

$$R^{i-1} = L^i$$

Reverse direction and swap left and right!

DES

The news here is not that DES is insecure, that hardware algorithm-crackers can be built, or that a 56-bit key length is too short. ... The news is how long the government has been denying that these machines were possible. As recently as 8 June 98, Robert Litt, principal associate deputy attorney general at the Department of Justice, denied that it was possible for the FBI to crack DES. ... My comment was that the FBI is either incompetent or lying, or both.

– Bruce Schneier, 1998

Data Encryption Standard (DES)

- ▶ Developed at IBM in 1975, or perhaps...

Data Encryption Standard (DES)

- ▶ Developed at IBM in 1975, or perhaps...
- ▶ at National Security Agency (NSA). Nobody knows for certain.

Data Encryption Standard (DES)

- ▶ Developed at IBM in 1975, or perhaps...
- ▶ at National Security Agency (NSA). Nobody knows for certain.
- ▶ 16-round Feistel network.

Data Encryption Standard (DES)


- ▶ Developed at IBM in 1975, or perhaps...
- ▶ at National Security Agency (NSA). Nobody knows for certain.
- ▶ 16-round Feistel network.
- ▶ Key schedule derives permuted bits for each round key from a 56-bit key. Supposedly not 64-bit due to parity bits.

Data Encryption Standard (DES)

- ▶ Developed at IBM in 1975, or perhaps...
- ▶ at National Security Agency (NSA). Nobody knows for certain.
- ▶ 16-round Feistel network.
- ▶ Key schedule derives permuted bits for each round key from a 56-bit key. Supposedly not 64-bit due to parity bits.
- ▶ Let us look a little at the Feistel-function f .



DES's f -Function

32 bits




48 bits


DES's f -Function




DES's f -Function



DES's f -Function



DES's f -Function



- ▶ **Brute Force.** Try all 2^{56} keys. Done in practice with special chip by Electronic Frontier Foundation, 1998. Likely much earlier by NSA and others.
- ▶ **Differential Cryptanalysis.** 2^{47} chosen plaintexts, Biham and Shamir, 1991. (approach: late 80'ies). Known earlier by IBM and NSA. DES is surprisingly resistant!
- ▶ **Linear Cryptanalysis.** 2^{43} known plaintexts, Matsui, 1993. Probably **not** known by IBM and NSA!

We have seen that the key space of DES is too small. One way to increase it is to use DES twice, so called “double DES”.

$$2DES_{k_1, k_2}(x) = DES_{k_2}(DES_{k_1}(x))$$

Is this more secure than DES?

This question is valid for any cipher.