

EQ2330 – Image and Video Processing

Exercise 8: Compression

Unless stated otherwise, the problems are from on R. C. Gonzales and R. E. Woods. *Digital Image Processing*, (second ed.), Prentice Hall, Upper Saddle River, New Jersey, 2002.

Problems to be solved in the classroom

1. **Problem 8.11, modified** The rate distortion function of a zero-memory Gaussian source of arbitrary mean and variance σ^2 with respect to the mean-square error criterion is

$$R(D) = \begin{cases} \frac{1}{2} \log \frac{\sigma^2}{D} & 0 \leq D \leq \sigma^2 \\ 0 & D \geq \sigma^2. \end{cases} \quad (1)$$

- (a) Plot this function.
 - (b) What is D_{max} ?
 - (c) Show that increasing/decreasing 1 bit decreases/increases the distortion by 6 dB.
 - (d) If distortion of no more than 75% of the source's variance is allowed, what is the maximum compression that can be achieved.
 - (e) Two independent zero-memory Gaussian sources with variances σ_1^2 and σ_2^2 are to be quantized. The total distortion is defined as the sum of their individual mean-square errors. The total rate is defined as the sum of their individual rates, say R_1 and R_2 . Given a total rate budget \bar{R} , find the R_1 and R_2 that minimize the total distortion.
2. **Uniform quantization** A random variable has the following probability density function

$$f_X(x) = \begin{cases} a & -1.5 \leq x < -0.5 \\ 2a & -0.5 \leq x < 0.5 \\ 4a & 0.5 \leq x \leq 1.5. \end{cases} \quad (2)$$

It is quantized by

$$Q_X(x) = \begin{cases} -1 & -\infty < x < -0.5 \\ 0 & -0.5 \leq x < 0.5 \\ 1 & 0.5 \leq x < \infty. \end{cases} \quad (3)$$

- (a) What is a ?
- (b) Plot the quantizer function.
- (c) Calculate the mean-square error of the quantization on the source.
- (d) Redo the calculation with another random variable, which has this probability density function

$$f_X(x) = 2, -0.25 \leq x \leq 0.25. \quad (4)$$

3. **Problem 8.21, modified** Derive the 1-bit Lloyd-Max cell centroids and quantization thresholds for the uniform distribution density function

$$p(s) = \begin{cases} \frac{1}{2A} & -A \leq s \leq A \\ 0 & \text{otherwise.} \end{cases} \quad (5)$$

4. **Lloyd-Max Scalar Quantizer** You are supposed to design a 2-bit scalar quantizer that uses a squared error criterion. Consider the experimental data $\{0, 0, 1, 2, 2, 6, 6, 6, 8, 8, 8\}$. You use as initial condition for your codebook $\{0, 1, 2, 3\}$.
- (a) Apply the Lloyd algorithm to train the above codebook with the given data.
 - (b) In what sense is the solution of the Lloyd algorithm optimal?
 - (c) Compute the total error for the solution you found above. Is the initial condition a good one and why? Can you define a better one?