

Laboratorium 1

Oracle PL/SQL


Mateusz Łopaciński

Spis treści

1. Schemat bazy danych.....	4
2. Tworzenie tabel.....	5
2.1. People.....	5
2.2. Trips.....	5
2.3. Reservations.....	5
2.4. ReservationsLog.....	5
3. Warunki integralnościowe.....	5
3.1. Trips.....	5
3.2. Reservations.....	5
3.3. ReservationsLog.....	6
4. Wstawianie danych do tabel.....	6
4.1. People.....	6
4.2. Trips.....	7
4.3. Reservations.....	7
5. Widoki.....	8
5.1. ReservationsView.....	8
5.2. TripsView.....	9
5.3. AvailableTripsView.....	10
6. Obiekty.....	10
6.1. TripParticipantObject i TripParticipantsTable.....	10
6.2. PersonReservationObject i PersonReservationsTable.....	10
6.3. AvailableTripObject i AvailableTripsTable.....	11
7. Funkcje skalarne.....	11
7.1. getBookedPlacesNum.....	11
7.2. getAvailablePlacesNum.....	11
7.3. doesTripExist.....	12
7.4. doesPersonExist.....	12
7.5. doesReservationExist.....	13
7.6. hasTripTakenPlace.....	13
8. Funkcje tabelaryczne.....	14
8.1. getTripParticipants.....	14
8.2. getPersonReservations.....	15
8.3. getAvailableTripsTo.....	16
9. Procedury (wersja 1.).....	16
9.1. addReservation.....	16
9.2. modifyReservationStatus.....	18
9.3. modifyReservationNoPlaces.....	19

9.4.	modifyMaxNoPlaces	20
10.	Triggery	21
10.1.	AI_ReservationInsert	21
10.2.	AU_ReservationStatusUpdate	22
10.3.	AU_ReservationNoPlacesUpdate	22
10.4.	BI_ReservationInsert	23
10.5.	BU_ReservationStatusUpdate	23
10.6.	BU_ReservationNoPlacesUpdate	24
10.7.	BU_TripMaxNoPlacesUpdate	24
11.	Procedury (wersja 2.)	25
11.1.	addReservation	25
11.2.	modifyReservationStatus	25
11.3.	modifyReservationNoPlaces	26
11.4.	modifyMaxNoPlaces	26

1. Schemat bazy danych



2. Tworzenie tabel

2.1. People

```
CREATE TABLE People (  
    person_id INT GENERATED ALWAYS AS IDENTITY NOT NULL,  
    firstname VARCHAR2(50) NOT NULL,  
    lastname VARCHAR2(50) NOT NULL,  
    CONSTRAINT People_pk PRIMARY KEY (person_id)  
);
```

2.2. Trips

```
CREATE TABLE Trips (  
    trip_id INT GENERATED ALWAYS AS IDENTITY NOT NULL,  
    name VARCHAR2(100) NOT NULL,  
    country VARCHAR2(50) NOT NULL,  
    trip_date DATE NOT NULL,  
    max_no_places INT NOT NULL,  
    CONSTRAINT Trips_pk PRIMARY KEY (trip_id)  
);
```

2.3. Reservations

```
CREATE TABLE Reservations (  
    reservation_id INT GENERATED ALWAYS AS IDENTITY NOT NULL,  
    trip_id INT NOT NULL,  
    person_id INT NOT NULL,  
    status CHAR(1) NOT NULL,  
    no_places INT NOT NULL,  
    CONSTRAINT Reservations_pk PRIMARY KEY (reservation_id)  
);
```

2.4. ReservationsLog

```
CREATE TABLE ReservationsLog (  
    log_id INT GENERATED ALWAYS AS IDENTITY NOT NULL,  
    reservation_id INT NOT NULL,  
    log_date DATE NOT NULL,  
    status CHAR(1) NOT NULL,  
    no_places INT NOT NULL,  
    CONSTRAINT ReservationsLog_pk PRIMARY KEY (log_id)  
);
```

3. Warunki integralnościowe

Poniżej umieściłem warunki integralnościowe, które nie zostały zdefiniowane w kodzie tworzącym tabele.

3.1. Trips

```
ALTER TABLE Trips  
ADD CONSTRAINT Trips_chk1 CHECK (max_no_places > 0);
```

3.2. Reservations

```
ALTER TABLE Reservations  
ADD CONSTRAINT Reservations_fk1 FOREIGN KEY (person_id)  
REFERENCES People(person_id);
```

```

ALTER TABLE Reservations
ADD CONSTRAINT Reservations_fk2 FOREIGN KEY (trip_id)
REFERENCES Trips(trip_id);

ALTER TABLE Reservations
ADD CONSTRAINT Reservations_chk1 CHECK (status IN ('n', 'p', 'c'));

ALTER TABLE Reservations
ADD CONSTRAINT Reservations_chk2 CHECK (no_places > 0);

```

3.3. ReservationsLog

```

ALTER TABLE ReservationsLog
ADD CONSTRAINT ReservationLog_chk1 CHECK (status IN ('n', 'p', 'c'));

ALTER TABLE ReservationsLog
ADD CONSTRAINT ReservationsLog_chk2 CHECK (no_places > 0);

```

4. Wstawianie danych do tabel

4.1. People

```

INSERT INTO People (firstname, lastname)
VALUES ('Adam', 'Kowalski');

INSERT INTO People (firstname, lastname)
VALUES ('Jan', 'Nowak');

INSERT INTO People (firstname, lastname)
VALUES ('Andrzej', 'Kowalczyk');

INSERT INTO People (firstname, lastname)
VALUES ('Anna', 'Klimek');

INSERT INTO People (firstname, lastname)
VALUES ('Zbigniew', 'Zygora');

INSERT INTO People (firstname, lastname)
VALUES ('Rafał', 'Noga');

INSERT INTO People (firstname, lastname)
VALUES ('Aleksandra', 'Sobczak');

INSERT INTO People (firstname, lastname)
VALUES ('Maryla', 'Ordon');

INSERT INTO People (firstname, lastname)
VALUES ('Piotr', 'Słota');

INSERT INTO People (firstname, lastname)
VALUES ('Aleks', 'Stachowiak');

COMMIT;

```

W rezultacie otrzymujemy tabelę:

	person_id	firstname	lastname
1	1	Adam	Kowalski
2	2	Jan	Nowak

3	3	Andrzej	Kowalczyk
4	4	Anna	Klimek
5	5	Zbigniew	Zygora
6	6	Rafał	Noga
7	7	Aleksandra	Sobczak
8	8	Maryla	Ordon
9	9	Piotr	Słota
10	10	Aleks	Stachowiak

Tabela 4.1. People

4.2. Trips

```
INSERT INTO Trips (name, country, trip_date, max_no_places)
VALUES ('wycieczka do Paryza', 'Francja', TO_DATE('2021-09-03', 'yyyy-mm-dd'), 5);
```

```
INSERT INTO Trips (name, country, trip_date, max_no_places)
VALUES ('wycieczka do Krakowa', 'Polska', TO_DATE('2022-12-05', 'yyyy-mm-dd'), 8);
```

```
INSERT INTO Trips (name, country, trip_date, max_no_places)
VALUES ('wycieczka do Warszawy', 'Polska', TO_DATE('2022-04-11', 'yyyy-mm-dd'), 12);
```

```
INSERT INTO Trips (name, country, trip_date, max_no_places)
VALUES ('wycieczka do Madrytu', 'Hiszpania', TO_DATE('2022-07-02', 'yyyy-mm-dd'), 8);
```

```
COMMIT;
```

W rezultacie otrzymujemy tabelę:

	trip_id	name	country	trip_date	max_no_places
1	1	wycieczka do Paryza	Francja	2021-09-03	5
2	2	wycieczka do Krakowa	Polska	2022-12-05	8
3	3	wycieczka do Warszawy	Polska	2022-04-11	12
4	4	wycieczka do Madrytu	Hiszpania	2022-07-02	8

Tabela 4.2. Trips

4.3. Reservations

```
INSERT INTO Reservations (trip_id, person_id, no_places, status)
VALUES (1, 1, 1, 'n');
```

```
INSERT INTO Reservations (trip_id, person_id, no_places, status)
VALUES (1, 2, 2, 'p');
```

```
INSERT INTO Reservations (trip_id, person_id, no_places, status)
VALUES (2, 1, 1, 'p');
```

```
INSERT INTO Reservations (trip_id, person_id, no_places, status)
VALUES (2, 2, 1, 'c');
```

```
INSERT INTO Reservations (trip_id, person_id, no_places, status)
VALUES (2, 4, 2, 'n');
```

```

INSERT INTO Reservations (trip_id, person_id, no_places, status)
VALUES (3, 5, 4, 'c');

INSERT INTO Reservations (trip_id, person_id, no_places, status)
VALUES (3, 5, 3, 'n');

INSERT INTO Reservations (trip_id, person_id, no_places, status)
VALUES (3, 6, 4, 'p');

INSERT INTO Reservations (trip_id, person_id, no_places, status)
VALUES (4, 7, 3, 'p');

INSERT INTO Reservations (trip_id, person_id, no_places, status)
VALUES (4, 9, 1, 'c');

INSERT INTO Reservations (trip_id, person_id, no_places, status)
VALUES (4, 8, 5, 'n');

COMMIT;

```

W rezultacie otrzymujemy tabelę:

	reservation_id	trip_id	person_id	status	no_places
1	1	1	1	n	1
2	2	1	2	p	2
3	3	2	1	p	1
4	4	2	2	c	1
5	5	2	4	n	2
6	6	3	5	c	4
7	7	3	5	n	3
8	8	3	6	p	4
9	9	4	7	p	3
10	10	4	9	c	1
11	11	4	8	n	5

Tabela 4.3. Reservations

5. Widoki

5.1. ReservationsView

reservations(country,trip_date,trip_name, firstname, lastname,reservation_id,no_places,status)

```

CREATE OR REPLACE VIEW ReservationsView
AS
SELECT
    t.trip_id,
    t.country,
    t.trip_date,
    t.name AS trip_name,
    p.person_id,
    p.firstname,
    p.lastname,
    r.reservation_id,
    r.no_places,
    r.status

```



```

FROM Trips t
INNER JOIN Reservations r
ON r.trip_id = t.trip_id
INNER JOIN People p
on p.person_id = r.person_id;

SELECT * FROM ReservationsView;

```

W rezultacie otrzymujemy tabelę:

	trip_id	country	trip_date	trip_name	person_id	firstname	lastname	reservation_id	no_places	status
1	1	Francja	2021-09-03	wycieczka do Paryża	1	Adam	Kowalski	1	1	n
2	2	Polska	2022-12-05	wycieczka do Krakowa	1	Adam	Kowalski	3	1	p
3	1	Francja	2021-09-03	wycieczka do Paryża	2	Jan	Nowak	2	2	p
4	2	Polska	2022-12-05	wycieczka do Krakowa	2	Jan	Nowak	4	1	c
5	2	Polska	2022-12-05	wycieczka do Krakowa	4	Anna	Klimek	5	2	n
6	3	Polska	2022-04-11	wycieczka do Warszawy	5	Zbigniew	Zygora	6	4	c
7	3	Polska	2022-04-11	wycieczka do Warszawy	5	Zbigniew	Zygora	7	3	n
8	3	Polska	2022-04-11	wycieczka do Warszawy	6	Rafał	Noga	8	4	p
9	4	Hiszpania	2022-07-02	Wycieczka do Madrytu	7	Aleksandr a	Sobczak	9	3	p
10	4	Hiszpania	2022-07-02	Wycieczka do Madrytu	8	Maryla	Ordon	11	5	n
11	4	Hiszpania	2022-07-02	Wycieczka do Madrytu	9	Piotr	Słota	10	1	c

Tabela 5.1. Tabela utworzona przez widok ReservationsView

5.2. TripsView

trips(country,trip_date, trip_name,max_no_places, no_available_places)

```

CREATE OR REPLACE VIEW TripsView
AS
SELECT
    trip_id,
    country,
    trip_date,
    name AS trip_name,
    max_no_places,
    getAvailablePlaces(trip_id) AS no_available_places
FROM Trips;

```

W rezultacie otrzymujemy tabelę:

	trip_id	country	trip_date	trip_name	max_no_places	no_available_places
1	1	Francja	2021-09-03	wycieczka do Paryża	5	2
2	2	Polska	2022-12-05	wycieczka do Krakowa	8	5
3	3	Polska	2022-04-11	wycieczka do Warszawy	12	5
4	4	Hiszpania	2022-07-02	wycieczka do Madrytu	8	0

Tabela 5.2. Tabela utworzona przez widok TripsView

5.3. AvailableTripsView

trips(country,trip_date, trip_name, max_no_places, no_available_places)

```
CREATE OR REPLACE VIEW AvailableTripsView
AS
SELECT *
FROM TripsView
WHERE trip_date > SYSDATE
AND no_available_places > 0;
```

W rezultacie otrzymujemy tabelę:

	trip_id	country	trip_date	trip_name	max_no_places	no_available_places
1	2	Polska	2022-12-05	wycieczka do Krakowa	8	5
2	3	Polska	2022-04-11	wycieczka do Warszawy	12	5

Tabela 5.2. Tabela utworzona przez widok AvailableTripsView

6. Obiekty

6.1. TripParticipantObject i TripParticipantsTable

```
CREATE OR REPLACE TYPE TripParticipantObject AS OBJECT (
    firstname VARCHAR2(50),
    lastname VARCHAR2(50),
    reservation_id INT,
    no_places INT,
    status CHAR(1)
);
```

```
CREATE OR REPLACE TYPE TripParticipantsTable IS TABLE OF
TripParticipantObject;
```

6.2. PersonReservationObject i PersonReservationsTable

```
CREATE OR REPLACE TYPE PersonReservationObject AS OBJECT (
    trip_id INT,
    country VARCHAR2(50),
```

```

        trip_date DATE,
        trip_name VARCHAR2(100),
        reservation_id INT,
        no_places INT,
        status CHAR(1)
    );

```

```

CREATE OR REPLACE TYPE PeopleReservationsTable IS TABLE OF
PersonReservationObject;

```

6.3. AvailableTripObject i AvailableTripsTable

```

CREATE OR REPLACE TYPE AvailableTripObject AS OBJECT (
    trip_id INT,
    name VARCHAR2(100),
    country VARCHAR2(50),
    trip_date DATE,
    max_no_places INT
);

```

```

CREATE OR REPLACE TYPE AvailableTripsTable IS TABLE OF AvailableTripObject;

```

7. Funkcje skalarne

7.1. getBookedPlacesNum

```

CREATE OR REPLACE FUNCTION getBookedPlacesNum(
    p_trip_id Trips.trip_id%TYPE
)
RETURN Reservations.no_places%TYPE
AS
    l_booked_places Reservations.no_places%TYPE;
BEGIN
    SELECT NVL(SUM(no_places), 0)
    INTO l_booked_places
    FROM Reservations
    WHERE trip_id = p_trip_id
        AND status != 'c';

    RETURN l_booked_places;
END;

```

Przykład działania:

```

BEGIN
    DBMS_OUTPUT.PUT_LINE(getBookedPlacesNum(1));
END;

```

Wynik: 3

7.2. getAvailablePlacesNum

```

CREATE OR REPLACE FUNCTION getAvailablePlacesNum(
    p_trip_id Trips.trip_id%TYPE
)
RETURN Reservations.no_places%TYPE
AS
    l_available_places Trips.max_no_places%TYPE;
BEGIN
    SELECT max_no_places - getBookedPlacesNum(trip_id)
    INTO l_available_places
    FROM Trips

```

```

WHERE trip_id = p_trip_id;

RETURN l_available_places;

EXCEPTION
    WHEN NO_DATA_FOUND THEN
        RAISE_APPLICATION_ERROR(-20000, 'Trip with id: ' || p_trip_id
|| ' does not exist');
        RETURN NULL;
END;
```

Przykład działania:

```

BEGIN
    DBMS_OUTPUT.PUT_LINE(getAvailablePlacesNum(1));
END;
```

Wynik: 2

7.3. doesTripExist

```

CREATE OR REPLACE FUNCTION doesTripExist(
    p_trip_id Trips.trip_id%TYPE
)
RETURN BOOLEAN
AS
    exist NUMBER;
BEGIN
    SELECT
        CASE
            WHEN EXISTS(SELECT * FROM Trips WHERE trip_id = p_trip_id) THEN 1
            ELSE 0
        END
    INTO exist
    FROM Dual;

    IF exist = 1 THEN
        RETURN TRUE;
    ELSE
        RETURN FALSE;
    END IF;
END;
```

Przykład działania:

```

BEGIN
    IF doesTripExist(1) THEN
        DBMS_OUTPUT.PUT_LINE('Trip exists');
    ELSE
        DBMS_OUTPUT.PUT_LINE('Trip does not exist');
    END IF;
END;
```

Wynik: Trip exists

7.4. doesPersonExist

```

CREATE OR REPLACE FUNCTION doesPersonExist(
    p_person_id People.person_id%TYPE
)
RETURN BOOLEAN
```

```

AS
    exist NUMBER;
BEGIN
    SELECT
        CASE
            WHEN EXISTS(SELECT * FROM People WHERE person_id = p_person_id) THEN 1
            ELSE 0
        END
    INTO exist
    FROM Dual;

    IF exist = 1 THEN
        RETURN TRUE;
    ELSE
        RETURN FALSE;
    END IF;
END;

```

Przykład działania:

```

BEGIN
    IF doesPersonExist(123) THEN
        DBMS_OUTPUT.PUT_LINE('Person exists');
    ELSE
        DBMS_OUTPUT.PUT_LINE('Person does not exist');
    END IF;
END;

```

Wynik: Person does not exists

7.5. doesReservationExist

```

CREATE OR REPLACE FUNCTION doesReservationExist(
    p_reservation_id Reservations.reservation_id%TYPE
)
RETURN BOOLEAN
AS
    exist NUMBER;
BEGIN
    SELECT
        CASE
            WHEN EXISTS(SELECT * FROM Reservations WHERE reservation_id =
p_reservation_id) THEN 1
            ELSE 0
        END
    INTO exist
    FROM Dual;

    IF exist = 1 THEN
        RETURN TRUE;
    ELSE
        RETURN FALSE;
    END IF;
END;

```

Przykład działania:

```

BEGIN
    IF doesReservationExist(10) THEN
        DBMS_OUTPUT.PUT_LINE('Reservation exists');
    ELSE
        DBMS_OUTPUT.PUT_LINE('Reservation does not exist');
    END IF;

```

```
END;
```

Wynik: Reservation exists

7.6. hasTripTakenPlace

```
CREATE OR REPLACE FUNCTION hasTripTakenPlace(  
    p_trip_id Trips.trip_id%TYPE,  
    p_date DATE DEFAULT SYSDATE  
)  
RETURN BOOLEAN  
AS  
    l_trip_date DATE;  
BEGIN  
    IF NOT doesTripExist(p_trip_id) THEN  
        RAISE_APPLICATION_ERROR(-20000, 'There is no trip with id ' ||  
p_trip_id || ' in the database');  
    END IF;  
  
    SELECT trip_date  
    INTO l_trip_date  
    FROM Trips  
    WHERE trip_id = p_trip_id;  
  
    IF l_trip_date <= p_date THEN  
        RETURN TRUE;  
    ELSE  
        RETURN FALSE;  
    END IF;  
END;
```

Przykład działania:

```
BEGIN  
    IF hasTripTakenPlace(2) THEN  
        DBMS_OUTPUT.PUT_LINE('Trip took place before');  
    ELSE  
        DBMS_OUTPUT.PUT_LINE('Trip has not taken place yet');  
    END IF;  
END;
```

Wynik: Trip has not taken place yet

8. Funkcje tabelaryczne

8.1. getTripParticipants

```
CREATE OR REPLACE FUNCTION getTripParticipants(  
    p_trip_id Trips.trip_id%TYPE  
)  
RETURN TripParticipantsTable  
AS  
    l_result TripParticipantsTable;  
BEGIN  
    IF NOT doesTripExist(p_trip_id) THEN  
        RAISE_APPLICATION_ERROR(-20000, 'There are is no trip with id ' ||  
p_trip_id || ' in the database');  
    END IF;  
  
    SELECT TripParticipantObject(  
        firstname,  
        lastname,
```

```

        reservation_id,
        no_places,
        status
    )
    BULK COLLECT INTO l_result
    FROM ReservationsView
    WHERE trip_id = p_trip_id
        AND status != 'c';

    RETURN l_result;
END;
```

Przykład działania:

```
SELECT * FROM getTripParticipants(3);
```

Rezultat:

	firstname	lastname	reservation_id	no_places	status
1	Zbigniew	Zygora	7	3	n
2	Rafał	Noga	8	4	p

Tabela 8.1. Przykładowa tabela zwrócona przez funkcję getTripParticipants

8.2. getPersonReservations

```

CREATE OR REPLACE FUNCTION getPersonReservations(
    p_person_id People.person_id%TYPE
)
RETURN PeopleReservationsTable
AS
    l_result PeopleReservationsTable;
BEGIN
    IF NOT doesPersonExist(p_person_id) THEN
        RAISE_APPLICATION_ERROR(-20000, 'There is no person with id ' ||
p_person_id || ' in the database');
    END IF;

    SELECT PersonReservationObject(
        trip_id,
        country,
        trip_date,
        trip_name,
        reservation_id,
        no_places,
        status
    )
    BULK COLLECT INTO l_result
    FROM ReservationsView
    WHERE person_id = p_person_id;

    RETURN l_result;
END;
```

Przykład działania:

```
SELECT * FROM getPersonReservations(2);
```

Rezultat:

	trip_id	country	trip_date	trip_name	reservation_id	no_places	status
1	1	Francja	2021-09-03	wycieczka do Paryża	2	2	p
2	2	Polska	2022-12-05	wycieczka do Krakowa	4	1	c

Tabela 8.2. Przykładowa tabela zwrócona przez funkcję `getPersonReservations`

8.3. `getAvailableTripsTo`

```
-- (When there are no remaining places, a trip is considered unavailable -
-- see Spain in examples)
-- (if p_from_date is lower than the current date, a function below will
-- return only trips which
-- date is between the current date and the p_to_date)
CREATE OR REPLACE FUNCTION getAvailableTripsTo(
    p_country_name Trips.country%TYPE,
    p_from_date DATE,
    p_to_date DATE
)
RETURN AvailableTripsTable
AS
    l_result AvailableTripsTable;
BEGIN
    -- Show warning information if the current date is greater than the
    p_from_date
    IF p_from_date < SYSDATE THEN
        DBMS_OUTPUT.PUT_LINE('Warning: Specified trip start date (' ||
p_from_date ||
                                ') is lower than the current date.' || 'Current
date (' || SYSDATE ||
                                ') will be used instead');
    END IF;

    SELECT AvailableTripObject(
        trip_id,
        trip_name,
        country,
        trip_date,
        max_no_places
    )
    BULK COLLECT
    INTO l_result
    FROM AvailableTripsView
    WHERE country = p_country_name
        AND trip_date BETWEEN p_from_date AND p_to_date;

    RETURN l_result;
END;
```

Przykład działania:

```
SELECT * FROM getAvailableTripsTo('Polska', '2020-01-01', '2022-12-31');
```

Rezultat:

	trip_id	name	country	trip_date	max_no_places
1	2	Wycieczka do Krakowa	Polska	2022-12-05	8
2	3	Wycieczka do Warszawy	Polska	2022-04-11	12

9. Procedury (wersja 1.)

9.1. addReservation

Poniżej znajdują się 1. wersje procedur (zanim zostały dodane triggerzy, które obsługują sprawdzanie poprawności odpowiednich danych).

```
CREATE OR REPLACE PROCEDURE addReservation(
    p_trip_id Trips.trip_id%TYPE,
    p_person_id People.person_id%TYPE,
    p_no_places Reservations.no_places%TYPE
)
AS
    l_available_places Reservations.no_places%TYPE;
BEGIN
    IF NOT doesPersonExist(p_person_id) THEN
        RAISE_APPLICATION_ERROR(-20001, 'The person with id ' || p_person_id
|| ' does not exist');
    END IF;

    IF hasTripTakenPlace(p_trip_id) THEN
        RAISE_APPLICATION_ERROR(-20001, 'The trip with id ' || p_trip_id || '
took place before');
    END IF;

    IF p_no_places < 1 THEN
        RAISE_APPLICATION_ERROR(-20001, 'Cannot book less than 1 place for a
trip');
    END IF;

    l_available_places := getAvailablePlacesNum(p_trip_id);

    IF l_available_places = 0 THEN
        RAISE_APPLICATION_ERROR(-20001, 'There are no available places for a
trip with id ' || p_trip_id);
    ELSIF l_available_places < p_no_places THEN
        RAISE_APPLICATION_ERROR(-20001, 'There are only ' ||
l_available_places ||
                                ' places available for a trip with id
' || p_trip_id);
    END IF;

    INSERT INTO Reservations (trip_id, person_id, status, no_places)
VALUES (p_trip_id, p_person_id, 'n', p_no_places);

    COMMIT;
END;
```

Przykład działania:

```
BEGIN
    addReservation(2, 1, 5);
END;
```

Rezerwacje po użyciu procedury:

	reservation_id	trip_id	person_id	status	no_places
1	1	1	1	n	1
2	2	1	2	p	2
3	3	2	1	p	1

4	4	2	2 c	1
5	5	2	4 n	2
6	6	3	5 c	4
7	7	3	5 n	3
8	8	3	6 p	4
9	9	4	7 p	3
10	10	4	9 c	1
11	11	4	8 n	5
12	12	2	1 n	5

Tabela 9.1. Rezerwacje po dodaniu nowej rezerwacji

Jak widzimy, w ostatnim wierszu tabeli 9.1. pojawiła się nowa rezerwacja o zadanych parametrach.

9.2. modifyReservationStatus

```

CREATE OR REPLACE PROCEDURE modifyReservationStatus(
    p_reservation_id Reservations.reservation_id%TYPE,
    p_status Reservations.status%TYPE
)
AS
    l_curr_status Reservations.status%TYPE;
    l_trip_id Reservations.trip_id%TYPE;
    l_no_places Reservations.no_places%TYPE;
    l_available_places Reservations.no_places%TYPE;
BEGIN
    SELECT
        status,
        trip_id,
        no_places
    INTO
        l_curr_status,
        l_trip_id,
        l_no_places
    FROM Reservations
    WHERE reservation_id = p_reservation_id;

    CASE p_status
    WHEN l_curr_status THEN
        DBMS_OUTPUT.PUT_LINE('The reservation with id ' || p_reservation_id
||
                                ' has already the status: ' || p_status);

        RETURN;
    WHEN 'c' THEN
        NULL;
    WHEN 'n' THEN
        RAISE_APPLICATION_ERROR(-20001, 'Cannot change the status of the
reservation with id ' ||
                                p_reservation_id || ' to: n');
    WHEN 'p' THEN
        -- Check if can make cancelled reservation available (paid) again
        -- (check if there are enough empty places for a trip)
        IF l_curr_status = 'c' THEN
            l_available_places := getAvailablePlacesNum(l_trip_id);

            IF l_available_places < l_no_places THEN
                RAISE_APPLICATION_ERROR(-20001, 'Not enough places available
to update the cancelled reservation status');
            END IF;
        END IF;
    END IF;
END IF;

```

```

ELSE
    RAISE_APPLICATION_ERROR(-20001, 'Status: ' || p_status || ' is not a
valid reservation status');
END CASE;

-- If everything is correct, update the reservation status
UPDATE Reservations
SET status = p_status
WHERE reservation_id = p_reservation_id;

EXCEPTION
    WHEN NO_DATA_FOUND THEN
        RAISE_APPLICATION_ERROR(-20001, 'There is no reservation with id
' || p_reservation_id || ' in the database');

COMMIT;
END;

```

Przykład działania:

```

BEGIN
    modifyReservationStatus(2, 'c');
    modifyReservationStatus(1, 'c');
    modifyReservationStatus(12, 'p');
END;

```

Rezerwacje po użyciu procedury:

	reservation_id	trip_id	person_id	status	no_places
1	1	1	1	c	1
2	2	1	2	c	2
3	3	2	1	p	1
4	4	2	2	c	1
5	5	2	4	n	2
6	6	3	5	c	4
7	7	3	5	n	3
8	8	3	6	p	4
9	9	4	7	p	3
10	10	4	9	c	1
11	11	4	8	n	5
12	12	2	1	p	5

Tabela 9.2. Rezerwacje po modyfikacji statusu wybranych rezerwacji

9.3. modifyReservationNoPlaces

```

CREATE OR REPLACE PROCEDURE modifyReservationNoPlaces (
    p_reservation_id Reservations.reservation_id%TYPE,
    p_no_places Reservations.no_places%TYPE
)
AS
    l_curr_no_places Reservations.no_places%TYPE;
    l_available_places Reservations.no_places%TYPE;
BEGIN
    SELECT
        no_places,
        getAvailablePlacesNum(trip_id)
    INTO
        l_curr_no_places,

```

```

        l_available_places
    FROM Reservations
    WHERE reservation_id = p_reservation_id;

    IF p_no_places <= 0 THEN
        RAISE_APPLICATION_ERROR(-20001, 'The number of booked places should
be greater than 0');
    ELSEIF p_no_places - l_curr_no_places > l_available_places THEN
        RAISE_APPLICATION_ERROR(-20001, 'There are not enough free places.
Max possible number of places to book: ' ||
                                (l_available_places +
l_curr_no_places));
    END IF;

    UPDATE Reservations
    SET no_places = p_no_places
    WHERE reservation_id = p_reservation_id;

    EXCEPTION
        WHEN NO_DATA_FOUND THEN
            RAISE_APPLICATION_ERROR(-20001, 'There is no reservation with id
' || p_reservation_id || ' in the database');

    COMMIT;
END;
```

Przykład działania:

```

BEGIN
    modifyReservationNoPlaces(1, 6);
END;
```

Rezerwacje po użyciu procedury:

	reservation_id	trip_id	person_id	status	no_places
1	1	1	1	c	6
2	2	1	2	c	2
3	3	2	1	p	1
4	4	2	2	c	1
5	5	2	4	n	2
6	6	3	5	c	4
7	7	3	5	n	3
8	8	3	6	p	4
9	9	4	7	p	3
10	10	4	9	c	1
11	11	4	8	n	5
12	12	2	1	p	5

Tabela 9.3. Rezerwacje po modyfikacji liczby miejsc w rezerwacji o id równym 1

9.4. modifyMaxNoPlaces

```

CREATE OR REPLACE PROCEDURE modifyMaxNoPlaces(
    p_trip_id Trips.trip_id%TYPE,
    p_max_no_places Trips.max_no_places%TYPE
)
AS
    l_booked_places Reservations.no_places%TYPE;
```

```

        l_curr_max_no_places Trips.max_no_places%TYPE;
BEGIN
    SELECT
        max_no_places,
        getBookedPlacesNum(p_trip_id)
    INTO
        l_curr_max_no_places,
        l_booked_places
    FROM Trips
    WHERE trip_id = p_trip_id;

    IF p_max_no_places = l_curr_max_no_places THEN
        DBMS_OUTPUT.PUT_LINE('The trip with id ' || p_trip_id ||
                               ' has already the maximum number of places set
to ' || l_curr_max_no_places);
        RETURN;
    END IF;

    IF p_max_no_places < l_booked_places THEN
        RAISE_APPLICATION_ERROR(-20001, 'The maximum number of places (' ||
p_max_no_places ||
                               ') cannot be lower than the total
number of booked places (' || l_booked_places ||
                               ') for a trip wit id ' || p_trip_id);
    END IF;

    UPDATE Trips
    SET max_no_places = p_max_no_places
    WHERE trip_id = p_trip_id;

    EXCEPTION
        WHEN NO_DATA_FOUND THEN
            RAISE_APPLICATION_ERROR(-20001, 'There is no trip with id ' ||
p_trip_id || ' in the database');
        COMMIT;
END;

```

Przykład działania:

```

BEGIN
    modifyMaxNoPlaces(4, 8);
    modifyMaxNoPlaces(3, 7);
    modifyMaxNoPlaces(2, 10);
END;

```

Wycieczki po użyciu procedury:

	trip_id	name	country	trip_date	max_no_places
1	1	wycieczka do Paryża	Francja	2021-09-03	5
2	2	wycieczka do Krakowa	Polska	2022-12-05	10
3	3	wycieczka do Warszawy	Polska	2022-04-11	7
4	4	wycieczka do Madrytu	Hiszpania	2022-07-02	8

Tabela 9.4. Wycieczki po modyfikacji maksymalnej liczby miejsc

10. Triggery

10.1. AI_ReservationInsert

```

CREATE OR REPLACE TRIGGER AI_ReservationInsert
AFTER INSERT
ON Reservations

```

```

FOR EACH ROW
BEGIN
    INSERT INTO ReservationsLog (reservation_id, log_date, status,
no_places)
    VALUES (:NEW.reservation_id, SYSDATE, :NEW.status, :NEW.no_places);
END;

```

Przykład działania:

```

BEGIN
    addReservation(2, 1, 1);
END;

```

Tabela ReservationsLog po dodaniu rezerwacji do tabeli Reservations:

	log_id	reservation_id	log_date	status	no_places
1	1	13	2022-03-12 02:05:23	n	1

Tabela 10.1. Tabela ReservationsLog po dodaniu nowej rezerwacji

10.2. AU_ReservationStatusUpdate

```

CREATE OR REPLACE TRIGGER AU_ReservationStatusUpdate
AFTER UPDATE
OF status ON Reservations
FOR EACH ROW
BEGIN
    IF :NEW.status != :OLD.status THEN
        INSERT INTO ReservationsLog (reservation_id, log_date, status,
no_places)
        VALUES (:NEW.reservation_id, SYSDATE, :NEW.status, :NEW.no_places);
    END IF;
END;

```

Przykład działania:

```

DECLARE
    l_reservation_id Reservations.reservation_id%TYPE;
BEGIN
    SELECT MAX(reservation_id)
    INTO l_reservation_id
    FROM Reservations;

    modifyReservationStatus(l_reservation_id, 'p');
END;

```

Tabela ReservationsLog po zaktualizowaniu statusu rezerwacji:

	log_id	reservation_id	log_date	status	no_places
1	1	13	2022-03-12 02:05:23	n	1
2	2	13	2022-03-12 02:10:14	p	1

Tabela 10.2. Tabela ReservationsLog po zaktualizowaniu statusu rezerwacji

10.3. AU_ReservationNoPlacesUpdate

```

CREATE OR REPLACE TRIGGER AU_ReservationNoPlacesUpdate
AFTER UPDATE
OF no_places ON Reservations
FOR EACH ROW
BEGIN
    IF :NEW.no_places != :OLD.no_places THEN
        INSERT INTO ReservationsLog (reservation_id, log_date, status,
no_places)

```

```

VALUES (:NEW.reservation_id, SYSDATE, :NEW.status, :NEW.no_places);
END IF;
END;

```

Przykład działania:

```

DECLARE
l_reservation_id Reservations.reservation_id%TYPE;
BEGIN
SELECT MAX(reservation_id)
INTO l_reservation_id
FROM Reservations;

modifyReservationNoPlaces(l_reservation_id, 2);
END;

```

Tabela ReservationsLog po zaktualizowaniu liczby zarezerwowanych miejsc:

	log_id	reservation_id	log_date	status	no_places
1	1	13	2022-03-12 02:05:23	n	1
2	2	13	2022-03-12 02:10:14	p	1
3	3	13	2022-03-12 02:13:16	p	2

Tabela 10.2. Tabela ReservationsLog po zaktualizowaniu liczby zarezerwowanych miejsc

10.4. BI_ReservationInsert

```

CREATE OR REPLACE TRIGGER BI_ReservationInsert
BEFORE INSERT
ON Reservations
FOR EACH ROW
DECLARE
l_available_places Reservations.no_places%TYPE;
BEGIN
IF NOT doesPersonExist(:NEW.person_id) THEN
RAISE_APPLICATION_ERROR(-20001, 'The person with id ' ||
:NEW.person_id || ' does not exit');
END IF;

IF :NEW.no_places < 1 THEN
RAISE_APPLICATION_ERROR(-20001, 'Cannot book less than 1 place for a
trip');
END IF;

l_available_places := getAvailablePlacesNum(:NEW.trip_id);

IF l_available_places = 0 THEN
RAISE_APPLICATION_ERROR(-20001, 'There are no available places for a
trip with id ' || :NEW.trip_id);
ELSIF l_available_places < :NEW.no_places THEN
RAISE_APPLICATION_ERROR(-20001, 'There are only ' ||
l_available_places ||
' places available for a trip with id
' || :NEW.trip_id);
END IF;
END;

```

Ten trigger pozwala na wyodrębnienie części funkcjonalności z procedury **addReservation**. Ponieważ nie wprowadza on nowej funkcjonalności, a jedynie pozwala na uproszczenie kodu procedury (nowy kod procedury zamieściłem w kolejnej sekcji), nie zamieszczam tutaj osobnych przykładów działania (działanie triggera wraz ze zmodyfikowaną procedurą jest analogiczne do działania wcześniejszej implementacji procedury **addReservation**).

10.5. BU_ReservationStatusUpdate

```
CREATE OR REPLACE TRIGGER BU_ReservationStatusUpdate
BEFORE UPDATE
OF status ON Reservations
FOR EACH ROW
DECLARE
    PRAGMA AUTONOMOUS_TRANSACTION;
    l_available_places Reservations.no_places%TYPE;
BEGIN
    CASE :NEW.status
    WHEN :OLD.status THEN
        DBMS_OUTPUT.PUT_LINE('The reservation with id ' ||
:NEW.reservation_id ||
                                ' has already the status: ' || :NEW.status);

        RETURN;
    WHEN 'c' THEN
        NULL;
    WHEN 'n' THEN
        RAISE_APPLICATION_ERROR(-20001, 'Cannot change the status of the
reservation with id ' ||
                                :NEW.reservation_id || ' to: n');

    WHEN 'p' THEN
        -- Check if can make cancelled reservation available (paid) again
        -- (check if there are enough empty places for a trip)
        IF :OLD.status = 'c' THEN
            l_available_places := getAvailablePlacesNum(:NEW.trip_id);

            IF l_available_places < :NEW.no_places THEN
                RAISE_APPLICATION_ERROR(-20001, 'Not enough places available
to update the cancelled reservation status');
            END IF;
        END IF;
    ELSE
        RAISE_APPLICATION_ERROR(-20001, 'Status: ' || :NEW.status || ' is not
a valid reservation status');
    END CASE;
END;
```

Ponownie, z tego samego powodu, co powyżej, nie zamieszczam przykładów.

10.6. BU_ReservationNoPlacesUpdate

```
CREATE OR REPLACE TRIGGER BU_ReservationNoPlacesUpdate
BEFORE UPDATE
OF no_places ON Reservations
FOR EACH ROW
DECLARE
    PRAGMA AUTONOMOUS_TRANSACTION;
    l_available_places Reservations.no_places%TYPE;
BEGIN
    l_available_places := getAvailablePlacesNum(:NEW.trip_id);

    IF :NEW.no_places <= 0 THEN
        RAISE_APPLICATION_ERROR(-20001, 'The number of booked places should
be greater than 0');
    ELSIF :NEW.no_places - :OLD.no_places > l_available_places THEN
        RAISE_APPLICATION_ERROR(-20001, 'There are not enough free places.
Max possible number of places to book: ' ||
                                (l_available_places +
:OLD.no_places));
    END IF;
END;
```


Ponownie, z tego samego powodu, co powyżej, nie zamieszczam przykładów.

10.7. BU_TripMaxNoPlacesUpdate

```
CREATE OR REPLACE TRIGGER BU_TripMaxNoPlacesUpdate
BEFORE UPDATE
OF max_no_places ON Trips
FOR EACH ROW
DECLARE
    l_booked_places Reservations.no_places%TYPE;
BEGIN
    l_booked_places := getBookedPlacesNum(:NEW.trip_id);

    IF :NEW.max_no_places = :OLD.max_no_places THEN
        DBMS_OUTPUT.PUT_LINE('The trip with id ' || :NEW.trip_id ||
                               ' has already the maximum number of places set
to ' || :OLD.max_no_places);
        RETURN;
    END IF;

    IF :NEW.max_no_places < l_booked_places THEN
        RAISE_APPLICATION_ERROR(-20001, 'The maximum number of places (' ||
:NEW.max_no_places ||
                               ') cannot be lower than the total
number of booked places (' || l_booked_places ||
                               ') for a trip wit id ' ||
:NEW.trip_id);
    END IF;
END;
```

Ponownie, z tego samego powodu, co powyżej, nie zamieszczam przykładów.

11. Procedury (wersja 2.)

Poniżej znajdują się 2. wersje procedur (z procedur została usunięta zawartość przeniesiona do triggerów).

11.1. addReservation

```
CREATE OR REPLACE PROCEDURE addReservation(
    p_trip_id Trips.trip_id%TYPE,
    p_person_id People.person_id%TYPE,
    p_no_places Reservations.no_places%TYPE
)
AS
BEGIN
    IF hasTripTakenPlace(p_trip_id) THEN
        RAISE_APPLICATION_ERROR(-20001, 'The trip with id ' || p_trip_id || ' took
place before');
    END IF;

    INSERT INTO Reservations (trip_id, person_id, status, no_places)
VALUES (p_trip_id, p_person_id, 'n', p_no_places);

    COMMIT;
END;
```

11.2. modifyReservationStatus

```
CREATE OR REPLACE PROCEDURE modifyReservationStatus(
    p_reservation_id Reservations.reservation_id%TYPE,
    p_status Reservations.status%TYPE
```

```

)
AS
BEGIN
    IF NOT doesReservationExist(p_reservation_id) THEN
        RAISE_APPLICATION_ERROR(-20001, 'There is no reservation with id ' ||
p_reservation_id || ' in the database');
    END IF;

    -- If everything is correct, update the reservation status
    UPDATE Reservations
    SET status = p_status
    WHERE reservation_id = p_reservation_id;

    COMMIT;
END;

```

11.3. modifyReservationNoPlaces

```

CREATE OR REPLACE PROCEDURE modifyReservationNoPlaces(
    p_reservation_id Reservations.reservation_id%TYPE,
    p_no_places Reservations.no_places%TYPE
)
AS
BEGIN
    IF NOT doesReservationExist(p_reservation_id) THEN
        RAISE_APPLICATION_ERROR(-20001, 'There is no reservation with id ' ||
p_reservation_id || ' in the database');
    END IF;

    UPDATE Reservations
    SET no_places = p_no_places
    WHERE reservation_id = p_reservation_id;

    COMMIT;
END;

```

11.4. modifyMaxNoPlaces

```

CREATE OR REPLACE PROCEDURE modifyMaxNoPlaces(
    p_trip_id Trips.trip_id%TYPE,
    p_max_no_places Trips.max_no_places%TYPE
)
AS
BEGIN
    IF NOT doesTripExist(p_trip_id) THEN
        RAISE_APPLICATION_ERROR(-20001, 'There is no trip with id ' || p_trip_id
|| ' in the database');
    END IF;

    UPDATE Trips
    SET max_no_places = p_max_no_places
    WHERE trip_id = p_trip_id;
END;

```