

EdX and its Members use cookies and other tracking technologies for performance, analytics, and marketing purposes. By using this website, you accept this use. Learn more about these technologies in the [Privacy Policy](#).



[Course](#) > [Week 2](#) > [Project...](#) > [p1_sea...](#)

p1_search_q8_replanning

Question 8 (3 points): Suboptimal Search

Sometimes, even with A* and a good heuristic, finding the optimal path through all the dots is hard. In these cases, we'd still like to find a reasonably good path, quickly. In this section, you'll write an agent that always greedily eats the closest dot.

`ClosestDotSearchAgent` is implemented for you in `searchAgents.py`, but it's missing a key function that finds a path to the closest dot.

Implement the function `findPathToClosestDot` in `searchAgents.py`. Our agent solves this maze (suboptimally!) in under a second with a path cost of 350:

```
python pacman.py -l bigSearch -p ClosestDotSearchAgent -z .5
```

Hint: The quickest way to complete `findPathToClosestDot` is to fill in the `AnyFoodSearchProblem`, which is missing its goal test. Then, solve that problem with an appropriate search function. The solution should be very short!

Your `ClosestDotSearchAgent` won't always find the shortest possible path through the maze. Make sure you understand why and try to come up with a small example where repeatedly going to the closest dot does not result in finding the shortest path for eating all the dots.