

EdX and its Members use cookies and other tracking technologies for performance, analytics, and marketing purposes. By using this website, you accept this use. Learn more about these technologies in the [Privacy Policy](#).



[Course](#) > [Week 2](#) > [Project...](#) > [p1_sea...](#)

p1_search_q7_eating_all_the_dots

Question 7 (4 points): Eating All The Dots

Now we'll solve a hard search problem: eating all the Pacman food in as few steps as possible. For this, we'll need a new search problem definition which formalizes the food-clearing problem: `FoodSearchProblem` in `searchAgents.py` (implemented for you). A solution is defined to be a path that collects all of the food in the Pacman world. For the present project, solutions do not take into account any ghosts or power pellets; solutions only depend on the placement of walls, regular food and Pacman. (Of course ghosts can ruin the execution of a solution! We'll get to that in the next project.) If you have written your general search methods correctly, A* with a null heuristic (equivalent to uniform-cost search) should quickly find an optimal solution to `testSearch` with no code change on your part (total cost of 7).

```
python pacman.py -l testSearch -p AStarFoodSearchAgent
```

Note: `AStarFoodSearchAgent` is a shortcut for `-p SearchAgent -a fn=astar,prob=FoodSearchProblem,heuristic=foodHeuristic`.

You should find that UCS starts to slow down even for the seemingly simple `tinySearch`. As a reference, our implementation takes 2.5 seconds to find a path of length 27 after expanding 5057 search nodes.

Note: Make sure to complete Question 4 before working on Question 7, because Question 7 builds upon your answer for Question 4.

Fill in `foodHeuristic` in `searchAgents.py` with a consistent heuristic for the `FoodSearchProblem`. Try your agent on the `trickySearch` board:

```
python pacman.py -l trickySearch -p AStarFoodSearchAgent
```

Our UCS agent finds the optimal solution in about 13 seconds, exploring over 16,000 nodes.

Any non-trivial non-negative consistent heuristic will receive 1 point. Make sure that your heuristic returns 0 at every goal state and never returns a negative value. Depending on how few nodes your heuristic expands, you'll get additional points:

Number of nodes expanded	Grade
more than 15000	1/4
at most 15000	2/4
at most 12000	3/4
at most 9000	4/4 (full credit; medium)
at most 7000	5/4 (optional extra credit; hard)

Remember: If your heuristic is inconsistent, you will receive *no* credit, so be careful! Can you solve `mediumSearch` in a short time? If so, we're either very, very impressed, or your heuristic is inconsistent.