

# Tidy Forecasting in R

Rob J Hyndman

ISF 2018

# forecast package

Pre 2003	Private functions used for consulting projects
July/August 2003	<b>ets</b> and <b>thetaf</b> added
August 2006	<b>v1.0</b> available on CRAN
May 2007	<b>auto.arima</b> added
May 2010	<b>arfima</b> added
Feb/March 2011	<b>tslm</b> , <b>stlf</b> , <b>naive</b> , <b>snaive</b> added
August 2011	<b>v3.0</b> . Box Cox transformations added
December 2011	<b>tbats</b> added
April 2012	Package moved to github
November 2012	<b>v4.0</b> . <b>nnetar</b> added
June 2013	Major speed-up of <b>ets</b>
February 2016	<b>v7.0</b> . Added ggplot2 graphics
February 2017	<b>v8.0</b> . Added <b>checkresiduals</b> , <b>tsCV</b> and <b>%&gt;%</b>
April 2018	<b>v8.3</b> . Added <b>mstl</b>
June 2018	≈ 100,000 package downloads per month

# fable package

A replacement for the forecast package.

## Why change?

- Interacting with tidyverse packages
- Sub-daily data and multiple seasonal data handled more easily
- Consistency of interface
- Distribution forecasting rather than point+interval
- Flexible transformations
- Extensibility
- Simpler interface for hierarchical and grouped forecast reconciliation
- Designed for forecasting many related time series
- Changes will break too much existing code
- Opportunity to re-think forecasting practice

# Example: Australian eating-out expenditure

fpp2::auscafe

##		Jan	Feb	Mar	Apr	May	Jun	Jul	Aug
##	1982				0.342	0.342	0.329	0.339	0.332
##	1983	0.369	0.348	0.366	0.351	0.360	0.347	0.364	0.376
##	1984	0.389	0.377	0.398	0.383	0.414	0.382	0.393	0.409
##	1985	0.426	0.392	0.416	0.420	0.446	0.407	0.449	0.466
##	1986	0.504	0.453	0.480	0.497	0.531	0.485	0.526	0.538
##	1987	0.572	0.525	0.544	0.558	0.565	0.542	0.599	0.584
##	1988	0.605	0.586	0.625	0.612	0.630	0.635	0.659	0.656
##	1989	0.733	0.661	0.713	0.694	0.710	0.722	0.741	0.746
##	1990	0.858	0.764	0.840	0.805	0.809	0.799	0.815	0.828
##	1991	0.862	0.771	0.813	0.797	0.821	0.801	0.829	0.854
##	1992	0.938	0.862	0.936	0.932	0.929	0.869	0.891	0.875
##	1993	0.918	0.838	0.870	0.862	0.852	0.828	0.882	0.867
##	1994	0.985	0.902	1.015	0.939	0.941	0.935	1.013	1.018
##	1995	1.076	0.982	1.099	1.068	1.083	1.045	1.094	1.110
##	1996	1.213	1.128	1.180	1.169	1.146	1.109	1.138	1.146
##	1997	1.180	1.060	1.148	1.141	1.170	1.113	1.165	1.173
##	1998	1.186	1.050	1.141	1.107	1.144	1.088	1.162	1.145

## Example: Australian eating-out expenditure

```
library(tsibble)
cafe <- as_tsibble(fpp2::auscafe)
cafe
```

```
## # A tsibble: 426 x 2 [1MONTH]
##       index value
##       <mth> <dbl>
## 1 1982 Apr 0.342
## 2 1982 May 0.342
## 3 1982 Jun 0.329
## 4 1982 Jul 0.338
## 5 1982 Aug 0.332
## 6 1982 Sep 0.342
## 7 1982 Oct 0.358
## 8 1982 Nov 0.375
## 9 1982 Dec 0.433
## 10 1983 Jan 0.369
## # ... with 416 more rows
```

## Example: Australian eating-out expenditure

```
library(fable)
cafe %>% ETS(value)
```

```
## # A tibble: 1 x 2
##   data                model
##   <list>              <list>
## 1 <tsibble [426 x 2]> <ETS(M,A,M)>
```

# Example: Australian eating-out expenditure

```
cafe %>% ETS(value) %>% summary()
```

```
## ETS(M,A,M)
##
## Call:
## ETS(data = ., formula = value)
##
## Smoothing parameters:
##   alpha = 0.6263
##   beta  = 0.0065
##   gamma = 0.0755
##
## Initial states:
##   l = 0.3477
##   b = 0.0038
##   s = 0.996 0.936 1.01 1.15 1.01 1.01
##         0.983 0.991 0.992 0.951 0.997 0.971
##
## sigma: 0.0249
##
```

## Example: Australian eating-out expenditure

```
cafe %>% ETS(value) %>% forecast()
```

```
## # A tibble: 1 x 3
```

```
##   data                                model          forecast
```

```
##   <list>                             <list>         <list>
```

```
## 1 <tsibble [426 x 2]> <ETS(M,A,M)> <tsibble [24 x 3]>
```




# Example: Australian eating-out expenditure

```
cafe %>% ETS(value) %>% forecast() %>% summary()
```

```
## # A tsibble: 24 x 4 [1MONTH]
##       index mean      `80%`      `95%`
##       <mth> <dbl>    <hilo>    <hilo>
## 1 2017 Oct   3.83 [3.71, 3.96]80 [3.65, 4.02]95
## 2 2017 Nov   3.81 [3.67, 3.96]80 [3.59, 4.03]95
## 3 2017 Dec   4.22 [4.04, 4.40]80 [3.94, 4.49]95
## 4 2018 Jan   3.83 [3.64, 4.01]80 [3.55, 4.10]95
## 5 2018 Feb   3.51 [3.33, 3.70]80 [3.24, 3.79]95
## 6 2018 Mar   3.87 [3.65, 4.09]80 [3.54, 4.20]95
## 7 2018 Apr   3.78 [3.56, 4.01]80 [3.44, 4.13]95
## 8 2018 May   3.81 [3.57, 4.05]80 [3.44, 4.18]95
## 9 2018 Jun   3.68 [3.43, 3.92]80 [3.30, 4.05]95
## 10 2018 Jul  3.88 [3.60, 4.15]80 [3.46, 4.29]95
## # ... with 14 more rows
```

# Example: Australian eating-out expenditure

```
cafe %>% ETS(value) %>% forecast() %>% autoplot()
```



# Example: Australian eating-out expenditure

```
cafe %>% ARIMA(log(value)) %>%  
  forecast() %>% summary()
```

```
## # A tsibble: 24 x 4 [1MONTH]  
##       index mean      `80%`      `95%`  
##       <mth> <dbl>      <hilo>      <hilo>  
## 1 2017 Oct  1.31 [0.557, 3.09]80 [0.354, 4.86]95  
## 2 2017 Nov  1.31 [0.557, 3.09]80 [0.354, 4.86]95  
## 3 2017 Dec  1.31 [0.557, 3.09]80 [0.354, 4.86]95  
## 4 2018 Jan  1.31 [0.557, 3.09]80 [0.354, 4.86]95  
## 5 2018 Feb  1.31 [0.557, 3.09]80 [0.354, 4.86]95  
## 6 2018 Mar  1.31 [0.557, 3.09]80 [0.354, 4.86]95  
## 7 2018 Apr  1.31 [0.557, 3.09]80 [0.354, 4.86]95  
## 8 2018 May  1.31 [0.557, 3.09]80 [0.354, 4.86]95  
## 9 2018 Jun  1.31 [0.557, 3.09]80 [0.354, 4.86]95  
## 10 2018 Jul 1.31 [0.557, 3.09]80 [0.354, 4.86]95  
## # ... with 14 more rows
```

## Example: prison data

```
fpp2::prisonLF
```

```
## # A tibble: 1,536 x 5
##   state gender legal      t      count
##   <fct> <fct>  <fct>   <date>   <dbl>
## 1 ACT    Female Remanded 2005-03-01     2
## 2 ACT    Female Remanded 2005-06-01     4
## 3 ACT    Female Remanded 2005-09-01     1
## 4 ACT    Female Remanded 2005-12-01     4
## 5 ACT    Female Remanded 2006-03-01     4
## 6 ACT    Female Remanded 2006-06-01     6
## 7 ACT    Female Remanded 2006-09-01     9
## 8 ACT    Female Remanded 2006-12-01     6
## 9 ACT    Female Remanded 2007-03-01     4
## 10 ACT   Female Remanded 2007-06-01     4
## # ... with 1,526 more rows
```

## Example: prison data

```
prison <- fpp2::prisonLF %>%  
  mutate(qtr=yearquarter(t)) %>%  
  select(-t) %>%  
  as_tsibble(index=qtr, key=id(state,gender,legal))  
prison
```

```
## # A tsibble: 1,536 x 5 [1QUARTER]  
## # Keys:      state, gender, legal [32]  
##   state gender legal    count    qtr  
##   <fct> <fct>  <fct>    <dbl>  <qtr>  
## 1 ACT   Female Remanded      2 2005 Q1  
## 2 ACT   Female Remanded      4 2005 Q2  
## 3 ACT   Female Remanded      1 2005 Q3  
## 4 ACT   Female Remanded      4 2005 Q4  
## 5 ACT   Female Remanded      4 2006 Q1  
## 6 ACT   Female Remanded      6 2006 Q2  
## 7 ACT   Female Remanded      9 2006 Q3
```

# Example: prison data

```
prison %>% ETS(count)
```

```
## # A tibble: 32 x 5
```

##	state	gender	legal	data	model
##	<fct>	<fct>	<fct>	<list>	<list>
## 1	ACT	Female	Remanded	<tsibble [48 x 2]>	<ETS(M,A,N)>
## 2	ACT	Female	Sentenced	<tsibble [48 x 2]>	<ETS(A,A,N)>
## 3	ACT	Male	Remanded	<tsibble [48 x 2]>	<ETS(M,N,N)>
## 4	ACT	Male	Sentenced	<tsibble [48 x 2]>	<ETS(A,N,N)>
## 5	NSW	Female	Remanded	<tsibble [48 x 2]>	<ETS(M,N,M)>
## 6	NSW	Female	Sentenced	<tsibble [48 x 2]>	<ETS(M,N,M)>
## 7	NSW	Male	Remanded	<tsibble [48 x 2]>	<ETS(M,A,A)>
## 8	NSW	Male	Sentenced	<tsibble [48 x 2]>	<ETS(M,A,A)>
## 9	NT	Female	Remanded	<tsibble [48 x 2]>	<ETS(M,N,N)>
## 10	NT	Female	Sentenced	<tsibble [48 x 2]>	<ETS(M,A,A)>
## #	... with 22 more rows				

# Example: prison data

```
prison %>% ETS(count) %>% forecast()
```

```
## # A tibble: 32 x 6
##   state gender legal      data      model      forecast
##   <fct> <fct>  <fct>    <list>    <list>    <list>
## 1 ACT   Female Remanded <tsibble [48 x 2]> <ETS(M,A,N)> <tsibble [8 x 3~
## 2 ACT   Female Sentenced <tsibble [48 x 2]> <ETS(A,A,N)> <tsibble [8 x 3~
## 3 ACT   Male   Remanded <tsibble [48 x 2]> <ETS(M,N,N)> <tsibble [8 x 3~
## 4 ACT   Male   Sentenced <tsibble [48 x 2]> <ETS(A,N,N)> <tsibble [8 x 3~
## 5 NSW   Female Remanded <tsibble [48 x 2]> <ETS(M,N,M)> <tsibble [8 x 3~
## 6 NSW   Female Sentenced <tsibble [48 x 2]> <ETS(M,N,M)> <tsibble [8 x 3~
## 7 NSW   Male   Remanded <tsibble [48 x 2]> <ETS(M,A,A)> <tsibble [8 x 3~
## 8 NSW   Male   Sentenced <tsibble [48 x 2]> <ETS(M,A,A)> <tsibble [8 x 3~
## 9 NT    Female Remanded <tsibble [48 x 2]> <ETS(M,N,N)> <tsibble [8 x 3~
## 10 NT   Female Sentenced <tsibble [48 x 2]> <ETS(M,A,A)> <tsibble [8 x 3~
## # ... with 22 more rows
```

Aggregation and reconciliation not yet implemented.

# Equivalent methods: forecast → fable

- `auto.arima` → ARIMA

- `ets` → ETS

- `tslm/lm` → LM

- `tbats` → TBATS

- `nnetar` → NNETAR

- `stlm` → STL %>%

`modelcomponents(ETS(seasadj),  
SNAIVE(season))`

- All functions have a formula interface with automatic modelling if no formula provided.

- All functions produce mable class objects.

- Some of these functions not yet implemented



# Equivalent methods: forecast → fable

- naive → NAIVE %>% forecast
  - snaive → SNAIVE %>% forecast
  - thetaf → THETA %>% forecast
  - stlf → STL %>%  
modelcomponents(ETS(seasadj),  
SNAIVE(season)) %>%  
forecast
  - hw → HW %>% forecast
  - holt → HOLT %>% forecast
  - ses → SES %>% forecast
  - splinef → SPLINE %>% forecast
  - croston → CROSTON %>% forecast
- forecast produces fable class objects.

# Download

```
devtools::install_github("tidyverts/tsibble")  
devtools::install_github("tidyverts/fable")
```

# NUMBATS



Di Cook



Earo Wang



Mitchell O'Hara-Wild

## More information

[tidyverts.org](https://tidyverts.org)

[robjhyndman.com/hyndsight](https://robjhyndman.com/hyndsight)