



Tidy Forecasting in R



Rob J Hyndman

useR2018: 13 July 2018

forecast package



Pre 2003	Private functions used for consulting
July/August 2003	ets and thetaf added
August 2006	v1.0 available on CRAN
May 2007	auto.arima added
Feb/March 2011	tslm , stlf , naive , snaive added
August 2011	v3.0 . Box Cox transformations added
December 2011	tbats added
April 2012	Package moved to github
February 2016	v7.0 . Added ggplot2 graphics
February 2017	v8.0 . Added checkresiduals , tsCV and %>%
April 2018	v8.3 . Added mstl
June 2018	≈ 100,000 package downloads per month

fable package

A replacement for the forecast package.



Why change?

- Integrating with tidyverse packages
- Designed for forecasting many related time series
- Consistency of interface using formulas
- Distribution forecasting rather than point + interval
- Flexible transformations
- Sub-daily data and multiple seasonal data handled more easily
- Simpler interface for forecast reconciliation

Formula model specification



All modelling functions use a formula similar to `lm()` with automated modelling if RHS not specified.

```
t(y) ~ {model specification}
```

LHS: Response

- Defines the response variable from the data
- Specification of transformations (which are automatically back-transformed)

RHS: Specials

- Model specific special functions
- Exogenous regressors (if supported by model)

Example: Australian eating-out expenditure



```
library(tsibble)
(cafe <- as_tsibble(fpp2::auscafe))
```

```
## # A tsibble: 426 x 2 [1MONTH]
##       index value
##       <mth> <dbl>
## 1 1982 Apr 0.342
## 2 1982 May 0.342
## 3 1982 Jun 0.329
## 4 1982 Jul 0.338
## 5 1982 Aug 0.332
## 6 1982 Sep 0.342
## 7 1982 Oct 0.358
## 8 1982 Nov 0.375
## 9 1982 Dec 0.433
## 10 1983 Jan 0.369
## # ... with 416 more rows
```

Example: Australian eating-out expenditure



```
library(fable)
cafe %>% ARIMA(log(value) ~ pdq(2,1,1) + PDQ(2,1,2))
```

```
## # A mable: 1 model [1MONTH]
##   data          model
##   <list>        <model>
## 1 <tsibble [426 x 2]> ARIMA(2,1,1)(2,1,2)[12]
```

Example: Australian eating-out expenditure



```
cafe %>% ARIMA(log(value) ~ pdq(2,1,1) + PDQ(2,1,2)) %>%  
summary()
```

```
## Series: log(value)  
## ARIMA(2,1,1)(2,1,2)[12]  
##  
## Coefficients:  
##          ar1      ar2      ma1      sar1      sar2      sma1      sma2  
##      -0.925  -0.318   0.588   0.724  -0.213  -1.437   0.557  
## s.e.   0.182   0.060   0.189   0.174   0.074   0.170   0.149  
##  
## sigma^2 estimated as 0.000554:  log likelihood=959.49  
## AIC=-1903   AICc=-1902.6   BIC=-1870.8  
##  
## Training set error measures:  
##              ME      RMSE      MAE      MPE      MAPE      MASE  
## Training set -0.0010597 0.037131 0.026734 -0.050621 1.7758 0.25586  
##  
##              ACF1  
## Training set 0.010111
```

Example: Australian eating-out expenditure



```
cafe %>% ARIMA(log(value) ~ pdq(2,1,1) + PDQ(2,1,2)) %>%  
  forecast()
```

```
## # A fable: 1 forecast [1MONTH]  
##   data                model                forecast  
##   <list>              <model>             <fc>  
## 1 <tsibble [426 x 2]> ARIMA(2,1,1)(2,1,2)[12] ~t(N) [h=24]
```


Example: Australian eating-out expenditure




```
cafe %>% ARIMA(log(value) ~ pdq(2,1,1) + PDQ(2,1,2)) %>%  
  forecast() %>% summary(level=90)
```

```
## # A tsibble: 24 x 3 [1MONTH]  
##       index mean          90%  
##       <mth> <dbl>         <hilo>  
## 1 2017 Oct  3.81 [3.6643, 3.9594]90  
## 2 2017 Nov  3.79 [3.6150, 3.9669]90  
## 3 2017 Dec  4.17 [3.9483, 4.3895]90  
## 4 2018 Jan  3.73 [3.5033, 3.9560]90  
## 5 2018 Feb  3.40 [3.1759, 3.6242]90  
## 6 2018 Mar  3.77 [3.5075, 4.0488]90  
## 7 2018 Apr  3.70 [3.4248, 3.9931]90  
## 8 2018 May  3.76 [3.4573, 4.0692]90  
## 9 2018 Jun  3.66 [3.3495, 3.9782]90  
## 10 2018 Jul 3.88 [3.5359, 4.2353]90  
## # ... with 14 more rows
```

Example: Australian eating-out expenditure

```
cafe %>% ARIMA(log(value) ~ pdq(2,1,1) + PDQ(2,1,2)) %>%  
  forecast() %>% autoplot()
```



Example: Half-hourly electricity demand



elecdemand

```
## # A tsibble: 17,520 x 4 [30MINUTE]
##       index          Demand Temperature WorkDay
##       <dtm>          <dbl>         <dbl>    <dbl>
## 1 2014-01-01 00:00:00    3.91         18.2        0
## 2 2014-01-01 00:30:00    3.67         17.9        0
## 3 2014-01-01 01:00:00    3.50         17.6        0
## 4 2014-01-01 01:30:00    3.34         16.8        0
## 5 2014-01-01 02:00:00    3.20         16.3        0
## 6 2014-01-01 02:30:00    3.10         16.6        0
## 7 2014-01-01 03:00:00    3.04         16.6        0
## 8 2014-01-01 03:30:00    3.01         16.7        0
## 9 2014-01-01 04:00:00    3.02         16.2        0
## 10 2014-01-01 04:30:00    3.03         16.6        0
## # ... with 17,510 more rows
```

Example: Half-hourly electricity demand



```
fit2 <- ARIMA(elecdemand,  
  Demand ~ Temperature + I(Temperature^2) + WorkDay)  
summary(fit2)
```

```
## Series: Demand  
## Regression with ARIMA(1,1,0)(2,0,2)[2] errors  
##  
## Coefficients:  
##          ar1      sar1      sar2      sma1      sma2  Temperature  I(Temperature^2)  
##          0.853   -0.181    0.523   -0.066   -0.792         -0.009              0  
## s.e.      0.005    0.015    0.012    0.012    0.011          0.002              0  
##          WorkDay  
##          0.016  
## s.e.      0.006  
##  
## sigma^2 estimated as 0.00846:  log likelihood=16949  
## AIC=-33881   AICc=-33881   BIC=-33811  
##
```

Example: Half-hourly electricity demand



```
fit2 <- ARIMA(elecddemand,  
  Demand ~ Temperature + I(Temperature^2) + WorkDay)  
summary(fit2)
```

```
## Series: Demand  
## Regression with ARIMA(1,1,0)(2,0,2)[2] errors  
##  
## Coefficients:  
##          ar1      sar1      sar2      sma1      sma2  Temperature  I(Temperature^2)  
##          0.853   -0.181   0.523   -0.066   -0.792          -0.009              0  
## s.e.      0.005    0.015    0.012    0.012    0.011           0.002              0  
##          WorkDay  
##          0.016  
## s.e.      0.006  
##  
## sigma^2 estimated as 0.00846:  log likelihood=16949  
## AIC=-33881   AICc=-33881   BIC=-33811  
  
forecast(fit2, newdata=elecddemandfuture) %>% autoplot()
```

Example: Australian prison population



prison

```
## # A tibble: 1,536 x 5 [1QUARTER]
## # Key:      state, gender, legal [32]
##   state gender legal    count    qtr
##   <fct> <fct>  <fct>    <dbl>  <qtr>
## 1 ACT   Female Remanded      2 2005 Q1
## 2 ACT   Female Remanded      4 2005 Q2
## 3 ACT   Female Remanded      1 2005 Q3
## 4 ACT   Female Remanded      4 2005 Q4
## 5 ACT   Female Remanded      4 2006 Q1
## 6 ACT   Female Remanded      6 2006 Q2
## 7 ACT   Female Remanded      9 2006 Q3
## 8 ACT   Female Remanded      6 2006 Q4
## 9 ACT   Female Remanded      4 2007 Q1
## 10 ACT  Female Remanded      4 2007 Q2
## # ... with 1,526 more rows
```

Example: Australian prison population



```
prison %>% ETS(count)
```

```
## # A mable: 32 models [1QUARTER]
## # Key:      state, gender, legal [32]
##   state gender legal      data      model
##   <fct> <fct>  <fct>    <list>    <model>
##  1 ACT   Female Remanded <tsibble [48 x 2]> ETS(M,A,N)
##  2 ACT   Female Sentenced <tsibble [48 x 2]> ETS(A,A,N)
##  3 ACT   Male   Remanded <tsibble [48 x 2]> ETS(M,N,N)
##  4 ACT   Male   Sentenced <tsibble [48 x 2]> ETS(A,N,N)
##  5 NSW   Female Remanded <tsibble [48 x 2]> ETS(M,N,M)
##  6 NSW   Female Sentenced <tsibble [48 x 2]> ETS(M,N,M)
##  7 NSW   Male   Remanded <tsibble [48 x 2]> ETS(M,A,A)
##  8 NSW   Male   Sentenced <tsibble [48 x 2]> ETS(M,A,A)
##  9 NT    Female Remanded <tsibble [48 x 2]> ETS(M,N,N)
## 10 NT    Female Sentenced <tsibble [48 x 2]> ETS(M,A,A)
## # ... with 22 more rows
```

Example: Australian prison population



```
prison %>% ETS(count) %>% forecast()
```

```
## # A fable: 32 forecasts [1QUARTER]
## # Key:      state, gender, legal [32]
##   state gender legal    data      model      forecast
##   <fct> <fct>  <fct>    <list>    <model>    <fc>
## 1 ACT   Female Remanded <tsibble [48 x 2]> ETS(M,A,N) ~N [h=8]
## 2 ACT   Female Sentenced <tsibble [48 x 2]> ETS(A,A,N) ~N [h=8]
## 3 ACT   Male   Remanded <tsibble [48 x 2]> ETS(M,N,N) ~N [h=8]
## 4 ACT   Male   Sentenced <tsibble [48 x 2]> ETS(A,N,N) ~N [h=8]
## 5 NSW   Female Remanded <tsibble [48 x 2]> ETS(M,N,M) ~N [h=8]
## 6 NSW   Female Sentenced <tsibble [48 x 2]> ETS(M,N,M) ~N [h=8]
## 7 NSW   Male   Remanded <tsibble [48 x 2]> ETS(M,A,A) ~N [h=8]
## 8 NSW   Male   Sentenced <tsibble [48 x 2]> ETS(M,A,A) ~N [h=8]
## 9 NT    Female Remanded <tsibble [48 x 2]> ETS(M,N,N) ~N [h=8]
## 10 NT   Female Sentenced <tsibble [48 x 2]> ETS(M,A,A) ~N [h=8]
## # ... with 22 more rows
```



Example: Australian prison population



```
prison %>% ETS(count) %>% forecast()
```

```
## # A fable: 32 forecasts [1QUARTER]
## # Key:      state, gender, legal [32]
##   state gender legal      data      model      forecast
##   <fct> <fct>  <fct>    <list>    <model>    <fc>
## 1 ACT   Female Remanded <tsibble [48 x 2]> ETS(M,A,N) ~N [h=8]
## 2 ACT   Female Sentenced <tsibble [48 x 2]> ETS(A,A,N) ~N [h=8]
## 3 ACT   Male   Remanded <tsibble [48 x 2]> ETS(M,N,N) ~N [h=8]
## 4 ACT   Male   Sentenced <tsibble [48 x 2]> ETS(A,N,N) ~N [h=8]
## 5 NSW   Female Remanded <tsibble [48 x 2]> ETS(M,N,M) ~N [h=8]
## 6 NSW   Female Sentenced <tsibble [48 x 2]> ETS(M,N,M) ~N [h=8]
## 7 NSW   Male   Remanded <tsibble [48 x 2]> ETS(M,A,A) ~N [h=8]
## 8 NSW   Male   Sentenced <tsibble [48 x 2]> ETS(M,A,A) ~N [h=8]
## 9 NT    Female Remanded <tsibble [48 x 2]> ETS(M,N,N) ~N [h=8]
## 10 NT    Female Sentenced <tsibble [48 x 2]> ETS(M,A,A) ~N [h=8]
## # ... with 22 more rows
```

Moving from forecast to fable



- All **forecast** `model()` functions will have equivalent **fable** `MODEL()` functions.
- All **fable** models produce `mable` class objects.
- `forecast()` works on `mable` objects to produce `fable` objects.
- **fable** will also replace the **hts** package

Extending fable



fable simplifies the model development process

Tools to easily create new fable models

- Easily create specials for model formulae
- Focus on model estimation and forecasts

Automatically supported fable functionality

- Transformations and back-transformations (with bias adjustments)
- Plotting tools
- Accuracy measures and evaluation
- Model combinations (hierarchies & ensembles)

More information

```
devtools::install_github("tidyverts/tsibble")  
devtools::install_github("tidyverts/fable")
```



Di Cook



Earo Wang



Mitchell O'Hara-Wild

Follow our progress

- tidyverts.org
- robjhyndman.com/hyndsight